

3G Fiber Transmission

3G FIBER CAMERA TRANSMISSION

The 3G Fiber transmission system for the LDK 8000 Elite and LDK 4000 Elite camera heads is the world's first Fiber system that delivers all HD video formats (720p, 1080i, and 1080p) from the base station.



The 3G Fiber transmission solution consist of the LDK 5420 camera adapter and the LDK 4410 base station. This 3rd generation fiber solution is a non-compromise, fully featured solution that can cope with the broadcast requirements of today and tomorrow.

The 3G Fiber transmission system is a heavy duty, high-quality, multi-standard, full-bandwidth transmission system with new and specially developed highly advanced technologies that is fully 3G and 3D ready and supports current 1080i50/60 and 720p50/60 formats as well as 1080p50/60 transmission from the LDK 8000 Elite WorldCam.

The 3G Fiber system is extremely powerful where long cable runs are needed. With SMPTE hybrid cable, cable runs up to 3,000m (9,842 ft.) can be reached. When "dark fiber" is used, cable length can go over 10 km (30,000 ft.)

LDK 4410 Base Station

The LDK 4410 base station offers extended connectivity with no less than eight HD outputs, of which six single link HD-SDI outputs (1.5 Gb / 3 Gb switchable) and two 1.5 Gb HD-SDI outputs, which automatically convert the signal in 1080i when the camera head is delivering 1080p. In addition, three HD return connections are incorporated, of which two can be selected as a return channel by the adapter.

Additionally, the audio connectivity offers great versatility with two analog outputs and two (digital) AES/EBU pair outputs (2 x 2-channels) which are also embedded in the HD-SDI outputs.

With a compact design of only 2 RU and weighing in at only 2.3 kg (5.1 lbs.), the LDK 4410 base station takes up minimal rack space. When combined with its low power consumption and efficient internal cooling that eliminates the need for space between adjacent units, the LDK 4410 base station is ideal for implementation in OB vans.

RefleX SuperXpander

To coincide with the introduction of the new 3G Transmission system, Grass Valley has developed a new large lens adapter—the RefleX SuperXpander.

As part of the RefleX SuperXpander, a new convenient hot shoe connection to the camera is implemented which directly powers the SuperXpander from the camera. This makes the new RefleX SuperXpander seamlessly compatible with the new 3G Fiber camera adapter.

Once the camera is inserted in the RefleX SuperXpander, the hybrid-fiber cable can be connected to the camera and all interfacing with the RefleX SuperXpander takes place through the hot shoe connector. This makes the RefleX SuperXpander transmission agnostic, which means that the RefleX SuperXpander can work with both the 3G Fiber and 3G Triax systems without any additional equipment for true flexibility.

KEY FEATURES

- 3G Fiber is a member of the versatile 3G Transmission family
- Full feature set for both today's and tomorrow's broadcast requirements
- Full support for all HD formats 720p/1080i/1080p
- 6X 3G video outputs / 8X 1.5G video outputs
- Extensive (analog/digital) audio connectivity
- Embedded audio
- 3 selectable return inputs (3G, HD, or SD)
- Convenient hot shoe connectivity for RefleX SuperXpander use
- Universal 3G power supply
- Long hybrid fiber cable capabilities 3.000m (9.842 ft.)
- Compact (2 RU) and robust base station



SPECIFICATIONS

Video

720p: 23.98/25/29.97/50/59.94 Hz

1080p (WorldCam):

23.98/24/25/29.97/50/59.94 Hz

1080i: 50/59.94 Hz

S/N ratio in Y signal: 61 dB typical

Modulation depth: 55% at 27 MHz typical

3G Fiber Adapter (LDK 5420)

General

Dimensions (HxWxL, approx.): 220 x 120 x 205 mm (8.7 x 4.7 x 8.1 in.) without handgrip

Operating temperature: -20 to +45° C (-4 to +113° F)

Storage temperature: -20 to +70° C (-4 to +158° F)

Operation humidity: Max. 90% (non-condensing)

Weight: 2.3 kg (5.1 lbs.)

Input Connectors

Front mic: XLR-3-31 type (female) balanced, +48V, ch1

Audio 1: XLR-3-31 type (female), selectable phantom +48V; mic/line switch

Audio 2: XLR-3-31 type (female), selectable phantom +48V; mic/line switch

DC (12V): XLR-4 pin type (male)

Output Connectors

HD-SDI VF: BNC type, 1.0 Vp-p, 75Ω

HD-SDI (EXT):

- BNC, SMPTE 292M, 1.5 Gb/s, 0.8 Vp-p, 75Ω
- BNC, SMPTE 425M-A, 3.0 Gb/s, 0.8 Vp-p, 75Ω (live output)

Scriptlight DC (0.25A/12V): 4-pin Hirose

DC (12V/1.5A) and tally indicators: 4-pin Hirose

Input / Output Connectors

Adapter (to base station): Fiber communication + power connection

Typical SMPTE hybrid fiber (SMPTE 311) cable length: 3,000m (9,842 ft.)

Intercom (to headset): XLR 5-pin (female)

Video Ref (input) / Teleprompter (output): BNC type, 1.0 Vp-p, 75Ω (tri-level sync input/SD-output)

Auxiliary / Data (private data): 1-pin (female)

Tracker: 11-pin (female)

VF mon./ext. output (analog)/AES-EBU input: BNC type, 1.0 Vp-p, 75Ω

Hot shoe connection (bottom plate): 20-pin connector (power + control)

3G Fiber Base Station (LDK 4410)

General

Dimensions (HxWxL, approx.): 438 (19" rack) x 88 (2 RU) x 510 mm

Operating temperature: 0 to +45° C (+32 to +113° F)

Storage temperature: -40 to +70° C (-40 to +158° F)

Operation humidity: Max. 90% (non-condensing)

Weight: 13.0 kg (28.66 lbs.) full option equipped

Power consumption: 380VA or 375 watt max. in studio configuration; 200 VA or 180 watt max. in portable configuration

Typical SMPTE hybrid fiber (SMPTE 311) cable length: 3,000m (9,842 ft.)

Connectors

Teleprompter in: BNC 1X (loop-through output), (CIVBS, 1.0 Vp-p, 75Ω)

Reference in: 1X (loop-through output), 1.0 Vp-p, 75Ω HD tri-level sync or SD black-burst

HD-SDI out:

- BNC 6X 0.8 Vp-p, 75Ω, SMPTE 292M, 1080i/720p at 59.94/50 Hz
- BNC 6X 0.8 Vp-p, 75Ω, SMPTE 425M-A/SMPTE 425M-B, 1080p at 59.94/50 Hz

HD-SDI out (live/effect): BNC 2X 0.8 Vp-p, 75Ω, SMPTE 292M, 1080i/720p at 59.94/50 Hz

HD monitoring out: BNC 1X 0.8 Vp-p, 75Ω, SMPTE 292M, 1080i/720p at 59.94/50 Hz

Composite video out: BNC 1X 1.0 Vp-p, 75Ω (CVBS text w/ or w/o video, for viewing purposes)

Signaling in/out: D-sub 15-pin, male; preview, green tally (call), dry contact; yellow tally (iso), dry contact; red tally (on-air), dry contact; remote audio level control (22-64 dB), DC

Auxiliary in/out: D-sub 9-pin, female; An0, 0-5 VDC in, An1, 0-5 VDC in, output on camera head; 16:9 <0.8 VDC in; private data in/out; 100 kb TTL (RS-232)

Control data: RJ-45 connector for Ethernet C21P

Power requirement: AC 115V/230V ±15%, 47 to 63 Hz

Power connector: IEC type, 3-pin male

Power consumption: 380 VA or 375W max. in studio configuration; 200 VA or 180W max. in portable configuration or Lemo hybrid fiber connector acc. SMPTE 304 / Fischer hybrid fiber connector acc. SMPTE 304. Other fiber connectors on request

External video in:

- HD-SDI or SD-SDI in 1, (loop-through output), 0.8 Vp-p, 75Ω
- HD-SDI or SD-SDI in 2, 0.8 Vp-p, 75Ω
- HD-SDI or SD-SDI in 3, 0.8 Vp-p, 75Ω

2-channel audio: Audio out, XLR-3 2X; 0/+6 dBu (±1.5 dB, max. 18 dBu, 600Ω, gain max. 70 dB)

Frequency response: 40 Hz to 15 kHz, (+1/-3 dB, 1 kHz, -10 dBu output level)

Distortion: Less than 0.5% (100 Hz/1 kHz, +6 dBu out, 600Ω)

S/N ratio: 58 dB (unweighted RMS)

AES-EBU 1+2: BNC 75Ω, digital audio output audio 1 and 2

AES-EBU 3+4: BNC 75Ω, Dig audio output audio 3 and 4

Intercom in/out (2/4-wire intercom): D-sub 15-pin, female (program in, production in/out, engineering in/out), in: 0 or 6 dBu; out: 0 or 6 dBu (±2 dB, max. 12 dBu)

Frequency response: 150 Hz to 6 kHz (1 kHz, -10 dBu output level)

Distortion: Less than 2% (1 kHz, +12 dBu level)

Option

SD-SDI output (LDK 4532/00): SDI out, BNC 2X, 0.8 Vp-p, 75Ω, SMPTE 259M, ITU-R BT.601

ORDERING INFORMATION

Please contact your authorized Grass Valley representative.

www.grassvalley.com/sales

CUSTOMER SUPPORT & PROFESSIONAL SERVICES

Our customer support and professional services offerings ensure optimal system performance and maximize uptime. These services include call centers staffed around the clock, commissioning, professional training courses, and technical maintenance programs and service agreements.

www.grassvalley.com/support

