



grass valley
A **BELDEN** BRAND

IGNITE/IGNITE KONNECT

User Manual
Software Version 10.0

071874705
JULY 2017

—

CERTIFICATE

Certificate Number: 510040.001

The Quality System of:

Grass Valley, A Belden Brand and its Grass Valley Affiliates

Headquarters: 3499 Douglas-B Floreani St. Laurent, Quebec H4S 2C6 Canada	3030 NW Aloclek Drive Hillsboro, OR 97124 United States
Street Bergschot 69 4817 PA Breda The Netherlands	125 Crown Point Court Grass Valley, CA 95945 United States

Including its implementation, meets the requirements of the standard:

ISO 9001:2008

Scope:

St. Laurent HQ: The design, manufacture and support of video and audio products and systems.

Grass Valley and Hillsboro: Design, outsource manufacture and support.

Breda: Design, manufacture, including outsource manufacture, and support.

This Certificate is valid until: June 14, 2018
This Certificate is valid as of: June 14, 2015
Certified for the first time: June 14, 2000



Dr. Cem O. Onus
Managing Director, Business Assurance
DEKRA Certification, Inc.

The method of operation for quality certification is defined in the DEKRA Master Services Agreement. Integral publication of this certificate is allowed.

DEKRA Certification, Inc.
1120 Welsh Road, Suite 210
North Wales, PA 19454
USA
Ph: (215)997-4519
Fax: (215)997-3810
ISO 9001 Cert 03/09/2015 Rev C

Accredited By:
ANAB



—



grass valley
A **BELDEN** BRAND

IGNITE/IGNITE KONNECT

User Manual
Software Version 10.0

071874705
JULY 2017

—

Copyright & Trademark Notice

Copyright © 2017, Grass Valley Canada. All rights reserved.

Belden, Belden Sending All The Right Signals, and the Belden logo are trademarks or registered trademarks of Belden Inc. or its affiliated companies in the United States and other jurisdictions. Grass Valley is a trademark or registered trademarks of Grass Valley Canada. Belden Inc., Grass Valley Canada, and other parties may also have trademark rights in other terms used herein.

Grass Valley Web Site

The Grass Valley Web (www.grassvalley.com) site offers the following:

Online User Documentation — Current versions of product catalogs, brochures, data sheets, ordering guides, planning guides, manuals, and release notes are available.

FAQ Database — Solutions to problems and troubleshooting efforts can be found by searching our Frequently Asked Questions (FAQ) database.

Software Downloads — Download software updates, drivers, and patches.

Grass Valley Technical Support

For technical assistance, contact our international support center, at 1-800-547-8949 (US and Canada) or +1 530 478 4148.

To obtain a local phone number for the support center nearest you, please consult the Contact Us section of Grass Valley's Web site (www.grassvalley.com).

An online form for e-mail contact is also available from the Web site.

Recycling

Visit www.grassvalley.com for recycling information.

—

Contents

Preface	19
About This Manual	19
Standard Documentation	19
Other Documentation	20
 Section 1 — System Overview	 21
Software Overview	22
Single-Point Device Control	22
Production Automation	24
Remote Client	24
Hardware Overview	25
Core Components	25
Options	26
Production Options	27
Redundancy Options	29
 Section 2 — Audio Module	 31
Overview	31
Klotz Audio	35
Overview	35
Fader Manual Virtual Source Control	35
Individual Faders	35
Audio Preview	37
Audio Program (LIVE)	37
Set Points	38
Master Output Faders	41
Audio Main Context Menu	42
Operation	62
Adjust an Audio Source	62
Change a Page Name	63
Fader Manual Virtual Source Control	63
Adjust Master Fader	65
Adjust/Setup/View Aux 1–Aux 6	65
Source Setting Independent of Virtual Sources	66
Control EQ, Dynamics, and Delay via Audio Profiles	70
Select A Talk Back Source	74
Select/Edit Monitor Sources	75
Point To Point Routing	78
Set Points	79
Virtual Sources	84
Set Up Audio Task Properties	91
Audio Preview	92
Audio Program (LIVE)	94

Yamaha Audio	95
Overview	95
Fader Manual Virtual Source Control	95
Individual Faders	96
Audio Preview	97
Audio Program (Live)	98
Set Points	98
Master Output Faders	102
Audio Main Context Menu	103
Operation	107
Adjust an Audio Source	108
Change a Page Name	108
Fader Manual Virtual Source Control	109
Adjust Master Fader	111
Adjust/Set Up/View Mixer Faders 1–16	111
Adjust/Set Up/View Cue Input/Output Faders	111
Adjust/Set Up/View Matrix Faders 1–8	112
Set Points	113
Virtual Sources – Edit a Virtual Source Entry	119
Set Up Audio Task Properties	121
Audio Preview	123
Audio Program (LIVE)	124
Wheatstone Audio	125
Overview	125
Manual Virtual Source Control	125
Individual Program Fader Controls	126
Audio Preview	127
Audio Program (Live)	128
Set Points	128
Master Output Faders	131
Audio Main Context Menu	134
Operation	141
Adjust an Audio Source	142
Change a Page Name	142
Manual Virtual Source Control	143
Adjust a Single Master Fader	146
Adjust/Set Up/View a Group of Masters	146
Set Points	147
Virtual Sources	153
Set Up Audio Task Properties	155
Create an Audio Layout	156
Save Current Audio Layout	158
Load An Audio Layout	160
Edit an Audio Layout	160
Delete an Audio Layout	162
Audio Preview	162
Audio Program (LIVE)	163
Calrec, Lawo, and Studer Audio	165
Overview	165
Fader Manual Virtual Source Control	166
Individual Program Fader Controls and Indicators	166
Audio Preview	168
Audio Live	169
Virtual Source Configuration	170

Setpoint Configuration	171
Show Profiles Configuration	172
Masters Mains Output Faders	173
Audio Task Configuration	174
Operation	176
Adjust an Audio Source	176
Configure Pages	177
Setpoint Configuration	178
Virtual Source Configuration	179
Show Profiles Configuration	181
Set Up/Edit Audio Task Properties	182
Audio Preview	183
Audio Live	184
Section 3 — Automation Control Panels	187
Ignite Katalyst Automation Control Panel	187
Overview	187
Button Module	189
Audio Module	195
Panel Profiles	196
Configuration	199
Create a Module	199
Configure a Button	203
Configure a Panel Profile	217
Identify/Change a Module IP Address	222
QUICbox Panel	223
Overview	223
Programmable Buttons	224
Audio Controls, Buttons, and Indicators	226
Configuration Interface	227
Configuration Interface Menu Bar	228
Configuration	231
Button Configuration	232
Audio Fader Configuration	235
Save Layout	237
Load Layout	238
Functional Test	239
Section 4 — Camera Preset Hotkey Module	241
Overview	241
Common Control Buttons	242
Operation	242
Create a Preset Hotkey – Grass Valley HDC and CameraMan Robotic Cameras	243
Save Presets In File	245
Load Presets From File	245
Create a Preset Hotkey – Vinten/Radamac Cameras	246
Create a Preset Hotkey—Telemetry Cameras	248
Create a Preset Hotkey—Cambotics	250
Section 5 — CG List Module	253
Overview	253

Common Control Buttons and Indicators	255
CG List Setup	256
General Tab	257
Display Settings Tab	258
Template Table Tab	261
Operation	262
Populate CG List	262
Set Display Mode	262
Narrow or Wide Mode	262
CG Column Order (Wide Mode Only)	263
CG Display Pattern (Narrow Mode Only)	264
CG Column Word Wrap (Wide Mode Only)	265
Edit a CG Display Pattern	266
Set Display Colors	267
CG Template Table	269
Add a Template	269
Delete A Template	271
Load a Script	272
 Section 6 — CG/SS Module	 275
Overview	275
Common Control Buttons	276
Operation	276
Create CG/SS Hotkeys	276
Place a CG on the Event Timeline	279
Delete CG/SS Hotkeys	279
 Section 7 — Clocks and Timers Module	 281
Overview	281
Common Control Buttons	282
Clocks	282
Show Clock (Green)	282
Manual Clock (Blue)	282
Event Clock (Yellow)	283
Timers	283
Server Countdown Timer	283
Timed Events	286
Operation	292
Clocks	292
Show Clock (Green)	293
Manual Clock (Blue)	293
Event Clock (Yellow)	293
Timers	294
Server Countdown Timer Configuration	294
Global Timed Events	296
Production Timed Events (NCS Coding)	303
 Section 8 — Device Control Module	 305
Overview	305
Device Color Indications	306
Device Controls	306

Video Server Device Control	309
VTR Device Control	310
Audio Clip Device Control	311
RAM Recorder Device Control	311
Stills Device Control	312
Clips Device Control	313
ENCO Audio Server Device Control	315
Operation	315
Select A Device Control	315
Add A Video Clip	316
Add An Audio Clip	317
Search For A Time Code	318
Scan/Shuttle A Video	318
RAM Recorder	319
Record A Still	319
Record A Clip	323
Trim A Clip	328
Play A Still	329
Play A Clip	330
Clips and Stills Maintenance	333
Section 9 — Device Manager Module	335
Overview	335
Devices Tab	336
Messages Tab	337
Mode and Configuration Control	337
Mode Control	338
Active Devices Configurations	338
Operation	340
Place Workstation in LIVE Mode	341
Set Active Devices Configuration	342
Verify Device Status	344
Verify/Clear Message Status	345
Place Workstation in PREP Mode	345
Section 10 — GV Stratus Digital Media Platform Module	347
Overview	347
Production	348
User Interface	348
Event Timeline Tools Menu	348
GV Stratus DMP Task Icon	349
DMP TME Item Type	349
Operation	351
Add DMP Icon to Event Timeline	351
Section 11 — Event Timeline Module	353
Overview	353
Event Timeline Controller	354
Ignite-X Playlist	356
Menu Bar	357
File Menu	357

Edit Menu	357
View Menu	358
Setup Menu	358
Window Menu	360
Help Menu	363
Tools Menu	363
TME™ (Transition Macro Event™)	364
Structure	367
Marks	367
Icons	368
Rundown List/Event Timeline Correlation	369
Import Rundowns	370
Import Rundowns Pre-Load Function	373
Import Rundown Update Indicator	374
Recommended Standard Settings	375
Rundown Import Configuration (Filtering)	376
Operation	377
Import Rundowns	379
Import and Monitor Rundowns	379
Pre-Load Rundown	380
Column Filtering	382
Insert a Note	382
Play/Restart	383
Pause/Stop	383
LBN (Late Breaking News)	383
Manual Override	383
Cursor Relocate/Jump	384
Re-cue	384
Advance Timeline	384
Page Break	385
TMEs (Transition Macro Event)	386
Build a TME	386
Save a TME	388
Modify/Open a TME	389
Set/Check/Change TME Task Properties	390
Manage TME Associations	391
Add TME Associations	391
Edit TME Associations	394
Delete TME Associations	397
Ignite-X Playlist	398
Launch Ignite-X	398
Change Ignite-X view mode	400
View IQ Template parameters in events	402
Modify parameter values of events	403
View event details via the Preview Event Inspector	403
View Ignite-X clip status	405
View connection status to the Ignite server	407
Run the show via the Playlist Controller	407
Change user preferences	408
Section 12 — Ignite IQ Module	409
Overview	409
Ignite IQ Templates	409

Ignite IQ Template Manager	411
Ignite IQ Template Manager – Initial Window	411
Ignite IQ Template Manager – Main Window	412
Menu Bar	413
Template Summary	414
Template Tables	415
Ignite IQ Auto Channel Assignment	417
M/E Tab	419
Video Channels Tab.	419
Common Features: Ignite/Ignite Konnect System and Ignite IQ Module	420
Operation	421
Ignite IQ Template Manager	421
Prerequisites for Creating Ignite IQ Templates.	421
Create an Ignite IQ Template.	422
Import a Parameter Name From An Existing IQ Template.	436
Ignite IQ Auto Channel Assignment	445
Assign Available Channels to an M/E Pool	445
Create a Video Channel Pool	447
Assign Available Channels to a Video Channel Pool.	450
 Section 13 — LBN (Late Breaking News) Module	 455
Overview	455
Operation	456
Create an LBN Hotkey	456
Modify an LBN Hotkey	458
Add an LBN to the Event Timeline.	459
 Section 14 — Show Builder Assistant Module	 461
Overview	461
Operation	463
Search for TMX/IQT via TME Search	463
Search for TMX/IQT via Category	465
Selecting a TMX	466
Import TMX via Import Rundown	467
Copy/Paste Function	467
Refreshing Rundowns.	469
 Section 15 — Switcher Module - Kayak	 471
Overview	471
General Setup Dialog Boxes.	474
Mainframe Setup	475
M/E Setup.	481
Source Setup Dialog Box	481
Configure Source Dialog Box.	482
Master Routing Dialog Box	484
Keyer	486
Effects Management	489
Effect Transition	490
Wipe Effect Setup Dialog Box	492
DPM Effect Setup Dialog Box	493
Keying	517

Key Setup Controls	518
Key Control Signal Adjustment	519
Chroma Key Control Signal Adjustment.	520
Key Setup Dialog Boxes.	522
Luma Key Setup Dialog Box	522
Luma-Linear Key Setup Dialog Box.	523
Additive Key Setup Dialog Box	525
Chroma Key Control Setup Dialog Box.	527
Preset Pattern Setup Dialog Box	532
Mask Setup Dialog Box	533
Matte Setup Dialog Box	534
Transitions	535
M/E Properties Dialog Box.	536
Operation.	538
Customize Switcher Bank	538
Customize Switcher Page.	538
Set Button Properties	541
Switcher Source Setup	543
Scalar Objects.	544
Associate a Video Format with a Scalar Object	545
Modify MatchDef™ Properties of a Scalar Object	547
Keyer.	553
Keyer Setup Menu.	553
Take Keyer To Air	556
Change Keyer Video Association.	556
Effects	557
Notes On Building Effects	557
Create a New Effect	558
Build a Wipe.	560
Build a Cut With a Key.	564
Set Keyer as a DPM.	567
Associate An Effect With a Wipe or DPM Effect	571
Effects Management	572
DPM Effects Management.	575
Effect Transitions.	586
Create a Chroma Key	587
Create a Chroma Key in a Double Box	590
Use the Utility Bus in an Effect.	590

Section 16 — Switcher Module - Konnect 595

Overview	595
Setup Drop-down Menu/Setup Menus	598
Source Setup Dialog Box	599
Master Routing Dialog Box	602
M/E Setup Dialog Box	604
Split M/E Source Equivalence Table Dialog Box.	605
Keyer.	606
Effects Manager.	607
Effects List Group Box	609
Effects Definition Group Box.	611
Transitions/E-MEM/Macros Group Box	612
Preview Effect Group Box	614
TME Property Page Dialog Box	615

M/E Effect Group Box	616
Transitions/Source Routes/OptionsGroup Box	618
IQ Auto Channel Pool Dialog Box	619
M/E Tab	620
Video Channels Tab.	621
IQ Template Manager Dialog Box.	622
Operation	623
Route Services	623
Main User Interface	623
Master Routing.	623
Manage Effects.	625
Create An Effect.	625
Edit An Effect	626
Delete An Effect	628
Perform Transition	629
Recall/Run E-MEM.	629
Run/Pause Master E-MEM	630
Execute Macro	630

Section 17 — General Operation Guidelines 631

Turn On/Off	631
Turn On.	631
Turn Off	631
Start Ignite/Ignite Konnect Software.	632
Start	632
System Status	632
Set Up A New Show	633
Open An Existing Show	634
Software Version	634
Quit Ignite/Ignite Konnect Software	635
Dock/Undock Modules	635
Building a Show	636
Producing a Show	636
Editing a Show	637
Multiple CG Automation	638
Modify CG Conversion Files	638
Coding a Show	639
Column-based Coding	639
Script-based Coding	640
Common Errors	640
Failure Recovery	641
Before a Failure Occurs - Recommendations.	641
All Systems - Network Failure	642
Single/Non-Redundant Failure Recovery.	642
Partial Redundant (Type 1 and 2) Failure Recovery	643
Full Redundant Failure Recovery	644
Failure Recovery From Primary Workstation-A.	645
Failure Recovery From Backup Workstation-B.	646

Index..... 647

Appendix A — Standardization 673

 Folders/Directories 673

 Abbreviations and Names 674

 TME Standards 674

 TME Abbreviations..... 674

 TME Names 676

 TME Effect Names 677

 IQT Standards 677

 IQ Template Abbreviations..... 677

 IQT Parameter Names 678

 IQT Value Abbreviations..... 679

 IQT Effect Names 679

 Color Relationships 680

Glossary..... 681

Preface

About This Manual

This manual is a part of the Ignite/Ignite Konnect Live Production Control System documentation set (refer to [Standard Documentation](#)). As a part of the documentation set, the contents of this manual support a specific purpose in either planning, installation/service, configuration, or use/operation. In all cases, the user is presumed to be familiar with associated concepts and terminology and to have the skills and experience necessary for that purpose.

Standard Documentation

The typical Ignite/Ignite Konnect documentation set comprises:

- Release Notes—When applicable, describes any release-specific information. New features and corrected problems not included in the base manual set are included, as well as software installation procedures.
- Release Notes Addendum—When applicable, describes corrected problems in the current and previous releases as well as any known software problems.
- User Manual—Intended for an Ignite/Ignite Konnect system operator, this manual describes basic operational procedures and provides background information users should understand before they operate the system.
- Installation Manual—Intended for facility engineering staff, this manual describes how to install the product within the customer environment.
- Installation Planning Guide—Briefly describes how the product is physically installed in a facility, including dimensions, power requirements, environmental conditions, and system specifications.

Other Documentation


This Ignite/Ignite Konnect Live Production Control System documentation provides information on the use of the peripheral components as they relate to the Ignite/Ignite Konnect system. For any other peripheral component information, refer to the respective support documentation.

System Overview

The Ignite™ Live Production Control System (Figure 1) is an integrated software and hardware production solution that enables one or two operators to produce and broadcast live high-definition (HD) programs. The Ignite/Ignite Konnect system accomplishes this by functioning as a single point-of-control for the devices used in live television production. This design places special emphasis on live broadcast news and therefore, it is also perfect for non-scripted events such as: election coverage, talk shows, live entertainment segments, and breaking-news stories.

Ignite/Ignite Konnect systems are fully scalable, enabling the video professional to choose the configuration that best fits both their capital budget and production needs.

Figure 1. Ignite/Ignite Konnect System Overview Example




Software Overview

Ignite/Ignite Konnect software combines single-point device control and sophisticated production automation features into a single tri-monitor graphical user interface (GUI) (Figure 2) where:

- The left monitor contains the Audio, Device Control, Device Manager, CG/SS Hotkeys, Camera Preset Hotkeys, and Clock modules.
- The middle monitor contains the Event Timeline, Playlist, Late Breaking News (LBN), and Script/CG List modules.
- The right monitor contains the Switcher module with Mix/Effects (M/E) buses and DPMs.

Figure 2. Ignite/Ignite Konnect Three-Monitor Sample GUI Display



Single-Point Device Control

Control of all production devices (video servers, VTRs, audio servers, audio mixers, video switchers, and cameras) is accomplished from the Ignite/Ignite Konnect GUI via individual device GUIs. Each device GUI has a unique look and color relationship specific to the device being emulated (Figure 3).

Note For a current list of supported/controlled devices, contact an authorized Grass Valley reseller or contact Grass Valley sales directly (refer to *Contacting Grass Valley* on page 4).

Figure 3. Device Control Module Examples (Video Server, VTR, Audio, RAM Recorder, ENCO)



A Device Manager (Figure 4) monitors the status of each device and provides event messages and status indicators to the operator. It provides the ability to change device configurations, and it also provides the ability to take or relinquish control of all production devices with the click of a button, by placing the workstation in the **LIVE** or **PREP** mode, in Ignite/Ignite Konnect systems with redundancy (refer to [Redundancy Options on page 29](#)).

Figure 4. Device Manager GUI



Production Automation

Production automation is accomplished using Transition Macro™ Events (TME). A TME is a group of individual production tasks that are combined to create an automated video production event. TMEs are created, saved, and recalled as necessary to automate and control the look, feel, and flow of a broadcast. Show-specific TMEs are then placed, in order, on the Event Timeline GUI. The timeline cursor sequentially executes each of the TMEs as its progresses along the timeline. Dynamic script synchronization keeps scripts synced to the timeline event changes.

A Newsroom Computer System (NCS) interface supports rundown conversion of news commands using TME associations. TME associations are automation directives embedded by the Director into news items on iNEWS and ENPS (MOS based) news systems. The Ignite/Ignite Konnect rundown converter retrieves and parses the rundown from the NCS, then automatically creates a show on the Ignite/Ignite Konnect event timeline based on the TME associations.

Late Breaking News (LBN) events are quickly and easily handled via LBN hotkeys. TMEs or sequences of multiple TMEs stored on any of 308 LBN hotkeys are inserted into the timeline for execution anytime during a show.

Remote Client

The remote client supports the Ignite-X Playlist, which displays the same sequence of events as the Ignite Event Timeline, but in a vertical list for users to easily navigate within a show. Events can be added, removed, edited, re-ordered, and filtered from within the playlist. The Playlist can either be embedded in the Event Timeline Module, or installed separately on a remote device accessible anywhere as long as it is connected to the Ignite server.

The Playlist supports the ability to display side-by-side the text-based vertical list view, and the block view for sequence of events on the Timeline. This is beneficial for Directors and Producers to monitor critical information in one place on the user interface. Users can also select a rundown from the list of rundowns, display and collapse items by segment, story, event and element, scroll past, present and future events, and refresh NCS updates directly via the Playlist Controller.

Figure 5. The Ignite-X Playlist on the remote client



Hardware Overview

Ignite™ Live Production Control Systems are modular and fully scalable, enabling the video professional to choose the configuration that best fits their production needs. Ignite/Ignite Konnect systems are available in HD switchable formats from 1 – 5 M/Es. The number of available M/Es depends on the installed switcher.

Core Components

Ignite/Ignite Konnect systems include the core hardware components listed in [Table 1](#). Core component configurations are determined by

selecting a standard system and adding production specific and redundancy options (refer to [Options on page 26](#)).

Table 1. Ignite/Ignite Konnect System Basic Configuration

Component	Description
Firewall	Provides intrusion prevention for the Ignite/Ignite Konnect network and reduces Ignite/Ignite Konnect system network traffic by isolating it from the facility (house) LAN (with the exception of a connection to the facility provided XMOS/MOP server).
Network Switch	28-port, 10/100/1000 Gigabit Ethernet switch provides connection to all Ignite/Ignite Konnect TCP/IP network devices. RJ45, auto-sensing ports detect and adjust their speed and duplex (half or full) to the connected device.
Automation CPU	Dual-processor with quad VGA graphics card and internal RAID drive array running Ignite/Ignite Konnect application software in a Windows™ operating system environment.
Remote Client	Provides control of the Ignite server via the Ignite client on a remote PC.
Video Switcher	Grass Valley™ K-Frame™, Kayenne™, Kayak™ digital production switchers
Serial Control Module	Enables communications with the serial devices via an ethernet network connection to the serial device control module interface. Device ports are software configurable RS-422 or RS-232 for controlling a wide range of devices.
Tally Expander	64 GPO relays for external device control operated through logic parameters or commands on the Ignite/Ignite Konnect event timeline. 32 GPI connections to control the Ignite/Ignite Konnect event timeline. Controlled through network connection using standard IP protocol.
Multi-Monitor Display Workstation	3 Ignite/Ignite Konnect GUI 20" VGA LCD monitors, keyboard, optical mouse, Ignite Katalyst™ panel, audio processor 19" VGA LCD monitor, keyboard, and optical mouse.
Ignite Katalyst Panel	<p>A compact, tactile, Ignite/Ignite Konnect automation-interface panel that works dynamically with Ignite/Ignite Konnect software to replace cumbersome traditional switchers and audio panels. It has 10-pages of 24-programmable keys (240 total) and 16 motorized, dynamic audio faders with audio control buttons for Hold. Button and fader configurations are easily programmed to store and recall simple or complex functions such as Manual Video Switching & Audio Mixing, Event Timeline Next Event Command, Manual CG & Keyer Controls, GPI Triggers, ShowBuilder Key Insert & Take Commands, and Audio Talk-Back. However Cue, Hold, & Group Commands are for specific third party audio mixers only.</p> <p>NOTE: The Ignite Katalyst™ panel is not required for Ignite/Ignite Konnect Live Production Control system operation but rather provides an alternate, manual event-triggering capability.</p> <p>NOTE: Audio option is required for audio fader modules to operate.</p>

Options

Customer-specific production and redundancy options are integrated into a selected standard system to produce a cost-effective, customized production solution for every user.

Production Options

Production options are listed in [Table 2](#).

Table 2. Production Options

Option	Description
Yamaha Audio Control	<p>This option provides Ignite/Ignite Konnect with the capabilities to use Yamaha Mixer LS9 (-16 and -32) series as an alternative choice to the Klotz audio processor.</p> <p>Standard Ignite/Ignite Konnect system audio processor hardware is omitted from the purchase order, and the Ignite/Ignite Konnect application is installed with Yamaha audio control component/functionality.</p> <p>Note Ignite audio option is required. The customer must provide all necessary audio processing hardware.</p>
Wheatstone Audio Control	<p>This option provides Ignite/Ignite Konnect with an automation interface to the D-10 panel. For panel-specific user and set up information, refer to the manufacturer's documentation.</p> <p>Standard Ignite/Ignite Konnect system audio processor hardware is omitted from the purchase order, and the Ignite/Ignite Konnect application is installed with Wheatstone audio control component/functionality.</p> <p>Note Ignite audio option is required. The customer must provide all necessary audio processing hardware.</p>
Calrec Audio Control	<p>This option provides Ignite/Ignite Konnect with an automation interface to the Calrec panel. For panel-specific user and set up information, refer to the manufacturer's documentation.</p> <p>Standard Ignite/Ignite Konnect system audio processor hardware is omitted from the purchase order, and the Ignite/Ignite Konnect application is installed with Calrec audio control component/functionality.</p> <p>Note Ignite audio option is required. The customer must provide all necessary audio processing hardware.</p>
Klotz Audio Control	<p>This option provides Ignite/Ignite Konnect with an automation interface to the Klotz panel. For panel-specific user and set up information, refer to the manufacturer's documentation.</p> <p>Standard Ignite/Ignite Konnect system audio processor hardware is omitted from the purchase order, and the Ignite/Ignite Konnect application is installed with Klotz audio control component/functionality.</p> <p>Note Ignite audio option is required. The customer must provide all necessary audio processing hardware.</p>
Lawo Audio Control	<p>This option provides Ignite/Ignite Konnect with an automation interface to the Lawo panel. For panel-specific user and set up information, refer to the manufacturer's documentation.</p> <p>Standard Ignite/Ignite Konnect system audio processor hardware is omitted from the purchase order, and the Ignite/Ignite Konnect application is installed with Lawo audio control component/functionality.</p> <p>Note Ignite audio option is required. The customer must provide all necessary audio processing hardware.</p>
SSL Audio Control	<p>This option provides Ignite/Ignite Konnect with an automation interface to the SSL panel. For panel-specific user and set up information, refer to the manufacturer's documentation.</p> <p>Standard Ignite/Ignite Konnect system audio processor hardware is omitted from the purchase order, and the Ignite/Ignite Konnect application is installed with SSL audio control component/functionality.</p> <p>Note Ignite audio option is required. The customer must provide all necessary audio processing hardware.</p>

Table 2. Production Options

Option	Description
Ignite/Ignite Konnect Without Audio	<p>This option is for customers who for financial or technical reasons, wish to control audio outside of the Ignite/Ignite Konnect system.</p> <p>Standard Ignite/Ignite Konnect system audio processor and Ignite Katalyst™ hardware are omitted from the purchase order, and the Ignite/Ignite Konnect application is installed without audio control component/functionality.</p> <p>Note The customer must provide all necessary audio processing hardware. .</p>
Kayak	This option is for GV Kayak switchers.
Konnect	This option is for GV Kayenne and Kalypto switchers.
GV Director	This option is for GV Director switchers.
Timed Events	Timed Events options are pre-defined actions that occur at specific times and triggered via TME. When it's time to play an event, the TME contained within the event is executed.
Serial Control:	16 serial control ports can be added to the 16 serial control ports of the Ignite/Ignite Konnect base system (for a total of 32).
Video – Manual Control Panel:	The Control panel is not intended to work while in automation mode with a Kayak switcher. With K-Frame the switcher frame can be used in suites mode to assign M/Es to another control panel however; the switcher control panel should never be used with the same suite as Ignite automation.
Prep Workstation:	<p>The second system that allows one director to prepare their show while another show is aired from the LIVE system. The Prep workstation includes 3 Ignite/Ignite Konnect GUI 20" VGA LCD monitors, keyboard, optical mouse.</p> <p>Note This does not include a second Ignite server. (The CPM-6001 is sold separately).</p>

Redundancy Options


Note Redundancy is the duplication of critical components of the system to increase system reliability in the form of backup (or fail-safe) operation.

Redundancy options are listed in [Table 3](#) and illustrated in [Figure 6](#).

Table 3. Redundancy Options


Option	Description
Single (Non-Redundant)	Single Ignite/Ignite Konnect systems have no backup for prep or recovery other than dual power supplies, dual controllers, dual NIC cards, and/or circuit card hot-swap capabilities built into individual system components.
Partially Redundant (Type 1)	<p>Adds a backup Ignite/Ignite Konnect CPU and requires a Customer Furnished Equipment KVMrouter for routing between the primary (A system) and backup (B system) CPUs.</p> <p>Note Does not include additional component mainframes or additional workstation.</p>
Partially Redundant (Type 2)	<p>Includes all Type 1 components plus a Prep workstation. The Prep workstation includes 3 Ignite/Ignite Konnect GUI 20" VGA LCD monitors, keyboard, and optical mouse.</p> <p>Note Does not include a second Ignite CPU and additional component mainframes. The CPM-6001 is sold separately. With this configuration, one workstation is in LIVE mode with full device control while the other is in PREP mode with the ability to rundown convert and check converted TMEs on the Ignite/Ignite Konnect timeline.</p>

Figure 6. Redundancy Options



Audio Module

Figure 7. Example Audio Module - Klotz Audio Configuration



Overview

Note This Audio Module section covers the Klotz, Yamaha, Wheatstone, Calrec, Lawo, and Studer configurations only. For a No Audio configuration, the entire audio module area is blank and this Audio Module information does not apply.

Depending upon the Ignite/Ignite Konnect system configuration, there are five possible audio control configurations:

- Klotz Audio control ([Klotz Audio on page 35](#))
- Yamaha (LS9) Audio control ([Yamaha Audio on page 95](#))
- Wheatstone [D-8 and D-10 only] Audio control ([Wheatstone Audio on page 125](#))

- Calrec, Lawo, and Studer Audio control ([Calrec, Lawo, and Studer Audio on page 165](#))
- No Audio control, where audio is controlled solely from a separate control panel with no Ignite/Ignite Konnect user interface.

Note For a specific audio interface, refer to that respective audio description in this section.

From an Ignite/Ignite Konnect Audio Module perspective, the differences among the Klotz audio, Yamaha audio, Wheatstone audio, Calrec, Lawo, and Studer audio configurations are listed in [Table 4](#).

Table 4. Ignite/Ignite Konnect Audio Configuration Comparisons

Characteristic	Klotz Vadis Audio	Yamaha Mixer LS9	Wheatstone [D-10 only]	Calrec/Lawo/Studer Mixer
Inputs	up to 96 stereo/192 mono	32 mono inputs (up to 64 with an add-in card)	Note Dependent on the Wheatstone configuration installed	Note Dependent on the Calrec configuration installed
Outputs	up to 48 stereo/96 mono	16 mono outputs (up to 48 with an add-in card)	Note Dependent on the Wheatstone configuration installed	Note Dependent on the Calrec configuration installed
Input Faders	16 mono/stereo faders	64 mono faders and 64 mono input channels. All 64 inputs can be on-air simultaneously	up to 36	Note Dependent on the Calrec console model. Calrec Alpha, Omega, Sigma, Zeta, Lawo mc² 56, and Studer Vista models are supported by Ignite
Cue Bus	One independent cue bus	Cue Input and Output.	Pre-fade and post-fade cue for channel strips only	Pre-fade Listen for channel faders and main faders
Monitor Channels	4	1	4	4
Monitor Sources	1 source at a time. Route sources to monitor channel for monitoring.	Selectable multiple monitor sources. Cue the source for monitoring (prefader)	N/A	N/A
Foldback Destinations	Uses Klotz dynamic mix minus features. 16 stereo mixers available for Foldback destinations	N/A	N/A	N/A
Aux Buses	6 aux buses	No aux buses provided. Up to 4 aux mixers can be used as aux buses	4 (Master fader control only)	Up to 4 (Main fader control only)
Mix type input channels	Stereo, stereo L(ef), stereo R(ight), and mono	Stereo and mono. A control is used to select either left or right source.	N/A	N/A
Input Channel Trim Gain Min/Max	-120 dB / +18 dB	-60 dB / +10 dB	N/A	N/A
Program and Aux Fader Min/Max	-60 dB / 0 dB	-60 dB / +10 dB	-72dB/0 dB	-100dB/ +10 dB
Cue Fader Min/Max	-60 dB / 0 dB	-20 dB / +10 dB	-72dB/0 dB	-100dB/ +10 dB

There are pages of user definable audio faders that provide the ability to customize the audio setup. Each fader control label is user definable. The Audio Module ([Figure 7](#)) includes:

- Individual faders – depending on the Ignite/Ignite Konnect system configuration, up to 16 available slots on each page for user definable audio faders that provide a user with the ability to customize the audio setup.

Note There are eight configurable pages for Klotz, Yamaha, and Wheatstone; while twelve pages for Calrec, Lawo, and Studer. Each available page is logically subdivided into 16 fader slots.

- Master Output faders – user controlled fader for the overall audio output level of the channel
- Audio **Preview** – shows the sources set to move On Air next
- Audio Program/Live – shows the Program sources
- Set Points – define a specific level between the maximum and minimum levels (i.e. a specific level between -128dB and 15dB in Lawo. 0dB for instance). Set points can be assigned custom colors and names to distinguish among them. (Set Points are called Preset Positions for Lawo and Studer)
- **Audio Main Context Menu** for each fader control (refer to [Table 5](#) and [Audio Main Context Menu on page 42](#))

Note The Calrec audio interface does not use an Audio Main Context Menu. Instead, the Calrec audio configuration is accomplished through a Virtual Source Configuration dialog box.

Table 5. Audio Main Context Menu

Klotz Audio Main Context Menu	Yamaha Audio Main Context Menu	Wheatstone Audio Main Context Menu
• Clear Fader	• Clear Fader	• Clear Virtual Source
• Virtual Source Maintenance	• Virtual Source Maintenance	• Virtual Source Maintenance
• Source Maintenance		• Import Virtual Source
• Audio Profile Maintenance		• Layouts
• Aux Configuration		
• Talk Back Source Selection		
• Monitor Source Selection		
• Point-to-Point Routing		

The Audio Module does not directly act on sources when setting levels, creating mixes, or applying signal processing. Any action that would change how a source is used in the mixer is actually accomplished through an entity known as a virtual source.

A virtual source acts as a container for a target source (known as the Primary Source), the primary source's optional back up source (known as the Backup Source), and the source's optional Foldback Path (the destination to which the source's mix minus is sent).

Note Only the Klotz implementation currently has the ability to route mix minus and foldback content. For the other implementations, these tasks are manually configured on the mixer by the user.


Because the Audio Module uses a virtual source to manipulate the audio content of the mixer, actions triggered either by automation or by the user manually are executed regardless of whether the primary or back up sources are currently active.

Note Before the audio can be controlled, virtual sources must be created and configured. Typically this is accomplished during initial installation.

The Audio Module also provides the ability to configure certain audio properties that are closely tied to specific sources independent of the controlling virtual source. The properties are adjusted via the virtual source control as the virtual source active source changes. These settings include Trim Gain, Mix Type, EQ, Compression, Expansion, Limiting, and Delay.

Klotz Audio

Figure 8. Audio Module - Klotz Audio



Overview

Note The Ignite/Ignite Konnect system provides an automation interface ([Figure 8](#)) to the Klotz Audio.

Fader Manual Virtual Source Control

In order to control a virtual source from within the Audio Module, a fader control must be created to represent the virtual source visually (refer to [Create a Fader Control on page 63](#)). Otherwise, the virtual source idly waits in the background for commands from Ignite/Ignite Konnect Timeline Automation or external fader control surfaces such as the QUICbox™ panel.

Individual Faders





Each fader control has four buttons (Figure 9) at the top:

- **B** (Backup)
- **C** (Cue)
- **T** (Talk Back)
- **H** (Hold)

When either the **B**, **C**, or **T** button is clicked, the button background highlights blue to indicate it is selected. When the **H** button is clicked, both the button background and the fader perimeter highlight amber to indicate it is selected.

Note For all of the buttons, a gray background indicates it is not selected.

Figure 9. Fader Buttons – Klotz

Selected	Function
	Backup – switches to a backup. Click to make the attached backup source the active source in the mix. This button has no effect if a backup source was not selected for the virtual source during configuration.
	Hold – holds a source on or off air. Click to hold the fader control at the current level. If the fader control is currently engaged in a fade triggered by automation, the fade is allowed to continue and the fader will be held at the final level resulting from the fade.
	Cue – monitors a channel. Click to add the attached virtual source into the Cue mix bus. The Cue bus mix is a pre-fade mix where sources enter the mix at unity gain.
	Talk back – provides a talk back channel. Click to insert talk back audio into the Fold Back path of the attached virtual source. This button has no effect if the attached virtual source did not have a Foldback Destination selected during virtual source configuration.


Fader control handles are used to adjust the virtual source active source level in the Program mix and any Aux mix in which the virtual source is included. Double-click the fader control above or below the fader handle to

force the active source to jump or cut to the desired volume. A manual fade is achieved by dragging the fader handle to the desired level.

Also, there are two different fader control handles (Figure 10):

- Mono – a single fader control that functions individually
- Stereo – a pair of handles that move as a single fader


Figure 10. Fader Control Handles – Klotz Audio



Audio Preview

Virtual sources transitioned via the Ignite/Ignite Konnect Event Timeline are populated into the **Audio Preview** area (Figure 11) as each TME is prepped. The virtual sources set to move to air next are shown in the **Audio Preview** area.

Figure 11. Audio Preview Area




Audio Program (LIVE)

The **Audio Program** area (Figure 12) shows the virtual sources presently On Air. Any virtual source that is moved above its off point is taken to air instantly and is shown in the **Audio Program** area.

Note Only the 8 most recent virtual sources to go on air and still exist on air are shown. Once 9 virtual sources are on air, the oldest on-air virtual source disappears and reappears if another is taken off air.

Figure 12. Audio Program Area



Set Points

Set Points are pre-established fader settings that are referenced via a TME (Transition Macro Event), refer to *TME™ (Transition Macro Event™)* [on](#)


[page 255](#). These set points set a source level for each source. Set Points can be named for easy reference. Via Event Timeline automation, each TME provides the system with the audio set point needed for that particular event.

To access the **Set Points Menu** ([Figure 13](#)), within a fader, right-click near the left edge of the fader control. The **Set Points Menu** has two selections:

- **Set Point Maintenance** – accesses the **Set Point Maintenance** dialog box
- **Clear All Fader Set Points** – clears all fader set points

Note The **Set Point Maintenance** dialog box opens in the same state regardless of where the user right-clicked to access the **Set Point Menu**. However, if a set point is loaded from this dialog, the set point is loaded to the fader that was right-clicked to access the **Set Point Menu**.

Figure 13. Set Point Menu



Set points must be created before creating audio tasks. A set point does not need to be assigned to a virtual source in order for the virtual source to use the set point, but at least one set point must exist. There are two default set-points that are system defined and non-editable by the user:


- **OFF** – used to bring a Virtual Source off air.
- **IGNORE** – used to flag a Virtual Source so that it will not be affected by the **Take All Sources to Zero** feature of Audio TMEs.

A set point does not need to be loaded in order to be assigned in a task. However, it does need to be loaded if the user wishes to modify the set point position for a particular virtual source during a show.

Set Point Maintenance

The **Set Point Maintenance** dialog box ([Figure 14](#)) is accessed from the **Set Points Menu**. This dialog box is used to create, edit, delete, or load set points.

Figure 14. Set Point Maintenance Dialog Box



Note All set points created via Set Point Maintenance are available globally for use by every virtual source in creating tasks for audio timeline objects.

The **Set Point Maintenance** dialog box includes:

- **OK** – saves the changes and closes the dialog box.
- **Load** - loads the selected set point to the fader that was right-clicked to access the **Set Point Menu**. A fader can only have one instance of the same set point loaded. When attempting to load a set point to a fader that already has the set point loaded, a Set Point already loaded message appears.
- **Add** - accesses the **Set Point Editor** dialog box with a new Set Point definition. If appropriately configured, the set point is created and added to the list.
- **Edit** - accesses the **Set Point Editor** for the selected Set Point changes.
- **Delete** – the **Delete Entry?** message appears.

Note Any TME audio task referencing a deleted setpoint will be unable to affect the associated virtual source during a transition. Such audio tasks automatically execute their transition using the OFF setpoint.

Click **Yes** to continue deleting the selected Set Point and immediately save the configuration to reflect the deletion. Click **No** to keep/not delete the item at this time and continue making changes.


- **Close** button– closes the dialog box without saving changes.

Set Point Editor

The **Set Point Editor** dialog box (Figure 15) is accessed from the **Set Point Maintenance** dialog box **Edit** button (Figure 14 on page 39).

Note All set points created via Set Point Maintenance are available globally for use by every source in creating tasks for audio timeline objects.

Figure 15. Set Point Editor Dialog Box



The **Set Point Editor** dialog box includes:

- **Color Selection** - changes the color of the target Set Point. Click a color to assign.
- **Volume Level** - click and drag to set the target volume level. Users can also use the Up-Down control attached to the **Value(dB)** field to achieve the same results.
- **OK** – saves the new/edited changes and closes the dialog box.

Note Before changing/saving, verifies that the Set Point Name is unique among Set Points and that the name does not match the default **Off** or **Ignore** Set Points name in any way. If invalid, a message appears stating the need and nature of the required change.

- **Cancel** – compares the saved configuration and the currently shown configuration. If no changes exist, the dialog box closes. If changes have been made, a **Cancel Changes?** message appears.


Click **Yes** to undo changes in real time and close the **Set Point Editor** dialog box. Click **No** to continue making configuration changes.

- **Close** button – closes the dialog box without saving changes.

Master Output Faders

The **Master Output Fader** (Figure 16) provides master control of the overall audio output level of the **Master Out Left** and **Master Out Right** channels. Five buttons comprise the various Master Volume Controls.

Figure 16. Master Output Fader



PGM

Updates the master faders to reflect the PGM volume and assumes control of that volume. When exiting AUX or MON dialog box control, PGM is the default/active volume control.

AUX

Accesses a separate Aux volume control dialog box that enables real time volume control of a single, selected Aux (Aux 1 through Aux 6). Clicking Done returns control to PGM.

CUE

Updates the master faders to reflect the CUE volume and assumes control of that volume.


MON

Accesses a separate Mon volume control dialog box that enables real time volume control of a single, selected Mon (Mon 1 through Mon 4). Clicking Done returns control to PGM.


TB

Updates the master faders to reflect the TB volume and assumes control of that volume.

Aux Volume Control Dialog Box



Mon Volume Control Dialog Box




The **PGM**, **CUE**, and **TB** buttons function similarly. When the respective button is clicked, the main faders update to reflect and assume control of that volume; i.e., **PGM**, **CUE**, or **TB**. When either the **AUX** or **MON** button is selected, a separate dialog box appears to enable specific selection of a particular Aux or Monitor to control. In any case, all changes are real time and take effect immediately

Note When exiting **AUX** or **MON** dialog box control, **PGM** is the default/active volume control.

Audio Main Context Menu

To access the **Audio Main Context Menu** (Figure 17), right-click near the right edge of a fader control.

Figure 17. Audio Main Context Menu – Klotz Audio



The **Audio Main Context Menu** items for the Klotz audio configuration are:


Audio Main Context Menu Item	Purpose
Clear Fader	Removes the selected fader (virtual source control) from view and replaces it with an empty slot. This does not delete the fader-associated virtual source, but that specific virtual source control (fader) is simply not shown. That audio virtual source (or any available audio virtual source) can be imported to an empty slot as a fader control using the Virtual Source Maintenance menu item. Refer to Virtual Source Maintenance Dialog Box on page 44 NOTE: This menu item is only available if a fader is selected (right-click). Refer to Figure 17 .
Virtual Source Maintenance	Accesses the Virtual Source Maintenance dialog box that enables a user to either edit or import a virtual audio source. Refer to Virtual Source Maintenance Dialog Box on page 44
Source Maintenance	Accesses the Source Maintenance dialog box that enables a user to edit source-specific properties; e.g., Trim Gain, Mixing Mode (whether or not the source is inserted into the mix as Stereo, Mono, Left Only, or Right Only), and the Audio Profile to be used by the Source. The Audio Profile can include settings for Parametric EQ, Dynamics, or Delay depending on the system type. Refer to Source Maintenance Dialog Box on page 48
Audio Profile Maintenance	Accesses the Audio Profile Maintenance dialog box that enables a user to create and edit Audio Profiles. Each created Audio Profile is edited using this dialog box. Refer to Audio Profile Maintenance on page 50
Aux Configuration	Accesses the Aux Configuration dialog box that enables a user to add and remove the configured virtual sources from the available Aux Bus mixes. Refer to Aux Configuration on page 57
Talk Back Source Selection	Accesses the Talk Back Source Selection dialog box that enables a user to select the System's Talk Back source. Refer to Talk Back Source Selection on page 58

Audio Main Context Menu Item -	Purpose - (continued)
Monitor Source Selection	Selecting this option opens the Monitor Source Selection Dialog Box. The user can select sources to drive the inputs of the available Monitors in the system using this configuration tool. Refer to Monitor Source Selection on page 59
Point-to-Point Routing	This option presents the user with the Point to Point Routing dialog box. The Point to Point Routing feature enables the user to route physical inputs (sources) directly to physical outputs (destinations). Refer to Point To Point Routing on page 61

Virtual Source Maintenance Dialog Box

The **Virtual Source Maintenance** dialog box ([Figure 18](#)) is accessed from the **Audio Main Context Menu**. The **Virtual Source Maintenance** dialog box provides a list of available virtual audio sources and from that list a user can either import a virtual source to the selected slot or edit/configure an already assigned virtual source.

Figure 18. Virtual Source Maintenance Dialog Box



Note If the **Audio Main Context Menu** is accessed via right-click near the edge of a fader, the **Virtual Source Maintenance** dialog box opens with the virtual source for the targeted fader already selected. If the **Audio Main Context Menu** is accessed via right-click on an empty fader slot, the first virtual source in the list is selected by default.

The **Virtual Source Maintenance** dialog box ([Figure 19](#)) includes:

- **Select a Virtual Source** – lists a source ID, virtual source name, and source abbreviation for each available virtual source. Any un-configured virtual source name and abbreviation is shown as a series of dashes.
- **OK** – saves the changes and closes the dialog box.

- **Import** – imports the selected virtual source to either a fader or an empty fader slot. The import position is based on the fader slot used to access the **Audio Main Context Menu**. If the fader slot is already populated by a fader, that virtual source is replaced with the virtual source selected from the **Select a Virtual Source** list.


Note Import is unavailable if a non-configured virtual source is selected.

- **Edit** – opens the **Virtual Source Editor** dialog box (refer to [Virtual Source Editor Dialog Box on page 45](#)). The **Virtual Source Editor** dialog box opens in one of two modes, either **Edit** mode (if the selected virtual source is already configured) or **Configuration** mode (if the selected virtual source is not configured).

Note When in Edit Mode, the Editor forces real time configuration change updates to the virtual source but in Configuration Mode it does not.

- **Erase** – deletes the virtual source entry. Any TME audio task associated with an erased virtual source will cease to function properly until the virtual source is re-configured.
- **Close** button – closes the dialog box without saving changes.

Figure 19. Virtual Source Maintenance Dialog Box




Virtual Source Editor Dialog Box

The **Virtual Source Editor** dialog box (Figure 20) is accessed from the **Virtual Source Maintenance** dialog box **Edit** button (Figure 19 on page 45). It enables a user to create and configure virtual sources for use in TMEs and to edit the configuration of an existing virtual source in real time. The **Virtual Source Editor** dialog box opens in one of two modes, either **Edit** mode (if the

selected virtual source is already configured) or **Configuration** mode (if the selected virtual source is not configured).

- **Edit Mode** - when configuring a pre-existing virtual source, the changes to **Primary**, **Backup**, and **Foldback Destination Mappings** take effect in real time. This feature enables a user to make critical alterations while Audio is live.
- **Configuration Mode** - when configuring a brand new virtual source. Since there is no way for a non-configured virtual source to be associated with a **fader control** or become part of a mix, there is little reason or validity to sending real time updates to any of the settings that the user alters.

Figure 20. Virtual Source Editor Dialog Box



The **Virtual Source Editor** dialog box (Figure 20) includes:

- **Virtual Source Identification** – text boxes for a user defined **Virtual Source Name** and **Abbreviation**.
 - **Name** – limited to 25 characters and is system monitored to prevent duplicates. This name is used to identify the virtual source in other configuration dialog boxes as well as System Error Logs.

- **Abbreviation** – limited to 4 characters and is system monitored to prevent duplicates. This abbreviation is the only identifier that appears on the fader control associated with that virtual source. This abbreviation is also used, along with the name, to identify the virtual source in other configuration dialog boxes as well as System Error Logs.
- **Sources** tab – Source Mapping enables a user to select the **Primary** and **Backup** source audio content that is inserted into a mix when the virtual source is either in Cue or On-Air.
 - **Primary** – shows the name of the currently mapped **Primary** source or **No Source** if a source is not mapped. A virtual source must have a mapped **Primary** source in order to complete the configuration.
The **Map** button assigns the selected source as the **Primary** source. Since a primary source must exist before the configuration can be completed, the **Map** button is disabled when the user selects **Do not use Source** from the **Sources** list box.
 - **Backup** – shows the name of the currently mapped **Backup** source or **No Source** if a source is not mapped. The **Map** button assigns the selected source as the **Backup** source. A **Backup** source does not have to be mapped. Selecting **Do not use Source** and clicking **Map** removes any previously mapped backup source and replaces it with a **No Source** entry. If a virtual source does not have a mapped backup source, the **Backup** button on any fader control to which that virtual source is associated has no effect when clicked.
- **Foldback** tab – enables a user to select the destination where the **Virtual Source Foldback** (return) audio is sent. This could include Mix Minus, Talk back, or Program Audio. The **Foldback** path is the physical output to which that audio content will be routed. If the virtual source does not have a Foldback path, the **Foldback** box shows **No Foldback**.
- Effects Send/Return tab (optionally):
 - Provides **Effects Send Destination Mapping** for the Virtual Source. When **Effects Send** is enabled and the Virtual Source is on air, the input channel signal path will be routed to this mapped destination.
 - Provides **Effects Return Source Mapping** for the Virtual Source.
 - Provides the ability to Enable/Disable the Effects Send/Return loop for the Virtual Source.

Enables/Disables the Effects Send. Effects Send is automatically disabled if the Effects Send Destination mapping is set to **Do not use Effects Send**.

CAUTION Failure to specify an Effects Return Source when Effects Send is enabled prevents the Virtual Source signal from getting to the mixer. The Virtual Source will not be present in the Program mix or any of the Aux mixes.

CAUTION Using Effects Send/Return loops introduces a point of failure into the input channel signal path. If the outboard processing unit fails to return audio to the Return Source, the Virtual Source signal does not reach the mixer and will not be present in the Program mix or any of the Aux mixes.

Note When the Effects Send is enabled and the Virtual Source is on air, the mapped Source is routed into the next stage in the input signal path.

- **OK** – verifies that the **Name** and **Abbreviation** boxes contain valid entries, confirms that a primary source is mapped to the virtual source, updates and saves the virtual source entry, then closes the dialog box.

Note If any **OK** condition is not met, an error dialog box appears to notify the user about the discrepancy, the change is not saved, and the **Virtual Source Editor** dialog box is not closed.


- **Cancel** – click functionality depends on the current dialog box mode: **Edit** or **Configuration**.
 - When in **Edit Mode**, if configuration changes have been made, a **Cancel Changes?** message appears.
Click **Yes** to undo changes and close the **Virtual Source Editor** dialog box. Click **No** to continue making configuration changes.
 - When in **Configuration** mode, the new virtual source entry is not created or saved and the dialog box closes.
- **Close** button – closes the dialog box without saving changes.

Source Maintenance Dialog Box

The **Source Maintenance** dialog box ([Figure 21](#)) is accessed from the **Audio Main Context Menu**. This dialog box is used to control audio content properties specific to **Sources**, not **Virtual Sources**. For instance, microphone EQ settings should be tied to the microphone itself and not the virtual source that uses it.

Note The Source Maintenance dialog box opens in the same state regardless of which strip was right-clicked to open the **Audio Main Context Menu**.

Figure 21. Source Maintenance Dialog Box



The **Source Maintenance** dialog box (Figure 21) includes:

- **Sources** – lists all user defined sources present in the Audio configuration. Included in each entry are the source port number, name, and active audio profile name.
- **Gain Trim (dB)** – edits the selected source gain trim value. Changes are updated in real time.
- **Mix Type** – edits the selected source mix type. Changes made using this control are updated in real time. There are 4 Mix Types:
 - **Stereo** – inserts the source L channel into the L channel of the stereo mix and inserts the source R channel into the R channel of the stereo mix.
 - **L Only** – the L channel of the source is inserted into both the L and R channels of the stereo mix.
 - **R Only** – the R channel of the source is inserted into the L and R channels of the stereo mix.
 - **Mono** – the L and R channels of the sources are summed with a -3 dB gain drop and the sum is inserted into both the L and R channels of the stereo mix.

- **Audio Profiles** – lists all available Audio Profiles. This control is used to assign an Audio Profile to the selected source. Making a selection with this control does not affect the selected source active profile.
- **Apply Selected Profile** – assigns the selected Audio Profile to the selected source. This update is made in real time.
- **OK** – saves the changes and closes the dialog box.
- **Cancel** – compares the saved configuration with the currently shown configuration. If no changes exist, the dialog box closes. If changes have been made, a **Cancel Changes?** message appears.

Click **Yes** to undo changes in real time and close the **Source Maintenance** dialog box. Click **No** to continue making configuration changes.


- **Close** button – closes the dialog box without saving.

Audio Profile Maintenance

The **Audio Profile Maintenance** dialog box (Figure 22) is accessed from the **Audio Main Context Menu**. This dialog box is used to create, delete, and/or edit Audio Profiles.

Note The **Audio Profile Maintenance** dialog box is not specific to individual faders. Therefore, the **Audio Profile Maintenance** menu item is available regardless of where, in the Audio fader area, a right-click is used to access the **Audio Main Context Menu**; i.e., either a fader or an empty fader slot.

Figure 22. Audio Profile Maintenance Dialog Box



The **Audio Profile Maintenance** dialog box (Figure 22) includes:

- **OK** – saves the changes and closes the dialog box.
- **Add** – causes the dialog to retrieve the next available Audio Profile ID and apply it to a newly created Audio Profile. The new Audio Profile is given the default name New Audio Profile X; where X is the Audio Profile ID. The name of the Audio Profile is then added to the list of existing profiles and the configuration is saved to reflect the addition of the new profile.
- **Edit** – loads the selected Audio Profile into a new instance of the **Audio Profile Editor** dialog box (refer to [Audio Profile Editor Dialog Box on page 51](#)). If there are no available or selected Audio Profiles, this button has no effect.
- **Delete** – the **Delete Entry?** message appears.

Click **Yes** to continue deleting the selected Audio Profile, update all affected sources, in real time, to **[No Profile]**, and immediately save the configuration to reflect the deletion. Click **No** to keep/not delete the item at this time and continue making configuration changes.

- **Close** button – closes the dialog box without saving changes.

Audio Profile Editor Dialog Box

The **Audio Profile Editor** dialog box (Figure 23) is accessed from the **Audio Profile Maintenance** dialog box **Edit** button (Figure 22 on page 50).

Figure 23. Audio Profile Editor Dialog Box



The **Audio Profile Editor** dialog box includes:

- A **Profile Name** box that shows the Audio Profile name selected for editing. That name can also be edited in this box.
- Depending on system configuration, Dynamic Audio tabs for each enabled module in the Audio configuration:
 - Equalizer ([Audio Profile Editor Equalizer Dialog Box on page 52](#))
 - Dynamics ([Audio Profile Editor Dynamics Dialog Box on page 54](#))
 - Delay ([Audio Profile Editor Delay Dialog Box on page 56](#))

Note Each available tab has the current settings and available editing controls for the selected Audio Profile.

- **OK** – saves the changes and closes the dialog box.
- **Cancel** – compares the saved configuration and the currently shown configuration. If no changes exist, the dialog box closes. If changes have been made, a **Cancel Changes?** message appears.

Click **Yes** to undo changes in real time and close the **Audio Profile Editor** dialog box. Click **No** to continue making configuration changes.

- **Close** button – closes the dialog box without saving changes.

Audio Profile Editor Equalizer Dialog Box

The **Audio Profile Editor Equalizer** current settings and available editing controls ([Figure 24](#)) are accessed by clicking the **Audio Profile Editor Equalizer** tab ([Figure 23 on page 51](#)).

Figure 24. Audio Profile Editor Equalizer Dialog Box



The **Audio Profile Editor Equalizer** dialog box has 7 setup functions:

- **Master Control:**
 - **Insert EQ** check box
 - **Level (dB)** fader
 - **Defaults** button
- **Low Band**
- **Mid Band 1**
- **Mid Band 2**
- **Mid Band 3**
- **Mid Band 4**
- **High Band**

Each of the **Low**, **Mid**, and **High Band** areas contain the same control functions:

- **Q Ratio** – controls the EQ band effective bandwidth. Values range from 0.1 to 3.0. Larger Q ratios result in wider effective bandwidths. The default setting is 1.0.

Note This setting is restricted to 1.0 on the Low and High bands.

- **Frequency** – controls the EQ band center frequency. Available values and default values depend on the band. Default values are:
 - **Low Band** – 100 Hz
 - **Mid Band 1** – 250 Hz
 - **Mid Band 2** – 630 Hz
 - **Mid Band 3** – 1.6 kHz
 - **Mid Band 4** – 4.0 kHz
 - **High Band** – 10 kHz
- **Level (dB)** fader – controls the EQ band gain. This gain value only applies to the target band. Settings range from -15 to +15 dB. The default value is unity.
- **Flat** button – resets the target band settings to default. This button effectively flattens the target band's effective contribution to the overall EQ curve.

Audio Profile Editor Dynamics Dialog Box

The **Audio Profile Editor Dynamics** current settings and available editing controls (Figure 25) are accessed by clicking the **Audio Profile Editor Dynamics** tab (Figure 23 on page 51).

Figure 25. Audio Profile Editor Dynamics Dialog Box



The **Audio Profile Editor Dynamics** dialog box has 5 setup functions:


- **Master Control:**
 - **Insert Dynamics**
 - **Input Delay**
 - **Level (dB)**
 - **Defaults**
- **Limiter:**
 - **Attack** – sets the speed at which the Limiter effects are applied to the channel once the threshold condition has been met
 - **Release** – sets the speed at which the Limiter effects are removed from the channel once the threshold condition is no longer met.
 - **Threshold** – sets the dB value that the channel signal must meet before the effects of the limiter are applied.
- **Side Chain:**
 - **Soft Knee** – sets whether or not the application of the expander and compressors effects should be smoothed to produce a less abrupt (and less noticeable) effect in the audio.
 - **Crest** – sets the Crest value for the side chain.
 - **Low Cut** – sets the corner frequency of the high pass filter associated with the side chain channel.
 - **Level** – sets the gain of the audio signal entering the side chain.
- **Expansion:**
 - **Ratio** – sets the ratio of applied gain versus actual gain for every dB of gain the channel exceeds the expander's threshold setting.
 - **Attack** – sets the speed at which the Expander effects are applied to the channel once the threshold condition has been met.
 - **Release** – sets speed at which the Expander effects are removed from the channel once the threshold condition is no longer met.
 - **Threshold** – sets the dB value that the channel signal must meet before the effects of the Expander are applied.
 - **Range** – sets the maximum dB level processed by the expander.
- **Compression:**
 - **Ratio** – sets the ratio of applied gain versus actual gain for every dB of gain the channel exceeds the Compressor's threshold setting.
 - **Attack** – sets the speed at which the Compressor effects are applied to the channel once the threshold condition has been met.

- **Release** – sets the speed at which the Compressor effects are removed from the channel once the threshold condition is no longer met.
- **Threshold** – sets the dB value that the channel signal must meet before the effects of the Compressor are applied.
- **Reference** – sets the reference dB level processed by the Compressor.

Audio Profile Editor Delay Dialog Box

The **Audio Profile Editor Delay** current settings and available editing controls (Figure 26) are accessed by clicking the **Audio Profile Editor Delay** tab (Figure 23 on page 51).

Figure 26. Audio Profile Editor Delay Dialog Box



The **Audio Profile Editor Delay** dialog box has 2 setup functions:

Insert Delay – sets whether or not delay should be included as a part of the audio profile.

Delay Units – selects the unit for showing the current delay time; either **Samples** or **Frm/s** (frames per second). If the delay unit is set to show frame values, the delay value is still set via the Klotz Audio Server using the equivalent number of samples.


- If set to **Samples**, and the delay value is set to a sample number somewhere between the frame delay values, the result is the corresponding number of samples to the nearest 10th of a frame.
- If set to **Frm/s**, the result is frame values to a tenth of a frame. The frame settings for 10ths of a frame are verified by setting both the Vadis and Ignite/Ignite Konnect Display Units to **Sample** and comparing the results for synchronization and accuracy.

Aux Configuration

The **Aux Configuration** dialog box (Figure 27) is accessed from the **Audio Main Context Menu**. This dialog box is used to add or remove configured virtual sources to/from the available Aux mixes. When the **Aux Configuration** dialog box is accessed, it shows the current Aux Configuration of the first available Aux.

Note The **Aux Configuration** dialog box is not specific to individual faders. Therefore, the **Aux Configuration** menu item is available regardless of where, in the Audio fader area a right-click is used to access the **Audio Main Context Menu**; i.e., either a fader or an empty fader slot.

Figure 27. Aux Configuration Dialog Box



Note The **Aux Configuration** dialog box opens in the same state regardless of which strip was right-clicked to open the **Audio Main Context Menu**.

The **Aux Configuration** dialog box includes:

- **Aux Selector** – selects the Aux to be configured/edited and shows the respective:
 - **Active** virtual sources list – contains all virtual sources that are currently configured to be inserted into the selected Aux bus according to the current configuration.
 - **Minus** virtual sources list – contains all virtual sources that are currently configured to be absent from the selected Aux bus according to the current configuration.

- **Minus Selection** button – moves the selected **Active** virtual sources to the **Minus** virtual sources list and sends the Audio Server the appropriate trigger commands to update the virtual source status in the selected Aux. If no virtual source is selected in the **Active** virtual sources list, this button has no effect.
- **Minus All** button – moves all **Active** virtual sources, whether selected or not, to the **Minus** virtual sources list and sends the Audio Server the appropriate trigger commands to update the virtual source status in the selected Aux.
- **Activate** button – moves the selected **Minus** virtual sources to the **Active** virtual sources list and sends the Audio Server the appropriate trigger commands to update the virtual source status in the selected Aux. If no virtual source is selected in the **Active** virtual sources list, this button has no effect.
- **Activate All** button – moves all **Minus** virtual sources, whether selected or not, to the **Active** virtual sources list and sends the Audio Server the appropriate trigger commands to update the virtual source status in the selected Aux.
- **OK** – saves the changes and closes the dialog box.
- **Cancel** – compares the saved configuration and the currently shown configuration. If no changes exist, the dialog box closes. If changes have been made, a **Cancel Changes?** message appears.


Click **Yes** to undo changes and close the **Aux Configurator** dialog box. Click **No** to continue making configuration changes.
- **Close** button – closes the dialog box without saving changes.

Talk Back Source Selection

The system employs a single Talk Back source. The **Talk Back Source Selection** dialog box ([Figure 28](#)) is accessed from the **Audio Main Context Menu**. This dialog box is used to select the source to be sent along a virtual source Foldback Path when the virtual source has the **Talk Back** button ([Individual Faders on page 35](#)) selected.

Note The **Talk Back Source Selection** dialog box is not specific to individual faders. Therefore, the **Talk Back Source Selection** menu item is available regardless of where, in the Audio fader area, a right-click is used to access the **Audio Main Context Menu**; i.e., either a fader or an empty fader slot.

Figure 28. Talk Back Source Selection Dialog Box



The **Talk Back Source Selection** dialog box includes:

- **Select a Source** – a list of selectable sources to drive the Talk Back. To avoid unnecessary routing there is also a **No Talk Back Source** available.
- **OK** – saves the changes and closes the dialog box.
- **Cancel** – compares the saved configuration and the currently shown configuration. If no changes exist, the dialog box closes. If changes have been made, a **Cancel Changes?** message appears.

Click **Yes** to undo changes and close the **Talk Back Source Selection** dialog box. Click **No** to continue making configuration changes.


- **Close** button – closes the dialog box without saving changes.

Monitor Source Selection

The **Monitor Source Selection** dialog box (Figure 29) is accessed from the **Audio Main Context Menu**. This dialog box is used to route Sources into a Monitor structure. Gain is then applied to the Source and the output of the Monitor is routed to any physical output on the system.

Note The **Monitor Source Selection** dialog box is not specific to individual faders. Therefore, the **Monitor Source Selection** menu item is available regardless of where, in the Audio fader area, a right-click is used to access the **Audio Main Context Menu**; i.e., either a fader or an empty fader slot.

Figure 29. Monitor Source Selection Dialog Box



The **Monitor Source Selection** dialog box includes:

- **Select a Monitor Destination** – list of available monitors from which the user selects the monitor to assign a source.
- **Route Selected Source** – routes the selected source to the input of the selected monitor. If **No Monitor Input** is selected in the **Source List**, any source previously routed into the monitor input is removed.
- **Source List** – shows the sources for monitoring. From left to right, the list box entries show the source Port Index (or Sys for system defined sources that originate from within the frame itself), the Source Name, and the Stereo/Mono level of the source. Refer to [Figure 29](#).
- **OK** – saves the changes and closes the dialog box.
- **Cancel** – compares the saved configuration and the currently shown configuration. If no changes exist, the dialog box closes. If changes have been made, a **Cancel Changes?** message appears.


Click **Yes** to undo changes in real time and close the **Monitor Source Selection** dialog box. Click **No** to continue making configuration changes.

- **Close** button – closes the dialog box without saving changes.

Point To Point Routing

The **Point to Point** dialog box (Figure 30) is accessed from the **Audio Main Context Menu**. This dialog box is used to route Sources.

Figure 30. Point-to-Point Routing Dialog Box




Note The **Point to Point** dialog box opens in the same state regardless of which strip was right-clicked to open the **Audio Main Context Menu**.

The **Point to Point** dialog box includes:

- **Select a Destination** – lists the physical outputs available for routing. The list contains the Port Index, Destination Name, Stereo/Mono level, and Current Destination.
- **Select a Source** – lists the sources available for routing to the destinations listed in **Select a Destination**. From left to right, the list box entries show the Port Index (Sys for system sources that originate from within the frame), Source Name, and Stereo/Mono level of the source. Also contained is an option for **No Route**.

- **Route Selected Source** – routes the selected source to the selected destination. If the **No Route** option is selected in **Select a Source**, any source that was previously routed to the selected destination is removed. If the destination is currently in use, a **Destination is in Use!** message (Figure 31) appears. The message explains the options and provides button selection instructions for proceeding.

Figure 31. Destination is in Use Message!



- **OK** – saves the changes and closes the dialog box.
- **Cancel** – compares the saved configuration and the currently shown configuration. If no changes exist, the dialog box closes. If changes have been made, a **Cancel Changes?** message appears.

Click **Yes** to undo changes in real time and close the **Point to Point** dialog box. Click **No** to continue making configuration changes.

- **Close** button – closes the dialog box without saving changes.

Operation

Note Before the audio can be controlled, virtual sources must be created and configured. Typically this is accomplished during initial installation.

Adjust an Audio Source

Note The fader handle(s) is used to adjust the level of the active virtual source in the Program mix and any Aux mix in which the virtual source is included.

Note While the **Hold** button is active, the fader cannot be controlled by automation.


- To manually adjust the level, click and drag the fader handle.
- To jump or cut the active source to a desired volume, double-click above or below the fader handle.

Change a Page Name

Note For all names, abbreviations, colors, and file structures, use established standards and consistent techniques and practices. Refer to *Standardization on page 467*.

1. Right-click the fader label. The **Modify this page's name** menu (Figure 32) appears.

Figure 32. Modify Page Name – Klotz Audio



2. Click **Modify this page's name**. The **Edit Tab Name** dialog box (Figure 33) appears.

Figure 33. Page Tab Naming Dialog Box



3. In the **Page Name** box, type the new name. Click **OK**.


Fader Manual Virtual Source Control

Note If the **Audio Main Context Menu** is accessed via right-click on a fader, the **Virtual Source Maintenance** dialog box appears with the virtual source for the targeted fader already selected. If the **Audio Main Context Menu** is accessed via right-click on an empty fader slot, the first virtual source in the list is selected by default.

Create a Fader Control


1. Click the **Page Tab** where the fader control is to be added. The selected **Page Tab** highlights (Figure 34).

Figure 34. Page Tabs/Fader Slots




- Note** Each of the 8 available pages is logically subdivided into 16 fader slots. Every two slots span the width of a Page Tab (refer to [Figure 34](#) inset).
2. Right-click the desired fader slot to create the fader control. The **Audio Main Context Menu** ([Figure 35](#)) appears.

Figure 35. Audio Main Context Menu - Virtual Source Maintenance



3. Click **Virtual Source Maintenance**. The **Virtual Source Maintenance** dialog box ([Figure 36](#)) appears.


Figure 36. Virtual Source Maintenance Dialog Box



- From the **Select a Virtual Source** list, click a virtual source for the fader to control and then click **Import**. A fader control (Figure 37) is placed in the selected fader slot.

Note The new fader control is labeled with the abbreviation of the selected virtual source.

Figure 37. New Fader Control Example – Klotz Audio



Clear/Remove a Fader Control

- Right-click near the right edge of the fader control to be removed. The **Main Context Menu** appears.
- Click **Clear Fader** (Figure 38).

Figure 38. Remove/Clear Fader Control




Adjust Master Fader

- Click and drag the left or right fader control to the required level.

Adjust/Setup/View Aux 1–Aux 6

- Click the **Master Fader AUX** button. The **Master Fader AUX** button highlights and the **Aux Fader** dialog box (Figure 39) appears.

Figure 39. Aux Fader Dialog Box – Klotz Audio



2. In the **Aux Fader** dialog box, click the desired Aux bus (1–6). Click and drag the **Aux Fader** dialog box fader control to the desired level.
3. Repeat [Step 2](#) for each **Aux** to be viewed or adjusted.
4. Click **Done**.

Source Setting Independent of Virtual Sources


These settings include Trim Gain ([Adjust Source Trim Gain on page 66](#)), Mix Type ([Adjust Source Mix Type on page 68](#)), EQ, Dynamics, and Delay ([Adjust Source Audio Profile on page 68](#)).

Adjust Source Trim Gain

Note If the **Audio Main Context Menu** is accessed via right-click near the edge of a fader control, the **Virtual Source Maintenance** dialog box opens with the virtual source for the targeted fader already selected. If the **Audio Main Context Menu** is accessed via right-click on an empty fader slot, the first virtual source in the list is selected by default.


1. Right-click anywhere in the Audio Module fader controls. The **Audio Main Context Menu** ([Figure 40](#)) appears.

Figure 40. Audio Main Context Menu



2. Click **Source Maintenance**. The **Source Maintenance** dialog box (Figure 41) appears.

Figure 41. Source Maintenance Dialog Box




3. In the **Sources** list, click the target source.
4. Adjust the gain trim by doing one of the following:
 - a. Click and drag the **Gain Trim (dB)** fader handle until the display reflects the desired gain value.
 - b. Click the fader handle and then press the keyboard arrow up and down keys until the display reflects the desired gain value.
 - c. Click the fader handle and then press the keyboard **Page Up** and **Page Down** keys until the display reflects the desired gain value.
5. Click **OK**.

Adjust Source Mix Type


1. Right-click anywhere in the Audio Module fader controls. The **Audio Main Context Menu** (Figure 42) appears.

Figure 42. Audio Main Context Menu



2. Click **Source Maintenance**. The **Source Maintenance** dialog box (Figure 43) appears.

Figure 43. Source Maintenance Dialog Box



3. Select the desired **Mix Type** (Stereo, L Only, R Only, or Mono).


Note This setting only affects stereo sources in stereo buses.

4. Click **OK**.

Adjust Source Audio Profile

1. Right-click anywhere in the Audio Module fader controls. The **Audio Main Context Menu** (Figure 44) appears.


Figure 44. Audio Main Context Menu



2. Click **Source Maintenance**. The **Source Maintenance** dialog box appears. Refer to Figure 45.

Note The current Audio Profile for the source is listed in the right most column of the **Sources** list.

Figure 45. Source Maintenance Dialog Box




3. In the **Sources** list, click the target source.

Note The current Audio Profile is listed in the right most column of the **Sources** list.

4. In the **Audio Profiles** list, click the desired audio profile. Click **Apply Selected Profile**. In the **Sources** list, the selected Audio Profile (Figure 46) updates accordingly.
5. Click **OK**.

Figure 46. Change Source Audio Profile




Control EQ, Dynamics, and Delay via Audio Profiles

Create An Audio Profile

1. Right-click anywhere in the Audio Module fader controls. The **Audio Main Context Menu** (Figure 47) appears.

Figure 47. Audio Main Context Menu



2. Click **Audio Profile Maintenance**. The **Audio Profile Maintenance** dialog box appears. Refer to (Figure 48).

Figure 48. Audio Profile Maintenance Dialog Box



3. Click **Add**. A new Audio Profile (Figure 49) is created and added to the list.

Note By default, newly created Audio Profiles are named **New Audio Profile x** where x is the next sequential number for Audio Profiles using the default **New Audio Profile** name.


Figure 49. Add New Audio Profile



Edit an Audio Profile

1. Right-click anywhere in the Audio Module fader controls. The **Audio Main Context Menu** (Figure 50) appears.

Figure 50. Audio Main Context Menu



2. Click **Audio Profile Maintenance**. The **Audio Profile Maintenance** dialog box appears. Refer to (Figure 51).

Figure 51. Audio Profile Maintenance Dialog Box



3. Click **Edit**. The **Audio Profile Editor** (Figure 52) dialog box appears.

Note This dialog box can contain a varying number of tabs, depending on the DSP capabilities of the system audio configuration.

Note EQ and DYN tabs only appear with a V880, 884, or 888 frame configuration.

Figure 52. Audio Profile Editor Dialog Box




4. Refer to [Audio Profile Editor Dialog Box on page 51](#) for Audio Profile Editor controls functionality.

Delete an Audio Profile

1. Right-click anywhere in the Audio Module fader controls. The **Audio Main Context Menu** ([Figure 53](#)) appears.

Figure 53. Audio Main Context Menu



2. Click **Audio Profile Maintenance**. The **Audio Profile Maintenance** dialog box appears. Refer to ([Figure 54](#)).

Figure 54. Audio Profile Maintenance Dialog Box



3. Click **Delete**. The **Delete Entry?** message appears:


- Click **Yes** to continue deleting the selected Audio Profile.
- Click **NO** to keep/not delete the item.

Note Deleting the selected Audio Profile, updates all affected sources, in real time, to **[No Audio Profile]** and immediately saves the configuration to reflect the deletion.

Select A Talk Back Source


1. Right-click anywhere in the Audio Module fader controls. The **Audio Main Context Menu** (Figure 55) appears.

Figure 55. Audio Main Context Menu




2. Click **Talk Back Source Selection**. The **Talk Back Source Selection** dialog box appears. Refer to (Figure 56).

Figure 56. Talk Back Source Selection Dialog Box



3. In the **Select a Source** box (Figure 57), type or select the desired talk back source.

Figure 57. Talk Back Select A Source Box Example




4. Click **OK**.

Select/Edit Monitor Sources


1. Right-click in the fader control area. The **Audio Main Context Menu** (Figure 58) appears.

Figure 58. Audio Main Context Menu



2. Click **Monitor Source Selection**. The **Monitor Source Selection** dialog box appears. Refer to [Figure 59](#).


Figure 59. Monitor Source Selection Dialog Box Example



864x-sc199-r0


3. In the **Select a Monitor Destination** box ([Figure 60](#)), select the target monitor.

Figure 60. Select a Monitor Destination List Example



4. In the **Source** list (Figure 61), click the **Source** to route to the monitor.

Figure 61. Monitor Source Selection - Source To Monitor Example




5. Click **Route Selected Source**, and then click **OK**. Refer to Figure 61.

Point To Point Routing


1. Right-click in the fader control area. The **Audio Main Context Menu** (Figure 62) appears.

Figure 62. Audio Main Context Menu



2. Click **Point to Point Routing**. The **Point to Point Routing** dialog box appears. Refer to Figure 63.

Figure 63. Point to Point Routing Dialog Box



3. In the **Select a Destination** list, click the target destination.
4. In the **Select a Source** list, click the target source.
5. Click **Route Selected Source**, and then click **OK**.


Set Points

Note A set point does not need to be loaded in order to be assigned in a task. However, it does need to be loaded if the user wishes to modify the set point position for a particular source during a show.

Create a Set Point


1. Right-click in the fader control volume level area. The **Set Point Context Menu** (Figure 64) appears.

Figure 64. Set Point Context Menu – Klotz Audio



2. Click **Set Point Maintenance**. The **Set Point Maintenance** dialog box appears. Refer to Figure 65.


Figure 65. Set Point Maintenance Dialog Box



Note All set points created via Set Point Maintenance are available globally for every source to use in creating tasks for audio timeline objects.

3. Click **Add**. The **Set Point Editor** dialog box (Figure 66) appears.

Figure 66. Set Point Editor Dialog Box – Klotz Audio



Note For all names, abbreviations, colors, and file structures, use established standards and consistent techniques and practices. Refer to *Standardization on page 467*.

4. Either:


- In the **Name** box, type a Set Point name
- On the **Color Menu**, click a Set Point color
- Assign a Set Point value by either:
 - Using the **Value(dB)** up and down arrows
 - Clicking and dragging the Set Point indicator on the **TEST** fader

5. Click **OK**.

Edit a Set Point

1. Right-click in the fader control volume level. The **Set Point Context Menu** (Figure 67) appears.

Figure 67. Set Point Context Menu – Klotz Audio




2. Click **Set Point Maintenance**. The **Set Point Maintenance** dialog box appears. Refer to [Figure 68](#).

Figure 68. Set Point Maintenance Dialog Box



3. From the **Select a Setpoint** list, click a Set Point to edit.
4. Click **Edit**. The **Set Point Editor** dialog box ([Figure 69](#)) appears.

Figure 69. Set Point Editor Dialog Box – Klotz Audio




5. Edit the Set Point as necessary.
6. Click **OK**.

Load a Set Point to a Virtual Source

1. Right-click on the fader control that controls the target virtual source. The **Set Point Context Menu** ([Figure 70](#)) appears.

Figure 70. Set Point Context Menu - Virtual Source – Klotz Audio



2. Click **Set Point Maintenance**. The **Set Point Maintenance** dialog box appears. Refer to [Figure 71](#).

Figure 71. Set Point Maintenance Dialog Box




3. From the **Select a Setpoint** list, click a Set Point to load, and then click **Load**
4. Click **OK**. The Set Point appears on the selected fader control.

Note Click and drag a Set Point to a virtual source-specific volume level up or down to force audio automation to use that level instead of the volume level associated with the global setpoint.

Delete a Set Point


1. Right-click in the fader control volume level area. The **Set Point Context Menu** ([Figure 72](#)) appears.

Figure 72. Set Point Context Menu – Klotz Audio



- Click **Set Point Maintenance**. The **Set Point Maintenance** dialog box appears. Refer to [Figure 73](#).

Figure 73. Set Point Maintenance Dialog Box




- From the **Select a Setpoint** list, click a Setpoint to delete.
- Click **Delete**. The **Delete Entry?** message appears:
 - Click **Yes** to continue deleting the selected Set Point.
 - Click **No** to keep/not delete the item.

Clear Set Points from a Virtual Source

- Right-click on the fader control that controls the target virtual source. The **Set Point Context Menu** ([Figure 74](#)) appears.

Figure 74. Set Point Context Menu – Klotz Audio



2. Click **Clear All Fader Set Points**. All Set Points specific to the virtual source controlled by the fader control are removed.


Virtual Sources

Edit a Virtual Source Entry

Note If the **Audio Main Context Menu** is accessed via right-click on a fader, the **Virtual Source Maintenance** dialog box appears with the virtual source for the targeted fader already selected. If the **Audio Main Context Menu** is accessed via right-click on an empty fader slot, the first virtual source in the list is selected by default.


1. Right-click near the right edge of the fader control to be edited. The **Audio Main Context Menu** (Figure 75) appears.

Figure 75. Audio Main Context Menu




2. Click **Virtual Source Maintenance**. The **Virtual Source Maintenance** dialog box appears. Refer to Figure 76.

Figure 76. Virtual Source Maintenance Dialog Box



3. In the **Select a Virtual Source** list, click a virtual source to edit and then click **Edit**. The **Virtual Source Editor** dialog box (Figure 77) appears.


Figure 77. Virtual Source Editor Dialog Box



4. Within **Virtual Source Identification** (Figure 78):
 - a. In the **Name** text box, type a name for the virtual source (required)


- b. In the **Abbreviation** text box, type an abbreviation for the virtual source (required)

Figure 78. Virtual Source Identification



5. Within **Source Mapping** (Figure 79):
 - a. In the **Sources** list, click a **Primary** source
 - b. Click **Primary Map** to assign the selected source as the Primary Source

Figure 79. Virtual Source Primary Mapping



Note The following Backup Mapping step is optional.

6. Within Source Mapping (Figure 79):

- a. In the **Sources** list, click a Backup source.
- b. Click **Backup Map** to assign the selected source as the Backup Source.


Note The following Foldback Mapping step is optional. This is the destination to which the active source mix-minus will be routed when the source is on air. Otherwise, program audio is routed instead.

7. Within Foldback Destination Mapping (Figure 79):

- a. In the **Destinations** list, click a **Foldback** Destination.
- b. Click **Foldback Map** to assign the selected source as the Foldback Destination.

8. Click OK. The Virtual Source Maintenance (Figure 80) dialog box appears with the just configured virtual source showing in the Select a Virtual Source list.

Figure 80. Select a Virtual Source List Example




Note To create more sources, click a different virtual source and perform [Step 1](#) through [Step 8](#).

9. Click **OK**.

Adding/Removing Virtual Sources From Aux Mixes


1. Right-click in the fader control area. The **Audio Main Context Menu** ([Figure 81](#)) appears.

Figure 81. Audio Main Context Menu




2. Click **Aux Configuration**. The **Aux Configuration** dialog box appears. Refer to [Figure 82](#).

Figure 82. Aux Configuration Dialog Box Example



3. In the **Aux** text box (Figure 83), type or select the target Aux Bus.

Figure 83. Aux Configuration Dialog Box - Aux Buses




Note Refer to [Aux Configuration on page 57](#) for button functionality.

Note Typical of most Windows functionality, the mouse, **SHIFT** key, and **CTRL** key can be used to perform ranged selections and line item selections.

4. Using the mouse and key combinations and the available buttons, add and/or remove virtual sources between the **Active** and **Minus** lists as necessary. Refer to the examples in [Figure 84](#).

Figure 84. Aux Configuration Dialog Box - Add/Remove Examples



864x-sc197c-r0


5. When complete, click **OK**.

Set Up Audio Task Properties

Note Set points must be created before creating audio tasks. A set point does not need to be assigned to a source in order for the source to use the set point, but at least one set point must exist. There are two default set points **OFF** and **IGNORE** that are system defined and non-editable by the user.

1. On the timeline, drag an audio command over. Double-click the Audio Property icon. The **Audio Timeline Task List** dialog box (Figure 85) appears.

Figure 85. Audio Timeline Task List Dialog Box




2. Click a task and then click either **Add New Task**, **Edit Task**, **Delete Task**, **Move Up**, or **Move Down** as needed. If either **Add New Task** or **Edit Task** is chosen an **Audio Task** dialog box (Figure 86) appears.
 - Complete the entries in this dialog box, click **OK**, and then proceed to the next step.

Note The duration field should be set to the number of frames over which the fade will occur. If left blank or set to 0, a cut is performed instead.

Note Click **IGNORE** to set an audio source so that the **Take all to Zero** command ignores that specific source when setting all sources to zero. Clicking **IGNORE** sets the duration to 0 frames and disables the **Please enter a duration** box. The **Ignore** feature is accessed through the individual Audio Module TME icon properties

Figure 86. Audio Task Dialog Box



3. Repeat [Step 1](#) and [Step 2](#) for adding tasks for each individual task in the same audio command.
4. Click **OK**.


Note Click the **Take All Sources to Zero** check box ([Figure 85](#)) to have all other sources without a task assigned to go off air at 0 duration.

5. Click **Done**.

Audio Preview

Audio sources transitioned via the Ignite/Ignite Konnect Event Timeline are populated into the Audio Preview area ([Figure 87](#)) as each TME is prepped. The sources set to move to air next are shown in the Audio Preview area.


Figure 87. Audio Preview Area Example – Klotz Audio



Note The previewed audio shows the audio fader level when the source is transitioned to air. If a different transition level is desired before going to air, adjust the level while it is in Preview.

- To set the desired program output, move the master output fader handle to the corresponding level.
- To prevent a source from going to air, after a TME has been prepped, click **H** to hold the source in preview.
- To toggle between this view and a view that is populated with the most recently used audio faders, click **Preview**. The **Last Used** view ([Figure 88](#)) appears.

Figure 88. Audio Last Used View Example – Klotz Audio




- In **Preview**, right-click an audio source to select either:
 - Send it to air immediately
 - Remove it from Preview and not go to air

Audio Program (LIVE)

The **Audio Program** area (Figure 89) shows the sources presently On Air. Any source that is moved above its off point is taken to air instantly and is shown in the **Audio Program** area.


Figure 89. Audio Program Area Example – Klotz Audio



- To remove the audio mix, right-click any source and then click **Take Off Air Now**.
- To hold the source on air, click **H** while the source is in the area.

Yamaha Audio

Figure 90. Audio Module - Yamaha Audio



Overview

Note The Ignite/Ignite Konnect system provides an automation interface ([Figure 90](#)) to this panel. For panel-specific user and set up information, refer to the manufacturer's documentation.

Fader Manual Virtual Source Control

Virtual Sources provide a mapping between Automation Events and Input Channels on the Yamaha Mixer. Virtual Sources play a significant role in Automation Events by enabling Automation Events to control target Sources regardless of which Input Channels the Sources have been assigned to on the Yamaha Mixer. As many as 64 pre-configured Virtual Sources are possible.

In order to control a virtual source from within the Audio Module, a fader control must be created to represent the virtual source visually (refer to [Create a Fader Control on page 109](#)). Otherwise, the virtual source idly waits in the background for commands from Ignite/Ignite Konnect Timeline Automation or external control surfaces such as the QUICbox™ panel.

Individual Faders

Each fader control has three available buttons (Figure 91) at the top:





- **B** (Backup)
- **H** (Hold)
- **C** (Cue)

Note The **T** (Talk Back) function is unavailable with the Yamaha audio control configuration. Therefore the **T** button is dimmed in this configuration

When either the **B** or **C** button is clicked, the button background highlights blue to indicate it is selected. When the **H** button is clicked, both the button background and the fader perimeter highlight amber to indicate it is selected.

Note For all of the buttons, a gray background indicates it is not selected.

Figure 91. Fader Buttons - Yamaha Audio

Selected	Function
	Backup – switches to a backup. Click to make the attached backup source the active source in the mix. This button has no effect if a backup source was not selected for the virtual source during configuration.
	Hold – holds a source on or off air. Click to hold the fader control at the current level. If the fader control is currently engaged in a fade triggered by automation, the fade is allowed to continue and the fader will be held at the final level resulting from the fade.
	Cue – monitors a channel. Click to add the attached virtual source into the Cue mix bus. The Cue bus mix is a pre-fade mix where sources enter the mix at unity gain.
	Note The Talk Back function is unavailable with the Yamaha audio control configuration. Therefore the T (Talk Back) button is dimmed in that configuration.


Fader control handles are used to adjust the virtual source active source level in the Program mix and any Aux mix in which the virtual source is

included. Double-click the fader control above or below the fader handle to force the active source to jump or cut to the desired volume. A manual fade is achieved by dragging the fader handle to the desired level. The level can not be controlled with the fader while the **Hold** button is active.

Also, there are two different fader control handles (Figure 92):

- Mono – a single fader control that functions individually
- Stereo – a pair of handles that move as a single fader


Figure 92. Fader Control Handles - Yamaha Audio



Audio Preview

Virtual sources transitioned via the Ignite/Ignite Konnect Event Timeline are populated into the **Audio Preview** area (Figure 93) as each TME is prepped. The virtual sources set to move to air next are shown in the **Audio Preview** area.

Figure 93. Audio Preview Area - Yamaha Audio




Audio Program (Live)

The **Audio Program** area (Figure 94) shows the virtual sources presently On Air. Any virtual source that is moved above its off point is taken to air instantly and is shown in the **Audio Program** area.

Note Only the 8 most recent virtual sources to go on air and still exist on air are shown. Once 9 virtual sources are on air, the oldest on-air virtual source disappears and reappears if another is taken off air.

Figure 94. Audio Program Area - Yamaha Audio



Set Points

Set Points are pre-established fader settings that are referenced via a TME (Transition Macro Event), refer to *TME™ (Transition Macro Event™)* on [page 34](#). These set points set a source level for each source. Set Points can be


named for easy reference. Via Event Timeline automation, each TME provides the system with the audio set point needed for that particular event.

To access the **Set Points Menu** (Figure 95), within a fader, right-click near the left edge of the fader control. The **Set Points Menu** has two selections:

- **Set Point Maintenance** – accesses the **Set Point Maintenance** dialog box
- **Clear All Fader Set Points** – clears all fader set points

Note The **Set Point Maintenance** dialog box opens in the same state regardless of where the user right-clicked to access the **Set Point Menu**. However, if a set point is loaded from this dialog, the set point is loaded to the fader that was right-clicked to access the **Set Point Menu**.

Figure 95. Set Point Menu - Yamaha Audio



Set points must be created before creating audio tasks. A set point does not need to be assigned to a virtual source in order for the virtual source to use the set point, but at least one set point must exist. There are two default set-points that are system defined and non-editable by the user:


- **OFF** – used to bring a Virtual Source off the air.
- **IGNORE** – used to flag a Virtual Source so that it will not be affected by the **Take All Sources to Zero** feature of Audio TMEs.

A set point does not need to be loaded in order to be assigned in a task. However, it does need to be loaded if the user wishes to modify the set point position for a particular virtual source during a show.

Set Point Maintenance

The **Set Point Maintenance** dialog box (Figure 96) is accessed from the **Set Points Menu**. This dialog box is used to create, edit, delete, or load set points.

Figure 96. Set Point Maintenance Dialog Box



Note All set points created via Set Point Maintenance are available globally for use by every source in creating tasks for audio timeline objects.

The **Set Point Maintenance** dialog box includes:

- **OK** – saves the changes and closes the dialog box.
- **Load** - loads the selected set point to the fader that was right-clicked to access the **Set Point Menu**. A fader can only have one instance of the same set point loaded. When attempting to load a set point to a fader that already has the set point loaded, a Set Point already loaded message appears.
- **Add** - accesses the **Set Point Editor** dialog box with a new Set Point definition. If appropriately configured, the set point is created and added to the list.
- **Edit** - accesses the **Set Point Editor** for the selected Set Point changes.
- **Delete** – the **Delete Entry?** message appears.

Click **Yes** to continue deleting the selected Set Point and immediately save the configuration to reflect the deletion. Click **No** to keep/not delete the item at this time and continue making changes.

- **Close** button – closes the dialog box without saving changes.

Set Point Editor

The **Set Point Editor** dialog box (Figure 97) is accessed from the **Set Point Maintenance** dialog box **Edit** button (Figure 98 on page 101).

Note All set points created via Set Point Maintenance are available globally for use by every source in creating tasks for audio timeline objects.

Figure 97. Set Point Editor Dialog Box





Figure 98. Set Point Maintenance Dialog Box



The **Set Point Editor** dialog box includes:

- **Color Selection** - changes the color of the target Set Point. Click a color to assign.
- **Volume Level** - click and drag to set the target volume level. Users can also use the Up-Down control attached to the **Value(dB)** field to achieve the same results.
- **OK** – saves the new /edited changes and closes the dialog box.

Note Before changing/saving, verifies that the Set Point Name is unique among Set Points and that the name does not match the default **Off** Set Points name in any way. If invalid, a message appears stating the need and nature of the required change.

- **Cancel** – compares the saved configuration and the currently shown configuration. If no changes exist, the dialog box closes. If changes have been made, a **Cancel Changes?** message appears.










Click **Yes** to undo changes in real time and close the **Set Point Editor** dialog box. Click **No** to continue making configuration changes.

- **Close** button – closes the dialog box without saving changes.

Master Output Faders

The **Master Output Fader** (Figure 99 on page 102) provides master control of the overall audio output level of the **Master Out Left** and **Master Out Right** channels. Six buttons comprise the various Master Volume Controls.

Figure 99. Master Output Fader - Yamaha Audio


		<p>Updates the master faders to reflect the PGM volume and assumes control of that volume. When exiting AUX or MON dialog box control, PGM is the default/active volume control.</p>	<p><i>MIX Fader Dialog Box</i></p> 
		<p>Updates the master faders to reflect the MIX volume control and assumes control of the selected mixer (MIX 1 through MIX 16) volume. Clicking Done returns control to PGM.</p>	
		<p>Updates the master faders to reflect the CUE prefader and post fader volume control dialog box and assumes control of that selected volume. Clicking Done returns control to PGM.</p>	<p><i>CUE Pre/Post Fader Dialog Box</i></p> 
		<p>Updates the master faders to reflect the MON volume and assumes control of that volume. Clicking Done returns control to PGM.</p>	<p><i>MTX Fader Dialog Box</i></p> 
		<p>Updates the master faders to reflect the MTX volume control dialog box and assumes control of the selected Matrix (MTX 1 through MTX 8) volume. Clicking Done returns control to PGM.</p>	

The **PGM** and **CUE** buttons function similarly. When the respective button is clicked, the main faders update to reflect and assume control of that volume; i.e., **PGM**, **CUE**, or **TB**. When either the **AUX** or **MON** button is selected, a separate dialog box appears to enable specific selection of a particular Aux or Monitor to control. In any case, all changes are real time and take effect immediately

Audio Main Context Menu

To access the **Audio Main Context Menu** (Figure 100), right-click near the right edge of a fader control.

Figure 100. Audio Main Context Menu - Yamaha Audio



The **Audio Main Context Menu** items for the Yamaha audio configuration are:

Audio Main Context Menu Item	Purpose
Clear Fader	Removes the selected fader (virtual source control) from view and replaces it with an empty slot. This does not delete the fader-associated virtual source, but that specific virtual source control (fader) is simply not shown. That audio virtual source (or any available audio virtual source) can be imported to an empty slot as a fader control using the Virtual Source Maintenance menu item. Refer to Virtual Source Maintenance Dialog Box on page 104 NOTE: This menu item is only available if a fader is selected (right-click). Refer to Figure 100 .
Virtual Source Maintenance	Accesses the Virtual Source Maintenance dialog box that enables a user to either edit or import a virtual audio source. Refer to Virtual Source Maintenance Dialog Box on page 104 .


Virtual Source Maintenance Dialog Box

The **Virtual Source Maintenance** dialog box ([Figure 101](#)) is accessed from the **Audio Main Context Menu**. The **Virtual Source Maintenance** dialog box provides a list of available virtual audio sources and from that list a user can either import a virtual source to the selected slot or edit/configure an already assigned virtual source.

Note If the **Audio Main Context Menu** is accessed via right-click near the edge of a fader, the **Virtual Source Maintenance** dialog box opens with the virtual source for the targeted fader already selected. If the **Audio Main Context Menu** is accessed via right-click on an empty fader slot, the first virtual source in the list is selected by default.

The **Virtual Source Maintenance** dialog box ([Figure 101](#)) includes:

Figure 101. Virtual Source Maintenance Dialog Box



- **Select a Virtual Source** – lists a source ID, virtual source name, and source abbreviation for each available virtual source. Any un-configured virtual source name and abbreviation is shown as a series of dashes.
- **OK** – saves the changes and closes the dialog box.
- **Import** – imports the selected virtual source to either a fader or an empty fader slot. The import position is based on the fader slot used to access the **Audio Main Context Menu**. If the fader slot is already populated by a fader, that virtual source is replaced with the virtual source selected from the **Select a Virtual Source** list.

Note Import is unavailable if an non-configured virtual source is selected.

- **Edit** – opens the **Virtual Source Editor** dialog box (refer to [Virtual Source Editor Dialog Box on page 106](#)). The **Virtual Source Editor** dialog box opens in one of two modes, either **Edit** mode (if the selected virtual source is already configured) or **Configuration** mode (if the selected virtual source is not configured).

Note When in Edit Mode, the Editor forces real time configuration change updates to the virtual source but in Configuration Mode it does not.


- **Erase** – deletes the virtual source entry
- **Close** button – closes the dialog box without saving changes.

Virtual Source Editor Dialog Box

The **Virtual Source Editor** dialog box (Figure 102) is accessed from the **Virtual Source Maintenance** dialog box **Edit** button (Figure 101 on page 105). It enables a user to create and configure virtual sources for use in TMEs and to edit the configuration of an existing virtual source in real time. The **Virtual Source Editor** dialog box opens in one of two modes, either **Edit** mode (if the selected virtual source is already configured) or **Configuration** mode (if the selected virtual source is not configured).

- **Edit Mode** - when configuring a pre-existing virtual source, the changes to **Primary**, and **Backup** take effect in real time. This feature enables a user to make critical alterations while Audio is live.
- **Configuration Mode** - when configuring a brand new virtual source. Since there is no way for a non-configured virtual source to be associated with a **fader control** or become part of a mix, there is little reason or validity to sending real time updates to any of the settings that the user alters.

Figure 102. Virtual Source Editor Dialog Box (Yamaha)



The **Virtual Source Editor** dialog box (Figure 102) includes:

- **Virtual Source Identification** – text boxes for a user defined **Virtual Source Name** and **Abbreviation**.
 - **Name** – limited to 25 characters and is system monitored to prevent duplicates. This name is used to identify the virtual source in other configuration dialog boxes as well as System Error Logs.
 - **Abbreviation** – limited to 4 characters and is system monitored to prevent duplicates. This abbreviation is the only identifier that appears on the fader control associated with that virtual source. This abbreviation is also used, along with the name, to identify the virtual source in other configuration dialog boxes as well as System Error Logs.

- **Source Mapping** – enables a user to select the **Primary** and **Backup** source audio content that is inserted into a mix when the virtual source is either in Cue or On-Air.
 - **Primary** – shows the name of the currently mapped **Primary** source or **No Source** if a source is not mapped. A virtual source must have a mapped **Primary** source in order to complete the configuration.
The **Map** button assigns the selected source as the **Primary** source. Since a primary source must exist before the configuration can be completed, the **Map** button is disabled when the user selects **Do not use Source** from the **Sources** list box.
 - **Backup** – shows the name of the currently mapped **Backup** source or **No Source** if a source is not mapped. The **Map** button sets the selected source as the **Backup** source. A **Backup** source does not have to be mapped. Selecting **Do not use Source** and clicking **Map** removes any previously mapped backup source and replaces it with a **No Source** entry. If a virtual source does not have a mapped backup source, the **Backup** button on any fader control to which that virtual source is associated has no effect when clicked.
 - **OK** – verifies that the **Name** and **Abbreviation** boxes contain valid entries, confirms that a primary source is mapped to the virtual source, updates and saves the virtual source entry, then closes the dialog box.

Note If any **OK** condition is not met, an error dialog box appears to notify the user about the discrepancy, the change is not saved, and the **Virtual Source Editor** dialog box is not closed.

- **Cancel** – click functionality depends on the current dialog box mode: **Edit** or **Configuration**.
 - When in **Edit** Mode, if configuration changes have been made, a **Cancel Changes?** message appears. Click **Yes** to undo changes and close the **Virtual Source Editor** dialog box. Click **No** to continue making configuration changes.
 - When in **Configuration** mode, the new virtual source entry is not created or saved and the dialog box closes.
- **Close** button – closes the dialog box without saving changes.

Operation

Note The Ignite/Ignite Konnect system provides an automation interface to this panel. For panel-specific user and set up information, refer to the manufacturer's documentation.

Note Before the audio can be controlled, virtual sources must be created and configured. Typically this is accomplished during initial installation.

Adjust an Audio Source

Note The fader handle(s) is used to adjust the level of the active virtual source in the Program mix and any Aux mix in which the virtual source is included.

Note The level can not be controlled with the fader while the **Hold** button is active.


- To manually adjust the level, click and drag the fader handle.
- To jump or cut the active source to a desired volume, double-click above or below the fader handle.

Change a Page Name

Note For all names, abbreviations, colors, and file structures, use established standards and consistent techniques and practices. Refer to *Standardization on page 577*.

1. Right-click the fader label. The **Modify this page's name** menu (Figure 103) appears.

Figure 103. Modify Page Name - Yamaha Audio



2. Click **Modify this page's name**. The **Page Tab Naming** dialog box (Figure 104) appears.

Figure 104. Page Tab Naming Dialog Box



3. In the **Page Name** box, type the new name. Click **OK**.

Fader Manual Virtual Source Control

Note If the **Audio Main Context Menu** is accessed via right-click on a fader, the **Virtual Source Maintenance** dialog box appears with the virtual source for the targeted fader already selected. If the **Audio Main Context Menu** is accessed via right-click on an empty fader slot, the first virtual source in the list is selected by default.

Create a Fader Control

1. Click the **Page Tab** where the fader control is to be added. The selected **Page Tab** highlights ([Figure 105](#)).

Figure 105. Page Tabs/Fader Slots



Note Each of the 8 available pages is logically subdivided into 16 fader slots. Every two slots span the width of a Page Tab (refer to [Figure 155](#) inset).


2. Right-click the desired fader slot to create the fader control. The **Audio Main Context Menu** ([Figure 106](#)) appears.

Figure 106. Audio Main Context Menu - Virtual Source Maintenance



3. Click **Virtual Source Maintenance**. The **Virtual Source Maintenance** dialog box ([Figure 107](#)) appears.


Figure 107. Virtual Source Maintenance Dialog Box



4. From the **Select a Virtual Source** list, click a virtual source for the fader to control and then click **Import**. A fader control (Figure 108) is placed in the selected fader slot.

Note The new fader control is labeled with the abbreviation of the selected virtual source.

Figure 108. New Fader Control Example - Yamaha Audio



Clear/Remove a Fader Control

1. Right-click near the right edge of the fader control to be removed. The **Main Context Menu** appears.
2. Click **Clear Fader** (Figure 109).

Figure 109. Remove/Clear Fader Control




Adjust Master Fader

- Click and drag the left or right fader control to the required level.

Adjust/Set Up/View Mixer Faders 1–16

- Click the **Master Fader MIX** button. The **Master Fader MIX** button highlights and the **MIX Fader** dialog box ([Figure 110](#)) appears.

Figure 110. Mixer Faders Dialog Box - Yamaha Audio




- In the **MIX Fader** dialog box, click the desired Mix bus (1–16) to adjust. Click and drag the **Mix Fader** dialog box fader control to the desired level.
- Repeat [Step 2](#) for each **Mixer** bus to be viewed or adjusted.
- Click **Done**.

Adjust/Set Up/View Cue Input/Output Faders

- Click the **Master Fader CUE** button. The **Master Fader CUE** button highlights and the **CUE Fader** dialog box ([Figure 111](#)) appears.

Figure 111. Cue Fader Dialog Box - Yamaha Audio




2. In the **CUE Fader** dialog box, click the desired CUE (Input – Output) to adjust. Click and drag the **CUE Fader** dialog box fader control to the desired level.
3. Repeat [Step 2](#) for each CUE to be viewed or adjusted.
4. Click **Done**.

Adjust/Set Up/View Matrix Faders 1–8

1. Click the **Master Fader MTX** (Matrix) button. The **Master Fader MTX** button highlights and the **MTX Fader** dialog box ([Figure 112](#)) appears.

Figure 112. Matrix Fader Dialog Box - Yamaha Audio



2. In the **MTX Fader** dialog box, click the desired Matrix bus (1–8) to adjust. Click and drag the **MTX Fader** dialog box fader control to the desired level.
3. Repeat [Step 2](#) for each **Matrix** bus to be viewed or adjusted.
4. Click **Done**.

Set Points

Note A set point does not need to be loaded in order to be assigned in a task. However, it does need to be loaded if the user wishes to modify the set point position for a particular source during a show.

Create a Set Point


1. Right-click in the fader control volume level area. The **Set Point Context Menu** ([Figure 113](#)) appears.

Figure 113. Set Point Context Menu - Yamaha Audio



2. Click **Set Point Maintenance**. The **Set Point Maintenance** dialog box appears. Refer to [Figure 114](#).


Figure 114. Set Point Maintenance Dialog Box



Note All set points created via Set Point Maintenance are available globally for every source to use in creating tasks for audio timeline objects.

3. Click **Add**. The **Set Point Editor** dialog box (Figure 115) appears.

Figure 115. Set Point Editor Dialog Box



Note For all names, abbreviations, colors, and file structures, use established standards and consistent techniques and practices. Refer to [Standardization on page 577](#).

4. Either:


- In the **Name** box, type a Set Point name
- On the **Color Menu**, click a Set Point color
- Assign a Set Point value by either:
 - Using the **Value(dB)** up and down arrows
 - Clicking and dragging the Set Point indicator on the **TEST** fader

- Click **OK**.

Edit a Set Point


- Right-click in the fader control volume level. The **Set Point Context Menu** (Figure 116) appears.

Figure 116. Set Point Context Menu - Yamaha Audio




- Click **Set Point Maintenance**. The **Set Point Maintenance** dialog box appears. Refer to Figure 117.

Figure 117. Set Point Maintenance Dialog Box



- From the **Select a Setpoint** list, click a Set Point to edit.
- Click **Edit**. The **Set Point Editor** dialog box (Figure 118) appears.

Figure 118. Set Point Editor Dialog Box




5. Edit the Set Point as necessary.
6. Click **OK**.

Load a Set Point to a Virtual Source


1. Right-click on the fader control that controls the target virtual source. The **Set Point Context Menu** (Figure 119) appears.

Figure 119. Set Point Context Menu - Virtual Source - Yamaha Audio



2. Click **Set Point Maintenance**. The **Set Point Maintenance** dialog box appears. Refer to Figure 120.

Figure 120. Set Point Maintenance Dialog Box




3. From the **Select a Setpoint** list, click a Set Point to load, and then click **Load**
4. Click **OK**. The Set Point appears on the selected fader control.

Note Click and drag a Set Point to a virtual source-specific volume level up or down to force audio automation to use that level instead of the volume level associated with the global setpoint.

Delete a Set Point


1. Right-click in the fader control volume level area. The **Set Point Context Menu** (Figure 121) appears.

Figure 121. Set Point Context Menu - Yamaha Audio



2. Click **Set Point Maintenance**. The **Set Point Maintenance** dialog box appears. Refer to Figure 122.

Figure 122. Set Point Maintenance Dialog Box




3. From the **Select a Setpoint** list, click a Setpoint to delete.
4. Click **Delete**. The **Delete Entry?** message appears:
 - Click **Yes** to continue deleting the selected Set Point.
 - Click **No** to keep/not delete the item.

Clear Set Points From a Virtual Source

1. Right-click on the fader control that controls the target virtual source. The **Set Point Context Menu** (Figure 123) appears.

Figure 123. Set Point Context Menu - Yamaha Audio




2. Click **Clear All Fader Set Points**. All Set Points specific to the virtual source controlled by the fader control are removed.

Virtual Sources – Edit a Virtual Source Entry

Note If the **Audio Main Context Menu** is accessed via right-click on a fader, the **Virtual Source Maintenance** dialog box appears with the virtual source for the targeted fader already selected. If the **Audio Main Context Menu** is accessed via right-click on an empty fader slot, the first virtual source in the list is selected by default.


1. Right-click near the right edge of the fader control to be edited. The **Audio Main Context Menu** (Figure 124) appears.

Figure 124. Audio Main Context Menu




2. Click **Virtual Source Maintenance**. The **Virtual Source Maintenance** dialog box appears. Refer to Figure 125.

Figure 125. Virtual Source Maintenance Dialog Box



3. In the **Select a Virtual Source** list, click a virtual source to edit and then click **Edit**. The **Virtual Source Editor** dialog box (Figure 126) appears.

Figure 126. Virtual Source Editor Dialog Box



4. Within **Virtual Source Identification**:

- a. In the **Name** text box, type a name for the virtual source (required)
- b. In the **Abbreviation** text box, type an abbreviation for the virtual source (required)

5. Within **Source Mapping**:

- a. In the **Sources** list, click a **Primary** source
- b. Click **Primary Map** to assign the selected source as the Primary Source


Note The following Backup Mapping step is optional.

6. Within **Source Mapping** (Figure 126):

- a. In the **Sources** list, click a **Backup** source.
- b. Click **Backup Map** to assign the selected source as the Backup Source.

7. Click **OK**. The **Virtual Source Maintenance** (Figure 127) dialog box appears with the just configured virtual source showing in the **Select a Virtual Source** list.

Figure 127. Select a Virtual Source List Example



Note To create more sources, click a different virtual source and perform [Step 1](#) through [Step 7](#).


8. Click **OK**.

Set Up Audio Task Properties

Note Set points must be created before creating audio tasks. A set point does not need to be assigned to a source in order for the source to use the set point, but at least one set point must exist. There is a default set point called OFF that is system defined and non-editable by the user that always brings the source off-air.

1. On the timeline, drag an audio command over. Double-click the Audio Property icon. The **Audio Timeline Task List** dialog box ([Figure 128](#)) appears.

Figure 128. Audio Timeline Task List Dialog Box




2. Click a task and then click either **Add New Task**, **Edit Task**, **Delete Task**, **Move Up**, or **Move Down** as needed. If either **Add New Task** or **Edit Task** are chosen an **Audio Task** dialog box (Figure 129) appears.
 - Complete the entries in this dialog box, click OK, and then proceed to the next step.

Note The duration field should be set to the number of frames over which the fade will occur. If left blank or set to 0, a cut is performed instead.

Note Click **IGNORE** to set an audio source so that the **Take all to Zero** command ignores that specific source when setting all sources to zero. Clicking **IGNORE** sets the duration to 0 frames and disables the **Please enter a duration** box. The **Ignore** feature is accessed through the individual Audio Module TME icon properties

Figure 129. Audio Task Dialog Box



3. Repeat [Step 1](#) and [Step 2](#) for adding tasks for each individual task in the same audio command.
4. Click **OK**.


Note Click the **Take All Sources to Zero** check box ([Figure 128](#)) to have all other sources without a task assigned to go off air at 0 duration.

5. Click **Done**.

Audio Preview

Audio sources transitioned via the Ignite/Ignite Konnect Event Timeline are populated into the Audio Preview area ([Figure 130](#)) as each TME is prepped. The sources set to move to air next are shown in the Audio Preview area.


Figure 130. Audio Preview Area Example - Yamaha Audio



Note The previewed audio shows the audio fader level when the source is transitioned to air. If a different transition level is desired before going to air, adjust the level while it is in Preview.

- To set the desired program output, move the master output fader handle to the corresponding level.
- To prevent a source from going to air, after a TME has been prepped, click **H** to hold the source in preview.
- To toggle between this view and a view that is populated with the most recently used audio faders, click **Preview**. The **Last Used** view ([Figure 131](#)) appears.

Figure 131. Audio Last Used View Example - Yamaha Audio



- In **Preview**, right-click an audio source to select either:
 - Send it to air immediately
 - Remove it from Preview and not go to air

Audio Program (LIVE)

The **Audio Program** area (Figure 132) shows the sources presently On Air. Any source that is moved above its off point is taken to air instantly and is shown in the **Audio Program** area.


Figure 132. Audio Program Area Example - Yamaha Audio



- To remove the audio mix, right-click any source and then click **Take Off Air Now**.
- To hold the source on air, click **H** while the source is in the area.

Wheatstone Audio

Figure 133. Audio Module - Wheatstone Audio



Overview

Note The Ignite/Ignite Konnect system provides an automation interface (Figure 133) to the D-8 and D-10 panels. For panel-specific user and set up information, refer to the manufacturer's documentation.

Manual Virtual Source Control

Virtual Sources provide a mapping between Automation Events and Input Channel Faders on the Wheatstone Mixer. Virtual Sources play a significant role in Automation Events by enabling Automation Events to control target Sources regardless of which Input Channels the Sources have been assigned to on the Wheatstone Mixer.





In order to control a virtual source from the Audio GUI, a program fader control must be created, on the Audio Module GUI, to represent the virtual source visually (refer to [Create a Program Fader Control – Select a Virtual Source on page 144](#)). Otherwise, the virtual source idly waits in the background for commands from Ignite/Ignite Konnect Timeline Automation or external control surfaces such as the QUICbox™ panel.

Individual Program Fader Controls

Each program fader control has four available buttons (Figure 134) at the top:

- **B** (Backup) – Triggers the fader's Source Preset button, effectively assigning the preset source to the fader (if one exists).
- **H** (Hold) – Enables/Disables the associated Virtual Source Automation Hold feature (latching).
- **P** (PFL) – Activates/Deactivates PFL (Pre-fade Listen) Cue for the associated Virtual Source (latching).
- **A** (AFL) – Activates/Deactivates AFL (Post-fade Listen) Solo for the associated Virtual Source (latching).

Figure 134. Fader Buttons – Wheatstone Audio

Selected	Function
	Backup Toggles between the associated Fader's current source and preset source (non-latching). Click to assign the associated fader's preset source to the fader. If the fader has not preset source assigned, this feature will act as a mute for the fader.
	Hold Enables/Disables the associated Virtual Source's Automation Hold feature (latching). When selected, both the button and the fader outline turn bright orange. This is an alert that the Program Fader and associated Virtual Source will ignore all Automation events until the Program Fader is taken off of Hold. Note If the Virtual Source does not have a mapped Fader, the outline of the Program Fader is red instead (Figure 135 on page 127).
	PFL (Pre Fade Listen/Cue) Activates or de-activates the PFL button for the Input Channel. Note PFL is disabled automatically by Automation Events that take the Virtual Source from OFF to any other level.
	AFL (Post Fade Listen/Cue) Activates or de-activates the AFL button for the Input Channel. Note AFL is disabled automatically by Automation Events that take the Virtual Source from OFF to any other level.


Note For all of the buttons, a gray background indicates it is not active.

When either the **B**, **P**, or **A** button is clicked, the button background highlights blue to indicate it is selected. When the **H** button is clicked, both the

button background and the program fader control perimeter highlight amber to indicate it is selected.

If the Virtual Source does not have a mapped Fader, the outline of the Program Fader is red (Figure 135). Also refer to [Virtual Source Maintenance Dialog Box on page 135](#) and [Layouts on page 138](#). A Virtual Source that does not have a fader mapped to it does not actually control any elements on the mixer. If a fader is later mapped to such a Virtual Source, the properties of the Virtual Source (level, AFL, PFL, etc.) will be applied to the Fader.


Figure 135. Example – Virtual Source Without Mapped Fader – Wheatstone Audio



Audio Preview

Virtual sources transitioned via the Ignite/Ignite Konnect Event Timeline are populated into the **Audio Preview** area (Figure 136) as each TME is prepped. The virtual sources set to move to air next are shown in the **Audio Preview** area.

Figure 136. Audio Preview Area – Wheatstone Audio




Audio Program (Live)

The **Audio Program** area (Figure 137) shows the virtual sources presently On Air. Any virtual source that is moved above its off point is taken to air instantly and is shown in the **Audio Program** area.

Note Only the 8 most recent virtual sources to go on air and still exist on air are shown. Once 9 virtual sources are on air, the oldest on-air virtual source disappears and reappears if another is taken off air.

Figure 137. Audio Program Area – Wheatstone Audio



Set Points

Set Points are pre-established fader levels that are referenced via a TME (Transition Macro Event), refer to *TME™ (Transition Macro Event™)* [on](#)


[page 34](#). Set points are used to set the fader level of a Virtual Source during a transition. Set Points can be named for easy reference. Via Event Timeline automation, each TME provides the system with the audio set point needed for that particular event.

To access the **Set Points Menu** ([Figure 138](#)), within a program fader control, right-click near the left edge of the program fader control. The **Set Points Menu** has two selections:

- **Set Point Maintenance** – accesses the **Set Point Maintenance** dialog box
- **Clear All Fader Set Points** – clears all fader set points

Note The **Set Point Maintenance** dialog box opens in the same state regardless of where the user right-clicked to access the **Set Point Menu**. However, if a set point is loaded from this dialog, the set point is loaded to the fader that was right-clicked to access the **Set Point Menu**.

Figure 138. Set Point Menu – Wheatstone Audio



Set points must be created before creating audio tasks. A set point does not need to be assigned to a virtual source in order for the virtual source to use the set point, but at least one set point must exist. There are two default set-points that are system defined and non-editable by the user:


- **OFF** – used to bring a Virtual Source off the air.
- **IGNORE** – used to flag a Virtual Source so that it will not be affected by the **Take All Sources to Zero** feature of Audio TMEs.

A set point does not need to be loaded in order to be assigned in a task. However, it does need to be loaded if the user wishes to modify the set point position for a particular virtual source during a show.

Set Point Maintenance

The **Set Point Maintenance** dialog box ([Figure 139](#)) is accessed from the **Set Points Menu**. This dialog box is used to create, edit, delete, or load set points.

Figure 139. Set Point Maintenance Dialog Box – Wheatstone Audio



Note All set points created via Set Point Maintenance are available globally for use by every virtual source in creating tasks for audio timeline objects.

The **Set Point Maintenance** dialog box includes:

- **OK** – saves the changes and closes the dialog box.
- **Load** - loads or assigns the selected set point to the virtual source associated with the program fader control that was right-clicked to access the **Set Point Menu**. A Virtual Source can only have one instance of the same set point loaded.
- **Add** - accesses the **Set Point Editor** dialog box with a new Set Point definition. If appropriately configured, the set point is created and added to the list.
- **Edit** - accesses the **Set Point Editor** for the selected Set Point changes.
- **Delete** – the **Delete Entry?** message appears.

Click **Yes** to continue deleting the selected Set Point and immediately save the configuration to reflect the deletion. Click **No** to keep/not delete the item at this time and continue making changes.


- **Close** button – closes the dialog box without saving changes.

Set Point Editor

The **Set Point Editor** dialog box (Figure 140) is accessed from the **Set Point Maintenance** dialog box **Edit** button (Figure 139).

Note All set points created via Set Point Maintenance are available globally for use by every virtual source in creating tasks for audio timeline objects.

Figure 140. Set Point Editor Dialog Box – Wheatstone Audio



The **Set Point Editor** dialog box includes:

- **Color Selection** - changes the color of the target Set Point. Click a color to assign.
- **Volume Level** - click and drag to set the target volume level. Users can also use the Up-Down control attached to the **Value(dB)** field to achieve the same results.
- **OK** – saves the new/edited changes and closes the dialog box.

Note Before changing/saving, verifies that the Set Point Name is unique among Set Points and that the name does not match the default **OFF** and **IGNORE** Set Points names in any way. If invalid, a message appears stating the need and nature of the required change.

- **Cancel** – compares the saved configuration and the currently shown configuration. If no changes exist, the dialog box closes. If changes have been made, a **Cancel Changes?** message appears.


Click **Yes** to undo changes in real time and close the **Set Point Editor** dialog box. Click **No** to continue making configuration changes.

- **Close** button – closes the dialog box without saving changes.

Master Output Faders

The **Master Output Fader** (Figure 141) provides master control of the overall audio output level of the **Master Out Left** and **Master Out Right** channels. Six buttons comprise the various Master Volume Controls.


Figure 141. Master Output Fader – Wheatstone Audio






Group Submix Master
Adjusts selected Group Submix Master's level.

GRP Dialog Box




Mix Minus Master
Adjusts the selected Mix Minus Master's level.

MXM Fader Dialog Box



Monitor Master
Adjusts the selected Monitor Master's level.


MON Fader Dialog Box



Audio Main Context Menu

To access the **Audio Main Context Menu** (Figure 142), right-click near the right edge of a program fader control.

Figure 142. Audio Main Context Menu - Wheatstone Audio



The **Audio Main Context Menu** items for the Wheatstone audio configuration are:

Audio Main Context Menu Item	Purpose
Clear Virtual Source	Removes the selected program fader control (virtual source control) from view and replaces it with an empty slot. This does not delete the program fader control-associated virtual source, but that specific virtual source control (program fader control) is simply not shown. That audio virtual source (or any available audio virtual source) can be imported to an empty slot as a fader control using either the Virtual Source Maintenance menu item or the Import Virtual Source menu item. Refer to Virtual Source Maintenance Dialog Box on page 135 NOTE: This menu item is only available if a program fader control is selected (right-click).
Virtual Source Maintenance	Accesses the Virtual Source Maintenance dialog box that enables a user to either edit or import a virtual audio source. Refer to Virtual Source Maintenance Dialog Box on page 135 .

Audio Main Context Menu Item -	Purpose - (continued)
Import Virtual Source	This menu item has 4 submenus. Each submenu contains 16 items, each item represents a Virtual Source by name. The selected virtual source is imported into the program fader slot the user right clicked to gain access to the short cut menu. This feature serves as a short cut for importing virtual sources. Refer to Import Virtual Source on page 138 .
Layouts	Automatically contains 2 submenu items, "Create Layout..." and "Save Current Layout As...". Create Layout and Save Current Layout As menu items both invoke the Layout Editor dialog box. Also contains a submenu representing each existing Layout by name. Each Layout menu item contains submenu options to Load, Edit, or Delete the layout. Load triggers the mixer to load the named layout and then proceed to update the virtual source to the fader mapping contained in the layout. Edit displays the Layout Editor dialog box, enabling the user to make changes to the associated layout. Delete causes the associated layout to be deleted. Refer to Layouts on page 138 .


Virtual Source Maintenance Dialog Box

The **Virtual Source Maintenance** dialog box ([Figure 143](#)) is accessed from the **Audio Main Context Menu**. The **Virtual Source Maintenance** dialog box provides a list of available virtual audio sources and from that list a user can either import a virtual source to the selected slot or edit the properties of a virtual source.

Note If the **Audio Main Context Menu** is accessed via right-click near the edge of a program fader control, the **Virtual Source Maintenance** dialog box opens with the virtual source for the targeted fader already selected. If the **Audio Main Context Menu** is accessed via right-click on an empty program fader slot, the first virtual source in the list is selected by default.

The **Virtual Source Maintenance** dialog box ([Figure 143](#)) includes:

Figure 143. Virtual Source Maintenance Dialog Box



- **Select a Virtual Source** – lists a source ID, virtual source name, source abbreviation, and the currently mapped fader for each available virtual source. (Unmapped if one is not mapped.)
- **OK** – saves the changes and closes the dialog box.
- **Import** – imports the selected virtual source to either an existing program fader control or an empty program fader slot. The import position is based on the program fader slot used to access the **Audio Main Context Menu**. If the program fader slot is already occupied by a virtual source, that virtual source is replaced with the virtual source selected from the **Select a Virtual Source** list. Refer to [Import Virtual Source on page 138](#).
- **Edit** – opens the **Virtual Source Editor** dialog box (refer to [Virtual Source Editor Dialog Box on page 136](#)). The **Virtual Source Editor** dialog box opens in one of two modes, either **Edit** mode (if the selected virtual source is already configured) or **Configuration** mode (if the selected virtual source is not configured).
- **Close button** – closes the dialog box without saving changes.

Virtual Source Editor Dialog Box

The **Virtual Source Editor** dialog box ([Figure 144](#)) is accessed from the **Virtual Source Maintenance** dialog box **Edit** button ([Figure 143 on page 136](#)). It enables a user to edit the properties of virtual sources.

Figure 144. Virtual Source Editor Dialog Box – Wheatstone Audio)



The **Virtual Source Editor** dialog box (Figure 144) includes:

- **Virtual Source Identification** – text boxes for a user defined **Virtual Source Name** and **Abbreviation**.
 - **Name** – limited to 25 characters and is system monitored to prevent duplicates. This name is used to identify the virtual source in other configuration dialog boxes as well as System Error Logs.
 - **Abbreviation** – limited to 4 characters and is system monitored to prevent duplicates. This abbreviation is the only identifier that appears on the program fader control associated with that virtual source. This abbreviation is also used, along with the name, to identify the virtual source in other configuration dialog boxes as well as System Error Logs.
- **Input Channel Mapping** – enables a user to select the fader to be controlled by the virtual source.
 - **Input Channel** – displays the currently mapped fader or **No Source** if a source is not mapped. A virtual source that does not have a mapped fader will appear on screen with a red outline. Though this type of virtual source can still be controlled manually or via automation events, such actions will not manipulate the mixer until a fader is mapped to the virtual source.

The **Map** button assigns the selected fader to the virtual source. If **Unmapped** is selected from the **Available Input Channel** drop down list, clicking the Map button will unmap any currently mapped fader.

 - **OK** – verifies that the **Name** and **Abbreviation** boxes contain valid entries, updates and saves the virtual source entry, then closes the dialog box.

Note If any **OK** condition is not met, an error dialog box appears to notify the user about the discrepancy, the change is not saved, and the **Virtual Source Editor** dialog box is not closed.


- **Cancel** – closes the dialog box without saving changes.
- **Close** button – closes the dialog box without saving changes.

Import Virtual Source

The Import Virtual Source function is accomplished in one of two ways:

- From the **Virtual Source Maintenance** dialog box (Figure 145 A)
- From the **Audio Main Context Menu** (Figure 145 B)


Figure 145. Virtual Source Maintenance Dialog Box



Layouts


The (Audio) **Layouts** (Figure 146) functionality, associated submenus, and dialog boxes are accessed from the **Audio Main Context Menu**. The Audio Layout functionality enables the user to manage Virtual Sources to Faders mapping for a particular Program Event.

Figure 146. (Audio) Layouts Submenus Example



The Wheatstone Audio starts with a blank undefined layout each time the application is started. This means that every Virtual Source is unmapped at application start up. The current layout can then be adjusted by updating the Fader mapping of Virtual Sources using the **Virtual Source Editor** dialog box (Figure 147). Refer to [Virtual Source Editor Dialog Box on page 136](#)

Figure 147. Virtual Source Editor Dialog Box – Wheatstone Audio)



Note When the application closes, changes made to the default layout are not automatically retained. To retain changed layout information, the user must either create a new layout or save the current layout.


Layout Editor Dialog Box

The **Layout Editor** dialog box is accessed from the **Audio Main Context Menu** (Figure 148):

- Click **Layouts**, and then click **Create Layout**
- Click **Layouts**, and then click **Save Current Layout As**
- Click **Layouts**, then click the <layout name>, and then click **Edit** – where <layout name> is chosen from the list of existing Audio Layouts.

Note If no Audio Layouts have been created or saved, the <layout name> option is not available.

Figure 148. Example Layout Name – MRN SHOW



The **Layout Editor** dialog box (Figure 149) includes:

- **Layout Identification** where:
 - **Name** is used to uniquely identify the layout. This field is limited to 20 characters and must be unique. The **Layout Editor** disables the **Name** field when the user has elected to edit an existing Layout.
 - **Preset** should contain the name of the associated Program Event from the Wheatstone mixer. This field is case sensitive and is limited to 8 characters just like Program Event names on the Wheatstone mixer.
- **Virtual Source Fader Assignments** where the mapping between each Virtual Source and mixer Fader is set up:
 - Option (radio) buttons **1 - 16**, **17 - 32**, **33 - 48**, and **49 - 64**. Each option button loads the virtual source names and fader mappings for that range into the **Virtual Source Fader Assignments**.
 - Virtual Source Names and Drop-down Lists - the label that appears just above each drop down list represents a virtual source from within the range selected by the respective option button; e.g., **1 - 16**, **17 - 32**. The drop down list displays the current fader mapping and provides a list of available faders that can be use to change the virtual source to fader mapping.


If a Virtual Source should not control a Fader for the given Program Event, the Virtual Source should be set as **Unmapped**. Virtual Source to Fader mappings default to **Unmapped**.

Note Each Fader can be mapped to one and only one Virtual Source.

- **OK** – saves the Audio Layout and closes the dialog box. Note that a user prompt occurs if the:
 - **Name** field is empty
 - **Name** field contains a name that is already in use by another layout. This only happens when the user is creating a layout.

- **Preset** field is empty
- **Cancel** – closes the dialog box without saving changes.
- **Close** button – closes the dialog box without saving changes.

Figure 149. Layout Editor Dialog Box



Operation

Note The Ignite/Ignite Konnect system provides an automation interface to the D-10 panel. For panel-specific user and set up information, refer to the manufacturer's documentation.

Note Before the audio can be controlled, virtual sources must be configured. Typically this is accomplished during initial installation.

Adjust an Audio Source

Note The program fader control handle is used to adjust the level of the virtual source's associated fader.


- To manually adjust the level, click and drag the program fader control handle.
- To jump or cut the active source to a desired volume, double-click above or below the program fader control handle.

Change a Page Name

Note For all names, abbreviations, colors, and file structures, use established standards and consistent techniques and practices. Refer to *Standardization on page 577*.


1. Right-click the page label. The **Modify this page's name** menu (Figure 150) appears.

Figure 150. Modify Page Name – Wheatstone Audio



2. Click **Modify this page's name**. The **Page Tab Naming** dialog box (Figure 151) appears.

Figure 151. Page Tab Naming Dialog Box



3. In the **Page Name** box, type the new name. Click **OK**.

Manual Virtual Source Control

Note If the **Audio Main Context Menu** is accessed via right-click on a program fader control, the **Virtual Source Maintenance** dialog box appears with the virtual source for the targeted program fader control already selected. If the **Audio Main Context Menu** is accessed via right-click on an empty program fader slot, the first virtual source in the list is selected by default.

Create a Program Fader Control – Import a Virtual Source

1. Click the **Page Tab** where the program fader control is to be added. The selected **Page Tab** highlights ([Figure 152](#)).


Figure 152. Page Tabs/Program Fader Slots



Note Each of the 8 available pages is logically subdivided into 16 program fader slots. Every two slots span the width of a Page Tab (refer to [Figure 152](#) inset).

2. Right-click the desired program fader slot to create the program fader control. The **Audio Main Context Menu** ([Figure 153](#)) appears.


Figure 153. Audio Main Context Menu - Virtual Source Maintenance



3. On the **Audio Main Context Menu**, click **Import Virtual Source**, then click **Virtual Sources x – y**, and then click a **Virtual Source Name** (refer to [Figure 154](#)) where:
 - **Virtual Sources x – y** is the Virtual Source ID range from which a Virtual Source will be selected for import
 - **Virtual Source Name** is the name of the Virtual Source to be imported

The program fader control is imported.


Figure 154. Virtual Source Name



Create a Program Fader Control – Select a Virtual Source

1. Click the **Page Tab** where the program fader control is to be added. The selected **Page Tab** highlights (Figure 155).


Figure 155. Page Tabs/Program Fader Slots



Note Each of the 8 available pages is logically subdivided into 16 program fader slots. Every two slots span the width of a Page Tab (refer to [Figure 155](#) inset).


2. Right-click the desired program fader slot to create the program fader control. The **Audio Main Context Menu** ([Figure 156](#)) appears.

Figure 156. Audio Main Context Menu - Virtual Source Maintenance



3. Click **Virtual Source Maintenance**. The **Virtual Source Maintenance** dialog box ([Figure 157](#)) appears.


Figure 157. Virtual Source Maintenance Dialog Box



4. From the **Select a Virtual Source** list, click a virtual source for the program fader to control and then click **Import**. A program fader control ([Figure 158](#)) is placed in the selected program fader slot.

Note The new program fader control is labeled with the abbreviation of the selected virtual source.


Figure 158. New Program Fader Control Example – Wheatstone Audio



Clear/Remove a Program Fader Control/Virtual Source

1. Right-click near the right edge of the program fader control to be removed. The **Main Context Menu** appears.
2. Click **Clear Virtual Source** (Figure 159).

Figure 159. Remove/Clear Program Fader Control or Virtual Source




Adjust a Single Master Fader

- Click and drag the left or right fader control to the required level.

Adjust/Set Up/View a Group of Masters

1. Click the **Master Fader** button for the proper group of masters (e.g., AUX, ST, GRP). The **Master Fader** button highlights and the **Master Fader** dialog box (Figure 160) appears.

Figure 160. Master Fader Dialog Box – Wheatstone Audio



2. In the **Master Fader** dialog box, from the list click the desired master.
3. Click and drag the **Master Fader** dialog box fader control to the desired level.
4. Repeat [Step 2](#) for each **Master** to be viewed or adjusted.
5. Click **Done**.


Set Points

Note A set point does not need to be loaded in order to be assigned in a task. However, it does need to be loaded if the user wishes to modify the set point position for a particular source during a show.

Create a Set Point


1. Right-click in the program fader control volume level area. The **Set Point Context Menu** ([Figure 161](#)) appears.

Figure 161. Set Point Context Menu – Wheatstone Audio



2. Click **Set Point Maintenance**. The **Set Point Maintenance** dialog box appears. Refer to [Figure 162](#).


Figure 162. Set Point Maintenance Dialog Box



Note All set points created via Set Point Maintenance are available globally for every virtual source to use in creating tasks for audio timeline objects.

3. Click **Add**. The **Set Point Editor** dialog box ([Figure 163](#)) appears.

Figure 163. Set Point Editor Dialog Box – Wheatstone Audio



Note For all names, abbreviations, colors, and file structures, use established standards and consistent techniques and practices. Refer to *Standardization on page 577*.

4. Either:


- In the **Name** box, type a Set Point name
- On the **Color Menu**, click a Set Point color
- Assign a Set Point value by either:
 - Using the **Value(dB)** up and down arrows
 - Clicking and dragging the Set Point indicator on the **TEST** fader

5. Click **OK**.

Edit a Set Point


1. Right-click in the program fader control volume level. The **Set Point Context Menu** (Figure 164) appears.

Figure 164. Set Point Context Menu – Wheatstone Audio




2. Click **Set Point Maintenance**. The **Set Point Maintenance** dialog box appears. Refer to [Figure 165](#).

Figure 165. Set Point Maintenance Dialog Box



3. From the **Select a Setpoint** list, click a Set Point to edit.
4. Click **Edit**. The **Set Point Editor** dialog box ([Figure 166](#)) appears.

Figure 166. Set Point Editor Dialog Box – Wheatstone Audio




5. Edit the Set Point as necessary.
6. Click **OK**.

Load a Set Point to a Virtual Source


1. Right-click on the program fader control that controls the target virtual source. The **Set Point Context Menu** ([Figure 167](#)) appears.

Figure 167. Set Point Context Menu - Virtual Source – Wheatstone Audio



2. Click **Set Point Maintenance**. The **Set Point Maintenance** dialog box appears. Refer to [Figure 168](#).

Figure 168. Set Point Maintenance Dialog Box




3. From the **Select a Setpoint** list, click a Set Point to load, and then click **Load**
4. Click **OK**. The Set Point appears on the selected program fader control.

Note Click and drag a Set Point to a virtual source-specific volume level up or down to force audio automation to use that level instead of the volume level associated with the global setpoint.

Delete a Set Point


1. Right-click in the program fader control volume level area. The **Set Point Context Menu** ([Figure 169](#)) appears.

Figure 169. Set Point Context Menu – Wheatstone Audio



2. Click **Set Point Maintenance**. The **Set Point Maintenance** dialog box appears. Refer to [Figure 170](#).

Figure 170. Set Point Maintenance Dialog Box




3. From the **Select a Setpoint** list, click a Setpoint to delete.
4. Click **Delete**. The **Delete Entry?** message appears:
 - Click **Yes** to continue deleting the selected Set Point.
 - Click **No** to keep/not delete the item.

Clear Set Points From a Virtual Source

1. Right-click on the program fader control that controls the target virtual source. The **Set Point Context Menu** ([Figure 171](#)) appears.

Figure 171. Set Point Context Menu – Wheatstone Audio



2. Click **Clear All Fader Set Points**. All Set Points specific to the virtual source controlled by the program fader control are removed.


Virtual Sources

Edit a Virtual Source Entry

Note If the **Audio Main Context Menu** is accessed via right-click on a program fader control, the **Virtual Source Maintenance** dialog box appears with the virtual source for the targeted program fader control already selected. If the **Audio Main Context Menu** is accessed via right-click on an empty program fader slot, the first virtual source in the list is selected by default.


1. Right-click near the right edge of the program fader control to be edited. The **Audio Main Context Menu** (Figure 172) appears.

Figure 172. Audio Main Context Menu




2. Click **Virtual Source Maintenance**. The **Virtual Source Maintenance** dialog box appears. Refer to Figure 173.

Figure 173. Virtual Source Maintenance Dialog Box




3. In the **Select a Virtual Source** list, click a virtual source to edit and then click **Edit**. The **Virtual Source Editor** dialog box (Figure 174) appears.

Figure 174. Virtual Source Editor Dialog Box – Wheatstone Audio)



4. Within **Virtual Source Identification** (Figure 175):
 - a. In the **Name** text box, type a name for the virtual source (required)
 - b. In the **Abbreviation** text box, type an abbreviation for the virtual source (required)

Figure 175. Virtual Source Identification



5. Within **Input Channel Mapping** (Figure 175):


- a. In the **Available Input Channels** list, click a fader (or Unmapped if the virtual source should not control a fader).
- b. Click **Map** to map the selected fader

Set Up Audio Task Properties

Note Set points must be created before creating audio tasks. A set point does not need to be assigned to a virtual source in order for the virtual source to use the set point, but at least one set point must exist.

1. On the timeline, drag an audio command over. Double-click the Audio Property icon. The **Audio Timeline Task List** dialog box (Figure 176) appears.

Figure 176. Audio Timeline Task List Dialog Box




2. Click a task and then click either **Add New Task**, **Edit Task**, **Delete Task**, **Move Up**, or **Move Down** as needed. If either **Add New Task** or **Edit Task** are chosen an **Audio Task** dialog box (Figure 177) appears.

- Complete the entries in this dialog box, click OK, and then proceed to the next step.

Note The duration field should be set to the number of frames over which the fade will occur. If left blank or set to 0, a cut is performed instead.

Note Click **IGNORE** to set an audio source so that the **Take all to Zero** command ignores that specific source when setting all sources to zero. Clicking **IGNORE** sets the duration to 0 frames and disables the **Please enter a duration** box. The **Ignore** feature is accessed through the individual Audio Module TME icon properties

Figure 177. Audio Task Dialog Box



3. Repeat Step 1 and Step 2 for adding tasks for each individual task in the same audio command.

4. Click **OK**.


Note Click the **Take All Sources to Zero** check box (Figure 176) to have all other sources without a task assigned to go off air at 0 duration.

5. Click **Done**.

Create an Audio Layout


1. Right-click near the right edge of a program fader control or in an empty program fader slot. The **Audio Main Context Menu** (Figure 178) appears

Figure 178. Audio Main Context Menu



2. Select **Layouts**, and then select **Create Layout**. The **Layout Editor** dialog box appears. Refer to [Figure 179](#).

Figure 179. Create an Audio Layout – Menu




Note The **Layout Identification Name** is limited to 20 characters and must be unique.

3. In **Layout Identification Name**, enter a unique name for the new Audio Layout.
4. In **Layout Identification Preset**, enter the name of the Wheatstone Mixer Program Event to be associated with the new Audio Layout.
5. In the **Virtual Source Fader Assignments** section, use the option buttons and drop-down lists to select the fader that should be controlled by each Virtual Source while the associated Program Event is loaded on the mixer.
6. Either:
 - Click **OK** to save the Audio Layout
 - Click **Cancel** to discard it.

Save Current Audio Layout


1. Right-click near the right edge of a program fader control or in an empty program fader slot. The **Audio Main Context Menu** ([Figure 180](#)) appears.

Figure 180. Audio Main Context Menu



2. Select **Layouts**, and then select **Save Current Layout As...** The **Layout Editor** dialog box appears. Refer to [Figure 181](#).

Figure 181. Create an Audio Layout – Menu




Note The **Layout Identification Name** is limited to 20 characters and must be unique.

3. In the **Layout Identification Name** box, enter a unique name for the new Audio Layout.
4. In **Layout Identification Preset**, enter the name of the Wheatstone Mixer Program Event to be associated with the new Audio Layout.
5. In the **Virtual Source Fader Assignments** section, update the option buttons and drop-down lists as necessary.
6. Either:
 - Click **OK** to save the Audio Layout
 - Click **Cancel** to discard it

Load An Audio Layout


1. Right-click near the right edge of a program fader control or in an empty program fader slot. The **Audio Main Context Menu** (Figure 182) appears

Figure 182. Audio Main Context Menu



2. Click **Layouts**, then click the <layout name>, and then click **Load** where <layout name> is chosen from the list of existing Audio Layouts (Figure 183). The **Load Layout?** message appears.

Figure 183. Load An Audio Layout Example




3. Either:
 - Click **Yes** to continue loading the selected layout
 - Click **No** to cancel loading

Edit an Audio Layout


1. Right-click near the right edge of a program fader control or in an empty program fader slot. The **Audio Main Context Menu** (Figure 184) appears.

Figure 184. Audio Main Context Menu



- Click **Layouts**, then click the <layout name>, and then click **Edit** where <layout name> is chosen from the list of existing Audio Layouts. The Layout Editor dialog box appears with the selected audio layout loaded. Refer to [Figure 185](#).

Figure 185. Edit An Audio Layout Example



Note The **Layout Identification Name** is limited to 20 characters and must be unique.

- In the **Layout Identification Name** box, edit the unique name as desired.
- In the **Layout Identification Preset** box, edit the preset as desired.
- In **Virtual Source Fader Assignments**, edit the option buttons and fader mapping drop-downs as desired.

6. Either:


- Click **OK** to save the edited Audio Layout
- Click **Cancel** to close without making the edit changes.

Note An Audio Layout must be reloaded in order for the saved changes to take effect if the layout in question was used to load the current audio layout.

Delete an Audio Layout


1. Right-click near the right edge of a program fader control or in an empty program fader slot. The **Audio Main Context Menu** (Figure 186) appears.

Figure 186. Audio Main Context Menu



2. Click **Layouts**, then click the <layout name>, and then click **Delete** (Figure 187) where <layout name> is chosen from the list of existing Audio Layouts. The **Delete Entry?** message appears.

Figure 187. Delete An Audio Layout Example




3. Either:

- Click **OK** to save the edited Audio Layout
- Click **Cancel** to close without making the edit changes.

Audio Preview

Audio sources transitioned via the Ignite/Ignite Konnect Event Timeline are populated into the Audio Preview area (Figure 188) as each TME is prepped. The sources set to move to air next are shown in the Audio Preview area.

Figure 188. Audio Preview Area Example – Wheatstone Audio




Note The previewed audio shows the program fader control level when the source is transitioned to air. If a different transition level is desired before going to air, adjust the level while it is in Preview.

- To set the desired post-transition fader level, move the program fader control handle to the desired level.
- To prevent a source from going to air, after a TME has been prepped, click **H** to hold the source in preview.
- In **Preview**, right-click an audio source to select either:
 - Take to Air Now – send it to air immediately
 - Remove From Preview – remove it from Preview and not go to air

Audio Program (LIVE)

The **Audio Program** area ([Figure 189](#)) shows the virtual sources presently On Air. Any source that is moved above its level point is taken to air instantly and is shown in the **Audio Program** area.


Figure 189. Audio Program Area Example – Wheatstone Audio



- To remove the audio mix, right-click any source and then click **Take Off Air Now**.

Calrec, Lawo, and Studer Audio

Figure 190. Audio Module - StuderAudio



Overview

Note The Ignite/Ignite Konnect system provides an automation interface (Figure 190) to the Calrec, Lawo, and Studer panel. For panel-specific user and set up information, refer to the manufacturer's documentation.

The Ignite Audio control interface provides the ability to control the following functions of a supported Calrec, Lawo, or Studer audio mixer:

- Control an available input channel fader on a mixing console. The interface offers up to 192 possible faders depending on the model of mixer.
- Manually control an available main fader on the console. The console offers up to 4 main faders depending on the model of mixer. Main faders are controlled from Ignite using the Masters Mains faders.
- Switch between backup and primary fader control from Ignite.
- Execute fades from automation.
- Turn On/Off PFL.
- Enable/disable channel Cut/On for channel faders (not controllable for master faders). This feature turns On/Off the CUT button located above a channel fader on the mixer. NOTE: The Cut feature is completely different from a fader being cut to a level.





Fader Manual Virtual Source Control



Virtual Sources provide a mapping between Automation Events and Input Channel Faders on the Audio Mixer. Virtual Sources play a significant role in Automation Events by enabling Automation Events to control target Sources regardless of which Input Channels the Sources have been assigned to on the Calrec, Lawo, or Studer Mixer.

In order to control a virtual source from the Audio GUI, configure a virtual source to a slot, via the **Page Configuration** dialog box, on the Audio Module GUI, to represent the virtual source visually. Otherwise, the virtual source idly waits in the background for commands from Ignite/Ignite Konnect Timeline Automation or external control surfaces such as the QUICbox™ panel.

Individual Program Fader Controls and Indicators

Figure 191. Fader Buttons – Calrec, Lawo, and Studer Audio

Selected	Function
	<p>Hold Enables/Disables the associated Virtual Source's Automation Hold feature (latching). This is an alert that the Program Fader and associated Virtual Source will ignore all Automation events until the Program Fader is taken off Hold.</p> <p>Note If the Virtual Source does not have a mapped Fader, the outline of the Program Fader is red instead).</p>
	<p>C (Cue - Pre Fade Listen/Cue) Activates or de-activates the PFL/Cue button for the Input Channel.</p> <p>In Studer, faders might not have Cue/PFL. In this case, the C button will be grayed out.</p> <p>Note PFL is disabled automatically by Automation Events that take the Virtual Source from OFF to any other level.</p>
	<p>B (Backup) Toggles between the associated Fader's primary and backup sources. When selected, it highlights blue and transfers control to the backup source. If no backup fader is assigned the button is unavailable.</p> <p>Note "The backup fader button, B, is unavailable if a backup fader is unassigned.</p>
	<p>Fader Level Control Displays and adjusts the volume level of the Virtual Source's Active Fader. When being adjusted, the handle turns blue and the dB/dBFS value displays in place of the Source Abbreviation at the bottom of the respective virtual source control. The handle is also blue when the mouse cursor is hovering over the handle, in which case the level is not being adjusted.</p>

Selected	Function
	Off / On Toggles a Cut on or off for the Virtual Source's Active Fader. When Cut is Off, highlights green. When Cut is On, highlights red.
	Displays either the Virtual Source Abbreviation or, when the fader is being moved, a dB/dBFS value.

Note For all of the buttons, a gray background indicates it is not active.

Each program fader control ([Figure 191](#)) has:

- **Hold** – Enables/Disables the associated Virtual Source Automation Hold feature (latching).
- **C** – (Cue) Activates/Deactivates PFL (Pre-fade Listen) Cue for the associated Virtual Source (latching). C might be unavailable in Studer.
- **B** – (Backup) Toggles between the associated primary and backup sources. If no backup fader is assigned the button is unavailable.
- Fader level control handle – Adjusts the virtual source dB/dBFS level. The fader control handle highlights blue when being adjusted. When adjusted the **Abbreviation/Level** display changes from the assigned abbreviation to the current dB level setting.
- **Off/On/Abbr/Value** – Selects and indicates:
 - **Off** (green) – (Toggled off) Deactivates **Cut** for the Virtual Source fader.
 - **On** (red) – (Toggled on) Activates **Cut** for the Virtual Source fader.
 - **Abbr** – Displays the assigned abbreviation when the fader is static.

Note The Katalyst panel or Automation Soft Panel (ASP) will display the Abbr.

- **Value** – Displays the numeric dB level setting when the fader control handle is moving.

When either the **C** or **B** button is clicked, the button background highlights blue to indicate it is selected. When the **Hold** button is clicked, the button background highlights amber to indicate it is selected.

If the Virtual Source does not have a mapped Fader, the outline of the Program Fader is red ([Figure 192](#)). A Virtual Source that does not have a

fader mapped to it does not actually control any elements on the mixer. If a fader is later mapped to such a Virtual Source, the properties of the Virtual Source will be applied to the Fader.

Figure 192. Example – Virtual Source Without Mapped Fader



Audio Preview

Figure 193. Audio Preview Area



Virtual sources transitioned via the Ignite/Ignite Konnect Event Timeline are populated into the **Preview** pane (Figure 193) as each TME is prepped. The virtual sources set to move to air next are shown in the **Preview** pane.

Available controls within the **Preview** pane are:


- **Take All Sources Off Air** - toggles the **Take All Sources Off Air** setting for the prepped audio automation task.

You can also right click on the Prepped Virtual Source and you have the options below:

- **Take to Air Now** - take it to air right away.
- **Remove from Preview** - totally ignore this fader when going through the TME.

Audio Live

Figure 194. Audio Program Area




The **Live** pane (Figure 194) shows the virtual sources presently On Air. Any virtual source that is moved above its off point is taken to air instantly and is shown in the **Live** pane.

Note Only the 8 most recent virtual sources to go on air and still exist on air are shown. Once 9 virtual sources are on air, the oldest on-air virtual source disappears and reappears if another is taken off air.

Virtual Source Configuration

Figure 195. Virtual Source Configuration




To access the **Virtual Source Configuration** dialog box, (Figure 195), click **Virtual Source** at the top right corner above **Masters** (Figure 195). Up to 192 mixer faders (depending on the model) can be assigned, or mapped, to Ignite Virtual Sources. The **Virtual Source Configuration** dialog box comprises a:

- **Virtual Source** list – selects the Virtual Source to edit .
- **Virtual Source** pane –
 - **Identification** area –
 - **Name** – text box for assigning/editing the virtual source name (1 – 20 characters)
 - **Abbreviation** – text box for assigning/editing the virtual source abbreviation (1 – 4 characters). This is the label for Katalyst and ASP panel.

- **Fader Assignment** area
 - **Primary Fader** – combo box for assigning a primary fader.
 - **Backup Fader** – combo box for assigning a secondary fader.
 - **Refresh Channel Labels** – button to update all channel labels of the Studer audio device. This button is only available for the Studer Audio configuration.
- **Setpoint Overrides** area
 - **Setpoint** list – selects the Setpoint to override for the Virtual Source.
 - **Level** fader – displays and edits the level of the selected Setpoint override
 - **Display Color Marker** – check this option to display a color marker control on the Virtual Source control in the Audio GUI. This color marker control can be dragged to update the override level dynamically.
- **Exempt from “Take All Sources Off”** – check this option to prevent the “Take All Sources Off” feature from affecting the virtual source.
- **Hide In LIVE Pane** – check this option to prevent the display of the virtual source in the Live Panel.

Setpoint Configuration

Figure 196. Set Point Configuration



Setpoints are pre-established fader levels that are referenced via a TME (Transition Macro Event), refer to *TME™ (Transition Macro Event™)* on [page 34](#). Set points are used to set the fader level of a Virtual Source during a transition. Setpoints can be named for easy reference. Via Event Timeline automation, each TME provides the system with the audio setpoint needed for that particular event. To access the **Setpoint Configuration** dialog box, ([Figure 196](#)), click **Setpoints** at the top right corner above **Masters** ([Figure 196](#)).

Two default setpoints are system defined and non-editable by the user:


- **OFF** – used to bring a Virtual Source off the air
- **IGNORE** – used to flag a Virtual Source so that it will not be affected by the **Take All Sources Off** feature of Audio TMEs

There are 24 configurable setpoints. The **Set Point Configuration** dialog box comprises:

- **Setpoint** list – used to select the setpoint to configure.
- **Setpoint** configuration pane.
 - **Name** – text box for assigning/editing up to a 16 character name.
 - **Level fader** – slide to select/set the setpoint level.
- **OK** – saves the changes and closes the dialog box.
- **Cancel** – closes the dialog box without saving changes.

Show Profiles Configuration

Figure 197. Show Profiles Configuration



The format is **ProfileName (SnapshotName)**. When the snapshot is not available (for example, it was deleted or renamed) the snapshot name is grayed out to let the user know that the profile is no longer mapped to a valid snapshot.

- Show Profiles are created in Ignite and you can include snapshots already configured in the audio device when creating a show profile.
- Snapshots are pre-established audio profiles that are referenced from the audio device via a TME (Transition Macro Event). Snapshots can also be selected in the Audio Task Editor.
- To create a new profile via the **New Show Profile** dialog box, click **Show Profiles > New Show Profile** on the Ignite Audio interface.
- To select a configured **Profile**, click **Show Profiles > Profiles** and select from the list of profiles. You can right click on a Show Profile to edit or delete a profile.
- To select a configured **Snapshot**, click **Show Profiles > Snapshots** and select from the list of snapshots.

Masters Mains Output Faders

The **Masters Mains Faders** ([Figure 198 on page 174](#)) are located on the **Masters** pane. The main fader(s) provide master control of the overall audio output level of the Master Out channels. Depending on system configuration, there are two to four Main faders:


- Master 0
- Master 1
- Master 2
- Master 3

If master fader(s) are hidden (not visible on the **Masters** pane), clicking the **Mains** expand arrow displays the available master output faders. To hide the displayed master faders, click the **Mains** collapse arrow.

Each fader has a **Cue** button that when selected, highlights blue, updates that master fader to reflect the **Cue** volume, and assumes control of that volume.

For Studer audio faders, each fader has a **Cut** button under the **Cue** button in the **Masters** pane as highlighted in red below. However, **Cut** buttons in the **Masters** pane are not supported for Lawo and Calrec audio faders.

Figure 198. Master Output Fader



Audio Task Configuration

Audio Task Configuration is accomplished via the **Audio Task Editor** dialog box. Access to the **Audio Task Editor** dialog box (Figure 199 on page 176) is via a TME Audio icon placed on the Event Timeline (refer to *TME™ (Transition Macro Event™)* on page 333).

The Audio Task Editor comprises:


- **Start Time** – displays and edits the task's starting time as it relates to the beginning of the timeline in frames.
- **Task List** – displays an entry for each Virtual Source and indicates what action should take place for that Virtual Source when the Audio Task is executed. In addition, Lawo and Studer has the Snapshot combo box that can be selected for the Audio Task.
 - **Snapshot** – displays the drop-down list of snapshots. This option is mutually exclusive with the task operations. In other words, if a Snapshot is selected, none of the tasks is available.
 - **Virtual Source** – displays the name of the Virtual Sources

- **Setpoint Action (None, Off, Ignore)** – displays and edits the Setpoint Action to be executed on the Virtual Source when the Audio Task is executed. The setpoint action can also be to take one of the 24 configurable setpoints (i.e. Take Setpoint 1).
- **Duration** – displays and edits the duration time (in frames) that the virtual source takes (if applicable) to move to that setpoint when the Audio Task is executed.
- **Take All Sources Off** – enables/disables the Take All Sources Off feature of the target Audio Task. When selected, highlights blue and takes every source that is not part of the current audio task to off.

In contrast, a virtual source set to setpoint action None is simply not included in the current audio task. So it may or may not be cut to off depending on whether it happens to be on air currently.

- **Override Auto Channel Duration** – enables/disables the override of the auto channel task duration specified by IQ. When selected, highlights blue and instead of the default duration set in IQ Auto Channel Pool setup, the IQ Auto Channel uses the duration entered in the box to bring the other channels off.
- **Override Duration box** – sets the **Override Auto Channel Duration**

Figure 199. Audio Task Editor Dialog Box



Operation

- Note** The Ignite/Ignite Connect system provides an automation interface to the Calrec panel.
For panel-specific user and set up information, refer to the manufacturer's documentation.
- Note** Before the audio can be controlled, virtual sources must be configured. Typically this is accomplished during initial installation.

Adjust an Audio Source

- Note** The program fader control handle is used to adjust the level of the virtual source's associated fader.
- To manually adjust the level, click and drag the program fader control handle.
 - To jump or cut the active source to a desired volume, double-click above or below the program fader control handle.

Configure Pages

Note For all names, abbreviations, colors, and file structures, use established standards and consistent techniques and practices. Refer to *Standardization on page 577*.

1. At the top right of the **Virtual Sources** pane (Figure 200), click **Pages**. The **Page Configuration** dialog box (Figure 201 on page 177) appears.

Figure 200. Modify Page Name





Figure 201. Page Configuration Dialog Box



2. Click the **Page** tab to configure.

3. In the **Name** text box, type/edit the name.
4. Configure the page with the desired slots and virtual sources.
5. Click **OK**.

Name or Rename a Page

1. If the **Page Configuration** dialog box is not open, at the top right of the **Virtual Sources** pane, click **Pages**. The **Page Configuration** dialog box appears.
2. In the **Name** text box, type/edit the desired name.
3. Click **OK**.

Add/Assign/Edit a Slot or Virtual Source

1. If the **Page Configuration** dialog box is not open, at the top right of the **Virtual Sources** pane, click **Pages**. The **Page Configuration** dialog box appears.
2. Click the **Page** tab to configure.
3. Click the respective **Slot** (1 – 16) arrow and select the the desired virtual source from the drop-down list.
4. Click **OK**.

Remove a Slot or Virtual Source


1. If the **Page Configuration** dialog box is not open, at the top right of the **Virtual Sources** pane, click **Pages**. The **Page Configuration** dialog box appears.
2. Click the **Page** tab to configure.
3. Click the respective slot arrow and select **Virtual Source None** from the drop-down list.
4. Click **OK**.

Setpoint Configuration

To configure a Setpoint:

1. Click **Setpoints** at the top right corner above **Masters**. The **Setpoint Configuration** dialog box appears. Refer to ([Figure 202](#)).

Figure 202. Set Point Configuration



2. Select a Setpoint from the Setpoint list.
3. In the **Name** box, type/edit up to a 16-character name.
4. Using the Setpoint level fader, select a value.

Note For fine tune adjustment (0.1 db) use either the up/down arrow control next to the level text box or left click the thumb control and use the up/down arrows on the keyboard.


5. Repeat Steps 1– 4 for each Setpoint.
6. Click **OK**.

Virtual Source Configuration

Note For all names, abbreviations, colors, and file structures, use established standards and consistent techniques and practices. Refer to *Standardization on page 577*.

1. Click **Virtual Source** at the top right corner above **Masters** (Figure 203). The Virtual Source Configuration dialog box appears.

Figure 203. Virtual Source Configuration



2. In the **Virtual Source** list, click a virtual source to configure.
 3. In the **Virtual Source** pane under **Identification**:
 - In the **Name** text box type a name.
 - In the **Abbreviation** text box type an abbreviation.
 4. In the **Virtual Source** pane under **Fader Assignment**:
 - Click the **Primary Fader** arrow and select a Primary Fader from the drop-down list.
 - Click the **Backup Fader** arrow and select a Backup Fader from the drop-down list.
- Note** The same fader cannot be assigned as both primary and backup.
5. In the **Virtual Source** pane **Setpoint Overrides** list, select a setpoint to override.


6. In the **Virtual Source** pane, **Setpoint Overrides**, **Setpoint** fader, slide the fader to the desired override level.
7. Select the **Display Color Marker** check box to display a color marker on the Virtual Source control in the Audio user interface.
8. Click **Override** to apply this Setpoint Override setting to the selected Virtual Source.
9. Click **OK**.

Show Profiles Configuration


To configure a Show Profile:

1. Click **Show Profiles** at the top right corner on the left of **Virtual Sources**. The **Show Profiles** menu appears.


Figure 204. Show Profiles menu



2. Select **New Show Profile** from the menu to create a new Show Profile. The **New Show Profile** dialog box appears.



3. Enter a Profile Name for the new Show Profile.
4. Select a Snapshot from the dropdown list, if desired.
5. Click **OK**. The Profile name appears on the Ignite Audio interface. The Snapshot name displays in parenthesis if also selected.




6. To rename a profile, click **Show Profiles > Save As** and enter another name for the profile.
7. To load an existing profile, click **Show Profiles > Profiles** and select a profile from the list.
8. To load an existing snapshot, click **Show Profiles > Snapshots** and select a snapshot from the list.

Set Up/Edit Audio Task Properties

Note Setpoints should be configured prior to creating an audio task. However, if a setpoint is not configured it's given a default value of unity so if a task references a nonconfigured setpoint the worst case senario is that the source's level will be set to 0 db.

1. On the **Event Timeline**, drag an audio command over. Double-click the Audio Property icon. The **Audio Task Editor** dialog box ([Figure 205](#)) appears.

Figure 205. Audio Timeline Task List Dialog Box



2. Complete the entries in this dialog box for each task property.

Note The duration field should be set to the number of frames over which the fade will occur. If left blank or set to 0, a cut is performed instead.

Note Click the **Take All Sources Off** toggle button (Figure 205) to have all other sources without a task assigned to go off air at 0 duration.

3. Click **OK**.

Audio Preview

Audio sources transitioned via the Ignite/Ignite Konnect Event Timeline are populated into the Audio **Preview** pane (Figure 206 on page 184) as each TME is prepped. The sources set to move to air next are shown in the **Preview** pane.

You can also right-click on the Prepped Virtual Source and select the options below:

- **Take to Air Now** - take it to air right away.
- **Remove from Preview** - totally ignore this fader when going through the TME.

Figure 206. Audio Preview Area




Note The previewed audio shows the program fader control level when the source is transitioned to air. If a different transition level is desired before going to air, adjust the level while it is in Preview.

- To set the desired post-transition fader level, move the program fader control handle to the desired level.
- To prevent a source from going to air, after a TME has been prepped, click **Hold** to hold the source in preview.

Audio Live

The Audio **Program/Live** pane ([Figure 207 on page 185](#)) shows the virtual sources presently On Air. Any source that is moved above its level point is taken to air instantly and is shown in the **Preview** area.

Figure 207. Audio Program Area



- To remove from the audio mix, right-click any source and then click **Take Off Air**.
- To hold the source on air, click **Hold** while the source is in the area.
- To take off air, right-click the source and then click **Take Off Air**.

Automation Control Panels

Ignite Katalyst Automation Control Panel

Figure 208. Ignite Katalyst Panel Examples



Overview

The Ignite Katalyst™ panel (Figure 208) works dynamically with Ignite/ Ignite Konnect software to provide programmable buttons and audio con-

trols that meet the workflow requirements of both individual stations and individual operators:

Note The **Ignite Katalyst** Automation Control Panel is not required for Ignite/Ignite Konnect Live Production Control system operation but rather provides an alternate, manual event-triggering capability

- Profiles are selected at runtime by the user
- Profiles are selected using the **Ignite Katalyst Profiles** dialog box, which is accessed from the **Event Timeline Setup** menu.
- Profiles are edited using the **Ignite Katalyst Profiles Editor**, which is accessed from the Windows **Start** button
- Buttons are configured using the **Ignite Katalyst Button Toolbox**.

Note In an Ignite/Ignite Konnect No-Audio configuration, the audio user interface area is blank and an Ignite Katalyst Panel is not supported; therefore, this Ignite Katalyst Panel information does not apply.

A modular and scalable peripheral Ignite Katalyst panel provides tactile control of Ignite system functions for:

- Events [up to 10 banks of 20 buttons per bank] (refer to [Button Module on page 189](#))
- Audio faders ([Audio Module on page 195](#))


Note Button programming is accomplished using the **Ignite Katalyst Button Toolbox**. The **Ignite Katalyst Button Toolbox** is accessed via the Windows **Start** button or from the Profile Editor, Button module, and Fader module **Tools** menus. Ignite Katalyst Profiles are configured/edited via the **Ignite Katalyst Profiles Editor**. The **Ignite Katalyst Profiles Editor** is accessed from the Windows **Start** button.

Programming includes the ability to store and recall both simple and complex functions such as:

- Manual Video Switching & Audio Mixing
- Event Timeline Next Event command
- Manual CG & Keyer Controls
- GPI Triggers
- ShowBuilder Key Insert & Take Commands
- Audio Talkback, Cue, Hold, & Group Commands

Button Module

Figure 209. Button Module Example



The Programmable Buttons Module ([Figure 209](#)) comprises 1 row of 10 bank selection buttons and 20 programmable buttons with associated OLED displays (4 rows with 5 buttons in each row).

Note To increase the number of available buttons, more than one Button Module can be used with an Ignite system.

The 10 bank selection buttons serve a fixed purpose and only button colors are configurable. Selecting a bank button causes all twenty programmable buttons to assume the programmed configuration for that bank.


Each of the 20 programmable buttons can be color coded in 1 of 20 colors and configured to execute either an Ignite timeline command or a TME

This bank/programmable buttons combination provides 200 programmable buttons. That is:

- When the **Bank 1** button is pressed, each of the 20 programmable buttons is individually configured to Bank 1
- When the **Bank 2** button is pressed, each of the 20 programmable buttons is individually configured to Bank 2
- When the **Bank 3** button is pressed, each of the 20 programmable buttons is individually configured to Bank 3
- And so on for each of the remaining Bank buttons 4 through 10

Programmable Buttons

Figure 210. New Button Module Dialog Box



A button can be programmed to execute either a TME or an Ignite command. This one-button TME/Ignite command functionality can comprise either:

- Insert a TME at the current cursor position on the Ignite timeline
- Auto-execute as a normal or hidden TME
- Perform an Ignite action

Note Button programming is accomplished using the **Ignite Catalyst Button Toolbox**.

Typical programmable-button functionality includes but is not limited to:

- Bus switching – the ability to program an Ignite Catalyst programmable button to manually change sources on PGM, PVW, AUX, or KEY buses.
- Switcher Events.
 - Set program (PP and any M/E) to black, matte, pattern, or any available video input.
 - Set preview (PP and any M/E) to black, matte, pattern, or any available video input.
 - Set Auxiliary Buses to black, matte, pattern, or any available video input.

- Set Keyer buses to black, matte, pattern, or any available video input.
- GPO/GPI triggering – the ability to manually trigger any device that can accept a GPO/GPI.
- Timeline control – provides one-button control for functions such as:
 - Next Step (skips the Event Timeline cursor to the next GPI mark).
 - Previous Step (skips the Event Timeline cursor to previous GPI mark).
 - Next Group (skips the Event Timeline cursor to the left edge of next group).
 - Previous Group (skips the Event Timeline cursor to left edge of previous group).
 - Next Slug (skips the Event Timeline cursor to left edge of next slug/page).
 - Previous Slug (skips the Event Timeline cursor to previous slug/page).
 - Next Story (skips the Event Timeline cursor to left edge of next story).
 - Previous Story (skips the Event Timeline cursor to previous story).
 - Cue (ALT+Q) moves the Event Timeline cursor to the beginning of the timeline.
 - Run (ALT+SPACEBAR) starts the Event Timeline cursor.
 - Pause (ALT+P) stops the Event Timeline cursor.
 - Go to Cursor (ALT+G) shifts timeline view to current cursor location.
 - Update Rundown (imports rundown to the Event Timeline when changes are made to rundown – if rundown is monitored). The button blinks if an Ignite rundown update is available.
- CG list control (TME assigned to a button):
 - Load next CG in list (advance CG list).
 - Load previous CG in list (moves to previous CG in CG list).
- Downstream CG keying – the ability to manually insert lower third or other keys from a CG device. This eliminates the need for a third party downstream key box or having to use the mouse for CG insertion.

Programmable Button Display Attributes

Note Button programming is accomplished using the **Ignite Katalyst Button Toolbox**. Refer to [Ignite Katalyst Button Toolbox on page 193](#).

Color

Color is configured individually for each button. Programmable buttons are configured either to:

- Be off (inactive)
- Display in one of 20 colors

Note The ten bank selection buttons serve a fixed purpose and only button colors are configurable. Pressing a bank selection button illuminates the button and causes all twenty programmable buttons to assume their configuration for that bank.

Text or Graphics

Ignite Katalyst programmable buttons are configurable to display either text or a graphic image.

- Text display is:
 - Proportional (variable-width) type
 - Upper and lower case, sans-serif font (similar to Arial Bold)
 - Either 3 lines of 9 point type (typically 1-9 characters/line), 3 lines of 12 point type (typically 1-6 characters/line, 2 lines of 16 point type (typically 1-5), or 1 line of 28 point type (typically 1-3 characters/line)
 - Aligned left, right, or center for the individual button as a whole
- Graphic displays can be either:
 - Bitmaps provided via the Button Toolbox
 - User-provided bitmaps

Ignite Katalyst Button Toolbox

Figure 211. Ignite Katalyst Button Toolbox Style, Color, Action, and Bitmap Pages



The **Ignite Katalyst Button Toolbox** (Figure 211) is accessed from the **Ignite Katalyst Profile Editor** (refer to [Profile Editor on page 198](#)). A physical button panel is configured using any/all of the four **Ignite Katalyst Button Toolbox** icons located along the top of the button toolbox (Figure 211):

- **Style** – assigns the type size (9 pt, 12 pt, 16 pt, or 28 pt) and justification (left, centered, right)
- **Color** – assigns a color from the available color pallet
- **Action** – assigns an action; e.g., Update Rundown, Next, Previous, Play,
- **Bitmap** – assigns a bitmap

All configuration is performed either by:

- Typing text in a programmable button display area
- Dragging a button from the **Ignite Katalyst Button Toolbox** and dropping it on a new or existing button
- Dragging and dropping a file from Windows Explorer and dropping it on a new or existing button

Features of the **Ignite Katalyst Button Toolbox** dialog box include:

- Copying Banks – the entire content of the currently selected bank can be copied to another bank by dropping one bank button on another.
 - When copying within the same button module, the current bank can be copied to any other bank.
 - When copying to another button module, to prevent inadvertently replacing a bank whose data is not currently displayed, the copy can only be to the currently selected bank in the target module.
- Bank Selection Buttons **1–10** – the top row of 10 bank buttons are dedicated to bank selection only; therefore, only button color is assigned.
- Action (command) buttons – The 20 programmable buttons are user configured for color, action (either execute an action or place a TME on the Ignite timeline), text, or a bitmap.
 - **Color** page – provides 20 standard button colors. Assign a button color by dragging and dropping the desired color button from the **Color** page onto a programmable button—either a bank or a programmable.
 - **Action** page – provides 13 standard Ignite commands. Assign an action by dragging and dropping the desired **Action** button onto a programmable button.

A TME **Action** is assigned to a button by dragging the desired .tmx or .iqt file from Windows Explorer and dropping it on a button. Ignite Katalyst stores only the file location, not the contents, so the latest version of a .tmx or .iqt is always used by Ignite Katalyst. Mark a TME **Auto Execute** or **Auto Execute Hidden** by dropping either of those buttons onto a programmable button.

Note To remove an Action or a TME from a button, drag and drop the **Remove Action** button onto a programmable button.

- **Style** page – provides a choice of 9-, 12-, 16-, and 28-point type in left, center, and right alignment combinations. A **Style** is assigned by dragging and dropping the desired **Style** button onto a programmable button.

Text is entered by clicking in the text area of a programmable button and typing up to four lines of text. The typed text closely approximates that of the physical Ignite Katalyst panel but the text should be downloaded to the Ignite Katalyst panel for a final text proofread.


- **Bitmap** page – enables assigning a bitmap to a programmable button either by dragging and dropping:
 - The desired bitmap from the **Bitmap** page onto a programmable button.
 - A customer provided .bmp file from Windows Explorer onto a programmable button.

Note User supplied graphics must be exactly 64 x 64 pixels, 4-Bit Monochrome bitmaps. The programmed button is changed from bitmap to text mode by dragging and dropping a style button onto a programmable button.

- **Save Configuration** – save the current button configuration.
- **Save Configuration As** – saves the current configuration as a different name.

Audio Module

Figure 212. Audio Module



An Audio Module (Figure 212) provides tactile control of Ignite system fader functions. Each motorized fader provides quick, tactile control of audio input. The motorized audio faders and related buttons operate in unison with, and mirror, the respective Ignite Audio Fader module controls, buttons, and button indications.

Note To increase the number of available faders, more than one Audio Module can be used with an Ignite system.

The displays across the top are automatically assigned to identify the fader type and the source being controlled. The three fader-related buttons are:

- **C** – (Cue) monitors a channel pre-fader
- **B** – (Backup) switches a channel to backup
- **H** – (Hold) holds a source on or off air

Note An illuminated **C**, **B**, or **H** button indicates that the button is selected.

Panel Profiles


A panel profile describes how Ignite Katalyst Button and/or Audio Modules are configured. Each individual profile contains all the information that an Ignite system needs to configure and communicate with the physical panels defined in that profile. A profile can describe more than one physical panel.

There are two profile dialog box versions:

- Run time (refer to [Ignite Katalyst Profiles \(Run Time\) Dialog Box on page 196](#))
- Design time (refer to [Ignite Katalyst Profiles \(Design Time\) Dialog Box on page 197](#))

Ignite Katalyst Profiles (Run Time) Dialog Box


Figure 213. Ignite Katalyst Profiles (Run Time) Dialog Box Example



The Ignite Katalyst Profiles (Run Time) dialog box ([Figure 213](#)), which is accessed from the **Event Timeline** module **Setup** menu, only allows a user to select an existing profile. All existing profiles are displayed in a list sorted by profile name. Selecting a profile button from the list uploads that profile information to the Ignite system and closes the profile selection window.

Ignite Katalyst Profiles (Design Time) Dialog Box

Figure 214. Ignite Katalyst Profiles (Design Time) Dialog Box Example



The **Ignite Katalyst Profiles** (Design Time) dialog box ([Figure 214](#)), which is accessed via the Windows **Start** button, displays all existing profiles in a list sorted by profile name. Accessing this dialog box enables a user to either:

- Select a profile from the list and upload that hardware configuration information to the appropriate Ignite Katalyst panel(s).
- Preview and edit a profile.
- Delete a profile


Note Uploaded profile configuration information is stored in non-volatile memory and is automatically reloaded once Ignite connects to the panel(s).

- Use the **Tools** menu to:
 - Add a **New Profile** – adds a new, empty profile to the profile list. The new profile can then be renamed and edited as desired.
 - Create a **New Fader Module** – displays an empty fader module configuration. The new module configuration can then be edited and added to a profile as desired.
 - Create a **New Button Module** – displays an empty button module configuration. The new module configuration can then be edited and added to a profile as desired.
 - **Open Button Toolbox** – opens the **Ignite Katalyst Button Toolbox**.

- Use the **File** menu to:
 - **Save Profiles** – saves all modifications made to the profile configuration. Modifications to the individual button and fader module configurations are not saved by this action.
- **Close** – closes the **Ignite Katalyst Profiles** dialog box, first asking if modified profiles should be saved. Any open button or fader module configuration window remains open.
- Add (+) a module configuration(s) – each physical Ignite Katalyst panel contains one or more audio and/or button modules. The user models an Ignite Katalyst physical configuration by adding a module configuration file to the profile for each of a panel's physical modules.
- Delete (X) a profile.

Profile Editor

Figure 215. Profile Editor



A **Profile** (Figure 215) is displayed by clicking the **Profile Editor** arrow at the left of the Profile Name to be edited. The **Profile Editor** enables a user to:

- Name/rename a profile – profiles are user named by typing in the **Profile Name** text box. There are no naming restrictions. Duplicate names are allowed but the Ignite system always selects the first occurrence of a profile name.
- Browse (...) to and select a module configuration(s) – button and fader configuration files are created independently of a profile. The configuration file(s) are then added to one or more profiles, as desired, by adding the configuration file path to the profile. Either type a module file path or open a file selection dialog by clicking the browse (...) icon.
- Add a module configuration(s) – each physical Ignite Katalyst panel contains one or more audio and/or button modules. The user models an Ignite Katalyst physical configuration by adding a module configuration file to the profile for each panel's physical modules.
- Assign the module configuration to a panel – although a physical Ignite Katalyst panel has only one name (i.e. the panel's modules are not addressed independently), in a profile the panel name is specified for the module configuration. This enables a profile to configure more than one physical panel, as well as allowing a module configuration file to be used in more than one profile.
- View and edit module details – a module configuration file can be opened for viewing and editing directly from the profile selection window.
- Delete a profile.


Configuration

Create a Module

Button Module

1. On the taskbar, click the Start button, and then point to All Programs. Point to Ignite Katalyst and then click Katalyst Profiles. The **Ignite Katalyst Profiles** (Design Time) dialog box ([Figure 216](#)) appears.

Figure 216. Ignite Katalyst Profiles (Design Time Dialog Box) Example



2. From the **Tools** menu, click **New Button Module**. The **New Button Module** dialog box (Figure 217) appears.
3. From the **Tools** menu, click **Open Button Toolbox**. The **Ignite Katalyst Button Toolbox** (Figure 217) appears.

Note The Ignite Katalyst Button Toolbox initially opens to the Style page.

4. From the **Ignite Katalyst Toolbox**, drag and drop the desired **Style**, **Color**, **Action**, and **Bitmap** options, to the **Button Module** (Figure 217). Refer to [Assign/Edit/Re-assign Button Style on page 203](#), [Assign/Edit Button Color on page 206](#), [Assign/Edit a Button Action on page 208](#), and [Assign/Edit a Button Bitmap on page 212](#).

Figure 217. Add New Module Example




5. On the **BUTTON MODULE** dialog box, from the **Files** menu, click either:
 - **Save Configuration** – to save the changes to the existing profile.
 - **Save Configuration As** – to name and save the changes as a new profile.
6. Close the **BUTTON MODULE**.
7. Close the **Ignite Katalyst Button Toolbox**.

Fader Module


1. On the taskbar, click the Start button, and then point to All Programs. Point to Ignite Katalyst and then click Katalyst Profiles. The **Ignite Katalyst Profiles (Design Time)** dialog box (Figure 218) appears.

Figure 218. Ignite Katalyst Profiles (Design Time Dialog Box) Example




2. From the **Tools** menu, click **New Fader Module**. The **New Fader Module** dialog box (Figure 219) appears.

Figure 219. New Fader Module Dialog Box Example



3. In the **New Fader Module** dialog box, click the **Size** arrow to the right of the fader to be added; e.g., **Fader 06**, **Fader 07**, **Fader 08**. The fader source drop-down list (Figure 220) appears.

Figure 220. Fader Source Drop-down List



4. Select the fader source
5. On the **New Fader Module**, from the **Files** menu, click either:
 - **Save Configuration** – to save the changes to the existing profile.
 - **Save Configuration As** – to name and save the changes as a new profile.
6. Close the **FADER MODULE**.


Configure a Button

Note Button configuration is accomplished from the Design Time Ignite Katalyst Profiles dialog box), which is accessed via the Windows Start button. Refer to [Ignite Katalyst Profiles \(Design Time\) Dialog Box](#) on page 197.

Assign/Edit/Re-assign Button Style


1. On the taskbar, click the **Start button**, and then point to **All Programs**. Point to **Ignite Katalyst** and then click **Katalyst Profiles**. The **Ignite Katalyst Profiles (Design Time)** dialog box ([Figure 221](#)) appears.

Figure 221. Ignite Katalyst Profiles (Design Time Dialog Box) Example



2. Click the **Size** arrow at the left of the Profile to be changed. The **Profile Editor** expands below the profile name and the **Size** arrow points downward (Figure 222).

Figure 222. Profile Editor



3. From the **Profile Editor**, click **E** to the right of the Button Module to be changed. The selected Button Module appears.
4. From the **Tools** menu, click **Open Button Toolbox**. The **Ignite Katalyst Button Toolbox** appears.

Note The Ignite Katalyst Button Toolbox initially opens to the Style page.

5. In the **Ignite Katalyst Toolbox**, if not selected, click the **Style** button (Figure 223).
6. From the **Style** options, drag the desired style from the **Ignite Katalyst Toolbox** to the **Button Module** button to be assigned/edited (Figure 223).

Figure 223. Ignite Katalyst Toolbox – Style Button




7. On the **BUTTON MODULE** dialog box, from the **Files** menu, click either:
 - **Save Configuration** – to save the changes to the existing profile.
 - **Save Configuration As** – to name and save the changes as a new profile.
8. Close the **BUTTON MODULE**.
9. Close the **Ignite Katalyst Button Toolbox**.

Assign/Edit Button Color


1. On the taskbar, click the Start button, and then point to All Programs. Point to Ignite Katalyst and then click Katalyst Profiles. The **Ignite Katalyst Profiles (Design Time)** dialog box ([Figure 224](#)) appears.

Figure 224. Ignite Katalyst Profiles (Design Time Dialog Box) Example



2. Click the **Size** arrow at the left of the Profile to be changed. The **Profile Editor** expands below the profile name and the **Size** arrow points downward ([Figure 225](#)).

Figure 225. Profile Editor




3. From the **Profile Editor**, click **E** to the right of the Button Module to be changed. The selected **Button Module** appears.
4. From the **Tools** menu, click **Open Button Toolbox**. The **Ignite Katalyst Button Toolbox** appears.

Note The Ignite Katalyst Button Toolbox initially opens to the Style page.

5. In the **Ignite Katalyst Toolbox**, click the **Color** button. The **Color** options page appears.
6. From the **Color** options, drag the desired color from the **Ignite Katalyst Toolbox** to the **Button Module** button to be assigned/edited ([Figure 226](#)).

Figure 226. Ignite Katalyst Toolbox – Color Button




7. On the profile dialog box, **Files** menu, click either:
 - **Save Configuration** – to save the changes to the existing profile.
 - **Save Configuration As** – to name and save the changes as a new profile.
8. Close the profile.
9. Close the **Ignite Katalyst Button Toolbox**.

Assign/Edit a Button Action

Assign/Edit a Button Toolbox Action


1. On the taskbar, click the Start button, and then point to All Programs. Point to Ignite Katalyst and then click Katalyst Profiles. The **Ignite Katalyst Profiles** (Design Time) dialog box (Figure 227) appears.

Figure 227. Ignite Katalyst Profiles (Design Time Dialog Box) Example



2. Click the **Size** arrow at the left of the Profile to be changed. The **Profile Editor** expands below the profile name and the **Size** arrow points downward (Figure 228).

Figure 228. Profile Editor



3. From the **Profile Editor**, click **E** to the right of the Button Module to be changed. The selected **Button Module** appears.
4. From the **Tools** menu, click **Open Button Toolbox**. The **Ignite Katalyst Button Toolbox** appears.

Note The Ignite Katalyst Button Toolbox initially opens to the Style page.

5. In the **Ignite Katalyst Toolbox**, click the **Action** button. The **Action** options page appears.
6. From the **Action** options, drag the desired action from the **Ignite Katalyst Toolbox** to the **Button Module** button to be assigned/edited ([Figure 229](#)).

Figure 229. Ignite Katalyst Toolbox – Action Button




874x-sc69c-10

7. On the profile dialog box, **Files** menu, click either:
 - **Save Configuration** – to save the changes to the existing profile.
 - **Save Configuration As** – to name and save the changes as a new profile.
8. Close the profile.
9. Close the **Ignite Katalyst Button Toolbox**.

Assign a Button a TME Action


1. On the taskbar, click the Start button, and then point to All Programs. Point to Ignite Katalyst and then click Katalyst Profiles. The **Ignite Katalyst Profiles (Design Time)** dialog box (Figure 230) appears.

Figure 230. Ignite Katalyst Profiles (Design Time Dialog Box) Example



2. Click the **Size** arrow at the left of the Profile to be changed. The **Profile Editor** expands below the profile name and the **Size** arrow points downward (Figure 231).

Figure 231. Profile Editor



3. From the **Profile Editor**, click **E** to the right of the Button Module to be changed. The selected **Button Module** appears.
4. From the TME folder, drag the desired TME to the button to be assigned/edited.

Note To re-assign a button bitmap to a text button, refer to [Assign/Edit/Re-assign Button Style on page 203](#).

5. On the **BUTTON MODULE** dialog box, from the **Files** menu, click either:
 - **Save Configuration** – to save the changes to the existing profile.
 - **Save Configuration As** – to name and save the changes as a new profile.
6. Close the **BUTTON MODULE**.
7. Close the **Ignite Katalyst Button Toolbox**.


Assign/Edit a Button Bitmap

Note Customer generated/provided bitmaps can also be used instead of those available from the **Ignite Katalyst Toolbox**. Refer to either [Katalyst Toolbox Bitmaps on page 213](#) or [User Provided Bitmaps on page 215](#).

Katalyst Toolbox Bitmaps


1. On the taskbar, click the Start button, and then point to All Programs. Point to Ignite Katalyst and then click Katalyst Profiles. The **Ignite Katalyst Profiles** (Design Time) dialog box ([Figure 232](#)) appears.

Figure 232. Ignite Katalyst Profiles (Design Time Dialog Box) Example



2. Click the **Size** arrow at the left of the Profile to be changed. The **Profile Editor** expands below the profile name and the **Size** arrow points downward ([Figure 233](#)).

Figure 233. Profile Editor



3. From the **Profile Editor**, click **E** to the right of the Button Module to be changed. The selected **Button Module** appears.


4. From the **Tools** menu, click **Open Button Toolbox**. The **Ignite Katalyst Button Toolbox** appears.

Note The Ignite Katalyst Button Toolbox initially opens to the Style page.

5. In the **Ignite Katalyst Toolbox**, click the **Bitmap** button. The **Bitmap** options page appears.

6. From the **Bitmap** options, drag the desired bitmap from the **Ignite Katalyst Toolbox** to the **Button Module** button to be assigned/edited (Figure 234).

Figure 234. Ignite Katalyst Toolbox – Bitmap Button




7. On the **BUTTON MODULE** dialog box, from the **Files** menu, click either:
 - **Save Configuration** – to save the changes to the existing profile.
 - **Save Configuration As** – to name and save the changes as a new profile.
8. Close the **BUTTON MODULE**.
9. Close the **Ignite Katalyst Button Toolbox**.

User Provided Bitmaps


1. On the taskbar, click the Start button, and then point to All Programs. Point to Ignite Katalyst and then click Katalyst Profiles. The **Ignite Katalyst Profiles (Design Time)** dialog box (Figure 235) appears.

Figure 235. Ignite Katalyst Profiles (Design Time Dialog Box) Example



2. Click the **Size** arrow at the left of the Profile to be changed. The **Profile Editor** expands below the profile name and the **Size** arrow points downward (Figure 236).

Figure 236. Profile Editor



3. From the **Profile Editor**, click **E** to the right of the Button Module to be changed. The selected **Button Module** appears.

Note Any/all user-supplied bitmaps must be exactly 64 x 64 pixels and 4-bit Mono-chrome bitmaps. The international prohibition symbol (⊘) appears when a non-conforming graphic is dragged across a destination drop button.

4. From a user-defined folder, drag the desired bitmap to the button to be assigned/edited.

Note To re-assign text to a bit mapped button, refer to [Assign/Edit/Re-assign Button Style on page 203](#).


5. On the **BUTTON MODULE** dialog box, from the **Files** menu, click either:
 - **Save Configuration** – to save the changes to the existing profile.
 - **Save Configuration As** – to name and save the changes as a new profile.
6. Close the **BUTTON MODULE**.
7. Close the **Ignite Katalyst Button Toolbox**.

Configure a Panel Profile

Add a Profile

1. On the taskbar, click the Start button, and then point to All Programs. Point to Ignite Katalyst and then click Katalyst Profiles. The **Ignite Katalyst Profiles (Design Time)** dialog box ([Figure 237](#)) appears.

Figure 237. Ignite Katalyst Profiles (Design Time Dialog Box) Examples



2. From the **Tools** menu, click **New Profile** ([Figure 238](#)). A **New Profile** is added to the **Katalyst Profiles** dialog box and the **Profile Editor** expands below the new profile name ([Figure 239](#)).

Figure 238. Tools Menu – New Profile





Figure 239. New Profile and Profile Editor



3. From the **Profile Editor**, in the **Profile Name** box (Figure 239), type a name for the new profile.
4. Click the **Browse (...)** icon. The **Select a module configuration** dialog box (Figure 240) appears.

Figure 240. Select a module configuration Dialog Box Example




5. In the File Name box, type a name for the profile, and then click **Open**.
6. From the File menu, click **Save Configuration**.

Delete a Profile

1. On the taskbar, click the Start button, and then point to All Programs. Point to Ignite Katalyst and then click Katalyst Profiles. The **Ignite Katalyst Profiles (Design Time)** dialog box (Figure 241) appears.

Figure 241. Ignite Katalyst Profiles (Design Time Dialog Box) Examples




2. From the **Ignite Katalyst Profiles** dialog box, click the red **X** icon to the right of the profile name.
3. Click **Save**.

Edit a Profile

1. On the taskbar, click the Start button, and then point to All Programs. Point to Ignite Katalyst and then click Katalyst Profiles. The **Ignite Katalyst Profiles** (Design Time) dialog box ([Figure 242](#)) appears.

Figure 242. Ignite Katalyst Profiles (Design Time Dialog Box) Examples




2. From the **Ignite Katalyst Profiles** dialog box, click the **Size** arrow at the left of the Profile Name. The **Profile Editor** expands below the profile name and the **Size** arrow points downward ([Figure 243](#)).

Figure 243. New Profile and Profile Editor



3. Click the **Browse (...)** icon. The **Select a module configuration** dialog box ([Figure 244](#)) appears.

Figure 244. Select a module configuration Dialog Box Example



4. From the list, select the module for this configuration, and then click **Open**.
5. From the **Profile Editor**, click **P** (Panel). The available panels list appears (Figure 245) appears.

Figure 245. Enter the Katalyst Panel Name Text Box



6. Click the desired panel.
7. From the File menu, click **Save Configuration**.

8. Click the **Size** arrow next to the Profile Name. The **Profile Editor** collapses and the **Size** arrow points to the profile name.

Identify/Change a Module IP Address

- Note** Defaults:
- IP Address – 10.11.1.41
 - Mask – 255.255.255.0
 - Gateway – 10.11.1.1

Identify a Hardware Panel IP Address

To begin the identification routine

- Press and hold down any two Ignite Katalyst buttons for 3 seconds. All LEDs and buttons flash for a predefined time and the panel displays its IP configuration.

To stop the identification routine


- Note** During the Identify Routine, pressing any Ignite Katalyst button stops the routine but does not initiate the typical button action.
- Press any Ignite Katalyst button.

Change a Module IP Address

A module IP Address is changed using the Grass Valley NetConfig program. Refer to the latest version of the *NetConfig NETWORKING CONFIGURATION APPLICATION Instruction Manual* available on the Grass Valley web site.

QUICbox Panel

Figure 246. QUICbox Control Panel



Overview

Note In an Ignite/Ignite Konnect No-Audio configuration, the audio user interface area is blank and a QUICbox Panel is not supported; therefore, this QUICbox Panel information would not apply.

The QUICbox™ panel (Figure 246) works dynamically with Ignite/Ignite Konnect software to provide programmable buttons and audio controls that meet the workflow requirements of both individual stations and individual operators. Programming includes the ability to store and recall both simple or complex functions such as:

- Manual Video Switching & Audio Mixing
- Event Timeline Next Event Command
- Manual CG & Keyer Controls
- GPI Triggers
- ShowBuilder Key Insert & Take Commands
- Audio Talk-Back, Cue, Hold, & Group Commands

Note The QUICbox panel is not required for Ignite/Ignite Konnect Live Production Control system operation but rather provides an alternate, manual event-triggering capability

Configurable button programming is accomplished using the QUICbox Configuration Interface.

Programmable Buttons

Physically, there are 24 programmable buttons, 4 rows with 6 buttons in each row (Figure 247). The button rows are labeled from the top (row **A**) to the bottom (row **D**). The buttons are numbered from the top left (number 1) to the bottom right (number 24):

- Row **A** comprises buttons **1-6**
- Row **B** comprises buttons **7-12**
- Row **C** comprises buttons **13-18**
- Row **D** comprises buttons **19-24**

Figure 247. Programmable Buttons



NOTE: The display and buttons above this line are for future enhancements and therefore non-functional at this time.

In addition, there is a row of 10 selectable **Bank** buttons (Figure 247), numbered from left (number **1**) to right (number **10**). These are the small white buttons located just above the larger programmable buttons. Each of the programmable buttons is configured in association with a **Bank** button. This combination provides a functional total of 240 programmable buttons. That is:

- When **Bank** button **1** is pressed, each of the 24 buttons is individually configured for **Bank 1**
- When **Bank** button **2** is pressed, each of the 24 buttons is individually configured for **Bank 2**
- When **Bank** button **3** is pressed, each of the 24 buttons is individually configured for **Bank 3**
- And so on for remaining **Bank** buttons **4** through **10**

Note The display and buttons above the 10 Bank selection buttons are for future enhancements and therefore non-functional at this time.

Each Bank/button configuration is programmed using the QUICbox Configuration Interface and each button is:

- A multi-colored 24 x 32 LCD that can display both text and graphics. This means that button programming includes color and label customization.
- Programmable for one-button control of some switcher and module functionality. This one-button operation simulates either a combination key press command, a combination keyboard and mouse command, or the consolidation of several individual events; e.g., taking video and audio to air instantaneously by inserting a specially built TME group onto an already moving Ignite/Ignite Konnect Event Timeline.

Typical programmable-button functionality includes:

Note Some of the functionality listed below is accomplished by building a TME to perform the desired action(s) and then assigning the TME to a QUICbox button.


- Bus switching – the ability to program a QUICbox button to manually change sources on PGM, PVW, AUX, or KEY buses.
- LBN insertion – the ability to insert LBN hotkeys on any given saved macro file on the timeline.
- Multiple task combination – the ability to program multiple tasks or keystrokes to accomplish a user defined event using a single button press. For example, to drop in an LBN key and then trigger the timeline to move forward.
- Switcher Events.
 - Set program (PP and any M/E) to black, matte, pattern, or any available video input.
 - Set preview (PP and any M/E) to black, matte, pattern, or any available video input.
 - Set Auxiliary Buses to black, matte, pattern, or any available video input.
 - Set Keyer buses to black, matte, pattern, or any available video input.
- GPO/GPI triggering – the ability to program a button to manually trigger any device that can accept a GPO/GPI.
- Timeline control – provides one-button control for functions such as:
 - Next Step (skips the Event Timeline cursor to the next GPI mark).
 - Previous Step (skips the Event Timeline cursor to previous GPI mark).
 - Next Group (skips the Event Timeline cursor to the left edge of next group).

- Previous Group (skips the Event Timeline cursor to left edge of previous group).
- Next Slug (skips the Event Timeline cursor to left edge of next slug/page).
- Previous Slug (skips the Event Timeline cursor to previous slug/page).
- Next Story (skips the Event Timeline cursor to left edge of next story).
- Previous Story (skips the Event Timeline cursor to previous story).
- Cue (ALT+Q) moves the Event Timeline cursor to the beginning of the timeline.
- Run (ALT+SPACEBAR) starts the Event Timeline cursor.
- Pause (ALT+P) stops the Event Timeline cursor.
- Go to Cursor (ALT+G) shifts timeline view to current cursor location.
- Update Rundown (imports rundown to the Event Timeline when changes are made to rundown – if rundown is monitored).
- CG list control (TME assigned to a button):
 - Load next CG in list (advance CG list).
 - Load previous CG in list (moves to previous CG in CG list).
- Downstream CG keying – the ability to program a button to manually insert lower third or other keys from a CG device. This eliminates the need for a third party downstream key box or having to use the mouse for CG insertion.

Audio Controls, Buttons, and Indicators

Each motorized fader ([Figure 248](#)) provides quick, tactile control of audio input. The 16 motorized audio faders and related buttons operate in unison with and mirror the respective Ignite/Ignite Konnect Audio Fader module controls, buttons, and button indications.

Figure 248. Audio Motorized Faders and Control Buttons



The lighted buttons across the top are user-configured to identify the fader type and source being controlled. Button label text is automatically assigned based on the selected or assigned audio source from the Ignite/ Ignite Konnect **Audio** GUI. The button color indicates the fader type as:

- Program - green
- Static Source - blue
- Unassigned/Default - black (unlit)


The three rows of fader-related buttons are:

- C** (Cue) monitors a channel pre-fader
- B** (Backup) switches to a backup
- H** (Hold) holds a source on or off air

Configuration Interface

The QUICbox control panel is user-programed using the **QUICbox Configuration** interface that is accessed in the **Event Timeline Setup** menu ([Figure 249](#)).


Figure 249. Event Timeline Setup Menu



The **QUICbox Configuration** interface (Figure 250) includes:

- A **Main** dialog box for individual button color, label, and command programming elements.
- Two **Audio** dialog boxes (**Module #1** and **Module #2**) for audio fader definition and layout programming elements. **Module #1** is for faders 1-8 and **Module #2** is for faders 9-16.

Figure 250. Button and Fader Configuration Dialog Boxes



Main

Module #1
(Faders 1-8)

Module #2
(Faders 9-16)

Configuration Interface Menu Bar

The **Configuration Interface** menu bar (Figure 251) has two menus:

- **File** menu
- **Switch GUI** menu

Figure 251. Configuration Interface Menu Bar



Note For all names, abbreviations, and colors, use established standards and consistent techniques and practices. Refer to [Standardization on page 673](#).

The **File** menu ([Figure 252](#)) commands are:

- **Load Layout** - to load a previously saved button layout

Note The default configuration layout file is: Save
C:\Program Files\GrassValley\Ignite\misc\QuicBox.xml.

- **Save Layout** - to save a new button layout for future use
- **Save Layout As** - to save a new button layout with a different file name
- **Test QUICbox** - to test the QUICbox hardware and software interface (fader movement, LED on/off, and LCD flashing are tested on the audio modules. Each bank of the main module is cycled and each button is tested for lighting, flashing, and color)
- **Exit** - to exit the **Configuration Interface**

Figure 252. Configuration Interface File Menu



The **Switch GUI** menu ([Figure 253](#)) commands are:

- **QUICbox Main** (for the 4 x 6 control buttons)
- **Audio Module #1** (for faders 1–8)
- **Audio Module #2** (for faders 9–16)


Figure 253. QUICbox Configuration Switch GUI Menu



Main Dialog Box (Button Layout)

The **Main** dialog box (Figure 254) provides the 4 x 6 button programming interface necessary to view properties and configure individual QUICbox buttons.

Figure 254. Main Dialog Box (Button Layout)



- Click a button to execute the action configured for that button.
- Right-click a button for access to the **Set up Button Status** dialog box.

Audio Modules #1 and #2 Configuration Dialog Boxes


There are two **Audio** dialog boxes (**Module #1** and **Module #2**) for audio fader definition and layout programming elements (Figure 255). **Module #1** is for faders 1-8 and **Module #2** is for faders 9-16. There are four types of programmable fader:

- Program - follows the Audio Module Program presentation

Note Program and Preview faders are assigned first-come first-served.

- Static Source - requires a specific source be statically assigned to the fader


Figure 255. Audio Module #1 and #2 Dialog Boxes



Configuration

1. On the **Setup** menu, click **QUICbox** (Figure 256).

Figure 256. Setup QUICbox Menu



2. Depending on last used, either the **QUICbox Configuration Main**, **Audio Module 1**, or **Audio Module 2** dialog box (Figure 250) appears.

Button Configuration

Note QUICbox button configuration is only possible via the **QUICbox Configuration Main** dialog box.

1. If the **Main** dialog box is not displayed, from the **QUICbox Configuration** menu (Figure 253), click **Switch GUI**, then click **QUICbox Main**.
2. Click the **Bank** button (1–10) for the bank and associated button(s) to configure. The selected **Bank** button highlights and the corresponding buttons for the selected bank are displayed.
3. Right-click a button to customize. The **button state select** menu (Figure 257) appears.


Figure 257. Button State Select Box



Default Appearance

1. Click **Default Settings** to set the button up/static condition.
2. The **Button Setup** dialog box (Figure 258) appears.

Figure 258. Button Setup Dialog Box



Note **Current TME**, **LBN Name**, and **Ignite Action** are shaded/unavailable when **Default Appearance** is selected.

3. Choose text or graphic display for the button static state by selecting the **Graphical Icon** or **Text** check box.

Note If the **Graphical Icon** check box is selected, the **Text** check box is shaded/unavailable. Conversely, if the **Text** check box is selected, the **Graphical Icon** check box is shaded/unavailable.

4. If the **Graphical Icon** check box is selected, click one of the 38 available icons from the list box.

Note The Ignite/Ignite Konnect QUICbox Main GUI button always displays a generic icon. Once saved, the QUICbox hardware button displays the selected icon.

Note For all names, abbreviations, colors, and file structures, use established standards and consistent techniques and practices. Refer to [Standardization on page 673](#).

5. If the **Text** check box is selected, select either **Text 2x7**, **Text 3x8**, or **Text 4x10**, and then type the desired text into the **Text** input box using the following parameters:
 - **Text 2x7** – 2 lines x 7 alphanumeric characters
 - **Text 3x8** – 3 lines x 8 alphanumeric characters
 - **Text 4x10** – 4 lines x 10 alphanumeric characters

Note To access lines 2 through 4, click in the desired text line area.

Note Once saved, the entered text will display on both the Ignite/Ignite Konnect QUICbox Main GUI button and the QUICbox hardware button.

6. Click a background color from the **Color Assignment** palette (there are 64 possible color combinations available).
7. Click either **Static** (solid background color) or **Flashing** (on and off background color) from the **LCD State** list box.

On Button Down

1. In the **Button State** list, click **On Button Down**.
2. Determine if the button will initiate a TME, LBN, or Ignite/Ignite Konnect action by selecting the **Current TME**, **LBN Name**, or **Ignite Action** check box.

Note Only one of the three button action types can be assigned to a single button. Selecting any one of the three clears the other two.

3. If the **Current TME** check box is selected, click the **Browse** button and then click the desired TME to populate the TME path/filename box, then do one of the following:

Note The selected show/user (macro) file starts the Event Timeline module with the presets/prebuilds specific to that show or user. Therefore, all changes/additions/deletions, customization, hotkeys, etc. are specific to that show/user interface.

- a. To insert the TME into the timeline so that the timeline cursor steps into the TME normally, select the **Auto Execute** check box and ensure that the **Run Hidden** check box is cleared.
 - b. To insert the TME into the timeline one frame in front of the timeline cursor, ensure that the **Run Hidden** and **Auto Execute** check boxes are cleared.
 - c. To execute the TME immediately, without inserting it into the timeline, select the **Run Hidden** check box.
4. If the **LBN Name** check box is selected, type the name of the desired LBN into the **LBN Name** box, then do one of the following:
 - a. To insert the LBN into the timeline so that the timeline cursor steps into the TME normally, select the **Auto Execute** check box.
 - b. To insert the LBN into the timeline one frame in front of the timeline cursor, ensure that the **Auto Execute** check box is cleared.

5. If the **Ignite Action** check box is selected, click one of the desired actions from the **Ignite Action** list. Available actions are listed in [Table 6](#).

Table 6. Ignite Actions

Label	Keyboard Equivalent	Action
Next Step	N/A	Jumps the timeline cursor to the next GPI
Previous Step		Jumps the timeline cursor to the previous GPI
Next Group		Jumps the timeline cursor to the next Group level
Previous Group		Jumps the timeline cursor to the previous Group level
Next Slug		Jumps the timeline cursor to the next Slug level
Previous Slug		Jumps the timeline cursor to the previous Slug level
Next Story		Jumps the timeline cursor to the next Story level
Previous Story		Jumps the timeline cursor to the previous Story level
Cue	Alt-Q	Sends the timeline cursor and view to the beginning of the macro
Run	Alt-Space	Advances the timeline cursor
Pause	Alt-P	Pauses the timeline cursor
Go to Cursor	Alt-G	Scrolls the timeline view to where the timeline cursor is located
Update Rundown	N/A	Allows user to import changes when available on a monitored rundown

Accept, Cancel, or Restore Default Button Configuration

1. To accept the current button configuration, click **OK**.

The **Button Setup** dialog box closes and returns to the **Main** dialog box. The new button configuration is displayed and is functional (for testing purposes) on the **Main** dialog box, but it is not transferred to the QUICbox hardware until a **Save Layout** or **Save Layout As** is initiated from the **Configuration Interface**, **File** menu (see [Save Layout on page 237](#)).

2. To cancel changes to the current button configuration, click **Cancel**.

The **Button Setup** dialog box closes without accepting changes and returns to the **Main** dialog box.

3. To restore a button to its default configuration, click **Reset Default**.

The **Button Setup** dialog box settings are restored to original default configuration.


Audio Fader Configuration

Note QUICbox audio fader configuration is only possible via the **QUICbox Configuration Audio Module #1** (for faders 1–8) and **Audio Module #2** (for faders 9–16) dialog boxes.

1. From the **QUICbox Configuration** menu ([Figure 253](#)), click **Switch GUI**, then click **Audio Module #1** (for faders 1–8) or **Audio Module #2** (for faders 9–16).

2. Right-click a color button to customize. The **Setup/Reset Fader** menu (Figure 259) appears.

Figure 259. Setup/Reset Fader Select Box



3. To return the fader to its default/non-configured state, click **Reset Fader**.
4. To configure the fader, click **Setup Fader**. The **Setup Audio Fader** dialog box (Figure 260) appears.

Figure 260. Setup Audio Fader Dialog Box



Fader Type and Source

1. To configure the fader as a **Program** fader, click **Program** from the **Fader Type** select box.

The **Source** select box becomes shaded/unavailable because the fader source is automatically assigned on a first available basis from the Ignite **Audio GUI**, **On Air** sources. Once saved, the button color displays green for **Program** and the button label text mimics the source label displayed on the Ignite **Audio GUI**.

Note A **Program** configured fader will always maintain its button color, but the assigned audio source and associated button text will change (based on the first available automatic assignment rule) as sources are taken **On/Off Air** from the Ignite **Audio** GUI.

2. To configure the fader as a **Source** fader, click **Source** from the **Fader Type** select box, then from the **Source** select box, click one of the available source names.

Once saved, the button color displays dark blue for **Source** and the button label text mimics the selected source label displayed on the Ignite/Ignite Konnect **Audio** GUI.

Note A **Source** configured fader will maintain its appearance and assigned audio source even when it is assigned to the **On Air**, **Preview**, or **Select** areas of the Ignite/Ignite Konnect **Audio** GUI.

Accept or Cancel Fader Configuration

1. To accept the current fader configuration, click **OK**.

The **Setup Audio Fader** dialog box closes and returns to the **Audio Module** dialog box. The new button configuration is displayed and is functional (for testing purposes) on the **Audio Module** dialog box, but it is not transferred to the QUICbox hardware until a **Save Layout** or **Save Layout As** is initiated from the **Configuration Interface**, **File** menu (see [Save Layout on page 237](#)).

2. To cancel changes to the current button configuration, click **Cancel**.

The **Setup Audio Fader** dialog box closes without accepting changes and returns to the **Audio Module** dialog box.

Save Layout

Note The **Main** and **Audio Module** configurations are not transferred to the QUICbox hardware until **Save Layout** or **Save Layout As** are initiated from the **Configuration Interface**, **File** menu.


1. To save changes to the current layout, click **Save Layout** from the **QUICbox Configuration** interface **File** menu ([Figure 252](#)). The **Save succeeded** dialog box ([Figure 261](#)) appears.

Figure 261. Save Succeeded Dialog Box



2. Click **OK**. The **Save succeeded** dialog box closes and returns to the last selected **Main** or **Audio Module** dialog box.
3. To save current changes to a different layout filename, click **Save Layout As** from the **QUICbox Configuration** interface **File** menu (Figure 252). The **Save As** dialog box (Figure 262) appears.

Figure 262. Save As Dialog Box




4. Click a directory / folder from the **Save in** list box, enter a filename in the **Filename** list box, then click **Save**. The **Save As** dialog box closes and returns to the last selected **Main** or **Audio Module** dialog box.

Load Layout

1. To load a previously saved layout, click **Load Layout** from the **QUICbox Configuration** interface **File** menu (Figure 252). The **Open** dialog box (Figure 263) appears.

Figure 263. Open Dialog Box



- Click a directory/folder from the **Look in** list box, enter a filename in the **Filename** list box, then click **Open**. The **Open** dialog box closes and returns to the last selected **Main** or **Audio Module** dialog box with the selected layout loaded to both the GUI and the QUICbox hardware.


Functional Test

Note The QUICbox test is a functionality test of the hardware panel in which each fader, button, and LED is exercised automatically. The operator must determine the pass/fail status of the panel based on the visual cues observed during the test.

Note This QUICbox test is only available if the Ignite/Ignite Connect system is LIVE mode. If a user attempts the test in PREP mode, a message appears instructing them to switch to LIVE mode.

- To test the QUICbox hardware panel, click **Test QUICbox** from the **QUICbox Configuration** interface **File** menu (Figure 252). The **Test QUICbox** dialog box (Figure 264) appears.

Figure 264. Test QUICbox Dialog Box



- Click either the **Test once** or the **Timed test** check box.

Note **Test once** is a single iteration test of the QUICbox hardware panel. The **Timed test** is the same test repeated continuously for the duration of time (in minutes) entered into the **Number of minutes to execute test** entry field.

- Click **OK**. The **Cancel QUICbox** dialog box (Figure 265) appears and the lower third of the **Test QUICbox** dialog box (Figure 266) displays the test description and **Time Remaining** (if **Timed test** was selected).

Figure 265. Cancel QUICbox Dialog Box






Figure 266. Test QUICbox Dialog Box



4. Allow the selected test to run to completion, or click the **Cancel QUICbox Test** button to cancel the test immediately. Either way, the **Cancel QUICbox** dialog box closes and the **Test Complete** dialog box (Figure 267) appears.


Figure 267. Test Complete Dialog Box



Click **OK** to acknowledge test completion, close the **Test Complete** and **Test QUICbox** dialog boxes (Figure 266 and Figure 267), and return to the **Configuration Interface** (Figure 250)

Camera Preset Hotkey Module

Figure 268. Camera Preset Hotkeys Module



Overview

The **Camera Preset Hotkey** Module (Figure 268) provides quick recall for predetermined camera positions. There are 10 page select buttons (1–10) and each page has 24 preset buttons on which to store shots. These pre-established, stored shots are saved for each camera. The information that is stored includes: camera, framing, focus, iris, and gain. The **Camera Preset Hotkeys** recall either presets or macros from the camera systems because some camera systems store the presets in the head, while others store the presets in the controller.

Presets are stored based upon an individual camera, so several cameras could have the same preset number but the pre-established shot could be different. For example, Preset number 1 for Camera 1 might be set for Talent 1 Close-up and Preset number 1 for Camera 2 might be set for Talent 2 Left Side.

Note Camera preset hotkeys are global and load when the Ignite/Ignite Konnect application is started. The selected show/user (macro) file starts the Event Timeline module with the presets/prebuilds specific to that show or user; e.g., CG/SS Hotkeys, LBNs, and any TMEs that are on the timeline.

For ease of reference and use, the recommended procedure is to use blocks of presets for specific cameras. For example, Camera 1 presets are 10-19 and Camera 2 presets are 20-29. Additionally, for ease of reference one page is a

commonly used preset page while the other pages are designated to a specific camera.

Note For quick reference and use, be sure to keep a defined list /log of all camera shots and the appropriate preset numbers.




Establish a default preset that is set up by engineering. Use this preset as a starting point for setting all show presets. This ensures proper color matching and camera setup. If sets/lighting vary from show to show, it is also a good idea to create a default preset for each show.

After presets are originally set, if cameras are moved for any reason, check and adjust the shots before going to air. Check presets before each show in case talent isn't seated in the same position or cameras are not in the exact location.

Common Control Buttons

Table 7 lists the common control buttons.

Table 7. Common Clock Control Buttons

Button	Control Function
 864x 5657-r0	Setup
 864x 5639-r0	Dock
 864x 5640-r0	Undock

Operation

Note Remember, Camera 1 and Camera 2 can be different shots yet be saved under the same preset number. For ease of reference and use, the recommended procedure is to use blocks of preset numbers for each program when the pre-established camera shots are different. As shots are blocked, if the shots are different for each program, be sure to assign camera preset numbers for each program; e.g., save the morning show camera shots in presets 1–30 and the noon show camera shots in presets 31–60.

Create a Preset Hotkey – Grass Valley HDC and CameraMan Robotic Cameras

Note Camera presets should be stored using the SHOT Director robotics/camera controller before assigning preset buttons in the Ignite/Ignite Konnect system. Refer to the respective SHOT Director Instruction Manual for procedures.

1. On the **Camera Preset** module (on the left monitor), click the **Page** button (1–10) for the page on which to store the hotkey.
2. On the **Camera Preset Hotkeys** module, click the **Setup** button, the **Setup** button highlights (Figure 269).


Figure 269. Camera Preset Hotkeys Setup Button



Note In the following step, if the selected button already has a preset established, that existing preset is replaced.

3. Click either a blank hotkey or a currently used hotkey to replace. The **Setup** dialog box (Figure 270) appears.

Figure 270. Camera Hotkey Setup Dialog Box – Grass Valley HDC Cameras



4. In the **Select Device** box, click a camera in the drop-down list.

Note For all names, abbreviations, colors, and file structures, use established standards and consistent techniques and practices. Refer to [Standardization on page 577](#).

5. In the **Description** box, type a description or abbreviation for the preset using established standards and consistent techniques and practices. Refer to [Standardization on page 577](#).
6. Click **Button Color Press to Change**. The **Color Palette** dialog box ([Figure 271](#)) appears.

Figure 271. Camera Hotkey Color Palette Dialog Box



7. Click the designated color, and then click **OK**.
8. In the **Preset** box, click a preset number in the drop-down list.

Note Depending on camera type, additional options might be available. For example, for Grass Valley cameras proceed to [Save Presets In File on page 245](#) and [Load Presets From File on page 245](#) and then click **OK**.

9. Complete any remaining options, and then click **OK**.

Save Presets In File

Note Presets for Grass Valley HDC robotic cameras are created and physically stored in the SHOT Director robotics/camera controller. It is good practice periodically, and certainly as presets are modified, to save all presets (**Save Presets in File**) to a file within Ignite/Ignite Konnect (Program Files/Grass Valley/Ignite/misc/GV04CameraPresets.xml). In the unlikely event that the SHOT Director controller fails, simply download the saved presets (**Load Presets from File**) to the replacement SHOT Director controller.

1. In the **Camera Preset Hotkeys** GUI, click the **Setup** button, the **Setup** button highlights (Figure 272).

Figure 272. Camera Preset Hotkeys



2. Click any currently used hotkey assigned to a Grass Valley camera preset. The **Setup** dialog box (Figure 270) appears.

Note In the following steps, the Ignite/Ignite Konnect system must be **ON-AIR**.

3. To upload and save presets for all Grass Valley robotic cameras on the Ignite/Ignite Konnect network, click **Save Presets in File**. The **Save Presets** confirmation dialog appears.

CAUTION Uploading presets from a SHOT Director controller will overwrite any existing saved presets in the Ignite/Ignite Konnect GV04CameraPresets.xml file.

Note Depending on the potential number of Grass Valley robotic cameras (1-16) on the Ignite/Ignite Konnect network, and the number of presets (0-300) stored for each camera, it could take up to two minutes to save or load all presets.

4. Click **Yes** to confirm and close the dialog. The **Presets saved** confirmation dialog appears.
5. Click **OK** to acknowledge/close the dialog.

Load Presets From File

1. In the **Camera Preset Hotkeys** GUI (Figure 269), click the **Setup** button, the **Setup** button highlights.

2. Click any currently used hotkey assigned to an Grass Valley camera preset. The **Setup** dialog box (Figure 270) appears.

Note In the following steps, the Ignite/Ignite Konnect system must be **ON-AIR**.

3. Click **Load Presets from File**. The **Load Presets** confirmation dialog appears.

CAUTION Downloading presets from a file to a SHOT Director controller overwrites any existing presets in the SHOT Director controller.

Note Depending on the potential number of Grass Valley robotic cameras (1-16) on the Ignite/Ignite Konnect network, and the number of presets (0-300) stored for each camera, it could take up to two minutes to save or load all presets.

4. Click **Yes** to confirm and close the dialog. The Presets loaded confirmation dialog appears.
5. Click **OK** to acknowledge/close the dialog.

Create a Preset Hotkey – Vinten/Radamac Cameras

1. On the **Camera Preset** module on the left monitor, click the **Page** button (1–10) for the page on which to store the Hotkey.
2. On the **Camera Preset Hotkeys** module, click the **Setup** button, the **Setup** button highlights (Figure 273).

Figure 273. Camera Preset Hotkeys



Note In the following step, if the selected button already has a preset established, that existing preset is replaced.

3. Click either a blank hotkey or a currently used hotkey to replace. The **Setup** dialog box (Figure 274) appears.

Figure 274. Camera Hotkey Setup Dialog Box – Vinten Cameras

4. In the **Select Device** box, click a camera in the drop-down list.

Note For all names, abbreviations, colors, and file structures, use established standards and consistent techniques and practices. Refer to *Standardization on page 577*.

5. In the **Description** box, type a description or abbreviation for the preset using established standards and consistent techniques and practices. Refer to *Standardization on page 577*.
6. In the **Show** box, click a show in the drop-down list.
7. In the **Devices** box, click a device in the drop-down list.

Note This refers to the actual camera.

8. In the **Presets** box, click a camera preset in the drop-down list.
9. Click either **Jump** or **Move** (to the position). In the **Duration** box, enter the desired time, in seconds, to reach the position.

Note Duration is only selectable if the preset is a Move.

10. Click **Button Color Press to Change**. The **Color Palette** dialog box (Figure 275) appears.

Figure 275. Camera Hotkey Color Palette Dialog Box



11. Click **OK** , and then click **OK**

Create a Preset Hotkey—Telemetry Cameras

1. In the **Camera Preset** module on the left monitor, click the **Page** button (1–10) for the page on which to store the Hotkey.
2. On the **Camera Preset Hotkeys** module, click the **Setup** button, the **Setup** button highlights ([Figure 276](#)).


Figure 276. Camera Preset Hotkeys



Note In the following step, if the selected button already has a preset established, that existing preset is replaced.

- Click either a blank hotkey or a currently used hotkey to replace. The **Setup** dialog box (Figure 277) appears.

Figure 277. Camera Hotkey Setup Dialog Box – Telemetry Cameras



- In the **Select Device** box, click a Telemetry device in the drop-down list.

Note For all names, abbreviations, colors, and file structures, use established standards and consistent techniques and practices. Refer to *Standardization on page 577*.

- In the **Description** box, type a description or abbreviation for the preset using established standards and consistent techniques and practices. Refer to *Standardization on page 577*.
- In the **Camera** box, click a camera in the drop-down list.
- In the **Presets** box, click a camera preset in the drop-down list.
- Click **Button Color Press to change color**. The **Color Palette** dialog box (Figure 278) appears.

Figure 278. Camera Hotkey Color Palette Dialog Box



9. Click **OK** , and then click **OK**

Create a Preset Hotkey—Cambotics

1. In the **Camera Preset** module on the left monitor, click the **Page** button (1–10) for the page on which to store the Hotkey.
2. On the **Camera Preset Hotkeys** module, click the **Setup** button, the **Setup** button highlights ([Figure 276](#)).


Figure 279. Camera Preset Hotkeys



Note In the following step, if the selected button already has a preset established, that existing preset is replaced.

3. Click either a blank hotkey or a currently used hotkey to replace. The **Setup** dialog box (Figure 277) appears.

Figure 280. Camera Hotkey Setup Dialog Box – Cambotics



4. In the **Select Device** box, click a Cambotics device in the drop-down list.

Note For all names, abbreviations, colors, and file structures, use established standards and consistent techniques and practices. Refer to *Standardization on page 577*.

5. In the **Description** box, type a description or abbreviation for the preset using established standards and consistent techniques and practices. Refer to *Standardization on page 577*.
6. In the **Presets** box, click a camera preset in the drop-down list.
7. Click **Button Color Press to change color**. The **Color Palette** dialog box (Figure 281) appears.


Figure 281. Camera Hotkey Color Palette Dialog Box



8. Click **OK** , and then click **OK**

CG List Module

Figure 282. CG List Module



Overview

The **CG List** Module ([Figure 282](#)) is located in the lower left corner of the center monitor, below the Event Timeline module. It enables the user to keep track of scripts/stories and their corresponding CGs within a show rundown. Dynamic script synchronization keeps scripts synced to Timeline changes.

The CG List has several user-selectable display options. Display options and settings are accessed by clicking the **Setup** icon.

- **Narrow** mode – recommended view when also using the ScriptViewer Module. Refer to [Figure 283](#) for:
 - Single line display
 - Multiple line display


- **Wide mode** – recommended when the ScriptViewer Module is not used. Wide mode also displays columns for **Machine Name**, **Field Data**, and **Template**. Refer to Figure 284 for:
 - Single line display
 - Word wrap display

Note When the CG list is docked, Wide Mode extends the CG List view over top of the area reserved for the ScriptViewer module.

Figure 283. Narrow Mode – Single Line and Multiple Line Examples









Figure 284. Wide Mode – Single Line and Word Wrap Examples



Note When using MOS templates with Chyron, the Template field displays the page number created in Camio, not the template name.

Common Control Buttons and Indicators

The common control buttons and functions are:

Button	Control Function	Button	Control Function
 864x 525/7-10	Next	 864x 525/7-10	Setup
 864x 525/9-10	Previous	 864x 525/10-10	Undock
 864x 525/1-10	Take – brings the CG to the Program channel	 864x 525/10-10	Dock


The common indicators ([Figure 285](#)) are:

Note These indicators (and related features) are only available with Chyron HyperX with Lyric version 6.5 and above.

- **Error** icon – indicates an error with the CG. This could be that either the page or the template doesn't exist or that there is a problem with the data.
- **PGM** icon – indicates a **Take** command was issued to this device for this CG page.
- **PVW** icon – indicates a **Load** command was issued to this device for this CG page.
- **Blue Outline** – indicates the current story and story CG in the list.

Note Using the **CG Settings** dialog box **Display Settings** tab, the background colors for Error, PGM, and PVW indications are also selectable.

Figure 285. CG List Common Indicators



CG List Setup

CG List settings are configured via the **CG List Setup** dialog box, which is accessed by clicking the **Setup** icon. The dialog box comprises three tabs and three common-command buttons that function regardless of the selected tab:


- [General Tab on page 257](#) – general operation and display settings
- [Display Settings Tab on page 258](#) – configures the CG List display
- [Template Table Tab on page 261](#) – provides a Template Name to Template ID reference list
- **OK** – saves the settings and closes the dialog box
- **Cancel** – ignores all changes and closes the dialog box
- **Apply** – saves the settings but does not close the dialog box

General Tab

The **General** tab (Figure 286) provides general operation and display settings including:

- **Default Machine Name** - Defines the default CG Machine Name used if a CG machine name is not provided, is not specified for CG items that are manually entered into the rundown. (Non-MOS CGs only)
- **NRCS Updates** - Selects one of the following options:
 - **Show NRCS updates immediately** - When selected, updates of an imported rundown from the NRCS will be displayed in the CG List immediately without any user intervention.
 - **Show NRCS updates when a rundown update is triggered** - When selected, updates of the rundown will be displayed in the CG List when the user chooses to update the rundown to the Ignite/Ignite Konnect timeline.
- **Restrict the Next/Previous CG operations to the same story:**
 - When selected, the next CG and previous CG operations are restricted to the current story.
 - When not selected, the Next CG and Previous CG operation transcend the current story.
- **Inhibit Non-MOS CG Creation** – When selected, the non-MOS CG items from the NRCS are not created on the CG device, are not displayed on the CG List, and do not populate CG List timeline icons. Also, non-MOS CGs cannot be created from the Ignite/Ignite Konnect CG List or the the Ignite/Ignite Konnect timeline.
- **Enable Preview/Program mode** – When selected, enables Program/Preview for the CG List.

Figure 286. CG List Settings Dialog Box – General Tab




Display Settings Tab

Note Some Display Settings depend on the view selected: narrow or wide mode.

Common to both **Narrow** and **Wide** modes is the **Colors** area near the bottom of the **Display Settings** tab (Figure 287) where the:

- **Colors** list - displays and enables user-defined color assignments for the selected CG List item.
- **Color selection list** – provides both a default color palette and an optional custom color dialog box for assigning item colors. This list is only available when an item is selected in the **Colors** list.
- **Use defaults** button - resets all colors to the default values assigned when the Ignite/Ignite Konnect system was first installed

Figure 287. Display Settings Tab – Colors




Narrow Mode

The **Display Settings** tab **Narrow** mode (Figure 288) provides CG List display configuration including:

- **View Mode** - sets either **Narrow** or **Wide** mode
- **CG Display Pattern** - displays the pattern and order that CG data will be displayed when in Narrow Mode

Note List contents shown in the example below are for illustration only and might differ slightly.

Figure 288. CG List Dialog Box – Display Settings Tab (Narrow Mode) Example



Wide Mode


The **Display Settings** tab **Wide** mode (Figure 289) provides CG List display configuration including:

- **View Mode** – sets either **Narrow** or **Wide** mode
- **CG Column Order** – user-defined order for column appearances.

Note The top list position corresponds to the left-most (1st) column and the bottom list position corresponds to the right-most (last) column of the CG list module.

- **Word Wrap CG Items:**
 - When selected, word-wraps CG item text that does not fit on one line in the column.
 - When not selected, CG text that does not fit on one line in the column is truncated and restricted to one line.

Figure 289. CG List Dialog Box – Display Settings Tab (Wide Mode)



Template Table Tab


Note The Template Table tab is for non-MOS CGs only.

The **Template Table** tab (Figure 290) provides a Template Name to Template ID reference list. It also has two available command buttons:

Add – Appends a new entry to the template table.

Remove – Removes the selected entry from the template table.

Figure 290. CG List Dialog Box – Template Table Tab



Operation


Note The CG List Preview features are only available with Chyron HyperX with Lyric version 6.5 and above.

Use the **Next** and **Previous** buttons as necessary.

Populate CG List

- On the **Event Timeline Tools** menu, click **Import Rundown**. The rundown appears to the left of the **Event Timeline** and in the **CG List** module (Figure 291).

Figure 291. CG List Rundown




Set Display Mode

Narrow or Wide Mode

1. Click the **Setup** icon. The **CG List Settings** dialog box appears (Figure 292).
2. Click the **Display Settings** tab (Figure 292).

Figure 292. CGList Dialog Box – Display Settings Tab



3. In the View Mode listbox, click either:

- **Narrow**
- **Wide**


4. Click either:

- **OK** – to save the settings and close the dialog box
- **Cancel** – to ignore all changes and close the dialog box
- **Apply** – to save the settings but not close the dialog box

CG Column Order (Wide Mode Only)

1. Click the **Setup** icon. The **CG List Settings** dialog box appears (Figure 293).
2. Click the **Display Settings** tab.
3. In the **View Mode** list, click **Wide** and then click **Apply**.

Figure 293. CGList Dialog Box – Display Settings Tab




Note The **CG List** module column displays (left to right) are represented in the **CG Column Order** (top to bottom) where the top column name is viewed as the left most column in the CG List module, the second down is the next column to the right, etc.

4. In the **CG Column Order** list, click a column to move, and then click either Move Up or Move Down as necessary to reposition that column.
5. Repeat [Step 4](#) as necessary until all columns are positioned as desired.
6. Click either:
 - **OK** – to save the settings and close the dialog box
 - **Cancel** – to ignore all changes and close the dialog box
 - **Apply** – to save the settings but not close the dialog box

CG Display Pattern (Narrow Mode Only)

1. Click the **Setup** icon. The **CG List Settings** dialog box appears ([Figure 294](#)).
2. Click the **Display Settings** tab.
3. In the **View Mode** list, click **Narrow** and then click **Apply**.

Figure 294. CGList Dialog Box – Display Settings Tab



4. Double-click a blank area (or at the end of the current list) within the **CG Display Pattern** list. A new Display Pattern entry field highlights.
5. Type the preferred display pattern variable(s); e.g., [MachineName], [Template], [FieldData].


Note Each variable or a combination of variables can be entered on an individual row in the Display Pattern Field. To add another row in the Display Pattern Field, type **SHIFT+ENTER**.

6. Press **Enter** and then click either:
 - **OK** – to save the settings and close the dialog box
 - **Cancel** – to ignore all changes and close the dialog box
 - **Apply** – to save the settings but not close the dialog box

CG Column Word Wrap (Wide Mode Only)

1. Click the **Setup** icon. The **CG List Settings** dialog box appears (Figure 295).
2. Click the **Display Settings** tab.
3. In the **View Mode** list, click **Wide** and then click **Apply**.

Figure 295. CGList Dialog Box – Display Settings Tab



4. Either:
 - Select the **Word Wrap CG Items** check box to use column word wrap and display on multiple lines as necessary.
 - Clear the **Word Wrap CG Items** check box to remove column word wrap and display on a single line.
5. Click either:
 - **OK** – to save the settings and close the dialog box
 - **Cancel** – to ignore all changes and close the dialog box
 - **Apply** – to save the settings but not close the dialog box

Edit a CG Display Pattern

Note Editing the default Display Patterns is not recommended. Instead, edit or create custom Display Patterns that provide the preferred CG List display.


1. Double-click the **Display Pattern** field and edit as necessary.
2. Click either:
 - **OK** – to save the settings and close the dialog box
 - **Cancel** – to ignore all changes and close the dialog box
 - **Apply** – to save the settings but not close the dialog box

Set Display Colors

Note To return colors to the default color, click **Use Defaults**.


1. Click the **Setup** icon.
The **CG List Settings** dialog box appears (Figure 296).
2. Click the **Display Settings** tab.

Figure 296. CGList Dialog Box – Display Settings Tab




3. In the **Colors** list, click the display item to be colored.
The currently assigned color appears in a list box to the right above the **Use Defaults** button (Figure 297).

Figure 297. CG Display Settings Color Example



4. Click the Color arrow to view more color options.
The Default Colors list appears (Figure 298).


Figure 298. CG Display Settings Default Colors List



5. In the Colors List, either:
 - Select a default color and then click either:
 - **OK** – to save the settings and close the dialog box
 - **Cancel** – to ignore all changes and close the dialog box
 - **Apply** – to save the settings but not close the dialog box
 - Click **Custom** to select a custom color.
The **Color** dialog box appears (Figure 299).

Note Click **Define Custom Colors** to customize/create a specific color.

Figure 299. CG Display Settings Custom Colors Dialog Box



6. Either:

- In the **Basic colors** or **Custom colors**, click the desired color
- Type in the **R**, **G**, and **B** color coordinates
- Point and click the desired color in the color palette

Note To add the color as a palette **Custom color**, click **Add to Custom Colors**

7. Click either:

- **OK** – to save the settings and close the dialog box
- **Cancel** – to ignore all changes and close the dialog box
- **Apply** – to save the settings but not close the dialog box


CG Template Table

Note The Template Table tab is for non-MOS CGs only.

Add a Template

1. Click the **Setup** icon. The **CG List Settings** dialog box appears (Figure 300).
2. Click the **Template Table** tab.


Figure 300. CG List Dialog Box – Template Table Tab



3. Click **Add**. A new default CG template is added to the list (Figure 301).

Note Added templates have a default name and default ID until changed. The default name is TEMPLATEn where n is the next sequential number starting from 0. The default ID is the next sequential number starting from 0.

Figure 301. Add a Template - Example



Note In the following two steps, the template name is restricted to 64 characters and the template ID must be between 0 and 99999999. Template names cannot be duplicated. Template IDs can be duplicated if desired.

Note The Template Name and Template ID columns are resizable. They can also be sorted either alphabetically by template name or numerically by template ID.

4. Click the default template name and type a new Template Name. The Template Name corresponds to a bracket CG or Star CG template from the NRCS system. Click the default template ID and type a new template ID.


Note The Template ID must correspond with a template graphic page number on the CG device.

5. Click either:
 - **OK** – to save the settings and close the dialog box
 - **Cancel** – to ignore all changes and close the dialog box
 - **Apply** – to save the settings but not close the dialog box

Delete A Template


1. Click the **Setup** icon.
The **CG List Settings** dialog box appears ([Figure 302](#)).

Figure 302. CG List Dialog Box – Template Table Table



2. Click the **Template Table** tab, and then click the template to be removed.
3. Click **Remove** A warning message (Figure 303) appears to confirm deletion.

Figure 303. Delete A Template – Confirmation




4. Either:
 - Press **ENTER** to confirm and delete the template
 - Click **Yes** to confirm and delete the template
 - Click **No** to cancel and not delete the template.

Load a Script

Note ScriptViewer must be configured, connected, and monitoring the corresponding Ignite/Ignite Konnect rundown for Load Script to function properly. Miniview mode is optional.

1. On the **Event Timeline Tools** menu, click **Import Rundown**. The rundown appears to the left of the **Event Timeline** and in the **CG List** module (Figure 304).

Figure 304. CG List Rundown




- Double-click a story name in the CG List to select it.
The selected story bounding box pointer moves to the selected story.
The currently loaded script is cleared and the selected story script loads into the prompter.

Note If Miniviewer is enabled, the currently loaded script is also cleared and the selected story script loads into the Miniviewer.

CG/SS Module

Figure 305. CG/SS Hotkeys Module



Overview

The CG/SS Module (Figure 305) provides hotkey access to preset static or animated text and graphics (e.g., crawls, tickers) such as name captions, other word graphics, and simple symbols that can be added to a program. Each generated graphic is assigned a CG/SS identifier and saved as a preset hotkey on the CG/SS Module. Channels are selected via the drop-down list. A total of 18 preset hotkeys can be assigned to each channel of a device. Up to 9999 pages can be recalled from the TME timeline.






Each device channel has its own CG/SS hotkeys page. There are 18 configurable hotkeys for each device channel. To change device channels, in the drop-down list at the top of the module, click the device.

Note The forward arrow advances forward by one ID number and the back arrow moves backward by one ID number.

Common Control Buttons

Table 8 lists the common control buttons.

Table 8. Common CG/SS Control Buttons

Button	Control Function	Button	Control Function
 864x-sc56-r0	Next	 864x-sc57-r0	Setup
 864x-sc59-r0	Previous	 864x-sc60-r0	Undock
		 864x-sc63-r0	Dock

Operation

Create CG/SS Hotkeys

Note For all names, abbreviations, colors, and file structures, use established standards and consistent techniques and practices. Refer to *Standardization* on [page 577](#).

1. Click the **Setup** button, the **Setup** button ([Figure 306](#)) highlights.

Figure 306. Hotkey Setup Button



2. Click a hotkey (either a blank one or one currently in use that will be replaced). The **Setup** dialog box ([Figure 4](#)) appears.

Note The number of text boxes and options depend on the CG being set up.

Note In the following steps, not all CGs use IDs. Some require template & field information (e.g., DekoMOS) and others want full MOS data (e.g., Vertigo).

Figure 307. CG Setup Dialog Box Example



3. If an ID field is present, type the ID for the CG/SS and label it.
4. Type the page number in the **Page Number** text box.
Type the button label information in the **Button Label** text box.
5. To change the color, click **Press to change color** .
The Color Palette ([Figure 308](#)) appears.

Figure 308. Color Palette



6. Click the desired color
 - a. Either:
 - Click **OK** to save and close the color palette
 - Click **Cancel** to close the color palette without saving.
 7. Either:
 - a. Click **OK** to save and close the CG Setup dialog box.
 - b. Click **Cancel** to cancel the setup and close the CG dialog box without saving.
 8. When complete, click **OK**.
- Note** Remember that CG/SS hotkeys store with the current show/user macro.
9. On the Event Timeline module, click the **File** menu, and then click either **Save** or **Save As**.

Place a CG on the Event Timeline


- Right-click the desired Hotkey and then drag and drop the CG onto the Event Timeline.

Delete CG/SS Hotkeys

Once created, hotkeys can not be deleted. Instead, create a blank hot key to replace a hotkey instead of deleting a hotkey.

Clocks and Timers Module

Figure 309. Clocks & Timers Module



Overview

The **Clocks and Timers** Module ([Figure 309](#)) has several clocks and timers that function within the Ignite/Ignite Konnect application only. As a default, the clocks are grouped together near the center of the left monitor. Timers are typically associated to and located with a specific Ignite/Ignite Konnect module function.

Without Timed Events active, these clocks work within the Ignite/Ignite Konnect system only and cannot be controlled by an outside device such as a switch or foot pedal, nor can time code nor house time be sent to them. The Event Clock and Manual Clock can be docked/undocked.





With Timed Events, these clocks work within the Ignite/Ignite Konnect system only and cannot be controlled by a switch, foot pedal, or house time. The difference with Timed Events is that the Show Clock can be set either manually to a set time or it can be set to use the system clock on the workstation where Ignite is installed. This enables setting Global commands

based on actual time instead of a predetermined show back-time. The Event Clock and Manual Clock can be docked/undocked.

Common Control Buttons

Table 9 lists the common control buttons for clocks and timers.

Table 9. Common Clock Control Buttons

Button	Control Function	Button	Control Function
	Start		Dock
	Stop		Undock

Clocks

Each clock has a different purpose within the Ignite/Ignite Konnect application. They cannot be controlled by an outside device such as a switch or foot pedal nor can time code or house time be sent to them.

Show Clock (Green)

The **Show Clock** (Figure 310) is a countdown clock that is triggered when a Time Line Timer Mark, with a time greater than zero assigned, is encountered on the Ignite/Ignite Konnect Event Timeline. When the assigned countdown duration is completed, the **Show Clock** display changes to red and the clock begins counting up from zero. The **Show Clock** can be stopped manually at any time.

Figure 310. Show Clock



Manual Clock (Blue)

The **Manual Clock** (Figure 311) is a count up clock with both a manual **Start** button and a manual **Stop** button. Subsequent clicks of the **Start** button reset and restart the **Manual Clock** from zero.

Figure 311. Manual Clock



Event Clock (Yellow)

The **Event Clock** (Figure 312) is a count up clock triggered when a Time Line Timer Mark, with zero time assigned, is encountered on the Ignite/Ignite Konnect event timeline. When triggered, it begins counting up from zero. The **Event Clock** can be stopped manually at any time.

Figure 312. Event Clock



Timers

Server Countdown Timer

Display


The **Server Countdown Timer** (Figure 313), when configured, initially appears on the center monitor, at the top-right of the Event Timeline Module. The timer can be repositioned to any of the Ignite/Ignite Konnect monitors using the Dock/Undock control function.

The **Server Countdown Timer** displays video clip duration, which is obtained from the server, in either:

- Countdown mode - displays time remaining.
- Count up mode - displays elapsed time.

Note Typically the Server Countdown Timer docks on the Event Timeline module but it can be undocked and/or pinned in another location—anywhere on the tri-monitor display.

Figure 313. Server Countdown Timer



Clip duration can be either the clip length (the physical length of the clip) or a segment of the clip as specified in the NRCS by the user. If the duration is not specified, the total clip length is assumed.

Also, four specific, user-defined timepoints can be set for assigned timer actions. Timepoints are formatted as time codes and display hours, minutes, and seconds as Hours:Minutes:Seconds. Each timepoint can be assigned one or both of the following actions.

- Change color to red, green, or amber.
- Trigger a user selectable GPI output

These timepoints are configured using either the beginning or the end of the clip as the reference point. timepoints and actions are globally assigned and are shared among all server devices.

To include a standard pad time at the end of a VO or SOT, the Server Countdown Timer is configured for a standard pad time in order to automatically calculate duration. The pad time amount is globally assigned and shared among all server devices. The allowed range of pad time is 0 to 90.

- Calculated duration = Clip length - Pad.
- NRCS duration < Calculated duration, where Calculated duration = NRCS duration.
- (NRCS duration > Calculated duration) and (NRCS duration <= Clip length), where Calculated duration = NRCS duration.
- NRCS duration > Clip length, where Calculated duration = Clip length.
- Once calculated duration expires, the clock runs negative for the remaining clip length.

In addition, the Server Countdown Timer is used to configure the count mode for supported Grass Valley UMD (Under Monitor Display) devices. in either:

- Countdown mode – UMD displays time remaining
- Count up mode – UMD displays elapsed time


The UMD driver supports serial communication and is responsible for transmitting time data to the UMD device. The supported Grass Valley UMD devices are:

- Grass Valley UMD-CTRL/16 (can be daisy chained with more controllers)
- Grass Valley UMD-TD/19 (16 per controller)

The **Server Countdown Timer Context Menu** (Figure 314) provides access to the **Open Configuration** and **Pin Clock** menu items. Right-click the **Server Countdown Timer** to display the context menu.

Note Typically the Server Countdown Timer docks on the Event Timeline module but it can be undocked and/or pinned in another location—anywhere on the tri-monitor display.

Figure 314. Server Countdown Timer Context Menu.



- **Open Configuration** – opens the timer configuration dialog box
- **Pin Clock** – docks and locks the timer at its current position. When pinned, the timer remains at that location, even if the Ignite/Ignite Konnect system is restarted. To move the timer it must be undocked first.

Configuration

Note Initially the **Server Countdown Timer** is pre-configured in the **Device Control** module, via the VDCP setup dialog box, during Ignite/Ignite Konnect installation.

The **Server Countdown Timer** is configured, via the **Context Menu**, by clicking the **Open Configuration** menu item. Configuration comprises:

- **Clip Settings**
 - **Count Mode** – sets the timer mode for either count up or count down.
 - **Pad time** – the amount of time, in seconds, included at the end of the clip. The default is zero and the allowed range is between 0 and 90.
 - **Negative Duration** – enables/disables ability to run negative for the remaining clip length after calculated duration expires.
- **Timepoint Configuration** – configures/enables user selected, color-coded (Red, green, or amber) timepoints. Up to four timepoints can be set for:
 - **TimePoint** –
 - **Reference point** – Clip Start or Clip End
 - **Color** – red, green, or amber
- **UMD Configuration** – lists all configured UMDs and the respective count mode.
- **OK** – saves the changes and closes the dialog box.
- **Cancel** – closes the dialog box without saving changes

Timed Events

Timed Events are pre-defined actions that occur at specific times. These Timed Events can be either:

- Global Timed Events – that follow the Show Clock (green clock).
- Production Timed Events – that follow the Event Clock (yellow clock).


These timed events are triggered via TME. When it's time to play an event, the TME contained within the event is executed.

Global Timed Events

Global Timed Events are TMEs that automatically run at a certain preset time on the Program Clock. These are usually set to trigger events that must happen at a fixed time in the program (e.g. rolling a closing server clip to time out a program).


The Global Clock is triggered when a green Global Timer Mark with its properties set to **Start Clock** is encountered in the timeline ([Figure 315](#)). The green Global Timer Mark is usually put in the first TME of a program timeline at the appropriate position to trigger at the start of the program.

Figure 315. Green Global Timer Mark



A Global Timed Event is set up by adding it directly to either the **Global Production List** or the **Timer Mark Property** dialog box.

Figure 316. Global Production List and Timer Mark Property Dialog Box Examples



If there are Global Events in an NCS rundown, the **Global Event List** is loaded when a rundown is imported and is displayed in the top-right of the left screen (over the top of the **CG Hot Keys** module). The **Global Production List** can be hidden and redisplayed by clicking the toggle icon on the **Green Clock** display (Figure 317).


Note The Global Production List can be set up to auto-toggle, so that it does not impede access to the CG Hot Keys. Refer to [Auto-toggle Production List on page 302](#)

Figure 317. Show Clock



Once the Global Clock (Green) is set running the TMEs in the Global Production List will execute at the set time. The clock is usually triggered from a green timer mark at the beginning of the program (Figure 318)


Figure 318. Green Global Timer Mark



Production Timed Events

Production Events are tied to a specific item in a rundown. Production events are triggered by the yellow Event Clock that is reset at the beginning of each TME requiring timed events. A TME that requires timed events must contain two yellow timer marks. The first mark re-sets and triggers the Event Clock and the second mark opens the Production Event window.

Figure 319. TME With Yellow Timer Marks



When the TME executes, the cursor crosses the first yellow mark to reset and trigger the yellow **Event Clock**. The cursor continues executing all icons until it reaches the second yellow mark where it stops and opens the **Event List** for the item in question. After all the events in the **Event List** have executed, the cursor continues and bus preps the next TME.

To keep the TME principle of only one operation per frame on the timeline, the first yellow mark (to trigger the clock) is placed 2 frames after the blue stop mark, as shown in [Table 10](#).

Table 10. Production Timed Events – TME Structure With Yellow Markers

Frame	Operation
0	Blue Stop Mark
1	Roll Server
2	First Yellow Mark
3	Audio
4	-


Table 10. Production Timed Events – TME Structure With Yellow Markers

Frame	Operation
5	Kayak
6	Second Yellow Mark

Where:


- The first yellow mark is set to trigger the **Event Clock**, by opening its properties window (right click mark and select properties or double click yellow mark) and selecting **Start Event Clock**, and then clicking **OK** (Figure 320).

Figure 320. Timer Mark Property Dialog Box - Start Event Clock




- The second yellow mark is set to open the **Event List**, by opening its properties window (right-click the mark and select properties or double-click the yellow mark) and select **Production Event List** (Figure 321).

Figure 321. Timer Mark Property Dialog Box - Yellow Mark Production Event List



Although **Timed Events** can be added directly to the **Timed Event List** using the **Timer Mark Property** dialog box (Figure 321), **Timed Events** are usually added to the list by adding codes to the NCS Rundown. To enable importing timed events from the rundown, the **Rundown Convert** check box (Figure 322) must be selected.

Figure 322. Timer Mark Property Dialog Box - Rundown Convert Check Box




MOS Objects can also be used to populate Timed Events. Newsroom Computer Systems (NCS) that support MOS (Media Object Server) protocol when paired with character generators that also support the MOS protocol generate CGs automatically from the NRCS script. Ignite uses these same MOS objects to populate the CG List when **Rundown Convert** is selected in a TME yellow **Timer Mark Property** dialog box.

When using MOS Objects and Ignite Timed Events, the in and out time of the CG is entered in the slug field.

Note If in/out time is not entered the page is still created and entered into the CG List, but a timed event is not generated.

For example, The CG MOS Objects entered in [Figure 323](#) would create the **CG List** shown in [Figure 324](#) and the **Timed Events Production List** shown in [Figure 70](#).

Figure 323. CG MOS Objects in iNEWS Example



SYD		INDIAN P
SYD	TAKE VTR	
MEL	SUPERS:	
SYD	*cg1 [A] (0:02 - 0:06) N1.lyr # MUMBAI # #	
MEL	00012409	
MEL	*cg1 [A] (0:35 - 0:40) N2.lyr # Sally Sara #	
SYD	SOUTH ASIA CORRESPONDENT #	
SYD	00012410	
MEL	I USOTB 0:53	
SYD		
MEL	*cg1 [A] (0:56 - 1:07) N3.lyr # NEW DELHI #	
SYD	Condoleezza Rice # US SECRETARY OF	
SYD	STATE 00012412	
MEL	*cg1 [A] (1:18 - 1:25) N2.lyr # Asif Ali Zardari #	
SYD	PAKISTAN PRESIDENT # 00012411	
SYD		
SYD	RUNS 1:48	
SYD	ENDS: ... ABC NEWS NEW DELHI."	
SYD		

CGs entered through Luci Plug-in

874x-sc91-r0

Figure 324. CG List From NCS Example



Machine Name	Template	Field Data
0 - Opening Titles		
1 - Lead Story		
2 - Another Story		
Name\Of\Someone\Here		
3 - Delhi Story		
CG1	012409	MUMBAI
CG1	012410	Sally Sara / SOUTH ASIA CORRESPONDENT
CG1	012412	NEW DELHI / Condoleezza Rice / US SECRETARY OF STATE
CG1	012411	Asif Ali Zardari / PAKISTAN PRESIDENT

874x-sc92-r0

Figure 325. Generated Timed Event Production List Example



Operation

Clocks

Note Without Timed Events active, these clocks work within the Ignite/Ignite Konnect system only and cannot be controlled by an outside device such as a switch or foot pedal, nor can time code nor house time be sent to them.

With Timed Events active, these clocks work within the Ignite/Ignite Konnect system only and cannot be controlled by a switch, foot pedal, or house time. The difference with Timed Events is that the Show Clock can be set either manually to a set time or it can be set to use the system clock on the workstation where Ignite is installed. This enables setting Global commands based on actual time instead of a predetermined show back-time.

Show Clock (Green)

- The **Show Clock** (Figure 326) is triggered and begins counting down when an Event Timeline Timer Mark (with a time greater than zero assigned) is encountered on the Ignite/Ignite Konnect Event Timeline. When the assigned countdown duration is completed, the **Show Clock** display changes to red and the clock begins counting up from zero.
- To manually stop the clock at any time, click the **Stop** button in the lower left of the clock.

Figure 326. Show Clock



Manual Clock (Blue)

The Manual Clock (Figure 327) has a manual **Start** button and counts up.

- To start the clock, click the **Start** button.
- To reset and restart the clock at zero, click the **Start** button
- To stop the clock, click the **Stop** button.

Figure 327. Manual Clock



Event Clock (Yellow)

The event clock (Figure 328) is designed for any TME that is to automatically start a clock, such as a TME that rolls a tape.

- The Event Clock is triggered and begins counting up from zero when a Time Line Timer Mark with zero time assigned is encountered on the Ignite/Ignite Konnect Event Timeline.

Note The Event Clock restarts at zero every time a Time Line Timer Mark is encountered.

- To manually stop the clock at any time, click the **Stop** button in the lower left of the clock.

Figure 328. Event Clock



Timers

Server Countdown Timer Configuration


Operation of the Server Countdown timer is via the Event Timeline through TMEs. To be functional, the timer must be configured via the Device Control module using the VDCP and AMP setup dialog boxes.

Note Initially the **Server Countdown Timer** is pre-configured in the **Device Control** module, via the VDCP setup dialog box, during Ignite/Ignite Konnect installation.

1. Right-click the **Server Countdown Timer** to access the context menu (Figure 329).


Note Typically the Server Countdown Timer docks on the Event Timeline module but it can be undocked and/or pinned in another location—anywhere on the tri-monitor display.

Figure 329. Server Countdown Timer Context Menu



2. Click **Open Configuration**.
The **Clock Timer Configuration** dialog box appears (Figure 330).

Figure 330. Clock Timer Configuration Dialog Box



3. Configure the Clip Settings:

- a. In the **Count Mode** list, click the relevant count mode, either **Count up** or **Count down**.
- b. In the **Pad Time (secs)** box, type or select a pad time between 0 and 90 seconds.
- c. For duration, either:
 - Click the **Negative Count** check box for negative duration
 - Clear the **Negative Count** check box to remove negative duration

4. Setup Timepoint Configurations:

Note There are four timepoint rows. Each row represents a single timepoint.

- a. Click a timepoint check box to enable that timepoint.
- b. In the **TimePoint** list, type or select a timepoint.
- c. In the **Reference Point** list select either:
 - Clip Start
 - Clip End

- d. In the Color list select either:
 - **Red**
 - **Green**
 - **Amber**
5. Click either:
 - **OK** – to save the configuration and close the dialog box.
 - **Cancel** – to close the dialog box without saving changes.


Global Timed Events

Trigger Global (Program) Clock

Note The green Global Timer Mark is usually placed in the first TME of a program timeline at the appropriate position to trigger at the start of the program.

1. Drag a green timer mark onto the TME.
2. Double-click the green mark. The properties dialog box ([Figure 331](#)) appears.

Figure 331. Timer Mark Property Dialog Box - Start Event Clock



3. Click **Start Event Clock**.

4. Click **OK**.


Note Start Time refers to the position of the timer mark on the timeline not the clock start time.

Setup Global Timed Events – Direct Entry

Note Global timed events can be added directly either to the Global Production List or to the Timer Mark Property Dialog.

1. Access either the Global Production List or the Timer Mark Property List dialog box. Refer to [Figure 332](#).

Figure 332. Global Production List and Timer Mark Property Dialog Box Examples



2. Click **Add**. A **Production Event Property** dialog box ([Figure 333](#)) appears.

Figure 333. Production Event Property Dialog Box



3. Click ... (Browse), and then click the desired TME.

4. In the Time box, to set the desired Global Time either:
 - Click the respective blue down arrow and select a number from the drop-down list.
 - Right/Left click a digit to increment the numbers up/down.
5. Click **OK**.

Note Events entered directly into the **Global Production List** are removed if an NCS Rundown update is performed.

Insert Production Cues – Global Timed Events (NCS Rundown)

Note The @ (At) symbol is the default symbol for Global Timed Events. If @ is used for other purposes in the NCS, Ignite is reconfigurable to use a different symbol.

- Enter the Global timed event(s) into the NCS rundown using the @ (At) symbol to designate a global event. The format of the production cue is: **@ TME Time** (refer to [Figure 334](#)).

Note The position of a global event production cue in the NCS rundown is not important unless the TME refers to another MOS object (e.g. a Video Clip MOS Object). Then the cue and the object must obviously be in the same NCS item.

Figure 334. Production Cues for Global Timed Events in the iNEWS NCS

MEL	# # 00012397	SHE'S ARRIVED IN TS
MEL	plasma (Security talks)	THE DIPLOMACY CO
MEL		INDIAN PROTESTER:
SYD		*****
SYD		RUNS: 1.48
MEL	@ NROLLB 28:59	ENDS: ABC NEWS
SYD	*cg1 [A] immed N1.lyr # MUMBAI # #	
MEL	00012409	
MEL	*cg1 [A] (SOONEST) N2.lyr # Sally Sara #	
SYD	SOUTH ASIA CORRESPONDENT #	
SYD	00012410	
MEL	### NO SUPER VOX POP @ 0.19 ###	
SYD		
MEL	*cg1 [A] (0.56 - 1.07) N3.lyr # NEW DELHI #	
SYD	Condoleezza Rice # US SECRETARY OF	
SYD	STATE 00012412	
BRIS	*cg1 [A] (1.18 - 1.25) N2.lyr # Asif Ali Zardari #	

874x-sc86-r0


Insert Production Cues – Global Timed Events (ENPS Rundown)

Square Bracket Markup

1. Open Notepad or similar equivalent software.
2. Type the markup.

3. Copy and paste the Notepad markup into ENPS.

Figure 335. ENPS Square Bracket Markup Example




Curly Bracket Markup

Note The ENPS manual mentions that curly braces are used by Teleprompters and this could cause the teleprompter to misread.

- Type the markup directly in the story body.

Figure 336. ENPS Curly Bracket Markup Example



Insert Event

1. Either:
 - Right-click and select **Insert** (Figure 337).
 - Press **Ctrl-J**.

The **INSERT** dialog box (Figure 338) appears.

Figure 337. Insert Menu Selection




Figure 338. Insert Dialog Box

2. Select **Other**.
3. Enter the markup information; e.g., **Name**, **Number**, **Incue**, **Outcue**, **At**, and **To** information.
4. When complete, click **Insert**.

Note Once the markup is inserted, double-clicking it reopens the Insert dialog box.

Automation Macro

1. Create the desired automation macro as shown in the [Figure 339](#) example.

Figure 339. Create Automation Macro Example

LOCALTIMEEVENT	Local Timed Event	TME	Start Time
GLOBALTIMEEVENT	Global Timed Event	TME	Start Time

Find New Delete Print

2. Program the macro into ENPS (). The full macro string example is:
{ROVER:SCRIPT:ED_INSERTAUTO_MACRO}{WAIT}{WAIT}L

Figure 340. Program Macro Into ENPS Example

Macros		Settings	Forward Searches
Unshifted		Ctrl+	
	Description	Macro	
F2	LOCALTIMEEVENTS	{ROVER:SCRIPT:ED_INSERTAUTO_MACRO}{WAIT}{WAIT}	
F3			

3. Within a story body, press F2 . The MACRO dialog box (Figure 341) appears.

Figure 341. MACRO Dialob Box Example

MACRO

Local Timed Event

TME

Start Time

4. In the **MACRO** dialog box, enter the **TME** and **Start Time** information.
5. Click **Save**. The production cue is saved within the story body (Figure 342).

Figure 342. Production Cue Within Story Body Example

auto1 [Andrew Timed Events [06/16/2009 15:00]]


Rundown: Andrew Timed Events [06/16/2009 15:00] Modified

AUTOMATION:MACRO\LOCALTIMEEVENT\Local Timed Event\TT10]

Auto-toggle Production List

1. On the **Event Timeline Setup** menu, click **Timed Events Setup**. The **Timed Events Configuration** dialog box (Figure 343) appears.

Figure 343. Timed Events Configuration Dialog Box



2. Select the **Clocks** tab.
3. Set **Global List ReOpen Time** to the number of seconds that you want the Global Production Event window to appear before the next event.
4. Set **Global List Linger** to the number of seconds to linger before minimizing after an event.

Note To prevent inadvertently loss of program timing and all future scheduled Global Timed Events, it is recommended that the **Confirm Clock Stop** check box is selected.

5. When **Confirm Clock Stop** is selected, a confirmation appears when you click the **Global Clock stop** button.
6. Click **Apply**, and then click **OK**.

Production Timed Events (NCS Coding)

Insert Production Cues – Production Timed Events (NCS Rundown)

Note The ! (Exclamation point) character is the default character for Production Timed Events. If ! is used for other purposes in the NCS, Ignite is reconfigurable to use a different symbol.

- Enter the Production timed event(s) into the NCS rundown using the ! (Exclamation) character to designate a production timed event. The format of the production cue is:
! TME Time (refer to [Figure 344](#)).

Figure 344. Production Cues for Production Timed Events in the iNEWS NCS

SYD		INDIAN P
SYD	TAKE VTR	*****
MEL	SUPERS:	RUNS: 1.
SYD	*cg1 [A] (0:02 - 0:06) N1.lyr # MUMBAI # #	ENDS:...
MEL	00012409	
MEL	*cg1 [A] (0:35 - 0:40) N2.lyr # Sally Sara #	
SYD	SOUTH ASIA CORRESPONDENT #	
SYD	00012410	
MEL	! USOTB 0:53	
SYD		
	*cg1 [A] (0:56 - 1:07) N3.lyr # NEW DELHI #	
MEL	Condoleezza Rice # US SECRETARY OF	
SYD	STATE 00012412	
BRIS	*cg1 [A] (1:18 - 1:25) N2.lyr # Asif Ali Zardari #	
SYD	PAKISTAN PRESIDENT # 00012411	
SYD	RUNS 1:48	
SYD	ENDS: ... ABC NEWS NEW DELHI."	
SYD		

874x-sc90-r0

Use MOS Objects for Timed Events

Newsroom Computer Systems (NCS) that support MOS (Media Object Server) protocol when paired with character generators that also support the MOS protocol generate CGs automatically from the NRCS script. Ignite uses these same MOS objects to populate the CG List when **Rundown Convert** is selected in a TME yellow **Timer Mark Property** dialog box

Device Control Module

Figure 345. Device Control Module Examples (Video Server, VTR, Audio, RAM Recorder, ENCO)




Overview

The **Device Control** Module provides individual controls (Figure 345) for connected VTRs, video servers, audio servers, and RAM recorders. Video, VTR, RAM Recorder, and Audio device operation is basically the same. Each device control has a unique look and color relationship specific to that device. The color band at the bottom of each device control matches the highlight color on Device Select area (refer to Figure 345).

Device Color Indications

The Device Control bottom bar color depends on the device selected. That same color is also used as the background color in the **Device Select** area ([Figure 346 on page 308](#)).

Table 11. Device Color Relationships

				
DIGI (Digicart)	MDS (Minidisk)	RAM Recorder	VDCC/AMP	VTR

Device Controls

Though available device controls differ in function and operation, common control buttons are used regardless of device type. [Table 12](#) lists the common device control buttons and the controlled device relationship.

Table 12. Common Device Controls


	Control Function	Video Server (VDCC)	VTR	Audio Server	Mini-Disk	RAM Still	RAM Clip	ENCO Audio Server
 854x-sc319-r0	Active Area					✓	✓	
 854x-sc51-r0	Add	✓		✓	✓	✓	✓	✓
 854x-sc12-r0	Begin						✓	
 854x-sc348-r0	Cue Track							✓
 854x-sc45-r0	Delete Clip/Still					✓	✓	
 854x-sc33-r0	Dock	✓	✓	✓	✓	✓	✓	✓
 854x-sc41-r0	E/E					✓	✓	
 854x-sc35-r0	Eject		✓	✓	✓			
 854x-sc41-r0	End						✓	
 854x-sc47-r0	Fast Forward	✓	✓					

Table 12. Common Device Controls - (continued)











	Control Function	Video Server (VDCP)	VTR	Audio Server	Mini-Disk	RAM Still	RAM Clip	ENCO Audio Server
 854k-sc31-f0	Forward Jog	✓						
 854k-sc52-f0	Loop			✓				✓
 854k-sc53-f0	New	✓						
 854k-sc58-f0	Next	✓		✓	✓			✓
 854k-sc54-f0	Pause	✓	✓	✓	✓		✓	✓
 854k-sc51-f0	Play	✓	✓	✓	✓	✓	✓	✓
 854k-sc59-f0	Previous			✓	✓			✓
 854k-sc55a-f0	Record					✓	✓	
 854k-sc55c-f0	Record Edit						✓	
 854k-sc55b-f0	Record ID					✓	✓	
 854k-sc43-f0	Remove	✓		✓	✓			✓
 854k-sc56-f0	Reverse	✓				✓	✓	
 854k-sc58-f0	Reverse Jog	✓					✓	
 854k-sc48-f0	Rewind		✓					
 854k-sc57-f0	Setup		✓	✓		✓	✓	
 854k-sc50-f0	Start Time Code Search	✓	✓					
 854k-sc50-f0	Stop	✓	✓	✓	✓	✓		✓

Table 12. Common Device Controls - (continued)

	Control Function	Video Server (VDCP)	VTR	Audio Server	Mini-Disk	RAM Still	RAM Clip	ENCO Audio Server
	Time Code	✓	✓					
	Undock	✓	✓	✓	✓	✓	✓	✓

Individual devices are selected using the **Device Select** area ([Figure 346](#)). All device controls appear below the Device Select area and they are typically docked and layered on top of each other with only the selected device control visible. Available devices are displayed in 3 rows of 4 devices each. If there are more than 12 available devices, a scroll bar appears at the right of the displayed devices.

To view and use individual device controls simultaneously, each one can be undocked and moved to another location on any of the three monitors. If undocked, each device control can also be docked to the Device Control Module.

Figure 346. Device Select Area



For specific device control button availability and location, refer to:

- [Video Server Device Control on page 309](#)
- [VTR Device Control on page 310](#)
- [Audio Clip Device Control on page 311](#)
- [RAM Recorder Device Control on page 311](#)
- [ENCO Audio Server Device Control on page 315](#)

Video Server Device Control

Figure 347. Video Server Device Control Example



The **Video** server device control (Figure Note) provides the following device controls:


• Rewind	• Play	• Time Code	• Next
• Reverse Jog	• Forward Jog	• Start Time Code Search	• Remove
• Reverse	• Fast Forward	• New	• Dock/Undock
• Pause	• Stop	• Add	

Note Refer to [Table 12 on page 306](#) for device control buttons, respective functionality, and device relationship.

In addition, the Video server device control can provide an automatic backup/mirroring function that operates behind the scene to provide failover in the event of a primary video server malfunction. To implement backup/mirroring capabilities, all mirrored devices must be of the same type. That is, primary and backup video servers must be the same make and model or at least have the same timing parameters; e.g., Cue time and Preroll time. Device set up requires that each primary server be given a **Backup Name** ([Figure 348](#)).


Note Manually switching to a backup server can also be accomplished from either the switcher panel or the Ignite Katalyst panel if configured.

Figure 348. Device Setup Backup/Mirroring Example



VTR Device Control

Figure 349. VTR Device Control Example




The **VTR** device control (Figure 349) provides the following device controls:

• Eject	• Fast Forward	• Time Code
• Rewind	• Record	• Start Time Code Search
• Pause	• Stop	• Dock/Undock
• Play	• Setup	

Note Refer to Table 12 on page 306 for device control buttons, respective functionality, and device relationship.

Audio Clip Device Control

Figure 350. Audio Clip Device Control Examples




The **Audio Clip** device control (Figure 350) provides the following device controls:

• Eject	• Play	• Add
• Previous	• Next	• Remove
• Pause	• Stop	• Dock/Undock

Note Refer to [Table 12 on page 306](#) for device control buttons, respective functionality, and device relationship.

RAM Recorder Device Control

Figure 351. RAM Recorder Device Control Example



The **RAM Recorder** device control enables the user to record up to 30 seconds of still images, video clips, or both stills and clips. The RAM


Recorder displays up to four channels on a DD/SD switcher and up to six channels on an HD switcher.

The **RAM Recorder** device control interface has two views ([Figure](#)):

- **Stills** control
- **Clips** control

Stills Device Control

Figure 352. RAM Recorder Device Control – Stills Setup



The **Stills** view ([Figure 352](#)) enables the user to load or store stills using the delegated channels and provides the following device controls:

Note Refer to [Table 12 on page 306](#) for device control buttons, respective functionality, and device relationship.


The **Setup** button – toggles access to the following **Stills** setup parameters:

- **Readout Still** – sets readout options that include:
 - **Field ½** – this mode is useful when a still is made from a graphic source that has generated motion, which is not in the expected field dominance.
 - **Field 1** – only field 1 is played out that results in “film look”, 25/30 motion updates per second.
 - **Field 2** – only field 2 is played out that results in “film look”, 25/30 motion updates per second.

- **Frame** – standard playout mode that consists of two fields: field 1 and field 2, a top field and a bottom field.
- **Vid/Key Mode** – sets the video/key mode where:
 - **Video** – the video part of the still is loaded in the selected channel.
 - **Video+Key** – the RAM pairs work together as a video/key pair.
 - **Key** – Displays the Key signal only
- **Ram Space** – displays the remaining RAM Memory space, in hh:mm:ss:ff format, that is available to record stills or clips.
- **Delegation** – lists RAM Recorder channels to designate either a still or clip.
- **Stills List** – lists the available stills in the switcher. The currently loaded still highlights green.

Clips Device Control

Figure 353. RAM Recorder Device Control– Clips Setup



The **Clips** view (Figure 353) enables the user to load, store, or play clips using the delegated channels and provides the following device controls:

Note Refer to [Table 12 on page 306](#) for device control buttons, respective functionality, and device relationship.

The **Setup** button – toggles access to the following **Clips** setup parameters:

- **Mode** – sets the clip play mode:
 - **Normal** – standard mode.
 - **Clip** – the clip is always played from Mark In to Mark Out.

- **Simple Loop** – the clip starts at the current position, plays to Mark Out, and executes the total range from Mark In to Mark Out n times, where "n" is the number of loops (0 = forever).
- **Extended Loop** – play may start before Mark In and Offset determines the post Mark Out play duration.


Note Mark In and Mark Out limit the accessible timecode range for **Clip**, **Simple Loop**, and **Extended Loop** modes.

- **Loops** – sets the number of loops to play in Loop mode. Zero indicates an infinite loop.
- **Readout Play** – sets the clip readout options:
 - **Field ½** – this mode is useful when a still is made from a graphic source that has generated motion that is not in the expected field dominance.
 - **Field 1** – only field 1 is played out that results in “film look”, 25/30 motion updates per second.
 - **Field 2** – only field 2 is played out that results in “film look”, 25/30 motion updates per second.
 - **Frame** – standard playout mode that comprises two fields: field 1 and field 2, a top field and a bottom field.
- **Mark In** – sets the **Mark In** point where the clip begins to play.
- **Mark Out** – specifies the **Mark Out** point where the clips stops.
- **Trim** – shortens the clip based on the **Mark In** and **Mark Out** points.
- **Rec Length** – sets the delay length for the delay line.
- **Delay Line** – turns delay line mode on so a user can delay a routed source for a specific RAM Channel by the amount of time entered in the **Rec Length** field.
- **Variable** – sets a variable clip speed where:
 - **3** = Triple speed
 - **1** = Normal speed
 - **2** = Double speed
 - **0.5** = Half speed
 - **0.25** = Reverse ¼ speed
 - **0.5** = Reverse half speed
 - **1** = Reverse normal speed
- **Timecode** – in mm:ss:ff, the time that is used to identify video frames on a recorded format.

Note In the **Clips** tab, the **Record ID** playout control button only appears on a Kayak HD.

ENCO Audio Server Device Control

Figure 354. Enco Audio Server Device Control Examples



The **ENCO Audio Clip** device control (Figure 354) provides the following device controls:

• Previous	• Loop
• Pause	• Setup
• Play	• Add
• Next	• Remove
• Stop	• Dock/Undock

Note Refer to [Table 12 on page 306](#) for device control buttons, respective functionality, and device relationship.

Operation

Select A Device Control

The device controls are stacked upon each other with only the selected device control visible below the **Device Select** area (Figure 355).

- To select a device control, click the respective **Device Select** button.
- To simultaneously view and use all device controls, individually undock and move each device control to another location on any of the three monitors. Refer to *Dock/Undock Modules* on page 262.

Figure 355. Device Select Area Example



Add A Video Clip

1. From the **Device Select** area (Figure 355), click a video device. The **Video Server Device Control** appears (Figure 356).


Figure 356. Video Server Device Control Example



Note In the following step, retrieving a large Clip List could take an extended period of time.

2. Click the **Add** button. A **Clip List** dialog box (Figure 357) appears.

Figure 357. Clip List Dialog Box Example




3. Click **Get Clips**.

4. Click **Done**.

Add An Audio Clip


1. From the **Device Select** area (Figure 355), click an audio device. The audio device control appears (Figure 358).

Figure 358. Audio Device Control Example



2. Click the **Add** button. A **Track List** dialog box (Figure 359) appears.


Figure 359. Track List Dialog Box Example



3. Double-click the clips to add them to the Track List. An **Add Clip** dialog box appears.

Note For all names, abbreviations, and colors, use established standards and consistent techniques and practices. Refer to *Standardization* on page 577.

Figure 360. Add Clip Dialog Box



4. In the **Input Name** box, type a name using common naming conventions. Refer to *Standardization* on page 577.
5. Click **Done**.

Search For A Time Code

Note This only applies to a loaded clip.

1. Click **Time Code**.
2. Enter the video time code.

Note In the following step, click the right side to search forward. Click the left side to search backward.


3. Click **Start Time Code Search**.

Note Use the Shuttle knob to scan a video and locate a particular frame.

Scan/Shuttle A Video

1. From the **Device Select** area (Figure 355), click an audio device. The audio device control appears (Figure 361).

Figure 361. VTR Device Control Example



2. Click and drag the **Shuttle** slider.

- Drag right to fast forward.
- Drag left to rewind.

Note The scan/shuttle speed changes proportionately with the position of the slider handle.


RAM Recorder

Record A Still

1. From the **Device Select** area, click an available RAM Recorder channel. The **RAM Recorder** device control appears (Figure 362).

Note When the RAM Recorder device control appears, either the **Stills** or the **Clips** button is highlighted, indicating the current view.


Figure 362. RAM Recorder Device Control Interface



2. Select the **Stills** view. The **Stills** button (Figure 363) highlights.

3. Click the **Setup** button. The **Stills** setup parameter options (Figure 363) appear above the controls.

Figure 363. RAM Recorder Device Control Interface – Stills View (Setup Parameters)



4. Click the **Delegation** arrow to view a list of available RAM Recorder channels, and then from the list click the desired channel. The selected channel appears as the delegation.
5. To view the input routed to the RAM Recorder, click the **E/E** button.
6. On the P/P switcher bank, click the appropriate RAM Recorder channel. For example, if RAM Recorder channel 2 was originally delegated, then click RAM Recorder channel 2 on the P/P switcher bank.
7. From the P/P switcher bank, click the **Browse Program Master Routing** button (Figure 364) to open the **Master Routing** dialog box (Figure 365):

Figure 364. Access Master Routing Button





Figure 365. Master Routing Dialog Box – Destination and External Source



8. Click the appropriate values for the **M/E BUSES**, **INTERNAL SOURCES**, and **RAM RECORDER**.

To route external sources into a RAM channel, first click the RAM Recorder Channel and then click the External Source. The destination (RAM Recorder Channel of **Ram1**) is always selected first and then the external source (**IN96**) is selected second.

Note In order to properly record a still, the RAM Recorder Channel in the **Master Routing** dialog box should match the designated channel in the **RAM Recorder** device control interface

9. From the **Stills** tab, to record a new still, click the **Record** button. The newly recorded still appears in the **Stills List**.
10. From the **Stills** view, to record over an existing still, do the following:
 - a. Select the desired still and click the **Record ID** button. The **Confirm Record** dialog box appears:

Figure 366. Confirm Record Dialog Box (Record ID a Still)




b. Either:

- To record over the existing still, click **Yes**. The default still name, still plus position number, appears in the stills list.
- To cancel recording over the existing still, click **No**.

11. To rename the still, right-click the still, and then click **Rename**. The **Rename Still** dialog box appears (Figure 367):

Figure 367. Rename Still Dialog Box



12. Either:

- Type the new name of the still in the **Still Name** text box and click **OK**.
- Keep the original name of the still and click **Cancel**.

Note For all names, abbreviations, and colors, use established standards and consistent techniques and practices. Refer to *Standardization* on page 577.

13. To verify still recording:

- a. On the P/P switcher bank, click the appropriate page source.
- b. To load the still, from the list, click the still and then click the **Load Still** button.


Record A Clip

Note After a clip has been recorded, it is recommended that you trim or shorten the clip to reduce space in the **Clip List**. Trimming clips also manages clutter on the Event Timeline module. Refer to [Trim A Clip on page 328](#).

1. From the **Device Select** area, click an available RAM Recorder channel. The **RAM Recorder** device control appears ([Figure 368](#)).

Note When the RAM Recorder device control appears, either the **Stills** or the **Clips** button is highlighted, indicating the current view.

Figure 368. RAM Recorder Device Control Interface




2. Select the **Clips** view. The **Clips** button ([Figure 363](#)) highlights.
3. Click the **Setup** button. The **Clips** setup parameter options ([Figure 363](#)) appear above the controls.

Figure 369. RAM Recorder Device Control Interface – Clips View (Setup Parameters)



4. Click the **Delegation** arrow to view a list of available RAM Recorder channels, and then from the list click the desired channel. The selected channel appears as the delegation.
5. To enter the recording length of the clip, click in the **Rec Length** text box. The **Timecode Editor – Record Length** dialog box appears:

Figure 370. Timecode Editor – Record Length Dialog Box




6. In **mm:ss:ff** format, either:
 - Type the time in the **Time Code** text box and click **OK**.
 - Use the key pad to enter time and click **OK**.
7. To bypass any video playout and display what is routed into the RAM Recorder channel as that channel's output, click the **E/E** button.
8. On the P/P switcher bank, click the appropriate RAM Recorder channel. For example, if RAM Recorder channel 2 was originally delegated, then click RAM Recorder channel 2 on the P/P switcher bank.
9. From the P/P switcher bank, click the **Access Master Routing** button (Figure 371) to open the **Master Routing** dialog box (Figure 372):

Figure 371. Access Master Routing Button



Figure 372. Master Routing Dialog Box – Destination and External Source



10. Click the appropriate values for the **M/E Buses**, **Internal Sources**, and **RAM Recorder**.


To route external sources into a RAM channel, first click the RAM Recorder Channel and then click the External Source. The destination (RAM Recorder Channel of **Ram1**) is always selected first and then the external source (**IN96**) is selected second.

Note The RAM Recorder Channel in the **Master Routing** dialog box must match the delegated RAM Recorder Channel in the **RAM Recorder** device control interface.

11. From the **Clips** tab, to record a new clip, click the **Record** button. A newly recorded clip appears in the **Clips List**.
12. From the **Clips** tab, to record over an existing clip, perform the following steps:
 - a. Select the desired clip and click the **Record ID** button. The **Confirm Record** dialog box appears:

Note On the **Clips** tab, the **Record ID** button only appears on a Kayak HD.

Figure 373. Confirm Record Dialog Box (Record ID a Clip)




- b. Either:
 - To record over the existing clip, click **Yes**. The default clip name, clip plus position number, appears in the clips list.
 - To cancel recording over the existing clip, click **No**.
13. From the **Clips** tab, to append to an existing clip, perform the following steps:
 - a. Select the desired clip.
 - b. In the **Rec Length** text box, set the timecode. Refer to [Step 5](#).

CAUTION Since the length of time entered in the **Timecode Editor – Record Length** dialog box appends the current clip from its current timecode position, be careful not to record over sections of a clip.

A typical scenario for a recording length of a clip:


- The beginning of a clip at 15 sec
 - The recording length of 5 sec
 - The **Record Edit** function records over the first 5 sec of the 15 second clip
- c. Click the **Record Edit** button. The **Confirm Record** dialog box appears:

Figure 374. Confirm Record Dialog Box (Record Edit a Clip)



14. To rename the clip, right-click the clip. The **Rename Clips** dialog box appears (Figure 375):

Figure 375. Rename Clips Dialog Box



15. Either:
- Type the new name of the clip in the **Clip Name** text box and click **OK**.
 - Keep the original name of the clip and click **Cancel**.

Note For all names, abbreviations, and colors, use established standards and consistent techniques and practices. Refer to *Standardization* on page 577.

16. To verify clip recording:
- a. On the P/P switcher bank, click the appropriate page source.
 - b. To load the clip, from the clip list click the clip and then click the **Load Clip** button.
 - c. To go to the beginning of the clip, click the **Begin** button
 - d. Click the **Play** button.

Note After a clip has been recorded, it is recommended that you trim or shorten the clip to reduce space in the **Clip List**. Trimming clips also manages clutter on the Event Timeline module. Refer to *Trim A Clip* on page 328.

Trim A Clip

CAUTION Once a clip has been trimmed, the clip cannot go back to its original **Mark In** and **Mark Out** settings.

1. From the **Device Select** area, click an available RAM Recorder channel. The **RAM Recorder** device control appears (Figure 376).


Note When the RAM Recorder device control appears, either the **Stills** or the **Clips** button is highlighted, indicating the current view.

Figure 376. RAM Recorder Device Control Interface



2. Select the **Clips** view. The **Clips** button (Figure 363) highlights.
3. From the **Clips List**, click a clip.
4. To load the clip, click the **Load Clip** button. The clip highlights green.
5. Set the **Mark In** and **Mark Out** times.
6. Click **Trim**. The **Trim Clip** confirmation dialog box appears:

Figure 377. Trim Clip Confirmation Dialog Box



7. Either:

- To trim the clip, click **Yes**.

The clip is trimmed based on the **Mark In** and **Mark Out** time settings.


- To cancel the function and return to the **Clip List**, click **No**.

Play A Still

1. From the **Device Select** area, click an available RAM Recorder channel. The **RAM Recorder** device control appears (Figure 2).


Note When the RAM Recorder device control appears, either the **Stills** or the **Clips** button is highlighted, indicating the current view.

Figure 378. RAM Recorder Device Control Interface



2. Select the **Clips** view. The **Clips** button (Figure 363) highlights.
3. Click the **Setup** button. The **Stills** setup parameter options (Figure 379) appear above the controls.

Figure 379. RAM Recorder Device Control Interface – Clips Tab (Expanded View)



4. On the **Stills** tab, from the **Delegation** drop-down list, click an available RAM Recorder channel.
5. From the **Stills List**, double-click the still.
6. Set the following parameters as necessary:
 - **Readout Still**
 - **Vid/Key Mode**
7. On the P/P switcher bank, click the appropriate RAM Recorder channel.


Note The RAM Recorder channel on the P/P switcher and the delegated RAM Recorder channel need to be the same.

Play A Clip

1. From the **Device Select** area, click an available RAM Recorder channel. The **RAM Recorder** device control appears (Figure 380).

Note When the RAM Recorder device control appears, either the **Stills** or the **Clips** button is highlighted, indicating the current view.

Figure 380. RAM Recorder Device Control Interface




2. Select the **Clips** view. The **Clips** button (Figure 380) highlights.
3. Click the **Setup** button. The **Clips** setup parameter options (Figure 381) appear above the controls.

Figure 381. RAM Recorder Device Control Interface – Clips View (Setup Parameters)




4. From the **Delegation** drop-down list, click an available RAM Recorder channel.
5. From the **Clips List**, double-click the clip.
6. Set the following parameters as necessary:
 - **Mode**
 - **Loops**
 - **Readout Play**
 - **Variable**
7. To set the Mark In point, click in the **Mark In** text box. The **Timecode Editor – Mark In** dialog box appears (Figure 382).

Figure 382. Timecode Editor – Mark In Dialog Box



- a. To enter time for the **Mark In** setting in **mm:ss:ff**, either:
 - Type the time in the **Time Code** text box and click **OK**.
 - Use the key pad to enter time and click **OK**.
 - b. To apply the time setting, click the **Mark In** button.
8. To set the Mark Out point, click in the **Mark Out** text box, the **Timecode Editor – Mark Out** dialog box appears:

Figure 383. Timecode Editor – Mark Out Dialog Box



- a. To enter time the **Mark Out** setting in **mm:ss:ff**, either:
 - Type the time in the **Time Code** text box and click **OK**.
 - Use the key pad to enter time and click **OK**.

- b. To apply the time setting, click the **Mark Out** button.
9. On the P/P switcher bank, click the appropriate RAM Recorder channel.

Note The RAM Recorder channel on the P/P switcher and the delegated RAM Recorder channel need to be the same.

10. To go to the beginning of the clip, click the **Begin** button.
11. Click the **Play** button.

Clips and Stills Maintenance

CAUTION The Ignite/Ignite Konnect switcher does not save stills and clips.

In case of a power failure or each time the switcher is turned off to update firmware, all clips and stills are removed from memory and no longer appear in the **Stills List** or **Clips List** of the RAM Recorder. It is recommended that you export all stills and clips before turning off the switcher and save them to an external storage device.

The only way to export stills and clips from the switcher to the PC or import them from the PC back to the RAM Recorder is via the switcher Sidepanel program. Refer to the current manual supporting your switcher product.

For a more detailed explanation on how to export/import stills and clips using the Sidepanel™ program. Refer to the current manual supporting your switcher product.

Delete Clips and Stills

1. From either the **Stills** view or the **Clips** view, click the still or clip for deletion.
2. Click the **Delete** button. The **Delete Still** or the **Delete Clip** confirmation dialog box appears:

Figure 384. Delete Still Confirmation Dialog Box





Figure 385. Delete Clip Confirmation Dialog Box



3. Either:

- To delete the still or clip from the list, click **OK**.
- To cancel the function and return to the stills list or the clips list, click **Cancel**.

Device Manager Module

Figure 386. Device Manager Module



Overview

The Device Manager module ([Figure 386](#)) enables the operator to set the system operating mode (**LIVE** or **PREP**), and control/monitor the physical devices (hardware) used to produce a live broadcast. It also plays a key role in device sharing and failure recovery in redundant Ignite/Ignite Konnect systems. Refer to *Redundancy* [on page 28](#) and *Failure Recovery* [on page 427](#).

The Device Manager module has three monitoring/control areas:

- [Devices Tab on page 336](#)
- [Messages Tab on page 337](#)
- [Mode and Configuration Control on page 337](#)

Devices Tab

Figure 387. Device Manger - Devices Tab



The **Devices** tab (Figure 387) displays the status of all devices configured for use in either **LIVE** or **PREP** mode. Device information is displayed in a column and row presentation where the number of columns and rows shown depends upon the number of configured devices. Device status is provided by either a green, red, or gray color indication:

- Green (Active) - indicates a device that is active in the current mode and communicating properly with the Device Manager.

Example: If **DKO1** is configured for **LIVE** use, the workstation is in **LIVE** mode, and **DKO1** is communicating properly with the Device Manager, it displays green (active).

- Red (Error) - indicates a device that should be active (based on current mode and configuration selection), but is unable to properly communicate with the Device Manager.

Example: If **DKO1** is configured for **LIVE** use, the workstation is in **LIVE** mode, but **DKO1** cannot communicate with the Device Manager, it displays red (communication error).

- Gray (Inactive) - indicates a device that is configured for use, but not active in the current mode.

Example: If **DKO1** is configured for **LIVE** use, but the workstation is in **PREP** mode, it displays gray (not active).

Messages Tab

Figure 388. Device Manager Messages Tab



The **Messages** tab (Figure 388) shows real-time messages generated by various Ignite/Ignite Konnect modules. Message status is shown as:

- Green - Information message.
- Yellow - Warning message - indicates a potential problem that requires operator evaluation.
- Red - Severe/Error message - indicates a severe error has occurred. These errors must be evaluated to determine if corrective action must be taken prior to attempting to produce a show.

Note Initial warning/error messages are normal at system startup.

Initial warning/error messages may occur at system startup when devices are unable to provide a timely reply to initial Device Manager status requests. These initial warning/error messages should be cleared by the operator (refer to [Verify/Clear Message Status on page 345](#)).

Subsequent warning/error messages indicate device or communication problems, and must be evaluated and corrected prior to attempting to produce and/or air a live show.

Mode and Configuration Control

There are two control buttons (Figure 389) at the bottom of the Device Manager module:

- Mode Control (LIVE/PREP)
- Active Device Configuration

Figure 389. Device Manager Control Buttons



Mode Control

The **Mode Control** button enables the user to change the workstation operating mode.

- In **LIVE** mode, the button is green to indicate to the operator that the system is configured to produce/air a live show.
- In **PREP** mode, the button is gray to indicate to the operator that the system is configured to prepare a show (rundown convert and check TME associations on the event timeline) but not to air a live show.

To change modes, click the button, then click yes to the popup confirmation dialog box; the workstation status and control button indicator changes to gray and indicates **WAIT** until all mode change request/acknowledge dialog boxes are processed and the appropriate devices are disconnected/connected. The mode then toggles to, and indicates, the requested state.

Active Devices Configurations

Device Configuration button

The **Device Configuration** button displays the current device configuration and enables the operator to change device configurations on-the-fly without changing operating mode or restarting the Ignite/Ignite Konnect application. The color of the device configuration button matches that of the Mode Control button.

To change the device configuration, click the Device Configuration button and then click a different configuration or reload the current configuration as described in [Set Active Devices Configuration Dialog Box on page 339](#).


Note If the device configuration is changed, all devices disconnect and then reconnect. Therefore, it is recommended that device configuration is not changed during a live show.

Set Active Devices Configuration Dialog Box

The **Set Active Devices Configuration** dialog box (Figure 390) is accessed by clicking the **Device Configuration** button. It supports:

- Up to 99 user-defined device configurations.
- Enables runtime configuration switching.
- Synchronizes grouped systems and device configurations at start-up.
- Saves the last used configuration as the default for system restarts, as changes occur.

Figure 390. Set Active Devices Configuration Dialog Box



The available configurations list at the top of the dialog box displays all available device configurations by identification **No.** and **Description**. A green (**LIVE**) or red (**PREP**) circle to the left of the **No.** column identifies the active device configuration and current mode status of the workstation. Double-click an inactive configuration to make it active. Double-click an active configuration to reload it (reloading an active configuration is useful for adding or deleting devices from a configuration).

Note Reloading an active configuration is necessary when adding or deleting devices from the active configuration. It is the only way to enact the changes. Adding or deleting devices, is done in the device configuration and setup (On the Event timeline Setup menu, click Device Configuration and Setup).

- The **Close** button, in the middle of the dialog box, closes the dialog box.
- The **Ignite Stations** list at the bottom of the dialog box displays all stations that are connected to the network, and powered-up with the Ignite/ Ignite Konnect application running. Each listed station is identified by **Name**, **Group**, **Type**, **Config#**, **Status**, **IP Address**, and **Port** assignment. A sun icon identifies the workstation displaying the dialog box. In the listing, systems with an identifier in the **Group** column are considered grouped. Systems sharing a common **Group** identifier are part of that common group. Stand-alone systems do not have **Group** identifiers.
 - Grouped systems communicate their presence and status to all other systems on the network; as do stand-alone systems. But unlike stand-alone systems, grouped systems employ a mode/ device configuration relationship to synchronize their mode and device configuration with other systems within the group.
 - Stand-alone systems also communicate their presence and status to all systems on the network, but operate independently.

All systems startup in the **WAIT** mode. During startup:

- A stand-alone system automatically switches to the default mode (PREP) and last used device configuration.
- A grouped system first checks for the presence of other active systems within the group.
 - If no other system in the group is detected, the system starts in the default mode (LIVE) and last used device configuration.
 - If a startup workstation detects an active workstation in its group, the startup workstation device configuration is matched and the mode is set to not conflict with the active system.

Note To avoid the possibility of device conflict at startup, never start two or more grouped Ignite/Ignite Konnect systems simultaneously. Wait for one system to fully start before starting the second grouped system.

Operation

Note The following procedures assume that the display of **Optional Information dialog boxes** is set to **NO** (default) and that **Auto-Accept** for mode and device configuration changes is set to **YES** (default). If not, the operator may see additional information and mode/device configuration change acknowledge dialog boxes not discussed here. These self-documented dialog boxes provide the operator real-time visual cues of system operation when performing mode or device configuration changes.

Note **Optional Information dialog boxes** and **Auto-Accept** settings should only be changed by qualified Grass Valley Field Service Engineers (refer to *Contacting Grass Valley* on page 4).

Use the following procedures to:

- [Place Workstation in LIVE Mode on page 341](#)
- [Set Active Devices Configuration on page 342](#)
- [Verify Device Status on page 344](#)
- [Verify/Clear Message Status on page 345](#)
- [Place Workstation in PREP Mode on page 345](#)

Place Workstation in LIVE Mode


Note The following procedure assumes the system is currently in **PREP** mode.

1. From the Device Manager module ([Figure 391](#)), click **PREP**.
The **Go to LIVE mode?** dialog box ([Figure 392](#)) appears.

Figure 391. Device Manager - Prep Mode



Figure 392. Go to LIVE Mode Dialog Box



2. Click **Yes** to continue.

In Stand-alone Systems:

The mode changes to **WAIT** while devices are disconnected, then changes to **LIVE** and connects to the required **LIVE** mode devices.

In Grouped Systems (System A and B):

Note The following assumes that System A is currently in **PREP** mode and is changing to **LIVE** mode.

System A changes to **WAIT** mode while devices are disconnected and the system checks for other active systems in the group.

- If no other grouped system is detected, System A changes to **LIVE** and connects to **LIVE** mode devices.
- If another system (System B) is detected, it changes to **WAIT** mode while devices are disconnected. System A then changes to **LIVE** and connects to **LIVE** mode devices. System B then changes to **PREP**, and connects to **PREP** mode devices.


Note If a user tries to change the configuration while in Prep mode, a message appears stating the system must be in Live mode to change configurations.

Set Active Devices Configuration

Note that:

- At startup, the active device configuration is set to the configuration that was active at shutdown, or in grouped systems, set to match the configuration of the active system in the group.
 - In stand-alone systems, device configuration changes are possible in either **LIVE** or **PREP** mode.
 - In grouped systems, only the **LIVE** system can change the active device configuration; the **PREP** system configuration is automatically synchronized with the **LIVE** system at start-up, and as changes occur.
 - This is also how a current configuration is reloaded after it has been modified—either devices added or removed.
1. From Device Manager, click the configuration button.
The **Set Active Devices Configuration** dialog box([Figure 393](#)) appears.


Figure 393. Set Active Configuration Dialog Box



- Double-click the active entry (red/green circle) to reload it, or an inactive entry to load and make it active.

A **Change Configuration?** dialog box (Figure 394) is displayed to confirm **RELOAD** or **CHANGE** of the current configuration.

Figure 394. Change Configuration? Dialog Box – RELOAD or CHANGE



- Click **Yes** to confirm and close the **Change Configuration?** dialog box.

The **Change Configuration?** and **Set Active Devices Configuration** dialog boxes close.

In Stand-alone Systems:

The mode changes to **WAIT** while devices are disconnected, the selected configuration loads, and the required devices are connected in **PREP** or **LIVE**.

In Grouped Systems (System A and B):

Note In grouped systems, only the **LIVE** system can change the active device configuration; the **PREP** system configuration is automatically synchronized with the **LIVE** system.

Note The following assumes that System A is **LIVE** using configuration 1.

System A changes to **WAIT** mode while the system checks for other active systems in the group.

- If no other grouped system is detected, devices are disconnected, the selected configuration is loaded, and the required devices are connected in **LIVE** mode.
- If another system (System B) is detected, it changes to **WAIT** mode while devices are disconnected. System A then changes to **LIVE** and connects to **LIVE** mode devices. System B then changes to **PREP**, and connects to **PREP** mode devices.

Note If a user tries to change the configuration while in Prep mode, a message appears stating the system must be in Live mode to change configurations.

Verify Device Status

1. From Device Manager, click the **Devices** tab ([Figure 395](#)).

Figure 395. Device Manger - Devices Tab



Note Devices that display red (error), are not communicating with the Device Manager module, and could adversely affect **LIVE** show production. Devices that display gray (inactive) are available in **PREP** mode, but not used in **LIVE** mode.

2. Verify that all devices are displayed in green (that no devices are displayed in red [error]).

Verify/Clear Message Status

Note Messages that display yellow (warning) or red (error) indicate processes that could adversely affect **LIVE** show production.

1. From Device Manager, click the **Messages** tab.


Note Initial warning/error messages at system startup are normal and should be cleared. Subsequent warning/error messages indicate device or communication problems, and must be evaluated and corrected prior to attempting to produce and/or air a live show.

Figure 396. Device Manager Messages Tab



2. Evaluate any yellow and red messages to determine their effect on the **LIVE** production. If necessary, troubleshoot and repair prior to attempting to air a **LIVE** show.
3. To clear messages, right-click in the messages area. The **Cancel/Clear Messages** dialog box (Figure 397) appears.

Figure 397. Cancel/Clear Messages Dialog Box



4. Click **Clear Messages**. The **Cancel/Clear Messages** dialog box closes and all messages are cleared (Figure 388).

Place Workstation in PREP Mode


Note The following procedure assumes the system is currently in **LIVE** mode.

1. From Device Manager, click **LIVE** (Figure 398). The **Go to PREP mode?** dialog box (Figure 399) appears.

Figure 398. Device Manger - Live Mode



Figure 399. Go to PREP Mode Dialog Box



2. Click **Yes** to continue.

In Stand-alone Systems:

The mode changes to **WAIT** while devices are disconnected, then changes to **PREP**, and connects to the required **PREP** mode devices.

In Grouped Systems (System A and B):

Note The following assumes that System A is currently in **LIVE** mode and is changing to **PREP** mode.

System A changes to **WAIT** mode while devices are disconnected and the system checks for other active systems in the group.

- If no other grouped system is detected, System A changes to **PREP** and connects to **PREP** mode devices.
- If another system (System B) is detected, it changes to **WAIT** mode while devices are disconnected, then changes to **LIVE** mode and connects to the required **LIVE** mode devices. System A then matches its configuration with System B, changes to **PREP** mode, and connects to **PREP** mode devices.

GV Stratus Digital Media Platform Module

Figure 400. Ignite/GV Stratus Digital Media Platform Interface



Overview

The GV Stratus Digital Media Platform (DMP) module is an Ignite/Ignite Konnect system option that is used exclusively with the Grass Valley GV Stratus DMP functionality. The Ignite/DMP interface consists of services that communicate with the NRCS, Stratus Core Services Server, K2 Summit, and the Encoder.

Production

Note After producing, editing, and coding a show in the NRCS, that rundown is imported onto the Ignite/Ignite Konnect Event Timeline. Once a rundown is imported it is automatically monitored until a different rundown is imported.

In the production phase, the NRCS information, including the DMP show and segment data, is imported into the Ignite/Ignite Konnect system via Rundown Conversion. Rundown convert is a part of the Ignite/Ignite Konnect application (requires Ignite DMP options to include Ignite version 7.3 and MOP) that imports a rundown graphical representation in preparation for taking a show to air. During processing, the rundown converter retrieves and parses the rundown from the NRCS, then automatically creates a show by placing pre-program show events (TMEs) on the Ignite/Ignite Konnect Event Timeline. The Event Timeline interface supports DMP data via the DMP icon properties within the TME which is processed via the DMP services.

User Interface

Event Timeline Tools Menu

Note For typical Ignite Event Timeline overview and operation information, refer to *Section 10-Event Timeline Module*.

When GV Stratus DMP is combined with Ignite, and the TMEs are built with the appropriate DMP icons on the Timeline, all DMP data is processed at rundown import.

GV Stratus DMP Task Icon

Figure 401. Event Timeline Icon Toolbox – GV Stratus DMP Icon .



A DMP icon ([Figure 401](#)) is added at the bottom of the Event Timeline Icon Toolbox. When placed in a TME, the DMP icon properties establish the DMP functionality via either automatic, MOS-generated configuration (import rundown) or manual configuration of a show or segment data task.

Note For typical Ignite Event Timeline overview and operation information, refer to *Section 10-Event Timeline Module*.

DMP TME Item Type


There are three device types that must be set up in the Ignite Device Manager ([Device Manager Module on page 335](#)):

- Stratus core server
- Summit record device
- An approved transcoder

The **DMP TME Property Window** has four possible actions (Figure 402):

- **None**
- **Start Show**
- **Stop Show**
- **Segment**

Figure 402. DMP TME Property Window



These can be embedded in the TME task instead of using the manual functions. Also, when embedded in a TME, that TME can be assigned to a Katalyst button for one-button activation.

Manually Managed DMP Task

As a TME task, a DMP icon can be manually added, edited, or deleted at anytime.


Operation

Note Operation is a function of GV Stratus. Refer to the respective GV Stratus information.

Add DMP Icon to Event Timeline


- From the Event Timeline Icon toolbox, drag and drop a DMP icon into the TME (Figure 403 on page 351).

Figure 403. IGNITE Event Timeline/GV Stratus DMP Toolbox Icon



Event Timeline Module

Figure 404. Event Timeline Module



Overview

The Event Timeline Module ([Figure 404](#)) is the central control area for show production. Basically it is an event occurrence line that is populated with a series of TMEs (refer to [TME™ \(Transition Macro Event™\)](#) on [page 364](#)). Collectively, the TMEs automate the tasks necessary to sequence and produce up to a two hour show. Event timeline control uses a combination of the associated TMEs, Timeline menus, playlists, manual controls, and LBN hotkeys.

Event Timeline Controller


There are six basic methods of Event Timeline control:

- The Event Timeline control GUI ([Figure 405](#)) provides play, pause, and timeline control.
- The timeline can also be controlled by the ALT + SPACEBAR keys on the keyboard. This is the most common method of advancing through a show.
- The embedded Ignite-X Playlist or the stand-alone Playlist on a remote client can also control the timeline. This allows a co-director or more than one operator to run a show simultaneously.
- The Ignite Katalyst Automation Control Panel and QUICbox panel.
- The Ignite Automation Soft Panel can be configured to provide play, pause and timeline control.
- An external GPI to the Ignite/Ignite Konnect system so that the timeline may be advanced by switches, foot pedals, or other external controls.

Note A user can manually override anything on the timeline at any time.

Note For DMP specific Event Timeline controller functionality, refer to [Section 10-GV Stratus Digital Media Platform Module](#).

Figure 405. Event Timeline Controller



The Event Timeline Controller has four indication states ([Figure 405 on page 355](#));

- Off – default state (gray) indicates there are no pending updates.
- Green – indicates there is a pending update and that update is all good—contains only messages and no warnings or errors.
- Amber – indicates there is a pending update, but that update contains one or more warnings.
- Red – indicates there is a pending update, but that update contains one or more warnings in addition to errors.

Note The red indicator supersedes an amber to signify more severe warnings and errors.

Ignite-X Playlist


The Ignite-X Playlist displays the same sequence of events as the Event Timeline, but in a vertical list that allows users to easily navigate within a show. Events can be added, removed, edited, re-ordered, and filtered within the playlist. The Playlist can either be embedded in the Event Timeline Module, or installed separately on a remote device that is accessible anywhere as long as it is connected to the Ignite server.

The Playlist supports the ability to display side-by-side the text-based vertical list view, and the block view of sequence of events on the Timeline. This permits Directors and Producers to monitor critical information in just one place on the user interface. Users can select a rundown from the list of rundowns, display and collapse items by segment, story, event and element, scroll past, present and future events, and refresh NCS updates directly via the Playlist Controller.

In addition, the Preview Event Inspector displays event contents that can be previewed in a chronological order. Each selected event and embedded events can be distinguished clearly in the Preview Event Inspector, while their TMEs may be overlapping on the Ignite Event Timeline.

You can also display the LBN (Late Breaking News) module in the Ignite-X application. Therefore, a configured LBN can easily be inserted or dragged into the Playlist during a show.

Figure 406. The Ignite-X Playlist



Menu Bar

The Event Timeline menu bar (Figure 407) is located below the title bar at the top of the Event Timeline module. Each menu item displays a list of available commands.

Figure 407. Event Timeline Menus



File Menu

The **File** (Figure 408) menu commands are:

File Menu Command	Purpose
New	To create a new show/user macro file.
Open	To open an existing show/user macro file.
Save	To save the currently open show/user macro file with timeline and LBNs, including any changes made. Also to save CG preset hotkeys.
Save As	To save the currently open show/user macro file with timeline and LBNs, including any changes made, with a different show/user macro file name. Also to save CG preset hotkeys.
Exit	To close the Ignite/Ignite Konnect live production control system application.

Figure 408. Event Timeline File Menu




Edit Menu

The **Edit** (Figure 409) menu commands are:

Edit Menu Item	Purpose
Undo	To reverse the last action.
Redo	To reverse the UNDO.
Cut	To remove selected items, placing them on the clipboard.
Copy	To copy selected items to the clipboard.
Paste	To put the current clipboard items on the timeline.
Delete	To remove the selected item(s) from the timeline.

Edit Menu Item	Purpose
Delete All	To delete all items on the Timeline.
Ignite-X User Preferences	To launch the User Preferences settings of the embedded Ignite-X Playlist panel.

Figure 409. Event Timeline Edit Menu




View Menu

The **View** (Figure 410) menu commands are:

View Menu Item	Purpose
Toolbar	To show or hide the timeline toolbar.
Cursor	To show or hide the timeline cursor.
Control Items	To bring objects to the foreground.
Control Groups	To bring groups to the foreground.
Slug	To bring slugs to the foreground.
Stories	To bring stories to the foreground.
Show Properties	To display timeline data.

Figure 410. Event Timeline View Menu




Setup Menu

The **Setup** (Figure 411) menu commands are:

Note In Ignite/Ignite Konnect systems configured as No Audio, no QUICbox Panel is available on this menu. Also, all audio control is outside the Ignite/Ignite Konnect system and the Ignite/Ignite Konnect Audio Module user interface area is blank. The QUICbox menu item is also absent when Ignite is configured as **No automation panel**.

Setup Menu Item	Purpose
Timeline Track	To customize the Timeline layout.
Timeline	To open the Timeline Settings dialog. You can also configure GPI mark settings and rundown import save options.
Configuration and Device Setup	To open the Ignite Devices Configuration dialog where devices are defined and assigned to configurations. You can also assign ports for peripheral devices; e.g., CG, camera, server.
Tally Controller	To create tally logic. Also to allow configuration of the Tally Expander settings, as well as enabling / disabling the device.
TME Associations	To associate TME column names with the actual TME within the Ignite/Ignite Konnect system and the Ignite IQ Module. (Refer to Manage TME Associations on page 391)
Ignite Katalyst	To setup Ignite Katalyst buttons and events (Refer to Configuration on page 37)
IQ Auto Channel Pool	To setup channels for the IQ Auto Channel Pool.
QUICbox	To setup QUICbox buttons and events. (Refer to Configuration on page 70) NOTE No QUICbox Panel option is available in Ignite/Ignite Konnect systems configured as No Audio. The QUICbox menu item is absent when Ignite is configured as <i>No automation panel</i> .
DekoMOS Setup	To select/set template styles, show or hide manual play controls during playout, and configure DekoMOS Gateway IP address and port assignment.
Timed Events Setup	To configure timed events on the Timeline.

Figure 411. Event Timeline Setup Menu Example



Window Menu

The **Window** (Figure 411-Figure 415) menu commands are:

Window Menu Item	Purpose
Narrow View	To shift the timeline right, allowing more space to move smaller Ignite/Ignite Konnect modules to the left of the timeline (Figure 412).
Wide View	To display an extended view of the timeline.
Ignite-X	To display the embedded vertical playlist.
Rundown List	To display the standard two-column rundown list, at the left of the timeline, that contains Story and Slug information (Figure 413).
Rundown List Detailed	To display a three-column rundown list that includes TME information (Figure 414). Note If configured with Aurora DNP, then clip status and thumbnails are included. Note If configured with Video Server Status (VDCP Device Control) thumbnails are not included.
Hide	To hide the rundown list (Figure 415).
Ignite-X View Options	To display view options of the Ignite-X vertical playlist. You can select one from these 3 options: No Item Blocks, Item Blocks, Labeled Item Blocks You can also set the Clip Status display on the Playlist.

Figure 412. Event Timeline Window Menu – Narrow View




Figure 413. Event Timeline Window Menu – Rundown List




Figure 414. Event Timeline Window Menu – Rundown List Detailed



Aurora DNP

Note If configured with Video Server Status (VDCP Device Control) thumbnails are not included.

Figure 415. Event Timeline Window Menu – Hide




Help Menu

The **Help** menu (Figure 416) displays version information.

Help Menu	Purpose
About IGNITE	To display Ignite/Ignite Konnect software version information.

Figure 416. Event Timeline Help Menu




Tools Menu

The **Tools** menu (Figure 417) selection is:

Tools Menu Command	Purpose
Import Rundowns	To enable the import of a coded rundown from the NRCS into the Ignite/Ignite Connect system or the Ignite IQ Module. (Refer to Import Rundowns on page 370)

Figure 417. Event Timeline Tools Menu



TME™ (Transition Macro Event™)

A Transition Macro™ Event (TME) is a group of individual production tasks that are combined to create an automated video production event. Show-specific TMEs (Figure 418) on the event timeline then sequence these programmed production events via cursor movement along the Event Timeline.

Figure 418. Sample TMEs













Individual icons representing those tasks are located on the Event Timeline icon toolbox (Table 419) to the left of the Event Timeline. A TME is created by dragging and dropping task icons on the timeline, defining the individual task properties, and then saving as a TME.

Note These icons are not dependent on device ID. Several devices may be duplicated in the list; however these device icons can be any device of that type.

For example, any of the three camera icons can represent any of the three cameras. The Event Timeline tracks are customizable to reflect on site devices. So that tracks accurately depict the TME icon, track setup must be completed before starting to build the TME library.

Figure 419. .Event Timeline Icon Toolbox Icons

Icon	Description
	Notes Label – TME file identification
	Step Marks (red = Jump, green = Clock Timer for local timed events, blue = pause (GPI/GPO stop), yellow = Clock Timer for global timed events) – control the timeline cursor as it travels along the timeline.
	Switcher – video transitions and effects
	Audio – audio processor
	ScriptViewer
	CG – still stores and character generator controls
	Camera – camera presets recall
	Device Control – video servers, VTRs, and/or audio servers
	GPO/GPI – external device triggers
	DMP (Digital Media Platform)
Note	This icon is only available in Ignite/Ignite Konnect systems supporting the optional GV STRATUS DMP functionality.

There are other components in a TME in addition to the Icons. The marks at the top of each TME control what the timeline cursor does as it travels along the Event Timeline and crosses each TME. There are four marks:

- Red = Jump (start)
- Green = Clock Timer to trigger local timed events
- Blue = Pause (GPO/GPI stop)
- Yellow = Clock Timer to trigger global timed events

When the cursor encounters a red jump mark, it jumps to the next blue GPI mark, stops, and waits for the next user input. If the user sets the Blue GPI trigger to 16, it can wait for a set duration in millisecond too. During the Jump, the system identifies and preps all of the upcoming events within the TME. Once prepped, the system waits for operator input to advance the timeline and execute the TME. This is called bus prepping and it is why the section between the first red mark and the blue GPI is called the TME prep area.

Show-specific TMEs on the Event Timeline then execute production events via cursor movement along the Event Timeline.

Note On the Event Timeline, a user can manually override anything at any time, except during the actual moment a current event is being executed. Refer to [Manual Override on page 383](#),

Since there is a corresponding TME for each show event, each event is executed as the cursor travels along the Event Timeline ([Figure 420](#)).

Figure 420. TME Examples



TMEs should have:

Note Refer to *Standardization* on page 577

- Standard and consistent naming
- Standard and consistent abbreviations
- Standard and consistent color use
- Standard and consistent file structure

Structure

When building a TME, there are basic mark and icon placements to consider (Figure 421). Refer to *Marks* and *Icons* below.

Figure 421. TME Mark and Icon Structure



Marks

Typically, Jump mark placement includes the following considerations:

- Place a red Jump mark at an even number on the Timeline; e.g., 00:00:01:00.
- Place a blue GPI mark 15 frames after the red Jump Mark.
- Place a green Clock Timer mark in the same frame as the first Switcher Icon.
- Place the last red Jump mark 1 frame after the last icon in the TME.

Icons

Typically, icon placement ([Figure 422](#)) includes the following considerations:

- Place the first TME prep icon 1 frame after first red Jump Mark and any additional icons are staggered. This includes server load, CG load, camera preset recall, etc.
- Place the first ME icon 1 frame before the blue GPI mark.

Note For each additional ME icon in TME Prep area, stagger 1 frame working toward the red Jump Mark.


Note When using a server cue icon, always place the icon one frame after the first red jump mark.

- Place the Server Play icon 1 frame after the GPI
- Place the GPO to play servers 1 frame after the blue GPI/GPO mark
- Place the CG Play icon 2 frames from the GPI
- Place the Audio icon 3 frames from the GPI
- Place the first Preview/Program Switcher icon 5 frames after the first Blue GPI

Note If this value must be increased, be sure to increase the Bus Prep area by the same increment; e.g. adding 5 frames to Bus Prep also requires adding 5 frames to the Bus Prep area. Anything over 10 requires a registry change.

- Place the second GPO to play servers 15 frames after the start of the previous blue GPI/GPO mark

Figure 422. TME Mark and Icon Placement




Rundown List/Event Timeline Correlation

After producing, editing, and coding a show in the NCS, the Rundown list is imported from the NCS into the Ignite/Ignite Konnect system. The rundown list then appears in the Event window both textually in the rundown list and graphically along the Event Timeline as an event driven process. Refer to [Figure 423](#).

Note Back-to-back Pages/Slugs with the same Title before the dash are grouped under the same Story.

Figure 423. Rundown List/Event Timeline Correlation




Import Rundowns

Rundown convert is the process within the Ignite/Ignite Konnect program that imports a rundown, displays it in a graphical representation for the preparation of taking a show to air. During processing, the rundown convert process retrieves and parses the rundown from the NCS, then automatically creates a show on the Ignite/Ignite Konnect event timeline. The director then has the ability to refine the show that has been created while being free of the time involved in recreating segments that are standard from show to show.

After producing, editing, and coding a show in the NCS, import that rundown onto the Ignite/Ignite Konnect Event Timeline. Once a rundown is imported onto the timeline, it is automatically monitored until a different rundown is imported or a different show is pre-loaded.

The **Import Rundowns** dialog box (Figure 424) provides detailed rundown data and the associated user options. A color-coded and highlighted indicator identifies every change and its status in the currently pending update. Once an update is accepted, the indicators clear from the dialog box and it begins to collect information for the next update.

Figure 424. Import Rundowns Dialog Box



A user has the ability to filter changes to the rundown in order to prevent them from affecting the Event Timeline. Filtering information in the message window eliminates all unwanted or unneeded data from appearing in the rundown update window for an operator to process. Filtered items do not trigger an update. The data and options include (refer to Figure 424 and Figure 425):

- **File menu:**

Note The following three **File** menu selections are also available using the **Pre-Load**, **Import**, and **Close** buttons at the bottom right of the **Import Rundowns** dialog box.

- **Pre-Load** – enables a user to quickly get large rundowns to the timeline, especially when only a small window of time exists to import the new rundown. Refer to [Import Rundowns Pre-Load Function on page 373](#)
- **Import** – immediately imports the currently expanded/selected rundown to the Event Timeline.
- **Close** – closes the **Import Rundowns** dialog box


- **Edit** menu:
 - **Clear Cache** – clears all TMEs/IQTs cached in memory and forces them to be re-read from the disk during the next import.
 - **Configure** – opens the Configuration dialog box for the rundown filtering function. Refer to [Rundown Import Configuration \(Filtering\)](#) on page 376
- **Name, Stories, and Start Time** buttons – sort the visible rundowns by either name, stories, or start time. Clicking the same button again toggles between ascending and descending sort orders.
- Rundown List – shows all currently active and viewable rundowns (Note: Some rundowns can be hidden during pinning process.)
- **Expand/Collapse** button – expands or collapses the selected rundown.

Note When a rundown is selected, it highlights blue and when expanded, all stories in that rundown are also highlighted blue.

When a selected rundown is expanded, all the stories in that rundown are shown. If that rundown is currently monitored, all rundown import information is also shown.

- **Currently Monitored Rundown** indicator ([Figure 425](#)) – indicates the rundown that is currently monitored for updates by the Event Timeline.

Figure 425. Pin Rundown




- Pin Rundown button ([Figure 425](#)) – regardless of the selected sort option, pins that rundown to the top of the rundown list. When multiple rundowns are pinned, they are sorted as a group using the currently active sort option but they remain grouped at the top of the list.
- ...Hide unpinned rundowns/...Show all rundowns button ([Figure 425](#)) – when rundowns are pinned, the ... Hide/Show all button toggles between hiding or showing all unpinned rundowns.
- **Error, Warning, and Info** check boxes – selecting the checkbox(es) sets the view filtering.
- **Pre-Load** button – enables a user to quickly get large rundowns to the timeline, especially when only a small window of time exists to import the new rundown. Refer to [Import Rundowns Pre-Load Function on page 373](#).
- **Import** button – immediately imports the currently expanded/selected rundown to the Event Timeline.
- **Close** button– closes the **Import Rundowns** dialog box

Import Rundowns Pre-Load Function

The **Pre-Load** button ([Figure 426](#)) enables a user to quickly load large rundowns to the timeline when only a small window of time exists to import the new rundown. This is accomplished by staging the new rundown to allow for a quicker, more time-sensitive timeline update.

Note Pre-Load does not change the time it takes to process the new rundown, it simply allows you to process it while still executing existing events on the timeline. So it's important to provide a sufficient amount of time for the new rundown to pre-load.

Figure 426. Pre-Load Button



Unlike the **Import** button, which processes a rundown and then instantly replaces the current timeline with the newly imported show, the **Pre-Load** button starts importing the next rundown but the timeline is not immediately overwritten. Once the new rundown is fully processed the update icon is replaced by a corresponding Preload update icon ([Figure 427 on page 374](#)). The current timeline is not replaced by the pre-loaded rundown until the user clicks the preload update icon.

Note Once a new rundown has been selected for preload and the preload button clicked, the operator loses the ability to make changes/updates to the current show on the timeline.


The Pre-Load icon on the Event Timeline Controller has three indication states;

Note Operators must distinguish between the preload update icon and the update rundown icon to avoid accidentally taking a show that has been pre-loaded to the timeline prematurely.

- Green – indicates there is a pending update and that update is all good—contains only messages and no warnings or errors.
- Amber – indicates there is a pending update, but that update contains one or more warnings.
- Red – indicates there is a pending update, but that update contains one or more errors.

Note The red indicator supersedes an amber to signify severe warnings in addition to other errors.

Figure 427. Import Rundowns Pre-Load Indication




Import Rundown Update Indicator

The Event Timeline Controller icon provides three import rundown indications (Figure 428):

- Green – indicates there is a pending update and that update is all good—contains only messages and no warnings or errors.
- Amber – indicates there is a pending update, but that update contains one or more warnings.
- Red – indicates there is a pending update, but that update contains one or more errors.

Note The red indicator supersedes an amber to signify severe warnings in addition to other errors.

Figure 428. Rundown Import Indicators




Recommended Standard Settings

The following settings are recommended for the most efficient implementation that takes full advantage of the Import Rundown features:


- Configuration ([Rundown Import Configuration \(Filtering\)](#) on page 376) should be set to eliminate unwanted information from reaching rundown import.
- Clear the **Info** message check box.
- View Mode default is set to 4 – the default view mode is set as a global Ignite variable in the IQ Configurator ([Figure 429](#)). DefaultMessageViewMode can be set to 1, 2, 3, or 4.

Figure 429. IQ Configurator Dialog Box



Rundown Import Configuration (Filtering)

Figure 430. Rundown Import Configurations Dialog Box



Rundown Import Configuration is accessed from the **Edit** menu (Figure on page 377). There are three types of filters:

- **Script Updated** – any changes to the script text, of any story in a monitored rundown, is completely ignored and not displayed on the Ignite timeline.
- **Story Updated** – changes to the story body content, of any story in a monitored rundown, is completely ignored and not displayed on the Ignite timeline.

Note There are no options for this filter.


- **Column Updated** – any changes to the configured column, of any story in a monitored rundown, are completely ignored and not passed on to the Ignite rundown.

Add a new filter by clicking **+ Add New...** in the **Rundown Import Configurations** dialog box. A new row (Figure 431) appears that includes a **Column Name** text box for entering a column name. When a monitored rundown is updated, each update shows, in parentheses, the type of change that triggered the update. When a column triggered the change, the column name, as defined in the NRCS, is visible. If this type of update is

undesirable, then that's the text string that should be entered here. For rundown monitoring, that information also appears in the Import Rundowns dialog box.

Note Multiple entries can be created and individually identified at that time. That column information appears later in the Import Rundown dialog box for rundown monitoring.

Figure 431. +Add New... Filter Dialog Box



Delete a filter by clicking the associated red **X**.

OK – saves the changes and closes the dialog box.

Cancel – closes the dialog box without saving changes.

Operation

Event Timeline operation is accomplished using a combination of:

- The **Play** and **Pause** buttons are used for advancing and pausing the timeline ([Figure 432](#))

Note The Play/Pause control can be docked/undocked and might be found in other than the default location.

- The associated TMEs
- External GPO/GPI to the Ignite/Ignite Konnect system so that the Event Timeline can be advanced by switches, foot pedals, or other external controls
- Late Breaking News Hotkeys ([Figure 433](#))
- Timeline menus (refer to [Menu Bar on page 357](#))
- The ALT+SPACEBAR on the keyboard
- The Ignite-X Playlist

Figure 432. Timeline Play and Pause Buttons





Figure 433. LBN Hotkeys



Once a show is ready for air, a user triggers the cursor, to advance the timeline using ALT+SPACEBAR to cross each TME (production event). As the cursor crosses the commands within the TMEs, the corresponding production events occur, such as take camera one with the talent one mic full.


Note On the Event Timeline, a user can manually override anything at any time, except during the actual moment a current event is being executed.

Import Rundowns

Import and Monitor Rundowns

1. On the **Event Timeline** menu, click **Tools | Import Rundowns**. The **Import Rundowns** dialog box ([Figure 434](#)) appears.

Figure 434. Import Rundowns Dialog Box




Note As a best practice, view mode #4 is recommended. This mode shows all messages without the story tree, but it displays the changes made since the last update to the timeline was accepted. The view mode default can be configured. Refer to [Recommended Standard Settings on page 375](#).

Regardless of the view mode, stories removed from the rundown (floated, deleted) are always displayed just below the rundown name. Since they are gone there are no name references, but a count is maintained to indicate how many story deletions are present in the current update.

2. Click a rundown in the dialog box list. The selected rundown expands to show the status and highlight any warning messages ([Figure 435](#)).

Note If errors in rundown conversion appear in the dialog box, correct any errors in the NRCS and then re-import the rundown.

Figure 435. Import Rundowns Dialog Box — Status and Warning Messages



3. Click **Import**.
4. To close the **Import Rundowns** dialog box, either:
 - Click the **Close** button.
 - Click the **Close** icon.

Pre-Load Rundown

1. Execute show (e.g. rundown #1) as usual until near the end when no further rundown updates are desired.

Figure 436. Pre-Load Timeline Example






Figure 437. Pre-Load Selection Example



- Click **Pre-Load**. Once show (#2) is processed, the update icon is replaced by a highlighted rundown update icon.

Figure 438. Import Rundowns Pre-Load Indication



- Finish playing out first show (i.e. rundown #1).
- Enter commercial break.
- Click the preload update icon to accept the pre-loaded show (i.e. rundown #2).
- Pre-loaded show (i.e. rundown #2), which is already pre-processed, loads into the timeline in a few seconds.
- Execute show (i.e. rundown #2).

Column Filtering

Note Data for columns to be filtered might or might not be named the same as the visible tag in the NCS.

1. Monitor a rundown that contains the column.
2. Make a change ([Figure 439](#)) to that column in a story.

Figure 439. Make a Column Change Example

Page	Story Slug	Segment	Producer	Float	TME
A1	STORY ONE				C1
	STORY 1.2			✓	
A2	STORY TWO				voeng'
A3	STORY THREE				VOWX
A4	STORY FOUR				C2
A5	STORY FIVE				C3

874x-sc113-10

3. In the Import Rundowns window, check that the story shows an update and the column data name is visible; i.e., the column name is shown as [x] in [x] Column Updated.
4. Configure filters from Edit>Configure in Import Rundowns window.
5. Press ENTER and then click OK.
6. Repeat [Step 2](#) & [Step 3](#), but ensure the change does not appear in Import Rundowns dialog box.

Insert a Note

1. Click and drag a **Note** icon onto the TME Event Timeline.
2. Double-click the **Note** icon.
3. In the Note dialog box, type the note text.
4. Click **OK**.

Play/Restart

There are several ways to play an event on the timeline:

- On the keyboard, press ALT+SPACEBAR.
- On the timeline control module, click the **Play** button.
- On the QUICbox control panel, click a pre-programmed (ALT+SPACEBAR) button.
- Click a pre-programmed command button on an Ignite Katalyst panel.
- Trigger the GPI Automation Input.

Pause/Stop

There are three different ways to pause an event on the timeline:

- On the keyboard, press either:
 - ALT+P
 - ALT+S
- On the timeline control module, click the **Pause** button.
- On the Katalyst control panel, click a pre-programmed **Pause Ignite** action button.

LBN (Late Breaking News)

There are two ways to add an LBN to the Timeline:

- Right-click and hold an LBN hotkey to drag it anywhere on the timeline.
- Click an LBN hotkey to insert it at the current cursor position on the timeline.

Note It is inserted just to the right of the cursor (as the next event).

Manual Override


Users can manually override anything on the timeline at any time. For example, to override any video source after a TME has been bus-prepped, except when a current event is actively being executed:

Select a new source on the preset bus of the switcher. This allows the new source to transition to **Program** when the TME is transitioned. This overrides the original source that was prepped in the TME, provided that the prepped effect included a background transition.

Cursor Relocate/Jump

1. Right-click in the **Event Timeline** sequencer at the position to relocate the cursor. A **Relocate Cursor** dialog box (Figure 440) appears.

Figure 440. Relocate (Jump) Cursor



2. Click **Relocate Cursor**. The cursor jumps to the selected new position.

Re-cue

- Press **Alt+Q**.


Note **Alt+Q** places the cursor at the beginning of the Event Timeline.

Advance Timeline

The Timeline is advanced by:

- TME, Slug, or story.
- The **Play** button and **Pause** button for rolling and pausing the timeline (Figure 441).
- The ALT+SPACEBAR on the keyboard.
- A foot pedal via a GPI.
- Using the buttons in the toolbar to advance through show events.

Figure 441. Timeline Play and Pause Buttons




Page Break

The default page break occurs when the cursor reaches the right most position of the viewable Event Timeline. At that time, the viewable Event Timeline jumps left and the next full Event Timeline page appears. This page break can be reset to occur before reaching the right-most position.

1. Right-click in the **Event Timeline** sequencer at the position to relocate the cursor. A Relocate Cursor/Page Break menu appears (Figure 442).

Figure 442. Page Break



2. Click **Page Break**. The page break resets to the selected new position.

TMEs (Transition Macro Event)

Build a TME

- Note** For tracks to accurately depict the TME icon, track setup must be completed before starting to build the TME library.
- Note** For all names, abbreviations, colors, and file structures, use established standards and consistent techniques and practices. Refer to *Standardization on page 577*.
- Note** If more than 8 audio tasks are required on any single audio icon, place a 2nd audio icon next to the first for 9-16 and so on.


The following is a sample TME build procedure. All the necessary build icons are located on the icon toolbox to the left of the Event Timeline window. Refer to [Table 419 on page 365](#).

1. On the icon toolbox, click and drag a red Jump mark to an even number on the Timeline; e.g., 00:00:01:00.
2. Double-click directly below the red Jump mark on the timeline. The Group Properties dialog box appears.

Note For all names, abbreviations, colors, and file structures, use established standards and consistent techniques and practices. Refer to *Standardization on page 577*.

3. Assign a TME color and a TME name. Click **OK**.
4. On the icon toolbox, click and drag a blue GPI mark to 15 frames after the red Jump mark.
5. On the icon toolbox, click and drag a Switcher icon to 5 frames after that blue GPI mark on the timeline.
6. Double-click that Switcher icon. An M/E Properties dialog box ([Figure 443](#)) appears (refer to the Switcher module).

Figure 443. ME Properties Dialog Box



7. Define the M/E properties for the desired video transition ([Figure 8](#)).
 - a. Click an M/E button. The respective M/E effects list appears.
 - b. From the effects drop-down list, Click an effect for the TME. All buttons related to the selected effect change to yellow, indicating Preview.
 - c. If an effect with a key source is selected, click the bottom half of the PVW button. The **Select Source** dialog box ([Figure 444](#)) appears.

Figure 444. Select Source Dialog Box



- d. From the drop-down list, select a source. Click **OK**.
 8. Click **Save**.
 9. On the icon toolbox, click and drag a red Jump mark to 1 frame after the last icon in that TME.
- Note** Typically, there are approximately 15 frames between the first jump mark and the GPI. Rare occasions might require increasing the frame duration between the first jump mark and GPI.
10. For events that need to take place in prep (e.g., to setup a server cue, cameras, or CG/Still Store recall before taking to air), click and drag the first task icon 1 frame after the first red Jump mark. Stagger each additional icon at least one frame after the previous icon. Be sure to define the desired properties for each icon.

Note When using a server cue icon, always place the icon one frame after the first red jump mark.

11. On the icon toolbox, click and drag an Audio icon to 3 frames after the blue GPI mark. Define the desired properties.
12. On the icon toolbox, click and drag a Notes icon to identify the TME. In the Notes label, assign a name to the TME using established standards and consistent techniques and practices. This name should be the same as the TME name assigned in [Step 3](#). Refer to *Standardization on page 577*.
13. Save the TME. Refer to [Save a TME on page 388](#).

Save a TME


Note In the following step, be sure to right-click in the color area. Right-clicking in the color area selects the entire TME. Hash marks through a TME indicate it is selected. Right-clicking an icon only saves that particular icon.

1. Right-click in the color area of the TME and then click **Export TME**. The **Save** dialog box appears.
2. Navigate to the appropriate C:\(station call letters)\TMEs subfolder for that TME.

Note In the next step it is strongly recommended that the TME name entered is the same name that is on the TME Notes label (refer to [Build a TME on page 386 Step 12](#)). This makes a TME easier to locate. All TME names should be based upon established standards and consistent techniques and practices. Refer to *Standardization on page 577*.

3. In the **Name** box ([Figure 445](#)), type or copy the TME name from the **Notes** label.

Figure 445. TME Name and Save




4. Click **Save**.

Modify/Open a TME

Note In the following step, be sure to right-click in the color area. Right-clicking in the color area selects the entire TME. Hash marks through a TME indicate it is selected. Right-clicking an icon only saves that particular icon.

1. Click the TME.
 - If the TME is on the Event Timeline:
 - Right-click in the color area and go to [Step 2](#).
 - If the TME is not on the Event Timeline:
 - a. Right-click anywhere in an open space on the Ignite/Ignite Konnect Event Timeline and then click **Import TME**. An **Open** dialog box appears.
 - b. Navigate to the C:\(station call letters)\TMEs subfolder ([Figure 446](#)) where the TME to modify is stored.

Figure 446. TME Cameras Subfolder Example



- c. Either:
- Double-click the appropriate TME file
 - Select the TME file and click the **Open** button.
2. Modify the TME.
3. Refer to [Save a TME on page 388](#) to save changes.

Set/Check/Change TME Task Properties

Once a task icon is added to a TME, the properties of that specific task are set/changed via a properties dialog box. Not all tasks have the same properties. Refer to [Table 13](#) for task element type examples.

Table 13. Task Element Type Examples

Button Number	Caret Position	CG Source
Command	Device	DPM Setup
Duration in frames	Message ID	Presets
Program	Set Points	Source
Speed	Start Time	Stop Time

Note To check/verify settings, simply place the cursor over the respective icon to view a pop-up window with the current settings.

1. Within the TME, double-click the task icon. The task properties dialog box appears.

2. Check, set, or change the associated properties as required.
3. Click **OK**, **Save**, **Cancel**, **Done**, or **Close** as appropriate.

Manage TME Associations

The TME Associations are the codes entered when building a rundown in the NRCS. TME Associations are managed in both the Ignite™ Live Production Control System as well as in the Ignite IQ™ Module.

In addition to adding TME Associations, the user can also delete one or multiple TME Associations and print the entire TME Association list as it appears in the **Template Association** dialog box.

Note For all names, abbreviations, colors, and file structures, use established standards and consistent techniques and practices. Refer to *Standardization* on [page 577](#).

Add TME Associations

Note Neither Ignite IQ templates nor TME files require an association unless these files are saved to a location that is different from the default path specified at installation time of the Ignite IQ™ Module.

1. On the Event Timeline window's **Setup** menu, click **TME Association**. The **TME Association** dialog box appears ([Figure 447](#)).

Figure 447. TME Association Dialog Box



Display information for each TME Association includes:


- **Thumbnail** – The graphic associated with the IQ template.

Note Thumbnails automatically appear in the **Thumbnail** column if an IQ template already has an associated thumbnail. However, you cannot assign thumbnails to an IQ template in the **TME Association** dialog box.

- **Name** – name of the TME Association.
- **Path** – location of the TME file.

2. To associate TME column names with the actual TME, click **Add**. The **New Association** dialog box appears (Figure 448).


Figure 448. New Association Dialog Box



Note In the next step, it is strongly recommended that IQ template name entered is the same as the IQ template file name. This makes an IQ template easier to locate. All names should be based upon established standards and consistent techniques and practices. Refer to *Standardization* on page 577.

3. In the **New Association** dialog box, do the following:
 - a. In the **Name** field, either:
 - For an IQ template association, type the name as it appears in the IQ template filename.
 - For TME association, type the name as it appears on the **Notes** label only if this label is static.
 - b. Click the... (**Browse**) button. An **Open** dialog box appears (Figure 449) appears. In the list, find and click the TME file to associate.


Figure 449. TME Open Dialog Box



4. Navigate to the desired TME folder.
5. From within the folder, double-click the TME to associate. The file name populates the **TME Open** dialog box.
6. In the **New Association** dialog box, either:
 - To save the TME Association, click **OK**.

The TME association is complete and is added to the association list in the **TME Association** dialog box (Figure 450).

Figure 450. TME Association Dialog Box – TME Association Added




- To cancel the TME Association, click **Cancel**. The **New Association** dialog box closes.

Edit TME Associations

Note Neither Ignite IQ templates nor TME files require an association unless these files are saved to a location that is different from the default path specified at installation time of the Ignite IQ™ Module.


1. On the **Event Timeline Setup** menu, click **TME Association**. The **TME Association** dialog box appears (Figure 451).

Figure 451. TME Association Dialog Box – TME Association Added



- From the **TME Association** dialog box, click the TME Association to edit (Figure 452).

Figure 452. Edit Selected TME Association



- Click **Edit**. The **Edit Association** dialog box (Figure 453) appears:

Figure 453. Edit Association



4. In the **Edit Association** dialog box, either/and:


a. Edit the **Name** field:

- For an IQ template association, type the name as it appears in the IQ template filename.
- For TME association, type the name as it appears on the **Notes** label only if this label is static.

Note To cancel the TME Association edit, click **Cancel**. The **Edit Association** dialog box closes.

b. Click the... (**Browse**) button. An **Open** dialog box appears (Figure 454) appears.

Figure 454. TME Open Dialog Box




Note To cancel the TME Association, click **Cancel**. The **Open** dialog box closes.

5. To close the **TME Association** dialog box, either:
 - Click the **Close** button.
 - Click the **Close** icon.

Delete TME Associations


1. On the Event Timeline's window **Setup** menu, click **TME Association**. The **TME Association** dialog box appears.
2. Select one or multiple TME Associations for deletion ([Figure 455](#)).

Figure 455. TME Association Dialog Box



3. Click **Delete**. The **Delete TME Association** dialog box appears ([Figure 456](#)):

Figure 456. Delete TME Association Dialog Box



4. Either:
 - To remove the selected TME Associations from the list, click **Yes**.
 - To keep the TME Associations, click **No**.


Ignite-X Playlist

Launch Ignite-X


You can launch the embedded Ignite-X in the Event Timeline Module or the stand-alone Ignite-X in a remote Ignite client.

Embedded Ignite-X

1. On the Event Timeline Module, select **Window | Ignite-X**.
2. The Ignite-X Playlist opens on the Timeline.




3. Click **Tools | Import Rundown**. The imported rundown populates both into the playlist and the timeline.




Stand-alone Ignite-X

1. On the Ignite remote client, go to **Start | Ignite Software | IgniteX**.
2. The Log On dialog opens.



3. Enter the IP address or the Ignite server name.
4. Click the **Log On** button. The Ignite-X Playlist opens.



5. The Ignite-X Playlist displays the same rundown that is currently populated on the Event Timeline.


The vertical playlist allows users to easily collapse and expand segments or stories just by clicking on the user interface. Hence, users can navigate through the show by clicking on any segment, story, or event, including embedded events, modify event properties, and jump instantly to a specific event on the timeline.

The playlist stays in-sync with the Event Timeline, so users can view and control the flow of the show via Ignite-X, even on remote devices.


Change Ignite-X view mode

You can select from three options of view modes available for the Playlist.

- On the embedded Ignite-X, select **Window | Ignite-X View Options**. View mode options appear as below:




- On the stand-alone Ignite-X, just click the view mode icon on the top right of the Ignite-X Playlist, and select from the list below:




No Item Blocks view mode

The **No Item Blocks** option displays stories and events only in the Playlist.




Item Blocks view mode

The **Item Blocks** option displays the list of stories along with a block view of TME icons as loaded on the Event Timeline.




The purpose of the block view is for users to offer a single consolidated user interface that represents the show and all of its stories and events.

In the Ignite-X Item block view, TME icons for different devices are represented by blocks with different colors as shown below:




Labeled Item Blocks

The **Labeled Item Blocks** option allows users to easily view all details of the show in one glance. The option displays the list of stories and labeled block view of TME icons for them.




In the Ignite-X Labeled Item Blocks view, TMEs for Prep, Camera, GPO, Switcher and DMP are represented by labeled individual blocks that span the vertical area. Video, Audio and CG blocks are displayed on 3 tracks that take up 1/3 of the vertical area.



View IQ Template parameters in events

Events in the Ignite-X Playlist display IQ Template parameters such as event description, event markup and event markup expansions.




The event description is displayed in bold on the user interface. Event markup and event markup expansions are displayed below the event description, if they are selected for display in the User Preferences dialog.

Event markup displays parameter names of each event. While event markup expansions display values for each parameter in a drop-down list if they are already configured in the IQ Template Manager.

Modify parameter values of events

You can also modify parameter values of events directly on the Ignite-X Playlist.

1. Click on the thumbnail of an event. Parameter values of the event display in the dialog as below:




2. Click the arrow on each drop-down list to display available values for each parameter.
3. Click to select a value from the list. The border color of the drop-down list changes to green to indicate that a new value has been selected for the parameter.
4. Click **Apply** to commit the change. You can also click **X** on the dialog to cancel the change.


View event details via the Preview Event Inspector

You can view each event in detail using the Preview Event Inspector.

1. Select the next/previous event in the Playlist or double-click an event to pre-execute the event in the Rundown. Event details display in the Preview Event Inspector with a blue bar as shown below:





2. Prep the event in the rundown by executing the timeline. The prepped event displays in the Preview Event Inspector with an orange bar as shown below:





View Ignite-X clip status

You can view the status of clips for each event in the Ignite-X Playlist.

- On the embedded Ignite-X, select **Window | Ignite-X View Options | Clip Status**.






- On the stand-alone Ignite-X, just click the Clip Status  icon on the top right of the Ignite-X Playlist.



After selecting to view the clip status, another column appears to display the clip name, status, duration, and thumbnail.



If the clip is ready to play, the clip thumbnail is shown along with a green indicator on the right side. If the clip is not ready to play, a default not-ready thumbnail is shown along with a red indicator on the right side.

Clip status can be identified as in the table below:

Icon	Description
	Play – The clip is playing.
	Cue – The clip is cued.
	Stop – The clip has stopped playing.

View connection status to the Ignite server

You can view the connection status to the Ignite server on the top right of the Ignite-X Playlist.







Icon	Description
	The Ignite-X Playlist is connected to the Ignite server.
	The Ignite-X Playlist is disconnected from the Ignite server.

Run the show via the Playlist Controller

The Playlist Controller is typically located at the bottom of the Ignite-X application and it allows you to run the show via a remote client. The Playlist Controller is also resizable and dockable. You can resize and dock the Playlist Controller anywhere in the Ignite-X application. As long as your device is connected to the Ignite server, you can run the show by using control buttons on the Playlist Controller.



Control buttons can be identified as in the table below:


Icon	Description
	Play – Click Play button to play an event and run the show on the timeline.
	Go to Next – Click Go to Next button to go to the next event.
	Go to Previous – Click Go to Previous button to go to the previous event.
	Update Rundown – Click Update Rundown button to update the currently loaded rundown on the playlist. The button color turns red when the rundown import has errors and warnings, and it turns orange when the rundown import has warnings only. The button turns green when there are no errors or warnings.
	Preload – Click Preload button to import a preloaded rundown into the playlist. The button turns red when the rundown has errors and warnings. While, it turns orange when only warnings are detected in the preloaded rundown.
	Preload – Click Preload button to import the preloaded rundown again into the playlist after rectifying the problems. The button color turns green when there are no errors or warnings detected in the rundown import.

Change user preferences

You can change the user preferences setting of Ignite-X to filter events displayed in the Playlist.

- On the embedded Ignite-X Playlist, select **Edit | Ignite-X User Preferences**.
- On the stand-alone Ignite-X Playlist, select **Edit | User Preferences**.

The User Preferences window appears.



In the Block View section, you can select any checkbox to filter specific event items from being displayed on the user interface. Only unselected items are displayed in the block view of the Ignite-X Playlist.

In the Event View section, you can select any checkbox to display Event Markup and Event Markup Expansion in the Playlist.

In the General section, you can select the checkbox to display the Progress Bar update on the background each time you import a rundown.

Ignite IQ Module

Overview

The Ignite IQ™ Module is an optional set of features that is purchased in addition to the Ignite™ Live Production Control System. The optional features that comprise the Ignite IQ Module include:

- [Ignite IQ Templates on page 409](#)
- [Ignite IQ Auto Channel Assignment on page 417](#)
- [Common Features: Ignite/Ignite Konnect System and Ignite IQ Module on page 420](#)

The feature set in the Ignite IQ Module adds automation to the Ignite/Ignite Konnect system and assists in entering production data, managing resources, and identifying resource conflict.

Ignite IQ Templates

Through the [Ignite IQ Template Manager](#) application, a new type of TME (refer to TME™ (Transition Macro Event™) [on page 38](#)) is created, which is known as an Ignite IQ Template. IQ templates provide flexibility to adapt to future changes in newsroom equipment and talent.

The following items comprise an IQ template ([Figure 457 on page 410](#)):

- IQ Template Names
- Parameter Names
- Parameter Name Values
- TME Device Data Values

Note For Ignite IQ template name abbreviations, parameter name abbreviations, and suggested parameter name values, use established standards and consistent techniques and practices. Refer to [Standardization on page 577](#).

Typically, an IQ template contains multiple parameter names where each parameter name is assigned a set of parameter name values. Each param-


eter name value is then assigned its own set of values, TME device data values. Refer to [Create an Ignite IQ Template on page 422](#) for the steps on how to add and remove these names and values to and from an IQ template.

The example of the Camera Template (Figure 457) shows the association between the template name, **CAM**, and all components that comprise this template. The sequence of components to enter for a TME in either the NRCS or the Rundown Markup dialog box is:

- **IQ Template Name.ParameterNameParameterNameValue.
ParameterName.ParameterNameValue.ParameterName.ParameterNameValue...**

Note A period separates the IQ template name from each parameter name and parameter name value group. Each TME can have multiple parameter name and parameter name value groups and each group can be entered in any order.

Figure 457. Example of an Ignite IQ Camera Template




At the bottom of (Figure 457) the example TME, **CAM.C1.EC.M1.P1**, means that the **CAM** template contains this specific TME when imported into the rundown, where **CAM**:

- **C1** – uses Camera 1
- **EC** – contains an Effect that is a Cut
- **M1** – uses Microphone 1
- **P1** – uses Camera Preset 1

Ignite IQ Template Manager

The Ignite IQ Template Manager is a standalone application that runs separately from the Ignite/Ignite Konnect system. To access the template manager, either:


- In Windows, On the **Start** menu, click **Programs > Ignite Software > IQ Template Manager**.
- Double-click the desktop shortcut – **IQT** .

Ignite IQ Template Manager – Initial Window

Note For Ignite Konnect IQ Template Manager information refer to [IQ Template Manager Dialog Box](#) on page 622.

The initial window (Figure 458) of the Ignite IQ Template Manager GUI appears:

Figure 458. Ignite IQ Template Manager GUI– Initial Window



In the initial window, either:


- To open an existing TME or IQ template file, click **Open...**
- To open a recently used file, click the file under **Open Recent**.

Note The last five files that were previously opened are listed under **Open Recent**.

Ignite IQ Template Manager – Main Window

After opening an existing TME file or recently used file, the main window (Figure 459) of the Ignite IQ Template Manager GUI appears:

Figure 459. Ignite IQ Template Manager – Main Window




The **Ignite IQ Template Manager – Main Window** is the interface used to manage TME and IQ template information. The window, from top to bottom, comprises the following main areas:

- **Template Summary** (Refer to [Template Summary](#) on page 414)
- **Template Tables** (Refer to [Template Tables](#) on page 415)
- **Close button** – closes the window without saving changes.

Menu Bar

The Ignite IQ Template Manager ([Figure 460](#)) menu bar is located below the title bar at the top of the Ignite IQ Template Manager module. Each menu item displays a list of available commands.

Figure 460. Ignite IQ Template Manager Menus




Open Menu

The **Open** ([Figure 461](#)) menu commands are:

Open Menu Command	Purpose
Open	To open an existing TME or IQ template file.
Open Recent	To open one of the last five previously opened files, either TME files (.tmx) or IQ template files (.iqt).

Figure 461. Ignite IQ Template Manager Open Menu




Save Menu

The **Save** ([Figure 462](#)) menu commands are:

Save Menu Command	Purpose
Save	To save the currently opened TME file, including any changes made, such as a template. For detailed information, refer to Create an Ignite IQ Template on page 422 .
Save As	To save the currently opened TME file, including any changes made, as an IQ template file.

Figure 462. Ignite IQ Template Manager Save Menu




Template Summary

The **Template Summary** area (Figure 463) contains descriptive information about the template, lists the devices used in the TME, and lists the device data associated with each device in the TME. Sections in the **Template Summary** area include:

- [Thumbnail and Description on page 414](#)
- [Icons in this TME on page 414](#)
- [TME Device Data on page 415](#)

Figure 463. Ignite IQ Template Manager – Template Summary



Thumbnail and Description

Area that enables a user to assign a thumbnail graphic and description to a template. Parameters include:

- **Thumbnail display** – displays the selected thumbnail.
- **Thumbnail select** – enables a user to select one of several default thumbnails (Figure 464) or a customer provided image.
- **Description text box** – text that describes the template.

Figure 464. Default Thumbnail Selections



Icons in this TME

Area that displays information about each device item in a TME. Parameters and display information include:

- **Name** – name of the TME icon.

Note For all TME device names and abbreviations, use established standards and consistent techniques and practices. Refer to *Standardization* on page 577.

- **Time** – position of the TME in the Event Timeline Module in **hh:mm:ss:ff** format. Change the time as necessary and then press **Enter**. Time is reflected in the following places:
 - Icons in the Event Timeline module. This is only reflected when a user imports the IQT after it has been saved with the update time info.
 - Icons in an IQ Template file (.iqt)

The following parameters consist of read-only information, obtained during TME import:

- **Device** – displays the device type used in the TME.
- **Command** – displays the TME function.
- **Tool tip** – provides additional information about the device used in the TME.

TME Device Data

When a TME element is selected under **Icons in this TME**, then the corresponding device data for that TME appears under **TME Device Data**.

For example, when the **Camera** icon is selected (Figure 463), then the Camera and Preset information appears under **TME Device Data**.


Template Tables

The **Template Tables** area enables a user to create, edit, and maintain the following items within a TME (Figure 465):

- [Parameter Names and Parameter Name Values on page 416](#)
- [TME Device Data Values on page 416](#)

Note Parameter names, parameter name values, and TME device data items and values are required to create an IQ template. Without completing this information, a template does not exist, only the original, base TME.

Figure 465. Ignite IQ Template Manager – Parameter Name Information



Parameter Names and Parameter Name Values

- **Name** – the name of the parameter.

Note As a best practice, it is recommended that parameter names are letters, one character in length. For IQ parameter names, use established standards, recommended abbreviations, and consistent techniques and practices. Refer to [Standardization on page 577](#).

- **Default Value** – The parameter name value(s) and default value assigned to the parameter name.

Note When parameters contain more than one value, only one value is the default value for each parameter. It is recommended that you save the first value as the default value. For example, parameter **C** has the default value of **1**. It is also recommended that the Default value should be the one most commonly used.

- **Add/Del** – one set of Add/Del buttons adds and deletes parameter names. The other set of buttons adds and deletes parameter name values. Refer to [Figure 465](#).


Note For more information on deleting parameter names and parameter name values and the overall the deletion hierarchy, refer to [Delete Parameter Name, Name Value, or TME Device Data Value on page 433](#).

TME Device Data Values

- **TME Device Data Items** – device data items that pertain to a specific TME.

Note TME device data items are added by dragging the selected item down from the **TME Device Data** area to the TME device data values area. Device data items receive their names from the combination between the TME name and the selected TME device data (Figure 466 on page 417).

Figure 466. Adding TME Device Data Items



- **TME Device Data Values** – values assigned to the TME device data item as well as the parameter name value. Refer to Figure 465 on page 416.
- **Parameter Name List** – drop-down list of all parameter names that comprise an IQ template Refer to Figure 465 on page 416.
- **Parameter Description** –

Ignite IQ Auto Channel Assignment

Note For Ignite Konnect IQ Auto Channel information refer to [IQ Auto Channel Pool Dialog Box](#) on page 619.

The Ignite IQ Auto Channel Assignment feature enables the user to create auto channel pools and assign the channels to designated pools. Auto channel assignment is accessed via the Event Timeline Module in the Ignite system. From the Event Timeline Module, on the **Setup** menu (Figure 467)

click **IQ Auto Channel Pool**. The **IQ Auto Channel Pool** dialog box (Figure 468) appears:

Figure 467. Event Timeline Setup Menu Example





Figure 468. IQ Auto Channel Pool Dialog Box – M/E Tab



The **IQ Auto Channel Pool** dialog box contains two tabs:

- **M/E**
- **Video Channels**

M/E Tab

Parameters, functional areas, and control functions on the **M/E** tab (Figure 468) comprise:

- **Available Channels** – a list of M/E channels that are not assigned to a channel pool.
- **Channel Pool** – a list of channels that are currently assigned in the channel pool.
- **Assign Channel** or **Right Arrow** icon – moves and assigns available channels to a designated channel pool. The channels no longer appear in the **Available Channels** list.
- **Remove Channel** or **Left Arrow** icon – moves the designated channels pools back as available channels. The channels no longer appear under the **Channel Pool** list.
- **Save** – saves changes made to the Auto M/E pool.
- **Cancel** – cancels changes made to the Auto M/E pool and closes the **IQ Auto Channel Pool** dialog box.

Video Channels Tab


Click the **Video Channels** tab (Figure 469) on the **IQ Auto Channel Pool** dialog box. All parameters, functional areas, and control functions for the **Video Channels** tab appear:

- **Video Channel Pools list** – drop-down list that displays names of the video channel pools.
- **Create New Pool** button – opens the **New Channel** dialog box to create a new video channel.
- **Available Channels** – a list of video channels that are not assigned to a channel pool.
- **Channel Pool** – a list of channels that are currently assigned to a channel pool.
- **Assign Channel** or **Right Arrow** icon – moves and assigns available channels to a designated channel pool. The channels no longer appear in the **Available Channels** list.
- **Remove Channel** or **Left Arrow** icon – moves the designated channels pools back as available channels. The channels no longer appear under the **Channel Pool** list.
- **Save All** – save changes made to all channel pools.
- **Delete** – deletes the currently selected pool and removes it from either list: **Available Channels** or **Channel Pool** list.

Note The channels associated with the deleted channel pool are moved back and made available under the **Available Channels** area.

- **Cancel** – cancels changes made to the video channel pools and closes the **IQ Auto Channel Pool** dialog box.

Figure 469. IQ Auto Channel Pool Dialog Box – Video Channels Tab



Common Features: Ignite/Ignite Konnect System and Ignite IQ Module

Common or shared features exist between the Ignite/Ignite Konnect system and the Ignite IQ Module. Shared features include:

- **TME Associations** – For more information on the TME Associations feature and how to manage TME Associations, refer to *Manage TME Associations* on page 57.
- **Import Rundowns** – For more information on the Import Rundowns feature and how to import a rundown, refer to *Importing a Rundown* on page 423.

- **Linked Fields Table** – This table is a key component of the Auto Assign function. A user must define the values selected in the Auto ME and VS pools. If this table is not completed then the auto assign functionality does not work.

After configuring and saving a linked fields table, unless a device is added or removed in an auto channel pool, it only needs done once in IQTM but it must be done when saving an IQT to hold a global setting.

For more information in defining the Linked Fields Table, refer to [Configure Linked Fields on page 434](#).

Operation

Ignite IQ Template Manager

Prerequisites for Creating Ignite IQ Templates

The following is a list of useful guidelines to assist in the design of your IQ template before template creation begins:

- Follow the recommended steps to create a TME in the Event Timeline module. Refer to *Event Timeline Control* [on page 32](#) for more information on building and saving a TME.

Note All IQ templates are based on an existing TME file that has a file extension of **.tmx**. You cannot create an IQ template without first creating a TME.

- In the TME file, verify that all required icons are in the TME and that these icons are fully populated with the correct properties.
- Define all channel pools: Auto M/E channel pools and video channel pools. Refer to the operations for *Ignite IQ Auto Channel Assignment* [on page 445](#).
- Properly configure the Linked Fields Table in the **Ignite IQ Template Manager** dialog box. Refer to [Configure Linked Fields on page 434](#).
- Define a list of static values associated with each commonly used TME in your current TME library.

Create an Ignite IQ Template

The general procedures to create and maintain an Ignite IQ Template, using the Ignite IQ Template Manager, include the following:

- [Import an Existing TME File on page 422](#)
- [Add a Thumbnail and a Description on page 424](#)
- [Add/Rename Parameter Name and Parameter Name Values on page 426](#)
- [Add TME Device Data Values to Parameter Name Values on page 429](#)
- [Delete Parameter Name, Name Value, or TME Device Data Value on page 433](#)
- [Configure Linked Fields on page 434](#)
- [Save TME File as an IQ Template on page 435](#)

Note The following procedures are based on a simulated camera TME file named **CAM.tmx**.


Import an Existing TME File

Note The Ignite IQ Template Manager GUI can only open TMEs that have a file extension of either **.tmx** or **.iqt**.

Note This procedure is based on a simulated camera TME file named **CAM.tmx**.

1. To access the **Ignite IQ Template Manager** GUI, either:
 - Click **Start > Programs > Ignite Software > IQ Template Manager**.
 - Click the desktop shortcut: **IQ Template Manager**. The initial window of the **Ignite IQ Template Manager** dialog box ([Figure 470](#)) appears.


Figure 470. Ignite IQ Template Manager Dialog Box– Initial Window



2. Either:

- Click **Open...** The **Open** dialog box appears. Browse to the TME file and click **Open**. The main window of the Ignite IQ Template Manager GUI (Figure 472) appears.


Figure 471. Open TME or IQ Template Dialog Box



- Click **Open Recent** and then click the desired TME file. The main window of the Ignite IQ Template Manager GUI (Figure 472) appears.

Note The information associated with the TME file now appears in the **Icons in this TME** and **TME Device Data** areas of the initial window.

Figure 472. Ignite IQ Template Manager – Main Window



864x-sc89-r1


Add a Thumbnail and a Description

There are seven default thumbnails images. Adding a description to an IQ template is optional. The selected thumbnail image and description are displayed in the Active X plug-in within the NRCS as well as the **TME Association** dialog box, which makes the template easier to recognize. Refer to *Manage TME Associations* on page 57.

Note If no thumbnail has been added previously, the default icon is the first of the seven icons available in the selection.


1. In the **Thumbnail and Description** area, click the existing icon. The default icon selections appear at the right (Figure 473).

Figure 473. Add a Thumbnail



2. Either
 - Select an image from the default icons.
 - Select a customer provided image
3. In the **Thumbnail and Description** area, click in the description field (Figure 474) and type a description.

Figure 474. Add a Description



Description Field

Add/Rename Parameter Name and Parameter Name Values

Parameter names and parameter name values are required to create an IQ template. In the camera template example, to create the template, based on the imported camera TME file, the following parameter names are required:

- C (Camera)
- E (Switcher and DPM Effects)
- G (Graphics)
- M (Microphones)
- P (Camera Presets)


Note For example purposes, only the steps on how to add the parameter name C to the camera template are outlined.

Note As a best practice, it is recommended that parameter names are letters, one character in length. For IQ parameter names, use established standards and consistent techniques and practices. Refer to *Standardization* on page 577.

Note This procedure is based on a simulated camera TME file named **CAM.tmx**.

1. To add parameter names, under the **Template Tables** area, click **Add** (Figure 475). The default parameter name, **P1**, appears in the parameter name and in the area where the TME device data values will be populated. (Figure 475).

Figure 475. Adding Parameter Names




2. To change the parameter name from the default value of **P1** to **C**, do the following:

- a. In the **Name** column, click the parameter and type the new parameter name, **C**.
- b. Press **Enter**.

C appears as the parameter name. The parameter name is automatically renamed in the TME device data area and the parameter drop-down list to match the parameter name, **C** (Figure 476).


Figure 476. Renaming Parameter Names



3. To add parameter name values to parameter name, **C**, click **Add**. A value of **NewValue1** appears (Figure 477).

Note As a best practice, it is recommended that the parameter name values are one character in length. Parameter value names should not exceed four characters and cannot exceed eight characters. For IQ parameter name values, use established standards and consistent techniques and practices. Refer to *Standardization* on page 577.

Figure 477. Adding Parameter Name Values to Parameter C



4. To rename the default value of the parameter name value, do the following:
 - a. In the **Default Value** column, click the value.
 - b. Right-click and click **Rename**.
 - c. Type a new value and press **Enter**.


For the camera example, add two values: **1** and **2**. The two values represent the number of cameras in the Camera IQ Template.

Note In the **Default Value** column, when parameters contain more than one value, only one value is the default value for each parameter. It is recommended that you save the first value as the default value. For example, parameter **C** has the default value of **1**. It is also recommended that the Default value should be the one most commonly used.

Once the parameter name values, 1 and 2, are added to parameter name, C, note that the system automatically creates two row entries for the parameter name values in the TME device data area (Figure 478).

Each parameter name value, 1 and 2, requires an assigned value. Refer to *Add TME Device Data Values to Parameter Name Values*.

Figure 478. Renaming Parameter Name Values




Add TME Device Data Values to Parameter Name Values

Note This procedure is based on a simulated camera TME file named **CAM.tmx**.

1. Under **Template Summary**, in the **Icons in this TME** area, click the Camera icon. The information associated with the Camera icon appears under the TME Device Data area (Figure 479).


Note In the **Name** field, the default names are **Item1**, **Item2**, etc. To rename the icons, select the text and type a new name that coincides with each TME icon.

Figure 479. Camera TME Device Data



2. Drag the Camera data from the TME Device Data to column **C**. The default name of the column is **Item2.Camera** (Figure 480)


Figure 480. Adding Camera TME Device Data



Note Item2 is the name of the Camera TME icon and Camera is the name of the selected TME device data. The name of the item now appears as **Item2.Camera**.

3. To select a value, click the drop-down arrow, and click an item value for each parameter name value (Figure 481):
 - The logical TME device data value to select for the parameter name and parameter name value group, **C1**, is **CAM1**.
 - The logical TME device data value to select for the parameter name and parameter name value group, **C2**, is **CAM2**.


Figure 481. Adding Values to Camera TME Device Data



Note It is common for the same parameter to have device data that comes from more than one device item and TME icons. In the next step, the Switcher PVW device data is added as an item value.


4. Under **Template Summary**, in the **Icons in this TME** area, click the Switcher icon. The information associated with the Switcher icon appears under the **TME Device Data** area (Figure 482).

Figure 482. Switcher TME Device Data



5. Drag the PVW item next to **Item2.Camera**. The name of the PVW item now appears as **Item6.PVW** (Figure 483)


Figure 483. Adding Switcher TME Device Data



Note Item6 is the name of the Switcher TME icon and PVW is the name of the selected TME device data.

6. To select a value for **Item6.PVW**, click the drop-down arrow, and click an item value for each parameter name value. Refer to [Figure 484](#).
- The logical TME device data value to select for the parameter name and parameter name value group, **C1**, is **CAM1**.
 - The logical TME device data value to select for the parameter name and parameter name value group, **C2**, is **CAM2**.

Figure 484. Adding Values to Switcher TME Device Data



Delete Parameter Name, Name Value, or TME Device Data Value

Parameter names, parameter name values, and TME device data values are deleted in the **Template Tables** area (Figure 485) of the **Ignite IQ Template Manager** dialog box.


Note This procedure is based on a simulated camera TME file named **CAM.tmx**.

To delete a parameter name

- a. Click next to the parameter name for deletion. The entire parameter name appears in blue.

Note Only one parameter name can be deleted at a time.


Figure 485. Parameter Name Selected



CAUTION In the next step, once a parameter name is deleted, all associated parameter name values and TME device data are also deleted.

- b. Click **Del** (Figure 485) located at the bottom right-hand corner of the parameter name area. The **Delete Confirmation** dialog box appears (Figure 486).

Figure 486. Parameter Name Delete Confirmation Dialog Box



c. Either:

- Click **Yes** to delete the parameter name, all associated parameter name values, and the TME device data values.
- Click **No** to cancel the action.


To delete a parameter name value associated with a parameter name:

a. Under the **Default Value** column, click the drop-down arrow, and click the parameter name value for deletion.

CAUTION In the next step, once a parameter name value is deleted, all associated TME device data values are also removed from the parameter name value.

b. Click **Del** (Figure 485) located next to the parameter name value. The **Delete Confirmation** dialog box appears (Figure 487):

Figure 487. Parameter Name Value Delete Confirmation Box



c. Either:

- Click **Yes** to delete the parameter name value and the associated TME device data.
- Click **No** to cancel the action.

To delete TME device data values associated with a parameter name value

a. Click the appropriate parameter name.

CAUTION The selected TME device data values for all parameter name values for the specified parameter name are deleted.

b. In the TME device data area, right-click the item value at the top of the column, and click **Delete**.

Configure Linked Fields

Note To hold a global setting, this procedure must be done once when saving an IQT.

The following procedure is an example only. The exact procedure depends on the specific IQT. This particular example is based on the Auto ME

having two MEs in the pool and AutoVS having three server channels selected.

1. Access the link fields table via the middle drop down tab in IQTM. A warning message appears stating that any changes made affect existing IQTs. Click **OK**.
2. At the bottom right hand corner of the IQTM, click **Add**.

Note In the following step, to determine the number of rows necessary, add the number of sources in the auto pools. In this example that is five—two for the MEs and three for the servers.

3. Enter the number of rows necessary. The resulting table contains the following information:

Channel	Kayak	Audio
ME1	ME1	(blank)
ME2	ME2	(blank)
VS1	VS1	VS1
VS2	VS2	VS2
VA3	VA3	VA3

4. Save the IQT.

Save TME File as an IQ Template

Note This procedure is based on a simulated camera TME file named **CAM.tmx**.

1. On the **Save** menu, click **Save as** to save the camera TME file as a camera template file.
2. In the **Save as** dialog box, do the following:
 - a. In the **Save in:** field, click the drop-down arrow and browse to a location to save the camera template file.
 - b. In the **File name:** field, type a name for the camera template file, such as **CAM**.

Note All IQ template files in your library should contain a consistent number of characters. As a best practice, it is recommended that IQ template files contain three characters. For IQ template name abbreviations, use established standards and consistent techniques and practices. Refer to *Standardization* on page 577.

- c. In the **Save as type:** field, click the drop-down arrow and click **.iqt**.
3. Either:
 - Click **Save** to save the file as a template to the desired location

- Click **Cancel**, to cancel the changes to the existing TME file

Import a Parameter Name From An Existing IQ Template

Import parameter names from an existing IQ template into either:


- An IQ Template file
- A TME (.tmx) file

Note The Ignite IQ Template Manager GUI only accepts and is only compatible with TME files that have a file extension of .tmx or .igt.

1. To access the **Ignite IQ Template Manager** GUI, either:

- Click **Start > Programs > Ignite Software > IQ Template Manager**.
 - Click the desktop shortcut: **IQ Template Manager**.
- The initial window of the **Ignite IQ Template Manager** GUI appears (Figure 488).

Figure 488. Ignite IQ Template Manager GUI– Initial Window:




2. Under **IQ Template Manager**, click **Open...** The **Open** dialog box appears (Figure 489 on page 437).

Figure 489. Open TME or IQ Template Dialog Box



3. Browse to the TME file and click **Open**. The main window of the Ignite IQ Template Manager GUI (Figure 490 on page 437) appears.

Figure 490. Ignite IQ Template Manager – Main Window




4. Under **Open Recent**, click the desired TME file. The main window of the Ignite IQ Template Manager GUI (Figure 490 on page 437) appears.

Note The information associated with the TME file now appears in the **Icons in this TME** and **TME Device Data** areas of the initial window.

Import a Parameter Name


1. On the **Open** menu, click **Import Table**. The **Import Table** dialog box appears (Figure 491 on page 438).

Figure 491. Import Table Dialog Box



2. Browse to the existing Ignite IQ template file (.iqt file) and click **Open**. The **Import Table(s)** dialog box appears (Figure 492).


Figure 492. Import Table(s) Dialog Box



Note This dialog box lists the available parameter tables to import, associated with the existing Ignite IQ template.

3. Click the available parameter table to import and either:
 - a. Click **Change Template**. The **Import Table** dialog box re-appears (Figure 493).

Figure 493. Import Table Dialog Box



b. Either:

- Browse to a different Ignite IQ template file (.iqt file) and click **Open**. All the selected tables are imported into the new template unless there is a duplicate name. If a duplicate name exists, it must be renamed or that table will not import.

Note If the **Import Table(s) Change Template** button is clicked but a selection has not been made, no tables are imported into the previous IQT.


- Click **Cancel**. The **Import Table** dialog box closes and you are returned to the **Import Table(s)** dialog box.

c. Click **Import**. An import additional tables dialog box appears.

d. Either:

- Click **Yes** to select another table. The **Import Table** dialog box (Figure 494) re-appears and allows you to import additional parameters from a different IQ Template file.
- Click **No** to close the dialog box and have the selected tables appear in the IQ Template Manager.

Figure 494. Import Table Dialog Box




e. Either:

- Repeat steps Step 2 and Step 3 as many times as necessary.

Note There is no limit on the number of IQ Template files from which to import parameter names.

- Click **Cancel**. The **Import Table** dialog box closes and you are returned to the **Import Table(s)** dialog box (Figure 495).


Figure 495. Import Table(s) Dialog Box



- Once finished selecting parameter names from different IQ Template files, click **Import**.

The **Import more table(s)** confirmation dialog box (Figure 496) appears.


Figure 496. Import More Table(s) Confirmation Dialog Box



- Either:
 - Click **Yes** to import additional parameter names from different IQ Template files. (Repeat steps Step 2 and Step 3 as necessary.)

The **Import Table(s)** dialog box lists the number of parameter names for import (Figure 497 on page 442).


Figure 497. Import Table(s) Dialog Box – Listed Parameter Names



- Click **No**. Parameter names from the previous IQ Template file(s) are imported in to the **IQ Template Manager** GUI (Figure 498).

Note An asterisk next to the parameter names indicates that they are imported from an IQ Template file.

Figure 498. Imported Parameter Names



- Optionally rename the imported parameter names.

Note As a best practice, it is recommended that the parameter name values are one character in length. Parameter value names should not exceed four characters and cannot exceed eight characters. For IQ parameter name values, use established standards and consistent techniques and practices. Refer to [Standardization on page 577](#).

- f. Click **Cancel**.

The **Import Table(s)** dialog box closes and you are returned to the IQ Template Manager main window.

Rename Parameter Name at Import

The **Parameter name conflict** warning dialog box (Figure 499) appears when any of the selected parameter names for import have the same names as the ones in the existing file. The IQ Template Manager does not accept identical parameter names.

Figure 499. Parameter Name Conflict Warning Dialog Box



1. When this warning dialog box appears, either:
 - Click **Yes** to rename the parameter. The **Rename Table** dialog box appears (Figure 500). Go to [Step 2](#).
 - Click **No** to close the **Parameter name conflict** dialog box and return to the **Import Table(s)** dialog box.

Figure 500. Rename Table Dialog Box



Note At this point, you are unable to select parameter names until the parameter name in conflict is renamed.

2. Either:
 - In the **New Name Box** (Figure 501), type a new name for the parameter. In this example, the parameter name is changed from E to Y.
 - Click **Cancel** to close the **Rename Table** dialog box and return to the **Import Table(s)** dialog box.

Note When **Cancel** is clicked, that table is no longer available for import. To import the table refer to [Import a Parameter Name on page 438](#).

Figure 501. New Parameter Name



Note As a best practice, it is recommended that parameter name values be one character in length. Parameter value names should not exceed four characters and cannot exceed eight characters. For IQ parameter name values, use established standards and consistent naming techniques and practices. Refer to *Standardization* on page 577.

3. Either:

- Click **OK**. The new parameter name now appears on the **Import Table(s)** dialog box (Figure 502).
- Click **Cancel** to close the **Rename Table** dialog box without renaming and return to the **Import Table(s)** dialog box.

Figure 502. New Parameter Name on Import Table(s) Dialog Box




Save Imported Parameter Name

Before you can save the imported parameter names, you need to first assign the appropriate TME device data information.

1. Click the **Select** drop-down list box and select the icon to associate with the TME device data (Figure 503).

Figure 503. Select Icons for TME Device Data



2. Click the drop-down list box to select values for the TME icons.

Note To add additional values, first associate the device data and save the IQT (Step 3). Then refer to [Import a Parameter Name on page 438](#).

3. On the **Save** menu, either:

- Click **Save**. The imported parameter names are saved to the IQ Template file.

Note If the file currently in IQTM is a TMX, **Save** will not save as an IQT without first naming the file in the file save dialog box. If it is an IQT, then **Save** uses the same name as the IQTM.

- Click **Save As** to save the IQ Template file under a different name.

Note All IQ template files in your library must contain a consistent number of characters. As a best practice, it is recommended that IQ template files contain three characters. For IQ template name abbreviations, use established standards and consistent techniques and practices. Refer to [Standardization on page 577](#).

Ignite IQ Auto Channel Assignment

Assign Available Channels to an M/E Pool

1. On the **Event Timeline Setup** menu ([Figure 504](#)), click **IQ Auto Channel Pool**. The **IQ Auto Channel Pool** dialog box appears ([Figure 505 on page 446](#)). Click the **M/E** tab.

Figure 504. Event Timeline Setup Menu






Figure 505. IQ Auto Channel Pool Dialog Box



2. Under the **Available Channels** column, select one or more channels, and click the **right-arrow** button.

The selected channels now appear under the **Channel Pool** column and comprise a designated channel pool (Figure 506).

Figure 506. Auto Channels Assigned to a Pool



3. Conversely, under the **Channel Pool** column, select one or more pools, and click the **left-arrow** button.

The selected pools now appear under the **Available Channels** column.

4. Either:
 - Click **OK** to save the M/E channel pool, click **Save** and then,
 - Click **Cancel** to close the **IQ Auto Channel Pool** dialog box without saving the changes.

Create a Video Channel Pool

1. On the **Event Timeline Setup** menu (Figure 507), click **IQ Auto Channel Pool**. The **IQ Auto Channel Pool** dialog box appears (Figure 508).

Figure 507. Event Timeline Setup Menu






Figure 508. IQ Auto Channel Pool Dialog Box




2. Click the **Video Channels** tab. Information about the video channels appears (Figure 509):

Figure 509. IQ Auto Channel Pool – Video Channels Tab



3. Click **Create New Pool**. The **Create New Pool** dialog box appears (Figure 510).

Figure 510. Create New Pool Dialog Box



4. In the **Name** field, type the name of the video channel pool.

Note For video channel pools, it is recommended to begin the name of the pool with “AUTO” followed by the abbreviation name of the device. For suggested abbreviations on device names, refer to *Standardization on page 577*.

5. Either:
 - Click **OK** to save and add the new video channel pool to the drop-down list. All available channels associated with the video channel pool appear under the **Available Channels** column.
 - Click **Cancel** to cancel the video channel pool.

Assign Available Channels to a Video Channel Pool

Note A channel assigned to a pool cannot be used in multiple pools. A channel can be re-assigned to another pool.

1. On the **Event Timeline Setup** menu (Figure 511), click **IQ Auto Channel Pool**. The **IQ Auto Channel Pool** dialog box appears (Figure 512).

Figure 511. Event Timeline Setup Menu






Figure 512. IQ Auto Channel Pool Dialog Box



2. Click the **Video Channels** tab. Information about the video channels appears ([Figure 513](#)):


Figure 513. IQ Auto Channel Pool – Video Channels Tab



3. From the **Video Channel Pool** drop-down list box, click the down arrow and then click the desired pool.


All available channels associated with the video channel pool appear under the **Available Channels** column ([Figure 514](#)).

Figure 514. Available Channels for a Video Channel Pool




4. Under the **Available Channels** column, do the following:
 - a. Select one or more channels, and click the **right-arrow** button.The channels appear under the **Channel Pool** column and are now assigned to the selected video channel pool (Figure 515).

Figure 515. Channels Assigned to a Video Channel Pool



- b. Under the **Channel Pool** column, to assign a device as the first auto channel, click the box next to the device. The selected box appears in blue (Figure 515).
 5. Conversely, under the **Channel Pool** column, select one or more channels and click the **left-arrow** button. The channels now appear under the **Available Channels** column.
 6. To save the channels to the selected video channel pool, click **Save** and then click **OK**.
- Note** The channels associated with the video pool also appear in each server element under the **TME Device Data** column in the **Ignite IQ Template Manager** dialog box.
7. To remove the video channel pool from the drop-down list, click the desired video channel and then click **Delete**. The **Delete Confirmation** dialog box appears (Figure 516).

Figure 516. Video Channel Pool – Delete Dialog Box




Either:

- Click **Yes** to remove the video channel pool from the drop-down list. The channels associated with the video channel pool are returned to the **Available Channels** column.
- Click **No** to keep the video channel pool in the drop-down list.
- Click **Cancel** to close the dialog box without saving any changes.

LBN (Late Breaking News) Module

Figure 517. LBN (Late Breaking News) Module



Overview

The **LBN** (Late Breaking News) Module ([Figure 517](#)) is a quick way to insert a stored element onto the Event Timeline during a show. There are a total of 308 hotkeys—7 pages with 44 hotkeys each. TMEs or sequences of multiple TMEs can be stored on a single LBN hotkey. LBNs are set up quickly, so selected events or tasks can be easily added to the buttons anytime during an On Air show. LBNs save with the current show/user macro.

Note The selected show/user (macro) file starts the Event Timeline module with the presets/prebuilds specific to that show or user. Therefore, all changes/additions/deletions, customization, hotkeys, etc. are specific to that show/user interface.

Operation


Note LBNs save with the current show/user macro.

Create an LBN Hotkey

Note For all names, abbreviations, colors, and file structures, use established standards and consistent techniques and practices. Refer to *Standardization* on [page 577](#).

1. Click and drag any TME group from the Event Timeline down to an available LBN hotkey ([Figure 518](#)). Make sure to click and drag from inside the color group so that the complete TME is included on the LBN hotkey.

Figure 518. Timeline TMEs/LBN Hotkeys



2. The **LBN Properties Dialog** box ([Figure 519](#)) appears.

Figure 519. LBN Properties Dialog Boxes



Note In the next step, the TME Notes label is automatically entered in the Description. It is strongly recommended that the LBN name retain the same name that is on the TME Notes label. All names should be based upon established standards and consistent techniques and practices. Refer to *Standardization on page 577*. By default the LBN is given a name based on the TME name from its' Notes label.

3. In the **Description** box, verify the name from the **Notes** label or type a new name.

Note In the following step, the LBN hotkey color selected should match the related TME color used. All colors used should be based upon established standards and consistent techniques and practices. Refer to *Standardization on page 577*.

4. In the **LBN Properties Dialog** box (Figure 519), click a color for the LBN label.

Note The Setup button, when clicked, also enables editing for LBN color and Description (name).

5. Click **OK**.

6. On the **File** menu click either **Save** or **Save As...**

Note LBNs save with the current show/user macro.

Modify an LBN Hotkey

LBN hotkeys can be edited to change color, text, and text color. For function, LBN hotkeys are replaced/over written rather than deleted.

1. ON the LBN module, click the **Setup** button.
2. Click the LBN to modify. The **LBN Properties Dialog** box ([Figure 520](#)) appears.

Figure 520. LBN Properties Dialog Box



Note In the following step, the LBN hotkey Description and color selected should match the related TME. All colors used should be based upon established standards and consistent techniques and practices. Refer to *Standardization on page 577*.

To Change the Color:

- a. In the **LBN Properties Dialog** box ([Figure 519](#)), click a color for the LBN label.

Note The Setup button, when clicked, also enables editing for LBN color and Description (name).

- b. Click **OK**.
- c. On the **File** menu click either **Save** or **Save As...**

Note LBNs save with the current show/user macro.

To Change the Description:

- a. In the **LBN Properties Dialog** box ([Figure 519](#)), type a new **Description** (name).

Note The Setup button, when clicked, also enables editing for LBN color and Description (name).

- b. Click **OK**.
- c. On the **File** menu click either **Save** or **Save As...**

Note LBNs save with the current show/user macro.

Add an LBN to the Event Timeline


Either:

- Click the desired LBN to place it right of the current Event Timeline cursor location.
- Right-click and drag the desired LBN to any position on the Event Timeline.

Show Builder Assistant Module

Overview


Figure 521. Show Builder Assistant



The Ignite Show Builder Assistant (Figure 521) is an NCS add-in for either iNEWS or ENPS (Figure 522). Using this add-in, Ignite users can either:

- Type TME/IQT names into a TME/IQT Production field.
- Select a TME/IQT from a list (with icons representing the production event) and drag & drop the production event into the NCS (Newsroom Computer System) script to be included in the MOS data sent to Ignite.

Figure 522. Show Builder Assistant – iNEWS and ENPS Add-in



The Ignite Show Builder Assistant is a second method for adding production MOS commands to the rundown. Using this add-in makes it easier for new or less experienced Ignite users to build automated shows. Instead of typing TME codes in a rundown column, Show Builder enables users to:

- Select templated production events
- Modify variable fields from a list of selectable items for that field
- Validate accuracy of the production data
- Copy/paste bar in the **ShowBuilder Assistant** that allows for quick coding via the TME column from **ShowBuilder Assistant**.
- Drag & drop the production event into the NCS script.

When using the Ignite Show Builder Assistant add-in, both the traditional quick-text input commands and the Show Builder Assistant can be used to create a show, providing complete flexibility and ease of use for both experienced and newer users.

Using the Ignite Show Builder Assistant add-in also removes the requirement for the user to be tied to the Ignite system when trying to find an Event Template. A user has access to the complete template library from anywhere in the Ignite system, which eliminates the need for separate template files that would have to be created and updated, or obsoleted.

One Ignite Show Builder Assistant license is included as a component of an Ignite system. Additional Show Builder Assistant licensing can be purchased.

Show Builder Assistant is started from the NCS.


Operation

Search for TMX/IQT via TME Search

1. From the NCS, open **ShowBuilder Assistant**. The Show Builder Assistant pane appears in the NCS and displays the available TMX/IQTs from the Ignite TME folder.
2. In the **TME** box, type an existing TMX/IQT. The search information displays ([Figure 523](#)).

Note The list of TMX/IQTs in search window is limited to the search criteria.

Figure 523. Search for TMX/IQT via TME Search



3. Double-click an IQT.
- The IQT expands to display parameter values.
 - All table names for the IQT are displayed.


Note This relates to the Table name in IQTM.

- All table values for the IQT are displayed.

Note This relates to the Values within the tables in IQTM.

Refer to [Figure 524](#).

Figure 524. IQT Parameter Values




4. Select the desired table value from the drop-down list. The selected table value appears in the drop-down box and the drop-down list collapses.
5. Click and drag the TME from the list into a story script within the NCS. The MOS ID appears in the script with the name of the selected IQT in the MOS ID.

Search for TMX/IQT via Category

1. From the NCS, open **ShowBuilder Assistant**. The Show Builder Assistant pane appears in the NCS and displays the available TMX/IQTs from the Ignite TME folder.
2. Click the **Category** drop-down list (Figure 525), the:
 - drop-down list expands downward.
 - drop-down list displays the names of the subfolders in the Ignite TME folder.

Figure 525. Search for TMX/IQT via Category



3. Select a category.
 - TMX/IQTs are displayed from the selected category.
 - Sub folders of the main folder are displayed as sub categories directly under the main category.

Note Example would be main category is Cameras, sub-category would be OTS. The OTS folder is a sub folder of Camera

4. Double-click an IQT.


- The IQT expands to display parameter values.
- All table names for the IQT are displayed.

Note This relates to the Table name in IQTM.

- All table values for the IQT are displayed.

Note This relates to the Values within the tables in IQTM.

Figure 526. IQT Parameter Values



5. Select the desired table value from the drop-down list. The selected table value appears in the drop-down box and the drop-down list collapses.
6. Click and drag the IQT from the list into a story script within the NCS. The MOS ID appears in the script with the name of the selected IQT in the MOS ID.

Selecting a TMX

Note TMXs should not expand since there are no parameters available.

- Double-click a TMX from the list. The file is selected, but does not expand

Import TMX via Import Rundown

1. From the Ignite Event Timeline menu, select **Tools** and then click **Import Rundowns**. The **Import Rundown** dialog box appears displaying active rundowns.
2. Double-click a rundown. The rundown expands showing stories from the NCS.
3. Click **Import**. The:
 - Rundown Import pane shows story specific information including processed information, warnings, and errors.
 - Ignite timeline is populated with TMX/IQT files in the same order they appear in the show in the NCS.

Note MOS IDs should appear in the order they are in the script.


- Rundown list window next to the Ignite Event Timeline, displays the name of the TMX or IQT with the chosen parameters if other than the defaults.
- Column data populates, however MOP data only displays the IQT name and not the selected values.

Note The Rundown List needs to be set to Rundown List Detailed to view this. From the Ignite Event Timeline menu select Window and then click Rundown List Detailed.

Copy/Paste Function

1. Select either a TME or IQT from the Show Builder Assistant (Figure 527). The selected item highlights blue and the Copy bar at the bottom displays either the TME or the entire IQT, including currently selected table options.

Figure 527. Copy/Paste Copy Bar Example



2. Click the **Copy Bar**. (The string is copied to the Clipboard.)
3. From the NCS, select the TME field where the markup is to be pasted.
4. Either (Figure 528):
 - Right-click and select paste
 - On the keyboard, click **Ctrl + V**.

The information is pasted into the TME column (Figure 529).

Figure 528. Paste Example





Figure 529.



Refreshing Rundowns

1. After making a change to the actively monitored show in the NCS.
 - Import Rundown window displays changes made and the correct information, error or warnings.
 - Information in the Timeline does not change.
 - Update Rundown button is highlighted in RED.
2. Click **Import** in the Rundown Window. The updated information appears in the Timeline.
3. Click **Update Rundown**. The updated information appears in the Timeline.

Switcher Module - Kayak

Figure 530. Switcher Module User Interface Example



Overview

For Switcher Module [Konnect] overview and operation information, refer to [Section 16-Switcher Module - Konnect](#).

The Switcher Module – Kayak version ([Figure 530](#)) provides Ignite interface control of the Kayak switcher. Depending on system configuration, the Switcher Module (Kayak version) can be one, two, three, or four Mix Effects banks—P/P, M/E 1, M/E 2, and M/E 3 respectively. The Switcher Module ([Figure 530](#)) routes video device inputs (including cameras, VTRs, VRs, character generators, or the internally generated matte/pattern or black screens) to:

- Preview outputs – (Prep) outputs display the next image before it is used
- Program outputs – (Active) outputs are linked to the devices indicated by the current image.
- Keyer Fill
- Keyer Key or Hole
- Aux Outputs
- Utility Bus

The number of Inputs and Outputs depends on the Ignite system installed (refer to [Table 14](#)).

Table 14. System Video Inputs/Output

System	Video	
	Standard	
	In	Out
1 M/E DD	16	15
2 M/E DDa	32	20
SD 2 M/E	48	24
SD 3 M/Eb	72	36
SD 4 M/Eb	96	48
HD 1 M/E	24	12
HD 2 M/Ec	48	24
HD 3 M/Ec	72	36
HD 4 M/Ec	96	48

The Ignite Switcher module is available with up to four total Mix Effects (M/E) banks (refer to [Figure 530 on page 471](#)) labeled:

- **P/P** – Program/Preview
- **M/E 1** – Mix Effects One
- **M/E 2** – Mix Effects Two
- **M/E 3** – Mix Effects Three

Each M/E bank has four Key layers. Any of the keyers can be assigned DPM (Digital Picture Manipulator) properties. DPM properties cannot be seen if the key layer is not on.

There are 10 customizable switcher pages and each page can have up to 24 buttons. When an M/E bank page is customized, the customization applies to that page across all M/E banks. The Switcher Module uses a Master Routing dialog box for quick source routing to destinations on any of the four effects banks. For descriptions of the basic interface, refer to [Figure 531](#) and [Table 15](#).

Note One and two M/E systems have one Utility Bus select button (U1); three and four M/E systems have two Utility Bus selection buttons (U1 and U2).

Note Only the first M/E has the Source Setup and the Setup icons. The Switcher module basic interface is shown in [Figure 531](#).

Figure 531. Switcher Module Basic Interface




Table 15. Basic Interface Functionality

Name	Description
Program Bus	
Preview Bus	
Keys/DPMs	Shows the current Keyer fill (refer to Keyer on page 486).
Sources	Shows the current PGM, PVW, and Utility Bus bus sources.
Pages/Page Tabs	Selects a Page of source buttons.
Setup (General)	Opens the Setup dialog box (refer to General Setup Dialog Boxes on page 474).
Source Setup	Opens the Source Setup dialog box (refer to Source Setup Dialog Box on page 481).
Browse Program Master Routing	Opens the Program Bus Master Routing dialog box (refer to Master Routing Dialog Box on page 484).
PGM/PVW Bus source buttons	Shows the current PGM and PVW bus sources.
U1 – U2	Opens the respective Utility Bus Master Routing dialog box (refer to Master Routing Dialog Box on page 484).
K1– K4	Opens the respective Key Layer Master Routing dialog box (refer to Master Routing Dialog Box on page 484).
AUTO	Depending upon either the Mix or Wipe button selection, preps the next transition to be executed when Take is clicked. Also highlights blue when a TME with either a Mix or a Wipe effect is prepped on the timeline.
CUT	Preps the next transition to execute as a Cut when Take is clicked. Also highlights blue when a cut effect is prepped.
Take	Takes the selected effect to air.

Table 15. Basic Interface Functionality

PVW	Displays the selected effect transition to PGM on the PVW (Preview) monitor.
Browse Effects	Opens the Effects Definition dialog box (refer to Keyer on page 486).
Expand Effects List	Enables a user to expand, view, select, and take an effect directly to air.
Effects List	Lists available programmed effects.

The Switcher M/E banks can be customized to meet show/user requirements via the **Master Routing** dialog box (refer to [Master Routing Dialog Box on page 484](#)). Each of the 10 switcher pages can be customized. When an M/E bank page is customized, the customization applies to that page across all available M/E banks.

General Setup Dialog Boxes

Access to the **General Setup** dialog boxes is from the Switcher Module **Setup** icon ([Figure 532](#)). The **General Setup** dialog box is the interface used to configure the Switcher module general parameters. When accessed, the General Setup dialog box appears in either Mainframe Setup ([Figure 533](#)) or M/E Setup ([Figure 534](#)) state.

Note The General Setup dialog box appears either as Mainframe Setup or M/E Setup. This is determined by the appearance the General Setup dialog box was in when last closed.

Figure 532. General Setup – Setup Icon



Figure 533. General Setup Dialog Box – Mainframe Setup





Figure 534. General Setup Dialog Box – M/E Setup



Mainframe Setup

The **Mainframe Setup** (Figure 533) includes:

- List of the currently connected switcher frames and the version.
- Selection lists for –
 - **Video Standard** – only shows the standards supported by the connected switcher.
 - **Genlock Type SD** –
 - **Genlock Type HD** – only enabled if the switcher is HD.
- **Aux Setup** button – opens the **Aux Setup** dialog box.

- **MEASURING ON AUX 1** – timing phase setting. (The AUX 1 bus must be delegated to an external source first.) When the phase is in range, the center bar turns green. The phase range is -32768 to +32767.
- **Color Background** button – opens the **Color Background** dialog box.
- **MatchDef™** button – opens the **MatchDef™ Scalar Configuration** dialog box.
- **Close** button – saves the current parameters and closes the dialog box.

Aux Setup Dialog Box

Access to the **Aux Setup** dialog box is from the **General Setup** dialog box **Aux Setup** button. The **Aux Setup** dialog box (Figure 535) includes:

- **Delegate** – Aux bus selection list.

Note The available Aux selections are listed automatically based on current system configuration.

- **CROSSHAIR** changes the Aux crosshair for the selected Aux bus –
 - **Enable** – on/off crosshair selection.
 - **Center** – resets the crosshair to the center position.
 - Crosshair position is set via either the **Horiz.** and **Vert.** knobs or typing in the respective text box.
- **SAFE TITLE** changes the Aux safe title for the selected Aux bus –
 - **Enable** on/off safe title selection
 - **Reset** to the center position
 - Position settings via either the **Top**, **Left**, **Right**, and **Bottom** knobs or typing in the respective text box.
- **Close** button – saves the current parameters and closes the dialog box.

Figure 535. Aux Setup Dialog Box



Color Background Dialog Box

Access to the **Color Background** dialog box is from the **General Setup** dialog box **Color Background** button (Figure 533). The **Color Background** dialog box (Figure 536) includes:

- **MATTE SETUP** – selects one of three internal backgrounds: **BACKGROUND 1**, **BACKGROUND 2**, or **WASH** for adjustment
- **COLOR OUTPUT** – select the background color output mode: **MATTE 1**, **MATTE 2**, or **WASH**
- **HUE, CHROMA, and LUMA** – adjusts the hue, chroma, and/or luma of the selected background color. It is set via either slider or typed into the respective text box.
- **MATTE 1** Tab
- **MATTE 2** Tab
- **WASH** Tab
- **Save** button – saves the current parameters and closes the dialog box.
- **Close** button – closes the dialog box without saving changes.

Figure 536. Color Background Dialog Box




MatchDef™ Scalar Configuration Dialog Box

The MatchDef™ feature is provided with the following types of switchers:

- SD/HD switchable video formats
- Large frame switcher that has up to four M/E banks

To appear on the **General Setup** dialog box, the MatchDef feature must be licensed to either of these switchers. Access to the **MatchDef™ Scalar Configuration** dialog box (Figure 537) is from the **General Setup** dialog box **MatchDef™** button.

Figure 537. MatchDef™ Scalar Configuration Dialog Box




Scalar Configuration

To access the scalar configuration parameters, click the **Scalar** button on the **MatchDef Scalar™ Configuration** dialog box. Scalar setup and configuration parameters include (Figure 538):

- **Scalar** button – shows a list of available scalar objects along with input, enabled/disabled state, and video format.
- **MatchDef™** button – shows the properties of the scalar object for review or modification.
- **Toggle On/Off** button – toggles the selected scalar object on or off.
- **Set Video Format** button – displays a list of available and supported video formats used to associate with the selected scalar object.
- **Close** button – closes the dialog box.

Figure 538. MatchDef™ Scalar Configuration Dialog Box – Scalar Configuration



MatchDef™ Configuration

To access the MatchDef configuration parameters, click the **MatchDef™** button on the **MatchDef Scalar™ Configuration** dialog box. MatchDef setup and configuration parameters include (Figure 539):

- **Scalar** button – shows the scalar object that is being viewed.
- **Aspect Ratio Conversion** button – shows the aspect ratio conversion associated with the current scalar object.

- **Color Background Set** button – modifies the color background of a scalar object. Color background parameters include:
 - **Hue**
 - **Chroma**
 - **Lum**
- **Crop Set** button – modifies the crop settings of a scalar object. Crop parameters include:
 - **Right**
 - **Left**
 - **Top**
 - **Bottom**

Note After parameter selection is made, parameters appear in the **COLORBACK-GROUND** and **CROP** areas in the dialog box.

- **Crop On** button – enables/disables crop properties.
- **Default Settings** button – resets all settings of the current scalar object to its default value of zero.
- **Control knobs** – changes the value of the selected setting, either the color background settings or the crop settings.
- **Close** button – closes the dialog box.

Figure 539. MatchDef Scalar Configuration Dialog Box – MatchDef™ Configuration



M/E Setup

The **M/E Setup** (Figure 534) includes:

- **M/E selection** – **P/P**, **M/E 1**, **M/E 2**, **M/E 3**

Note The available M/E selections are listed automatically based on current system configuration.

- **CLEAN FEED** – sets the clean feed layer for the selected M/E.
- **FORMAT** – sets the format for the selected M/E
- **Close button** – saves the current parameters and closes the dialog box.

Source Setup Dialog Box


Access to the **Source Setup** dialog box is from the Switcher Module (Figure 531) Source Setup icon. The **Source Setup** dialog box (Figure 540) includes:

- **Page Configuration**
 - **Page Name** – name for the currently selected page.
 - **# of Buttons** – number of source buttons to show (24 maximum) for the currently selected page; an entry in this box is effective immediately.
- **Text Color** – page name text color / opens the **Color Chooser** dialog box (refer to [Configure Source Dialog Box on page 482](#)).
- **Back Color** – page button background color / opens the **Color Chooser** dialog box (refer to [Configure Source Dialog Box on page 482](#)).
- **Source** – opens the **Configure Source** dialog box (refer to [Configure Source Dialog Box on page 482](#)). An external source must be selected for this button to appear (Figure 541).
- **Undo** – undoes the last operation.
- **Internal Sources** – currently available internal sources that can be configured to a Switcher Module button on the currently selected page
- **External Sources** – currently available external sources that can be configured to a Switcher Module button on the currently selected page.
- **Close button** – closes the dialog box.

Figure 540. Source Setup Dialog Box



Figure 541. Source (Source) Setup Dialog Box



Configure Source Dialog Box

Accessed from the **Source Setup** dialog box, the **Configure Source** dialog box (Figure 542) enables a user to configure the currently selected internal/external source button. It includes:

- **Source Name** – (limited to 9 characters)
- **Source Title** – (limited to 4 characters)
- **Key Source** – shows available key sources that can be coupled to the currently selected source. The currently coupled key source does not appear in this list.

- **BUTTON COLOR** – color selection palette. Additional colors are available by clicking the **Preview Source** icon.
- **BUTTON DECAL** – decal selection library
- **KEY SOURCE** – depicts the selected key source
- **Save** button – saves the current parameters (only available if/when a change is made).
- **Next** – Moves the configuration ahead to the next button configuration.
- **Previous** – Moves the configuration back to the previous button configuration.
- **Copy** – When checked, copies the current configuration and, using the **Next** or **Previous** button, applies that configuration to the next/previous button.
- **Close** button – closes the dialog box without saving changes.

Note The **Configure Source** dialog box is only accessible from the **Source Setup** dialog box **Source** button. The **Source** button is available only after either an Internal or External Source button is selected for configuration.

The dialog box also has a **Source** preview to depict the color, decal, and source configuration before saving and closing the dialog box. Clicking the **Source** preview, opens the **Color Chooser** dialog box to enable a color change.

Figure 542. Configure Source Dialog Box



Note To move the dialog box, click the title bar and drag.

When configuring more than one source, the **Configure Source** dialog box **Previous** and **Next** buttons provide sequential navigation through the **Source Setup** dialog box **INTERNAL SOURCES** and **EXTERNAL SOURCES**.

Note The **Next** and **Previous** buttons provide navigation from button to button and any/all changes are maintained but not saved until the **Save** button is clicked.

Note To move the dialog box, click the title bar and drag.

Master Routing Dialog Box

The **Master Routing** dialog box (Figure 543) is the initial interface used to set up both the Switcher module and the keyers. The dialog box has two main areas:

- Destinations on the left–
 - **M/E** – depicts and enables selection of the available M/E banks.
 - **M/E BUSES** – depicts and enables selection of the available buses and keyers.
 - **M/F BUSES** – depicts and enables selection of the available mainframe (Aux) buses.

Note Ignite 3000 and 4000 systems also have page left/page right navigation buttons.

- Sources on the right–
 - **INTERNAL SOURCES** – depicts and enables selection of hard inputs in the switcher.

Note Ignite 3000 and 4000 systems also have page up/page down navigation buttons.


- **EXTERNAL SOURCES** – depicts and enables selection of sources connected to the switcher

Note The Master Routing dialog box automatically scales to match the current Ignite system configuration and the number of inputs available on the licensed Kayak™ frame.

- **Close** button – closes the dialog box.

The M/E button indications are interactive and reflect the status/assignments for that particular button. That is, when an M/E or bus destination is selected, that button highlights and the associated internal and external sources also highlight.

Figure 543. Master Routing Dialog Box - Example Normal View Scaled With 96 Inputs



Access to the **Master Routing** dialog box is from several Switcher module (Figure 531) icons/buttons:

- Right-click a keyer button
- Access Key Layer Master Routing icon (K1–K4)
- Access Utility Bus Master Routing icon (U1 and U2)
- Right-click PGM Master Routing icon

Note Depending on which access method is used, the Master Routing dialog box opens for viewing/editing that respective selection; i.e., K1, K2, K3, K4, U1, U2, ...

Note To move the dialog box, click the title bar and drag.

The dialog box also has three user-selectable view options (Figure 544):

- Normal
- Narrow
- Wide

These view options are selected using the associated resize icon at the bottom right of the dialog box.

Figure 544. Master Routing Dialog Box



- Close button – closes the dialog box.


Keyer

Each M/E bank has up to four key layers (K1 through K4) active at once. Each has a corresponding switcher button on both the Program Bus and the Preview Bus. Keyers can also act as DPM/DVE channels where clicking the gray area of a keyer turns on a channel of the DPM/DVE, which then fills with the source routed to that keyer. It is designated as on air by a color

highlight and a small yellow DPM icon in the upper right hand corner. Highlight colors correspond to their respective bus (Figure 545):

- Green with a yellow bar for keys on the DPM/DVE Program bus
- Yellow with a yellow bar for keys on the DPM/DVE Preview bus

Figure 545. Keyers On Air



- Click the top half of keyer to toggle the keyer
- Right-click the top half of keyer to access the DPM context menu (Figure 546). Click **Set Keyer Fade Rate** to access the **Keyer Fade Rate** dialog box and enter a transition time for the fade.

Figure 546. DPM Context Menu



- Click the lower half of keyer to change source routing.
- Click the respective P/P, M/E 1, M/E 2, or M/E 3 **Browse Effects** button (Figure 547) to open the **Effects Definition** dialog box (Figure 548).

Figure 547. Browse Effects Definition button



Figure 548. Effects Definition Dialog Box



Note Displays the current M/E to which the current effects are saved. Possible values (P/P, M/E 1, M/E 2, M/E 3).

The **Effects Definition** dialog box is a consolidated interface for effects management, transition, and association. The dialog box segments, from left to right, include (Figure 549):

- Effects management (Refer to [Effects Management on page 489](#))
- Effect transitions (Refer to [Effect Transition on page 490](#))
- Wipe Effect Setup (Refer to [Wipe Effect Setup Dialog Box on page 492](#))
- DPM Effect Setup (Refer to [DPM Effect Setup Dialog Box on page 493](#))

Figure 549. Effects Definition Dialog Box Groups



- **Save** button – saves the current parameters.
- **Close** button – closes the dialog box without saving changes.

Effects Management

The **Effects List** is a list of user created effects. These effects are managed using a right-click and shortcut menu. The **Effects List** separated into three sub-lists:


Note Effects in each of the three sub-lists are managed easily via shortcut menu selections (Figure 550). The shortcut menus are accessed via right-click.

- **All Effects** – lists all effects that are visible on the Switcher module. Using shortcut menu selections (Figure 550), a user manages the **All Effects** sub-list. Effects deleted from the **All Effects** sub-list are recoverable from the **Recycle Bin** using a right-click and shortcut menu selection.
- **Hidden Effects** – lists effects that are not visible on the Switcher module. Using shortcut menu selections (Figure 550), a user manages the **Hidden Effects** sub-list. Effects deleted from the **Hidden Effects** sub-list are recoverable from the **Recycle Bin** using a right-click and shortcut menu selection.

CAUTION Effects deleted from the **Recycle Bin** cannot be recovered.

- **Recycle Bin** – all effects deleted from both **All Effects** sub-list and **Hidden Effects** sub-list are automatically moved to the **Recycle Bin** sub-list and can be recovered/moved from the **Recycle Bin** sub-list using shortcut menu selections (Figure 550). Effects deleted from the **Recycle Bin** sub-list cannot be recovered.

Figure 550. Effects List Management



Three command buttons comprise the remainder of the Effect Management function. These commands are also available by using a right-click and shortcut menu.

- **Add** – create/add a new effect to the Effects List. A default name is automatically generated for the new effect but it should be renamed to conform with established standard naming conventions.

Note For all names, abbreviations, and colors, use established standards and consistent techniques and practices. Refer to *Standardization* on page 577.

- **Del (Delete)** – Removes the selected effect and places it in the **Effects List Recycle Bin**.
- **Edit** – enables the **Effect Transition**, **Wipe Effects**, and **DPM Effects** functions for editing the selected effect.

Note Effects created by prepping an existing effect and adding keyers to create a new effect, will be executed once and deleted immediately after use. Only permanent effects will be selectable from the main GUI drop down list indefinitely.

Note Effects can be placed on the Ignite **Event Timeline** by right-clicking and dragging an effect.

Effect Transition

The **Effect Transition** function includes the following areas:

- **EFFECT NAME** – in edit mode, the effect name can be changed by entering a different name in the **EFFECT NAME** box.


- **KEY PRIORITY** – changes the keyer priorities.
Send – sends the new key priority data that is utilized when the effect is taken to air.
- **Transition** – Sets the components to include in the transition. From left to right:
 - The first column of buttons/indicators settings:
 - Gray – the component is not included
 - Red – use the current setting
 - Yellow – include the component.
 - The second column of buttons/indicators sets whether the effect is a Wipe or a Mix.
 - The third column of buttons/indicators sets whether the effect is a Cut or an Auto transition.
 - The fourth column sets the Auto transition time (in frames) for the effect.
 - The fifth column of buttons/indicators sets DPM control:
 - Gray – off
 - Red – use current
 - Yellow – on
 - The sixth column of button/indicators opens the keyer effects dialog box.
 - The seventh column of button/indicators sets whether or not to send the keyer effect data when the effect is taken to air:
 - Green – send
 - Gray – do not send
- **Default** (button below each column) – Resets the respective column data to default values.
 - Reset keyers to OFF state on a PVW transition
 - Reset to MIX
 - Reset to AUTO
 - Reset to 30 Frames
 - Reset to DPM OFF
 - Reset to keyer Luma defaults
 - Reset send keyer data to OFF
- **To Air** – sends the effect to the switcher but does not start the transition.
- **Take** – sends the effect to air and begins the transition.

- **Transition Slider** – enables a user to manually control the transition.

Wipe Effect Setup Dialog Box

When the effect is a wipe transition, a wipe pattern must be associated with the wipe. Click the **Access** button at the bottom right of the **WIPE EFFECTS** function to access the **Wipe Effect Setup** dialog box.

Figure 551. Wipe Effect Setup Dialog Box



The **Wipe Effect Setup** dialog box is the interface used to set up/edit a wipe pattern. Available setup/edit configuration includes:

- **WIPE EFFECT** list – This list contains wipe effects created by a user.
- **Add** – create/add a new effect to the **WIPE EFFECT** List. A default name is automatically generated for the new effect but it should be renamed to conform with established standard naming conventions.

Note For all names, abbreviations, and colors, use established standards and consistent techniques and practices. Refer to *Standardization* on page 577.

- **Cpy** (Copy) – copies the selected effect parameters for edit/re-use as a modified/different effect.
- **Edit** – enables parameter editing of the selected effect.
- **Del** (Delete) – removes the selected effect. A confirmation dialog box appears to confirm the deletion.
- **Effect Name** – the wipe effect name can be changed here.
- **SELECT PATTERN** – lists the pre-defined wipe patterns in the switcher. A wipe pattern must be selected from this list and used as the base pattern for the wipe effect.
- **BACKGROUND WIPE** – set by a user to adjust the wipe effect parameters:
 - **ADJUST MULTIPLE**
 - **ADJUST COLOR**
 - **ADJUST MODULATION**
 - **ADJUST MIX**

Note For a detailed explanation of the BACKGROUND WIPE parameters, refer to the Kayak User Manual.

- **TAKE** – wipe slider that enables a user to preview the wipe effect as it would appear in a transition.
- **Save** button – saves the current parameters.
- **Close** button – closes the dialog box without saving changes.

DPM Effect Setup Dialog Box

Click the **Access** button at the bottom right of the **DPM EFFECTS** function to access the **DPM Effect Setup** dialog box. The Ignite Digital Picture Manipulator (DPM) function provides transition control over picture position, shape, luminance, chroma key, luma, and motion.


The dialog box contains three tabs:

- **Timeline** tab (Refer to the *Timeline Tab* on page 493)
- **Transform** tab (Refer to the *Transform Tab* on page 496)
- **Special Effects** tab (Refer to the *Special Effects Tab* on page 500)

Timeline Tab

From the **DPM Effect Setup** dialog box (Figure 552), click the **Timeline** tab to access the initial interface used to set up/edit the DPM effect, display key-frame duration, and display the DPM timeline.

Figure 552. Timeline Tab



Setup and configuration parameters include:

- **DPM EFFECTS** list – displays the DPM effects in the current M/E of the switcher. This is the same DPM effects list as seen in the **Effects Definition** dialog box (Figure 548).
 - **Edit** – enables the DPM effect to be edited from the **DPM EFFECTS** list.
 - **Copy/Paste** – when not in editing mode, enables the user to copy the selected effect and paste this effect into a different DPM register.
 - **Delete** – when not in editing mode, removes the selected effect from the list. All keyframes associated with the DPM effect are also removed.








Note The **DPM Delete** dialog box (Figure 572 on page 517) appears when any effects are associated with the current DPM effect.

- **Lock** – when not in editing mode, enables the user to lock an effect.
- **Name** – allows the DPM effect to be renamed.







Note For all names, abbreviations, and colors, use established standards and consistent techniques and practices. Refer to *Standardization* on page 577.

- **Current DPM Effect Time** – shows the current position of the DPM timeline cursor. Format is hh:mm:ss:ff; ff = 1 second.

- **Playout Controls** – playout controls for the keyframe include:

Control	Function
	Go to the first keyframe in the timeline
	Go to the previous keyframe in the timeline
	Reverse play
	Pause
	Play
	Go to next keyframe
	Go to last keyframe

- **Keyframe Editing Controls** – keyframe editing controls include:

Control	Function
	Insert keyframe before the current cursor position
	Insert keyframe after the current cursor position
	Modify the keyframe with current effect parameters
	Modify DPM timeline duration
	Modify DPM keyframe duration
	Delete current keyframe

- **Keyframe Delegation** – keyframe delegation options include:
 - **INCLUDE IN EFFECT** – includes the selected channel in the effect. Channels that are not included cannot be delegated.

- **DELEGATE CONTROL** – delegates a channel and allows it to be edited. For example, if channels 1 and 2 are delegated, then clicking the **Insert Keyframe** icon inserts a keyframe into each channel. Channels that are not delegated are not affected.
- **ASSIGN GLOBAL** – determines whether a channel is affected by the global transformation, the last channel is green.
- **DPM ON** – turns the DPM effect on and off for the keyer.
- **GLOBAL** – sets the modifications to a channel keyframe at the global level.

Note It is recommended that you set all channel keyframes to the **Global** keyframe delegation option. Keyframe channels that are not set to **Global** may recall off screen.

- **Timeline Zoom** – enables zoom-in and zoom-out capabilities in the DPM timeline.
- **Timeline Ruler** – displays the timeline ruler in hh:mm:ss:ff format, where ff = 1 second.
- **Timeline View** – displays the current keyframes in the DPM effect.
- **M/E Indicator** – displays the current M/E to which the current effects are saved. Possible values (P/P, M/E 1, M/E 2, M/E 3).
- **Close button** – closes the dialog box.

Transform Tab

From the **DPM Effect Setup** dialog box, click the **Transform** tab ([Figure 553](#)) to access the interface used to change the appearance of a DPM effect.

Note The **Transform** tab contains functions that are common to the **Timeline** tab and **Special Effects** tab such as editing and deleting a DPM effect and applying keyframe options to channels.

Figure 553. Transform Tab



The main functions of the **Transform** tab include:

- **Reset GEO PARMS** – resets geometric parameters for the delegated channels.
- **Reset ALL PARMS** – resets all parameters for all channels.
- **Close** button – closes the dialog box.

The **Transform** tab has three subtabs:

- **Locate** – manipulates the position of a two-dimensional picture on the X, Y, or Z axis.
- **Skew** – slants the two-dimensional picture in the X and Y directions.
- **Crop** – trims and manipulates the size of a two-dimensional picture.
- **DPM Knob Controls** – All three subtabs contain DPM knob controls used to adjust the parameters, either ranged or unranged. Click and drag the knob either to the left or right to manipulate the parameters.

DPM Transform – Locate Subtab


Parameters on the **Locate** subtab enable movement, rotation, or spin of the keys from the viewpoint of source or target. From the **Transform** tab, click the **Locate** subtab to access the parameters.

Parameters are organized in the following categories:

- **SOURCE/TARGET** – options for source or target viewpoint. When **Source** is selected, the **Size** parameter appears.
- **LOCATE** – X, Y, Z location coordinates and path parameters for transform location.
- **LOCATE AXIS** – X, Y, Z location coordinates and path parameters for pivot point location.
- **TARGET ROTATE** – X, Y, Z location coordinates and path parameters for target rotation.
- **SPIN** – X, Y, Z location coordinates and path parameters for spin effect.

Note For a detailed explanation of the parameters on the **Locate** subtab, refer to the Kayak User Manual.

Figure 554. DPM Transform – Locate Subtab



864k-sc288-r0

DPM Transform – Skew Subtab

Parameters on the **Skew** subtab enable perspective transformation, which allows the keys to be stretched. From the **Transform** tab, click the **Skew** subtab to access the parameters.

Parameters are organized in the following categories:

- **SKEW** – X, Y components and path parameters that scale the picture.
- **ASPECT** – X, Y scaling components and path parameters that slant the picture.
- **PERSPECTIVE** – X, Y components and path parameters that change the viewer's apparent viewpoint of the picture.
- **POST XFORM** – X, Y components and path parameters that may affect the size and location operations and picture projection.

Note For a detailed explanation of the parameters on the **Skew** subtab, refer to the Kayak User Manual.

Figure 555. DPM Transform – Skew Subtab



DPM Transform – Crop Subtab


From the **Transform** tab, click the **Crop** subtab to access the parameters. Parameters are organized in the following categories:

- **CROP** – option that applies the cropping parameters to the picture.
- **PATH** – selection of path type such as curve, linear, or S-linear.
- **CROP EDGE** – parameters that crop the edge of the picture.

- **CROP SOFT** – parameters that apply a gradient edge to the picture.
- **EASY CUBE** – option that creates a cube out of three keyers.
- **REVERSE IMAGE** – parameters that enable the picture to be mirrored horizontally and vertically.

Note For a detailed explanation of the parameters on the **Crop** subtab, refer to the Kayak User Manual.

Figure 556. DPM Transform – Crop Subtab




Special Effects Tab

From the **DPM Effect Setup** dialog box, click the **Special Effects** tab (Figure 557) to access the interface used to apply special effect parameters to a DPM effect.

Note The **Special Effects** tab contains functions that are common to the **Timeline** tab and **Transform** tab such as editing and deleting a DPM effect and applying keyframe options to channels.

Figure 557. Special Effects Tab – KURL OFF Subtab



Special effect functions and parameters include:

- **Reset GEO PARMS** – resets geometric parameters for the delegated channels.
- **Reset ALL PARMS** – resets all parameters for all channels.
- **Type** – special effect types include:
 - **KURL**– From the **Type** drop-down list box, when **KURL** is selected, seven subtabs appear.
 - **OFF** (Refer to [Figure 557](#))
 - **Page Turn** (Refer to [Figure 558 on page 503](#))
 - **Page Roll** (Refer to [Figure 559 on page 504](#))
 - **Pos/Size Mod** (Refer to [Figure 560 on page 505](#))
 - **Slits** (Refer to [Figure 561 on page 506](#))
 - **Ripple** (Refer to [Figure 562 on page 507](#))
 - **Sphere** (Refer to [Figure 563 on page 508](#))
 - **SPLITS** – From the **Type** drop-down list box, when **SPLITS** is selected, the **SPLITS** subtab appears. Refer to [Figure 564 on page 509](#).
 - **ADVANCED EFFECT** – From the **Type** drop-down list box, when **ADVANCED EFFECT** is selected, six additional subtabs appear:
 - **Defocus** (Refer to [Figure 565 on page 510](#))

- **Glow** (Refer to [Figure 566 on page 511](#))
- **Drop Shadow** (Refer to [Figure 567 on page 512](#))
- **Shadow Crop** (Refer to [Figure 568 on page 513](#))
- **Output Recursive** (Refer to [Figure on page 514](#))
- **Light Path** (Refer to [Figure 570 on page 515](#))
- **Light Sources** (Refer to [Figure 570 on page 515](#))
- **DPM Knob Controls** – knobs for parameter adjustment are ranged or unranged. Values for ranged knobs are limited to the minimum and maximum. Unranged knobs are limitless; the user can click and drag repeatedly.
- **Close** button – closes the dialog box.

DPM Special Effects – Kurl – OFF Subtab

The **OFF** subtab turns off all Kurl special effects. This subtab does not have any parameters.

DPM Special Effects – Kurl – Page Turn Subtab

Parameters on the **Page Turn** subtab simulate a page-turning effect that starts from a specific point on the edge of the keyer. To access the parameters on this subtab:

- From the **Special Effects** tab, click **KURL** from the **TYPE** drop-down list
- Click the **Page Turn** subtab

Figure 558. DPM Special Effects – KURL Page Turn Subtab



Parameters are organized in the following categories:

- **PATH** – selection of path type such as curve, linear, or S-linear.
- **PAGE FOLD** – parameters that adjust the radius, angle, and offset of the picture.
- **BACK COLOR** – parameters that change the color of the matte on the back side of the turned picture.
- **SPLIT AXIS** – parameters that control split page turn and roll effects.
- **FOLD** – options that determine the orientation of the fold.
- **SIDES** – options that determine which side of the picture displays.

Note For a detailed explanation of the parameters on the **Page Turn** subtab, refer to the Kayak User Manual.

DPM Special Effects – Kurl – Page Roll Subtab

Parameters on the **Page Roll** subtab are similar to the parameters on the **Page Turn** subtab. The difference is that a Page Roll effect is where the entire edge of the keyer is curled. To access the parameters on this subtab:

- From the **Special Effects** tab, click **KURL** from the **TYPE** drop-down list
- Click the **Page Roll** subtab

Figure 559. DPM Special Effects – KURL Page Roll Subtab



Parameters are organized in the following categories:

- **PATH** – selection of path type such as curve, linear, or S-linear.
- **PAGE FOLD** – parameters that adjust the radius, angle, and offset of the picture.
- **BACK COLOR** – parameters that change the color of the matte on the back side of the rolled image.
- **SPLIT AXIS** – parameters that control split page turn and roll effects.
- **FOLD** – options that determine the orientation of the fold.
- **SIDES** – options that determine which side of the picture displays.


Note For a detailed explanation of the parameters on the **Page Roll** subtab, refer to the Kayak User Manual.

DPM Special Effects – Kurl – Pos/Size Mod Subtab

Parameters on the **Pos/Size Mod** subtab adjust the position of the keyer and associate the keyer with another pattern such as Sine wave, triangle, source, circle, etc. To access the parameters on this subtab:

- From the **Special Effects** tab, click **KURL** from the **TYPE** drop-down list
- Click the **Pos/Size Mod** subtab

Figure 560. DPM Special Effects – KURL – Pos/Size Mod Subtab



Parameters are organized in the following categories:

- **PATH** – selection of path type such as curve, linear, or S-linear.
- **HORIZONTAL** – selection of effect pattern such as Sine, triangle, circle, etc., mode selection, and additional parameters that are applied to the horizontal axis of the picture.
- **VERTICAL** – selection of effect patterns such as Sine, triangle, circle, etc., mode selection, and additional parameters that are applied to the vertical axis of the picture.

Note For a detailed explanation of the parameters on the **Pos/Size Mod** subtab, refer to the Kayak User Manual.

DPM Special Effects – Kurl – Slits Subtab

Parameters on the **Slits** subtab divide and cut the keyer into separate, parallel slits. To access the parameters on this subtab:

- From the **Special Effects** tab, click **KURL** from the **TYPE** drop-down list
- Click the **Slits** subtab

Figure 561. DPM Special Effects – Kurl – Slits Subtab



Parameters are organized in the following categories:

- **PATH** – selection of path type such as curve, linear, or S-linear.
- **MODULATION** – waveform-pattern options and parameters applied to the picture.
- **SLITS** – parameters applied to each separate slit that is created.


Note For a detailed explanation of the parameters on the **Slits** subtab, refer to the Kayak User Manual.

DPM Special Effects – Kurl – Ripple Subtab

Parameters on the **Ripple** subtab apply wave effects to the keyer. To access the parameters on this subtab:

- From the **Special Effects** tab, click **KURL** from the **TYPE** drop-down list
- Click the **Ripple** subtab

Figure 562. DPM Special Effects – Kurl – Ripple Subtab



Parameters are organized in the following categories:

- **PATH** – selection of path type such as curve, linear, or S-linear.
- **RIPPLE** – parameters that manipulate the angle, aspect, and cycle of the ripple effect and also selection of effect pattern
- **POSITION** – parameters that manipulate the position of the effect on the X, Y axes.


Note For a detailed explanation of the parameters on the **Ripple** subtab, refer to the Kayak User Manual.

DPM Special Effects – Kurl – Sphere Subtab

Parameters on the **Sphere** subtab wrap the keyer into a ball-like shape. To access the parameters on this subtab:

- From the **Special Effects** tab, click **KURL** from the **TYPE** drop-down list
- Click the **Sphere** subtab

Figure 563. DPM Special Effects – Kurl – Sphere Subtab



Parameters are organized in the following categories:

- **PATH** – selection of path type such as curve, linear, or S-linear.
- **SPHERE** – parameters that alter the size and aspect of the effect.
- **POSITION** – parameters that manipulate the position of the effect on the X, Y axes.
- **WRAP** – parameters that create a “wrap around” effect on the X, Y axes.


Note For a detailed explanation of the parameters on the **Sphere** subtab, refer to the Kayak User Manual.

DPM Special Effects – Splits – Splits Subtab

Parameters on the **Splits** subtab enable the keyer to be split and mirrored. To access the parameters on this subtab:

- From the **Special Effects** tab, click **Splits** from the **TYPE** drop-down list. The **Splits** subtab appears.

Figure 564. DPM Special Effects – Splits – Splits Subtab



Parameters are organized in the following categories:

- **MODE** – option that applies the splits parameters to the picture.
- **PATH** – selection of path type such as curve, linear, or S-linear
- **SPLITS** – parameters that adjust the modulation values of the split effect on the X, Y axes.
- **SEP SIDES** – parameters that adjust the sides of the effect.
- **SPLIT MODIFIERS** – type of splits to select. Values include:
 - **DOUBLE IMAGE**
 - **MIRROR TOP**
 - **MIRROR LEFT**
 - **MIRROR RIGHT**
 - **MIRROR BOTTOM**


Note For a detailed explanation of the parameters on the **Splits** subtab, refer to the Kayak User Manual.

DPM Special Effects – Advanced Effect – Defocus Subtab

Parameters on the **Defocus** subtab apply a blurring effect to the keyer. To access the parameters on this subtab:

- From the **Special Effects** tab, click **ADVANCED EFFECT** from the **TYPE** drop-down list
- Click the **Defocus** subtab

Figure 565. DPM Special Effects – Advanced Effect – Defocus Subtab



Parameters are organized in the following categories:

- **PATH** – selection of path type such as curve, linear, or S-linear.
- **DEFOCUS** – on/off mode selection and additional parameters that adjust the mode.
- **NAM MATTE** – parameters that manipulate the matte color and brightness of the effect.


Note For a detailed explanation of the parameters on the **Defocus** subtab, refer to the Kayak User Manual.

DPM Special Effects – Advanced Effect – Glow Subtab

The parameters on the **Glow** subtab add a glow effect of a specific color to the keyer. To access the parameters on this subtab:

- From the **Special Effects** tab, click **ADVANCED EFFECT** from the **TYPE** drop-down list
- Click the **Glow** subtab

Figure 566. DPM Special Effects – Advanced Effect – Glow Subtab



Parameters are organized in the following categories:

- **PATH** – selection of path type such as curve, linear, or S-linear.
- **GLOW** – on/off mode selection and additional parameters that adjust the mode.
- **MATTE** – parameters that manipulate the matte color and brightness of the effect.


Note For a detailed explanation of the parameters on the **Glow** subtab, refer to the Kayak User Manual.

DPM Special Effects – Advanced Effect – Drop Shadow Subtab

Parameters on the **Drop Shadow** subtab add a shadow behind the keyer of a specific color and the same shape of the keyer. To access the parameters on this subtab:

- From the **Special Effects** tab, click **ADVANCED EFFECTS** from the **TYPE** drop-down list
- Click the **Drop Shadow** subtab

Figure 567. DPM Special Effects – Advanced Effect – Drop Shadow Subtab



Parameters are organized in the following categories:

- **PATH** – selection of path type such as curve, linear, or S-linear.
- **SHADOW** – on/off mode selection and additional parameters that adjust the mode.
- **COLOR** – parameters that adjust the color of the shadow.


Note For a detailed explanation of the parameters on the **Drop Shadow** subtab, refer to the Kayak User Manual.

DPM Special Effects – Advanced Effect – Shadow Crop Subtab

Parameters on the **Shadow Crop** subtab crop the shadow that was added to the keyer with the drop shadow. To access the parameters on this subtab:

- From the **Special Effects** tab, click **ADVANCED EFFECT** from the **TYPE** drop-down list
- Click the **Shadow Crop** subtab

Figure 568. DPM Special Effects – Advanced Effect – Shadow Crop Subtab



Parameters are organized in the following categories:

- **STATE** – values include:
 - **UseImageCrop** – crop values of the shadow match the crop values used for the primary image.
 - **UseShadow Crop** – the edges of the drop shadow can be given crop values that are different from the primary image.
- **PATH** – selection of path type such as curve, linear, or S-linear.
- **SHADOW CROP** – parameters that adjust the drop shadow edges.
- **CROP SOFTNESS** – parameters that adjust the softness of the drop shadow edges.


Note For a detailed explanation of the parameters on the **Shadow Crop** subtab, refer to the Kayak User Manual.

DPM Special Effects – Advanced Effect – Output Recursive Subtab

Parameters on the **Output Recursive** subtab add a trail to the keyer. To access the parameters on this subtab:

- From the **Special Effects** tab, click **ADVANCED EFFECT** from the **TYPE** drop-down list
- Click the **Output Recursive** subtab

Figure 569. DPM Special Effects – Advanced Effect – Output Recursive Subtab



Parameters are organized in the following categories:


- **PATH** – selection of path type such as curve, linear, or S-linear.
- **OUTPUT RECURSIVE** – parameters that apply the trail effect to a keyer as well as mode and layering mode.
- **STROBE** – parameters that apply a strobe effect to the keyer.
- **APPEARANCE** – parameters that affect the appearance of the keyer.

DPM Special Effects – Advanced Effect – Light Path Subtab

Parameters on the **Light Path** subtab are used in conjunction with the parameters on the **Light Sources** subtab. To access the parameters on this subtab:

- From the **Special Effects** tab, click **ADVANCED EFFECT** from the **TYPE** drop-down list
- Click the **Light Path** subtab

Figure 570. DPM Special Effects – Advanced Effect – Light Path Subtab



Parameters are organized in the following categories:

- **SOURCE** – sources can include four light sources.
- **AMBIENT SHADING** – parameters that adjust the ambient shading of the effect.
- **AMBIENT PATH** – selection of path type such as curve, linear, or S-linear.
- **POS/ROT PATH** – parameters that adjust the position and rotation of the effect's path.
- **ATTRIB PATH** – selection of path type.


Note For a detailed explanation of the parameters on the **Light Path** subtab, refer to the Kayak User Manual.

DPM Special Effects – Advanced Effect – Light Sources Subtab

Parameters on the **Light Sources** subtab allow simulated lighting from up to four light sources. To access the parameters on this subtab:

- From the **Special Effects** tab, click **ADVANCED EFFECTS** from the **TYPE** drop-down list
- Click the **Light Sources** subtab

Figure 571. DPM Special Effects – Advanced Effect – Light Sources Subtab



Parameters are organized in the following categories:

- **SOURCE** – sources can include up to light four sources.
- **LIGHT** – on/off mode.
- **FLARE** – parameters that adjust the ratio and intensity of flare suppression applied to the effect.
- **POSITION** – parameters that adjust the position of the light on the X, Y, Z axes.
- **ROTATION** – parameters that adjust the rotation of the light on the X, Y, Z axes.
- **APPEARANCE** – parameters that manipulate the appearance of the light.
- **LIGHT COLOR** – parameters that manipulate the color of the light.
- **FLARE COLOR** – parameters that adjust the flare color of the light.


Note For a detailed explanation of the parameters on the **Light Sources** subtab, refer to the Kayak User Manual.

DPM Delete Dialog Box

Functions and parameters in the **DPM Delete** dialog box (Figure 572) include:

- **DPM EFFECT** – the associated DPM effect as seen in the **SWITCHER EFFECTS** list.
- **ASSOCIATE NEW DPM** – associates the listed switcher effects with a new DPM effect in the **DPM EFFECTS** list.
- **DELETE ALL Associated Switcher Effects** – deletes all associated switcher effects as listed in the **SWITCHER EFFECTS** list.
- **SWITCHER EFFECTS** – switcher effects that are associated with the DPM effect and are marked for deletion.
- **DPM EFFECTS** – list of DPM effects for reassignment.
- **Close** button – closes the dialog box.

Figure 572. DPM Delete Dialog Box



Keying

Keying inserts part of one picture into another to create a composite picture. Keying involves three signals:

- Background
- Key cut, used to specify where to cut a hole in the background

- Key fill, used to fill the hole in the background

The fill can be an incoming video signal or it can be an internally generated matte fill. A separate key cut input signal is not necessarily required for keying. The Ignite system supports:

Key	Function
Luma	Uses the luminance values in a layer to determine the transparency of that layer.
Luma-Linear	The gain is approximately one, preserving the shaping of key source edges. Linear keying using anti-aliased sources produces smooth key edges
Additive	Creates a composite image from two complementary video signals that have already been shaped by multiplication with a key signal
Chroma	Renders a specific color in a layer transparent.
Preset Pattern	Uses a preset pattern

Key Setup Controls

Available keying setup controls are:

Luma	Luma-Linear	Additive	Chroma				Preset Pattern
			Key Control	Primary Suppression	Secondary Suppression	Miscellaneous	
Matte	Matte	Matte	Matte				
Mask	Mask	Mask	Mask				
Invert	Invert	Invert	Invert	Invert	Invert	Invert	
Matte Fill	Matte Fill	Matte Fill	Matte Fill	Matte Fill	Matte Fill	Matte Fill	Matte Fill
			FGD Fade	FGD Fade	FGD Fade	FGD Fade	
			Cursor				
	Auto		Auto				
	Clip Hi/Lo		Clip Hi/Lo				
Clip	Clip	Clip	Clip				
Gain	Gain	Gain	Gain				
Opacity	Opacity	Opacity	Opacity				
			Output	Output	Output	Output	
				Luma	Luma		
				Chroma	Chroma		
				Flare Suppr	Second Suppr		
				Hue	Hue		
				Selection	Selection		
				Flare S.			
					Angle		
							Wipe Effect
							Size
Size Pos/Size	Size Pos/Size	Size Pos/Size	Size Pos/Size				
Reset/Position	Reset/Position	Reset/Position	Reset/Position				
						Shadow	

Luma	Luma-Linear	Additive	Chroma				Preset Pattern
			Key Control	Primary Suppression	Secondary Suppression	Miscellaneous	
						Coring	
						Fringe	
							Border/Width
							Border/Opacity
							Soft/Softness
							Border/Symmetr

Key Control Signal Adjustment

During keying, the selected key cut signal can be converted into a key control signal. It is the key control signal that actually cuts the hole in the background video. Adjusting the key control signal (Clip and Gain) is essential in the keying process. The art of setting up a good key is to use just enough Gain to suppress any imperfections in the incoming key signals. Setting Gain too high can cause ragged key edges.

The Ignite system provides two methods for adjusting the key control signal, Clip and Gain, and Clip Hi and Clip Lo. Note that the same basic keying process is controlled by either of these methods.

Clip and Gain

The Clip and Gain operation selects a threshold of the selected key cut video that will be used to cut the hole in the background video. Clip controls the threshold, and Gain controls the softness of the key edges and any translucent areas. High portions of the key cut signal specifies what video is retained, and low portions determine what video is removed. Intermediate levels specify a soft blend of the background and fill video.

Clip Hi/Lo

Clip Hi/Lo is available on both the [Luma-Linear Key Setup Dialog Box](#) (page 523) and the [Additive Key Setup Dialog Box](#) (page 526). With Clip Hi/Lo, two thresholds are established. The upper threshold specifies at what point video will be completely removed from the background, and the lower threshold determines at what point background video will be retained completely intact.

In this mode, Gain changes when either control is adjusted. The difference between the upper and lower keying thresholds is equivalent to gain:

- $\text{Clip Hi} = \text{Clip} + \text{Gain}/2$
- $\text{Clip Lo} = \text{Clip} - \text{Gain}/2$

Clip Hi/Lo control is more appropriate for low gain keys, to enable independent control of the two thresholds. For example, when adjusting a linear key the operator wants to control where the fill becomes opaque

(Clip Hi) and where the fill becomes transparent (Clip Low). In Clip Hi/Lo mode adjusting the point of opacity does not change the point of transparency, and vice versa.

Clip, Gain, and Clip Hi/Lo adjustments always interact. Changing one always results in changes to two other values. Changing Clip Hi/Lo changes both Clip and Gain, not just Gain.

Opacity

The opacity of a key is adjustable. When opacity is reduced below 100% some background video is allowed to show through areas where it is normally excluded. Key opacity is an adjustment to the overall intensity of the key, and is separate from Clip and Gain controls. Note that a common mistake is to set opacity to zero and forget the adjustment was made, which can cause confusion later when that key is selected but not visible.

Invert

Keys can be inverted, causing holes to be cut in the background where a normal key retains the background, and vice versa. Key invert makes the white areas of the key cut signal produce transparency, and the black areas produce opacity, the opposite of a standard key.

Matte Fill

Serves to select a color matte as a fill signal for the respective key in place of the Fill bus signal.

Key Size

Key size allows the key cut signal to be narrowed slightly. This can greatly enhance self keys and chroma keys that have been reshaped.

Key Positioning

Key positioning allows slight adjustment of the horizontal position of the key cut signal relative to the key fill signal. This is useful if the timing of the two signals at the switcher inputs are not matched properly. This is generally only a problem if the cut or fill follow analog paths from source to switcher or if the source has video/key timing adjustments which have been set to compensate for other delays within the facility.

Chroma Key Control Signal Adjustment

The terms foreground and background are often a source of confusion when used for chroma keys. Foreground refers to the people or objects in a chroma key scene that are in front of the colored backdrop. Background refers to the scene that will replace the backing color (same as a linear or

luminance key) in the final picture. Background does not refer to the backdrop of the foreground scene.

Coring

When noise exists in areas that are supposed to be transparent, it can appear in the background portion of the keyed composite. To help reduce this video noise in chroma keys, when luminance signal pixels are below the adjustable threshold after primary suppression, Coring replaces them with black. In other words, to eliminate the noise resulting from incomplete suppression, Coring replaces the noisy black areas outside the shaped fill with clean black before it is summed.

While coring can improve some keys, it can easily be over done. Coring thresholds much above black will affect dark grays that are actually part of the foreground subject, making the chroma key composite look unnatural.

Flare Suppression

Flare suppression can be used to compensate for backing color reflected onto foreground objects, or for lens flare (backing color reflections within the camera lens). In these cases, the foreground object will take on a slight greenish or bluish tint. Flare suppression subtracts a slight amount of the primary suppression color from the foreground.

Primary (Color) Suppression

Primary suppression is the most critical chroma key parameter, and the easiest to set. Auto Setup should take care of this, but manual adjustments can be made if desired. Primary color suppression replaces the old backing color with black before replacing it with the new background video. It usually has a very low selectivity and therefore suppresses a wide range of colors. The goal is to suppress as much of the backing color as possible without affecting foreground regions.

Note If primary suppression is set wrong, it is impossible to achieve a good chroma key with the other controls.

Secondary (Color) Suppression

The goal of secondary suppression is to restore the natural color of the foreground object. Secondary suppression is essentially a second chroma keyer that is intended to improve the color of translucent areas (e.g., glass or smoke) or fine detail near the edge of a foreground subject (e.g., hair). These areas can take on some of the backing color. Much less secondary suppression is needed than is used for primary suppression, because the foreground color is only partially corrupted by the backing color. Because there is a mixture of backing color and foreground color, the secondary suppression Hue and the direction (Angle) will be different from primary suppression.

Primary and secondary suppression adjustments are used to select the hue to be replaced and for adjusting the luminance and chrominance levels in the areas of the picture where suppression is applied. In general, medium to high selectivity values will be used.

Note If FGD Fade has been applied, it is unlikely enough edge detail will remain to use secondary color suppression.

FGD Fade

FGD Fade is useful when shading variations exist in the backing color. A better alternative, if time permits, is to adjust the lighting on the set to even out the backing color. This may improve the key so that FGD Fade is not needed. FGD Fade helps with backing color suppression at the expense of a harder looking key with more noticeable edge artifacts. A drawback of FGD Fade is loss of detail in the keyed edge. For example, smoke and hair in the foreground will probably be lost.

Key Setup Dialog Boxes

The **KEY Setup** dialog box is the interface used to select and configure a **KEY MODE: Luma, Luma-Linear, Additive, Chroma, or Preset Pattern**. Each key mode selection accesses the additional dialog boxes necessary to completely configure the key. When finished:

- **Save** button – saves the current parameters and closes the dialog box.
- **Close** button – closes the dialog box without saving changes.

Luma Key Setup Dialog Box


A luminance key uses the luminance of an incoming source to specify where to cut the hole in the background. A matte fill key is a type of luminance key. Luminance keying is typically done on sources that do not have an accompanying key cut signal, like a video camera. The key cut signal must be generated from the incoming video signal, using clip and gain controls. When only one source is used for both key cut and key fill, the same key source signal is multiplied by the key cut signal to create the key fill, and then the signals are summed.

The **Luma** Key setup dialog box ([Figure 573](#)) includes:

- Parameter settings for **Clip, Gain, Opacity, Size, and Position**. These parameters are set via either slider or typing in the respective text box.
- On/off toggles for **Invert** and **Matte Fill**
- **Reset** – resets parameters to the default settings:
 - Clip – 50%
 - Gain – 100%

- Opacity – 100%
- Size – 0%
- Position – 0%
- **Clip Hi/Lo** – toggles between Clip/Gain mode and Clip Hi/Lo mode. The Clip/Gain sliders and label text will change to reflect this.
- Button access to both the **Mask Setup** dialog box (refer to [Mask Setup Dialog Box on page 533](#)) and the **Matte Setup** dialog box (refer to [Matte Setup Dialog Box on page 534](#)).
- **Save** button – saves the changes and closes the dialog box.
- **Close** button – closes the dialog box without saving changes.

Figure 573. Luma Key Setup Dialog Box



Luma-Linear Key Setup Dialog Box

A linear key typically uses separate key cut and key fill input signals that are intended to be used for linear keying. The key cut and key fill are usually anti-aliased (soft edged) shaped signals created by a character generator or graphics system. There may also be translucent areas intended to allow some background to show through the key (watermarks). The level of the key cut signal determines where and how deeply the hole will be cut into the background. The intended soft edge and translucency of the key can then be faithfully reproduced.


The **Luma-Linear** Key setup dialog box ([Figure 574](#)) includes:

- Parameter settings for:
 - **Clip**
 - **Gain**
 - **Opacity**
 - **Size**
 - **Position**

These parameters are set via either slider or by typing in the respective text box.

- **Invert** – on/off toggle
- **Matte Fill** – on/off toggle
- **Reset** – resets parameters to the default settings:
 - Clip – 50%
 - Gain – 100%
 - Opacity – 100%
 - Size – 0%
 - Position – 0%
- **Clip Hi/Lo** – toggles between Clip/Gain mode and Clip Hi/Lo mode. The Clip/Gain sliders and label text will change to reflect this.
- **Mask Setup** – accesses the **Mask Setup** dialog box (refer to [Mask Setup Dialog Box on page 533](#))
- **Matte Setup** – accesses the **Matte Setup** dialog box (refer to [Matte Setup Dialog Box on page 534](#)).
- **Save** button – saves the changes and closes the dialog box.
- **Close** button – closes the dialog box without saving changes.

Figure 574. Luma-Linear Key Setup Dialog Box



Additive Key Setup Dialog Box


Chroma keys are set up by suppressing the backing color in the foreground scene, cutting a hole in the background, and then combining the two processed signals. When conditions are ideal, complete suppression of the backing color is possible and the hole cut in the background will match the suppressed foreground, permitting these two signals to be added successfully.

This is called an additive chroma key. When conditions do not permit adequate backing color suppression, the foreground with its backing color suppressed can be multiplied by the keying signal to prevent contaminating areas of the background outside the keyed area. This is called a multiplicative chroma key.

The **Additive** Key setup dialog box (Figure 575) includes:

- Parameter settings for **Clip**, **Gain**, **Opacity**, **Size**, and **Position**. These parameters are set via either slider or typing in the respective text box.
- On/off toggles for **Invert** and **Matte Fill**
- **Reset** – resets parameters to the default settings:
 - Clip – 50%
 - Gain – 100%
 - Opacity – 100%
 - Size – 0%
 - Position – 0%
- **Clip Hi/Lo** – toggles between Clip/Gain mode and Clip Hi/Lo mode. The Clip/Gain sliders and label text will change to reflect this.
- Button access to both the **Mask Setup** dialog box (refer to [Mask Setup Dialog Box on page 533](#)) and the **Matte Setup** dialog box (refer to [Matte Setup Dialog Box on page 534](#)).

Figure 575. Additive Key Setup Dialog Box



A chroma key is a key that detects color (rather than luminance) in a video image and replaces it with a new background. For example, a reporter may be in a studio sitting in front of a backdrop with a blue or green backing color, and the new background can be a mountain scene. The completed chroma key consists the mountain scene replacing the backing color, creating the illusion that the reporter is sitting in front of the mountain.

Note Setting up a successful chroma key involves more adjustments than other keys. However, no amount of adjustment can overcome problems caused by an improperly set up studio chroma key scene.

The **Chroma** key mode setup dialog box (Figure 576) includes setup tabs for:

- **Key Control** – accesses the **Key Control** setup dialog box (refer to [Chroma Key Control Setup Dialog Box on page 527](#))
- **Primary Suppression** – accesses the **Primary Suppression** setup dialog box (refer to [Chroma Key Primary Suppression Setup Dialog Box on page 529](#))
- **Secondary Suppression** – accesses the **Secondary Suppression** setup dialog box (refer to [Chroma Key Secondary Suppression Setup Dialog Box on page 530](#))
- **Miscellaneous** – accesses the **Miscellaneous** setup dialog box (refer to [Chroma Key Miscellaneous Setup Dialog Box on page 532](#))

Chroma Key Control Setup Dialog Box

The **Key Control** setup dialog box includes:

- Parameter settings for –
 - **Clip**
 - **Gain**
 - **Opacity**
 - **Size**
 - **Position**

These parameters are set via either slider or by typing in the respective text box.

- **Invert** button – on/off toggle.
- **Matte Fill** button – on/off toggle.
- **FGD FADE** – on/off toggle.
- **Cursor** – accesses the auto chroma key cursor dialog box (Figure 577). General functions of the **Cursor** dialog box include:
 - Left-click and drag to position the cursor over the color to be keyed out within the dialog box.

Note The position of the cursor in the **Cursor** dialog box is seen on the preview monitor of the current M/E.

- Right-click and drag to move the entire dialog box to the desired location.
- Left-click the dialog box a second time to close the dialog box.

Note The aspect ratio of dialog box changes depends on whether the current video mode is 4:3 or 16:9.

- **Auto** – selects the current color under the cursor.
- **Clip Hi/Lo** – toggles between Clip/Gain mode and Clip Hi/Lo mode. The Clip/Gain sliders and label text change to reflect the toggle state.
- **Mask Setup** – accesses the **Mask Setup** dialog box (refer to [Mask Setup Dialog Box on page 533](#)).
- **Matte Setup** – accesses the **Matte Setup** dialog box (refer to [Matte Setup Dialog Box on page 534](#)).
- **Save** button – saves the changes and closes the dialog box.
- **Close** button – closes the dialog box without saving changes.

Figure 576. Chroma Key Control Setup Dialog Box





Figure 577. Cursor Dialog Box



Chroma Key Primary Suppression Setup Dialog Box

The **Primary Suppression** setup dialog box adjustments (Figure 578) should be set while looking at the foreground. Ideally the backing color appears as a small dot on the vector scope and a perfectly flat line on the waveform display; but this never occurs due to set lighting variations, shadows, etc. Therefore, pick the best suppression for the overall look of the key. Adjust Hue, Selectivity, Chroma, and Luma primary suppression to eliminate the backing color.

Figure 578. Chroma Primary Suppression Setup Dialog Box



The Primary Suppression setup dialog box includes:

- Luma** suppression – adjustments may be necessary if shading is visible in the backing area with FG Only selected, or if the shading adversely affects the background image. Primary Luma suppression is hardly ever desired when FGD Fade is on. To adjust, increase Luma suppression and observe the backing color move toward black. You want to make the backing color just black. Increasing this control too much will make the chroma key hard and noisy. When not enough, highlights will be added to the background. Note that incomplete luminance suppression is not necessarily bad. The highlights added to the background will match the shading on the backing wall, adding natural shadows and perhaps eliminating the need to add artificial shadows.

- **Chroma** – suppression can be set accurately with Auto Setup. To adjust, increase Chroma suppression and observe the backing color dot on the vector scope move toward the center. You want to center it exactly, so no chroma exists in the backing area. 100% chroma suppression is the correct setting for all chroma keys. At this point, you will probably see a line through the center of the vector scope. With increased selectivity, this line will become an arc.
- **Flare S.** – (suppression) adds a small amount of color to the entire foreground image to cancel the splash or flare. Typically less than 2% of the backing color is needed to neutralize the flare.
- **Hue** – can be set accurately with Auto Setup. Hue should center on the primary color of the backing area of the foreground scene. Depending on where Luma and Chroma primary suppression are set, adjusting Hue may not make any noticeable change on the scene. Chroma suppression should be preset to 100% and Luma set to 0%. Hue can then be tuned to remove the backing color.
- **Selection** – selectivity may need to be increased if there are colors in the foreground image that are being suppressed. Selectivity should be set as low as possible without including colors that should not be suppressed. For example, when keying on green, a greenish yellow shirt might be affected by the suppression. If so, adjust the selectivity high enough to reject that color. Too high a selectivity is one of the classic causes of a noisy key. If the foreground subject is stationary, consider using a force mask instead of increasing selectivity.
- **Save** button – saves the changes and closes the dialog box.
- **Close** button – closes the dialog box without saving changes.

Chroma Key Secondary Suppression Setup Dialog Box

The **Secondary Suppression** dialog box adjustments ([Figure 579](#)) are used to select the hue to be replaced and for adjusting the luminance and chrominance levels in the areas of the picture where suppression is applied. Adjust secondary suppression Hue and Selectivity so that the translucent area is affected, but opaque areas of the foreground are not. The final hue will lie somewhere between the backing color (primary suppression hue) and the uncorrupted foreground color.

Figure 579. Chroma Secondary Suppression Setup Dialog Box



Note When adjusting, it is helpful to turn the secondary Chroma Suppression to maximum, and the secondary Suppression Angle to produce an unnatural color in the affected area. This makes the changes to secondary suppression more obvious.

- **Luma** – increase secondary suppression to balance lightness of the translucent and opaque areas.
- **Chroma** – decrease secondary suppression for the best match between corrupted (translucent) and uncorrupted (opaque) areas. Interaction between secondary suppression Angle and Chroma suppression may require repeating these adjustments.
- **Angle** – adjust the secondary angle so that changing secondary Chroma suppression moves the color in the desired direction. You are trying to match the color of the translucent areas to an opaque (uncorrupted) area of the foreground subject.
- **Selection** – selectivity should be kept as wide as possible. Only narrow (increase its value) selectivity if you cannot avoid changing opaque areas of the foreground.
- **Save button** – saves the changes and closes the dialog box.
- **Close button** – closes the dialog box without saving changes.

Chroma Key Miscellaneous Setup Dialog Box

The **Miscellaneous** setup dialog box (Figure 580) includes:

- **Clip** and **Gain** – appropriate for high gain keys, to easily adjust where the relatively hard transition from background to fill occurs. In this mode, changing the Clip control moves the threshold up and down without affecting Gain, which is adjusted separately with its own Gain control.

Figure 580. Chroma Miscellaneous Setup Dialog Box



- **Opacity** – adjustment to the overall intensity of the key, separate from Clip and Gain controls.
- **Coring** – to help reduce video noise in chroma keys, when luminance signal pixels are below the adjustable threshold after primary suppression.
- **Fringe** – to restore color to the gray portions of the foreground color resulting from secondary suppression adjustments. This control is only active when secondary suppression is on.
- **Save** button – saves the changes and closes the dialog box.
- **Close** button – closes the dialog box without saving changes.


Preset Pattern Setup Dialog Box

A preset pattern uses a wipe pattern generator, rather than an incoming key cut signal to define the hole cut in the background. Key clip and gain controls are not available for a preset pattern, but controls over the location, size, border, opacity, and edge softness are available.

The **Preset Pattern** Key setup dialog box ([Figure 581](#)) includes:

- **Wipe Effect** selection
- Parameter settings for **Size** and **Opacity**. These parameters are set via either slider or typing in the respective text box.
- On/off toggle for **Matte Fill**.
- Border **Width** and **Opacity** set via either slider or typing in the respective text box.
- **Softness** and **Symmetr** (Symmetry) set via either slider or typing in the respective text box.
- **Pattern Source** selection via the drop-down list box
- Button access to the **Matte Setup** dialog box ([Matte Setup Dialog Box on page 534](#)).

Figure 581. Preset Pattern Key Setup Dialog Box




Mask Setup Dialog Box

Masking defines areas that are protected from keying or always key. The shape of the mask can originate from a wipe pattern generator or by a selected mask signal (typically a key fill signal delivered via the Utility bus). The mask signal can be a frozen page of video or a key fill. Complex mask shapes are often easier to draw by hand than to create with multiple wipe patterns.

The **Mask Setup** dialog box (Figure 582) includes:

- **MASK PATTERN SOURCE** selection for –
 - **Wipe**
 - **Key Wipe**
 - **Box Wipe**
 - **Utility Bus**
- **Wipe Effect** selection list for **Wipe2** and **Key Wipe**
- Key Mask parameter for **Size** set via either slider or typed into the respective text box.
- **Force** – on/off toggle
- **Inhibit** – on/off toggle
- **Soft** – on/off toggle
- When selected, softness parameters for **Softness** and **Opacity** set via either slider or typing in the respective text box.

Figure 582. Mask Setup Dialog Box




Matte Setup Dialog Box

The **Matte Setup** dialog box enables keyer matte configuration and also the selection of the wipe effect for key wipe and wipe2 pattern source. Select the key matte pattern source and adjust the parameters accordingly.

The **Matte Setup** dialog box (Figure 583) includes:

- **MATTE PATTERN SOURCE** selection for –
 - **Wipe**
 - **Key Wipe**
 - **Box Wipe**
 - **Utility Bus**
- **BASE SOURCE Wipe Effect** selection list for **Wipe2** and **Key Wipe**
- **BASE SOURCE Matte** parameters for **Hue**, **Sat.** (Saturation), and **Lum.** (Luminance) set via either slider or typed into the respective text box.
- **BASE SOURCE Border** parameters for
- **WASH SOURCE** parameters for **Hue**, **Sat.** (Saturation), and **Lum.** (Luminance) set via either slider or typed into the respective text box.

Figure 583. Matte Setup Dialog Box



Transitions

Video transitions transpose two video images from two different internal/external video devices (cameras, VTRs, CGs, Still Stores, etc.). The Ignite Digital Picture Manipulator (DPM) function provides transition control over picture position, shape, luminance, chroma key, luma, and motion. Using inputs from different video input devices (character generators, still

stores), the DPM provides more interesting transitions from one video frame/scene to another rather than just switching scenes. Examples include picture-in-picture, image-squeeze, real-time horizontal and/or vertical resizing effects, fading or dissolving the frame, wiping one frame over another, flipping the frame and simulating a camera lens opening and closing (iris effect). The Ignite DPM can be used to combine multiple DPM images to create a sequence – a continual progression of effects.

Note The Ignite Digital Picture Manipulator (DPM) does not create the effects but rather transposes the images from different input devices (character generators, still stores).

The five available transition types include:

Wipe	Where the switch from one picture to another is by moving a geometric form (circle, line, arrow) through the screen.
Fade	(fade-out) where a full picture dissolves to a black screen (fade-in) where a black screen dissolves to a full picture
Cross-Fade	Involves two pictures where one picture fades in while another picture fades out.
Mix	A transition from one picture to another where the new picture fades in as the existing picture fades out. During a standard mix transition, a superimposition of both pictures at a lower intensity is visible. The KayakDD system allows mixing from one background to another and to mix up to four separate keys on or off over a background. Background and key mixes can be done separately or simultaneously.
Cut	One image is instantly switched to another without using any effects.

Note The transition effects themselves are selected from a drop-down box at the bottom left corner of each M/E bank.

M/E Properties Dialog Box

Accessed from the **Event Timeline** via right-click on a switcher icon (*Build a TME on page 46*) and selecting **Properties**, the **M/E Properties** dialog box (*Figure 584*) includes:

- **Start Time** – sets the start time for the TME item.
- **End Time** – sets the end time for the TME item.

Note For the following, the available selections are listed automatically based on current system configuration.

Note For the following, click the text portion in the lower half to access/select a source.

- **P/P, M/E 1, M/E 2, or M/E 3** selection to setup respective properties for the switcher selected on the **Event Timeline**. Available M/E options are –
 - **Aux** – source selection to route a source to a selected Aux bus.
 - **M/E Settings**
 - **PGM, PVW** – selects whether the transition affects PGM or PVW. The selected button highlights yellow.
 - **Util 1, Util 2** – selects the respective Utility bus. Clicking on the text in the lower half will popup a dialog to select the source for that bus.
 - **Keyer 1 – 4**
 - **Fill**

K1, K2, K3, K4 – selects which keyers are on for the selected TME. Clicking the DPM icon determines whether to turn it on for this keyer. Refer to [Figure 584](#) and [Keyer on page 486](#). For both keyers and DPMs –

 - Gray – off
 - Yellow – on
 - Red (keyers only) – use current
 - Green – toggle between on and off states (available only when **None** is selected in the **Effects List**)
 - **Cut**

K1, K2, K3, K4 – selects which keyers are on for the selected TME. Clicking the DPM icon determines whether to turn it on for this keyer. Refer to [Figure 584](#) and [Keyer on page 486](#). For both keyers and DPMs. –

 - Gray – off
 - Yellow – on
 - Red (keyers only) – use current
 - Green – toggle between on and off states (available only when **None** is selected in the **Effects List**)
 - **Effects List** – lists the available effects for the respective TME. Selecting **None** from this list enables keyer toggling without affecting transition types already in prep by TMEs.
- Routes can be assigned when **None** is selected in the **Effects List**. This configuration state is used to either:
- Enable a user to hot punch sources on the PGM bus
 - Change keyer routes without opening the **Master Routing** dialog box

- **Duration** – sets the duration when **Auto** is selected.
- **Cut** – sets the transition as a cut.
- **Auto** – sets the transition to auto.
- **Close button** – closes the dialog box without saving changes.
- **Save button** – saves the current parameters and closes the dialog box.

Figure 584. M/E Properties Dialog Box




Operation

Customize Switcher Bank

Customize Switcher Page

1. Click the **Page Tab** to select the page for customization.
2. In the lower right of the **Effects Bank**, click the **Source Setup** icon (Figure 585).

Figure 585. Sample Effects Bank




Source Setup icon

Note For all names, abbreviations, and colors, use established standards and consistent techniques and practices. Refer to *Standardization* on page 577

3. The **Source Setup** dialog box (Figure 586) appears. In the **PAGE NAME** box, type a name for the page using established standards and consistent techniques and practices. Refer to *Standardization* on page 577.

Figure 586. Source Setup Dialog Box



864x-sc319-r0

4. In the **# of BUTTONS** box (Figure 586), click or type the number of input buttons for the page.
5. Click a source. The source highlights and a **Source** button (Figure 587) appears in the **Source Configuration** panel above the **Undo** button.

Figure 587. Source Setup Dialog Box



6. Click the **Source** button. The **Configure Source** dialog box (Figure 588) appears.

Figure 588. Configure Source Dialog Box



- Using the **Configure Source** dialog box selections and the **Next** and **Previous** buttons, configure the page.

Note Use the Next and Previous buttons to move along the page from source to source

- Click **OK** when complete.

Set Button Properties

- In the lower right of the **Effects Bank**, click the **Source Setup** icon ([Figure 589](#)).

Figure 589. Sample Effects Bank



Note For all names, abbreviations, and colors, use established standards and consistent techniques and practices. Refer to *Standardization* on [page 577](#)

- The **Source Setup** dialog box ([Figure 590](#)) appears.

Figure 590. Source Setup Dialog Box



3. From **EXTERNAL SOURCES**, click the source to be changed, and then click **Source**. The **Configure Source** dialog box (Figure 591) appears.

Figure 591. Source Configuration Dialog Box



Note Though [Step 4](#) enables changing the Source Name, to easily identify which physical input the source is connected to, it is recommended that the default name (Input #) be left as is. To accept the default name, go to [Step 5](#).

Note For all names, abbreviations, and colors, use established standards and consistent techniques and practices. Refer to *Standardization on page 577*.

Note In [Step 4](#) and [Step 5](#), if only updating or changing the Source Name or the Source Title, press Enter to Save and Close.

4. In the **Source Name** box, type the button name using established standards and consistent techniques and practices. Refer to *Standardization on page 577*.
5. In the **Source Title** text box, type an input text label.
6. From **Button Color**, click a color.
7. From **Button Decal**, click a decal.
8. If the input requires a key signal, like a CG or SS device, from **Key Sources**, click the appropriate key source.

Note When selected, links the key source with the fill source.

9. Click **Save**.
10. Once button customization is complete, click the **Close** button. The **Button Configuration** dialog box closes.

Switcher Source Setup

1. Click the **Page** tab to indicate the page to customize.
2. In the lower right of the Effects Bank, click the **Source Setup** icon ([Figure 592](#)).

Figure 592. Sample Effects Bank



3. The **Source Setup** dialog box ([Figure 593](#)) appears.

Figure 593. Source Setup Dialog Box



4. From either **INTERNAL SOURCES** or **EXTERNAL SOURCES**, right-click, hold, and drag the desired source to an available position on the Switcher, and then release.
5. Click the **Close** button.

Scalar Objects

The large frame switcher supports the use of up to four scalars per M/E that can be used for up-conversion of SD sources to HD formats. The MatchDef™ dual video input scalars enable the user to match SD sources into an HD production or HD sources into an SD production. Users can associate a video format with a scalar object and cross match different HD formats as well without sacrificing critical production elements such as keyers.

Scalars also enable the user to set up, modify, or view the following MatchDef properties of the scalar object:

- Current scalar objects and select a different object (Refer to [To select a different scalar object on page 549](#))
- Aspect ratio conversion methods (Refer to [To select an aspect ratio conversion method on page 550](#))

- Color background settings (Refer to [To set the color background of the scalar object on page 551](#))
- Crop area settings (Refer to [To set the crop area of the scalar object on page 552](#))
- All current settings reset to default setting (Refer to [To reset all parameters of the scalar object on page 552](#))

Associate a Video Format with a Scalar Object


1. From the P/P switcher bank, click the **Setup** icon (Figure 594). The **General Setup** dialog box appears (Figure 595).

Figure 594. P/P Switcher Bank




General Setup Icon

Figure 595. General Setup Dialog Box - Mainframe Setup




2. Click the **MatchDef™** button. The **MatchDef™ Scalar Configuration** dialog box appears (Figure 596) with a list of scalar objects.

Figure 596. MatchDef™ Scalar Configuration Dialog Box



3. Select the scalar object from the list. To enable the object, click the **Toggle On/Off** button.
4. To associate a video format with the scalar object, click the **Set Video Format** button. The **SELECT VIDEO FORMAT** list of video formats appears (Figure 597).

Figure 597. MatchDef™ Scalar Configuration Dialog Box – Select Video Format



5. Select the video format from the list and either:
 - To associate the selected video format with the scalar object, click **OK**.
 - To cancel the video format selection and return to the **MatchDef™ Scalar Configuration** dialog box, click **Cancel**.

Modify MatchDef™ Properties of a Scalar Object


1. From the P/P switcher bank, click the **Setup** icon (Figure 598). The **General Setup** dialog box (Figure 599) appears.

Figure 598. P/P Switcher Bank




General Setup Icon

Figure 599. General Setup Dialog Box – Mainframe Setup



2. Click the **MatchDef™** button. The **MatchDef™ Scalar Configuration** dialog box (Figure 600) appears with a list of scalar objects.

Figure 600. MatchDef™ Scalar Configuration Dialog Box



3. In the **SCALER CONFIGURATION** list, click a scalar object and then click the **MatchDef™** button. The MatchDef properties for the scalar object appear (Figure 601).

Figure 601. MatchDef™ Scalar Configuration Dialog Box – MatchDef™ Configuration




4. To set up, modify, or view current scalar object MatchDef settings, perform any of the following optional procedures:

To select a different scalar object

- a. Click the **Scalar 1** (2, 3, 4 etc.) button (Figure 601). The list of scalar objects (Figure 602) appears:

Figure 602. MatchDef™ Scalar Configuration Dialog Box – List of Scalar Objects




- b. Select a different scalar object from the list and either:
- Click **Select** to associate the selected scalar object as the current object, .
 - Click **Cancel** to cancel the scalar object selection and return to the **MatchDef™ Scalar Configuration** dialog box.

To select an aspect ratio conversion method

- a. Click the **Asp. Ratio Conv.** button (Figure 601). The **ASPECT RATION CONVERSION** list (Figure 603) appears.

Figure 603. MatchDef™ Scalar Configuration Dialog Box – List of Aspect Ratio Conversions



- b. Select one of the following aspect ratio conversions from the list:
 - **FULLSCREEN 16 9 TO FULLSCREEN 16 9**
 - **THROUGH**
 - **FULLSCREEN 4 3 TO PILLARBOX 16 9**
 - **FULLSCREEN OR LETTERBOX 4 3 TO 16 9**
 - **FULLSCREEN 16 9 TO LETTERBOX 4 3**
- c. Either:
 - Click **OK** to associate the selected aspect ratio conversion mode to the current scalar object.
 - Click **Cancel** to cancel the aspect ratio conversion mode selection and return to the **MatchDef™ Scalar Configuration** dialog box.

To set the color background of the scalar object

- a. Click the **Color Background Set** button (Figure 601). The color background parameters appear in the right side of the dialog box:
 - **Hue**
 - **Chroma**
 - **Lum**

b. To manipulate the color background parameters, either:

- Click and drag the control knobs left or right.
- Use the **Up/Down** arrow keys.
- Type a value directly in the text box.

After parameter selection is made, parameters appear in the **COLOR BACKGROUND** area of the dialog box.

To set the crop area of the scalar object

a. Click the **Crop Set** button (Figure 601). The crop parameters appear in the right side of the dialog box:

- **Right**
- **Left**
- **Top**
- **Bottom**

b. Click **Crop On** to turn on the crop settings.

c. To manipulate the crop parameters, either:


- Click and drag the control knobs left or right.
- Use the **Up/Down** arrow keys.
- Type a value in the text box.

After parameter selection is made, parameters appear in the **CROP** area of the dialog box.

To reset all parameters of the scalar object

a. Click the **Default Settings** button (Figure 601). The **Default Settings Confirmation** dialog box (Figure 604) appears.

Figure 604. Default Settings Confirmation Dialog Box



b. Either:

- Click **Yes** to reset all parameters to the default setting of zero.
- Click **No** to save the current parameters.

Keyer

Note Each effects bank can have up to four layers of keys active at once; K1 through K4. Each has a corresponding button on the switcher for the program bus as well as the preview bus.

Keyer Setup Menu

Note Effects created by prepping an existing effect and adding keys to create a new effect, will be executed once and deleted immediately after use. Only permanent effects will be selectable from the main GUI drop down list indefinitely.

1. Click the **Browse Effects** button (Figure 605). The **Effects List** dialog box (Figure 606) appears.

Figure 605. Browse Effects Button



Figure 606. Effects ListDialog Box – Effects Controls



2. In the **Effect List** dialog box click **Add**.

- From **Transition**, click the **Key** number button (**Key 1**, **Key 2**, **Key 3**, or **Key 4**) for the **Add**. The selected button highlights (Figure 607).

The **Key** button has three different states. Each click advances one state:

- Gray – keyer will turn off
- Yellow – keyer will turn on
- Red – no change to the keyer On Air state

Figure 607. Effects List Dialog Box – Transition Key Selection



- From **Transition**, click the selected keyer **Access** button. A **Keyer Setup** dialog box (Figure 608 and Figure 609) appears where:

Key	Function
Luma	Uses the luminance values in a layer to determine the transparency of that layer.
Luma-Linear	The gain is approximately one, preserving the shaping of key source edges. Linear keying using anti-aliased sources produces smooth key edges
Additive	Creates a composite image from two complementary video signals that have already been shaped by multiplication with a key signal
Chroma	Renders a specific color in a layer transparent.
Preset Pattern	Uses a preset pattern

Note Chroma setup has four separate tabs for chroma settings (Figure 609). To adjust individual settings, click the respective tab.

Figure 608. Keyer Setup – Luma, Luma-Linear, Additive, and Preset Pattern Dialog Boxes





Figure 609. Keyer Setup – Chroma Dialog Boxes



5. Use the faders inside the dialog box(es) (Figure 608 and Figure 609) to adjust levels and create any of the four types of keys as well as a preset pattern.

Note Mask and matte can also be adjusted in this dialog box.

6. Click **Save**.

Take Keyer To Air

- Click the top half (Figure 610) gray area of a keyer. The gray area changes from gray to either yellow or green.

Note Click the top half of a keyer to toggle the keyer, click the lower half of a keyer to change source routing.

Highlight colors correspond to their respective bus:

- Green for keys on the Program bus
- Yellow for keys on the Preview bus

Figure 610. Keyers On Air



Change Keyer Video Association

Note Click the top half of a keyer to toggle the keyer, click the lower half of a keyer to change source routing.

1. Click the lower half (Figure 611 black/title area) of a keyer. The **Master Routing** dialog box (Figure 612) appears.

Figure 611. Keyers On Air





Figure 612. Master Routing Dialog Box



2. From **M/E BUSES**, check that the desired key fill source (e.g., **K1-F**) button is highlighted. If not, click the desired key fill source (e.g., **K1-F**) button.
3. Click a source from either **INTERNAL SOURCES** or **EXTERNAL SOURCES** to associate with that keyer.

Note If a key fill source is already associated with the selected keyer, unless changed it remains associated.

4. Click **Close**.

Effects

Notes On Building Effects

If building an effect with just the background transition, make sure that all keyers are set to the same transition duration as the background. This applies to all switcher wipes, dissolves, and cuts. Even though the keyers

are not being turned on during the effect, they still transition at whatever frame rate is currently defined in the effect dialog.

- There are three keyer states: On, Off, and No Change. These states are identified by color:
 - Gray is off
 - Green is on
 - Red is no change.
- On the Switcher module, manual effects operation requires that after every transition an effect needs to be re-prepped for use.
 - Click an effect in the **Effects List**.
 - After taking the selected effect to air, the Switcher module defaults to **None**. It must be selected again to continue flip-flopping the video bus.
 - After building an effect, click **Effect List** to verify the effect has been added.
- Right-clicking an effect in the **Effects List** and selecting Set As Default from the shortcut menu makes that effect the default.

Create a New Effect

Note Effects created by prepping an existing effect and adding keyers to create a new effect, will be executed once and deleted immediately after use. Only permanent effects will be selectable from the main GUI drop down list indefinitely.

1. Click the **Browse Effects** button (Figure 613). The **Effects List** dialog box (Figure 614) appears.

Figure 613. Browse Effects Button



Figure 614. Effects List Dialog Box – Effects Controls



2. In the **Effects List** dialog box click **Add**.
3. Click the button(s) next to the properties for the type of effect desired.
For example, a cut is a simple preview to program transition.
 - Click **PVW**. The **PVW** button highlights. Check that **PVW Auto/Cut** button is toggled to **Cut** (Figure 615). If not, click **Auto** to toggle the button to **Cut**.

Note Cut and Auto are alternate actions of the same button. If the button shows Cut, clicking the button changes it to Auto and vice versa.

Note Selecting PGM indicates that there is no background transition. Selecting PVW indicates that there is a preview to program background transition when the effect is executed.

Note When doing a background transition, the duration set for PVW determines the duration for everything including the four keyer durations. If PVW is selected, ensure that all keyer durations are set the same as PVW. If PGM is selected, keyers can be brought on and off with independent durations.

Note For all names, abbreviations, and colors, use established standards and consistent techniques and practices. Refer to *Standardization* on page 577.

Figure 615. Effects List - PVW Cut



4. In the **Effect Name** box, enter a name using established standards and consistent techniques and practices. Refer to *Standardization* on page 577.
5. Click **Save**.

Build a Wipe

1. Click the **Browse Effects** button (Figure 616). The **Effects List** dialog box (Figure 617) appears.

Figure 616. Browse Effects Button



Figure 617. Effects List Dialog Box – Effects Controls



2. In the **Effects List** dialog box click **Add**.
3. In the **Effect Name** box, enter a wipe name using established standards and consistent techniques and practices. Refer to *Standardization on page 577*.

Note Selecting PGM indicates that there is no background transition. Selecting PVW indicates that there is a preview to program background transition when the effect is executed.

4. Click **PVW**. The **PVW** button highlights.

Note When doing a background transition, the duration set for PVW determines the duration for everything including the four keyer durations. If PVW is selected, ensure that all keyer durations are set the same as PVW. If PGM is selected, keyers can be brought on and off with independent durations.

Note Mix and Wipe are alternate actions of the same button. If the button shows Mix, clicking the button changes it to Wipe and vice versa.


5. Check that **PVW Mix/Wipe** button is toggled to **Wipe** (Figure 618). If not, click **Mix** to toggle the button to **Wipe**.

Figure 618. Effects List Dialog Box – Wipe Effects List




6. In **Transition**, enter the desired transition rate.
7. Click the **Wipe Effects Access** button (Figure 618). The **Wipe Setup** dialog box (Figure 619) appears.

Figure 619. Wipe Effect Setup Dialog Box



8. Click **Add**.
9. From the **WIPE EFFECT** list, click the newly added **Unnamed Effect**.
10. Click **Edit**. An **Edit Effect TME Caution** dialog box appears (Figure 620). Click **OK**.


Figure 620. Edit Effect - TME Caution



Note For all names, abbreviations, and colors, use established standards and consistent techniques and practices. Refer to *Standardization on page 577*.

11. In the **Effect Name** box, enter a wipe name using established standards and consistent techniques and practices. Refer to *Standardization on page 577*.
12. In the **SELECT PATTERN** list, click the desired pattern.
13. Using the buttons and controls available in the **Wipe Effect Setup** dialog box (Figure 619), adjust the new wipe properties as desired.
14. Click **Close** to save effect and close the **Wipe Effect Setup** dialog box. A **Confirm** dialog box appears.

Figure 621. Wipe Effect Addition



15. Click **Yes**. The **Wipe Effect Setup** dialog box (Figure 622) appears.

Figure 622. Effects Definition Dialog Box



16. Either:

- a. To save and close the **Wipe Effect Setup** dialog box, click **Close**.
- b. To save but not close the **Wipe Effect Setup** dialog box, click **Save**.

Build a Cut With a Key

1. Click the **Browse Effects** button (Figure 623). The **Effects List** dialog box (Figure 624) appears.

Figure 623. Browse Effects Button



Figure 624. Effects List Dialog Box – Effects Controls



2. In the **Effects List** dialog box click **Add**. A new **Unnamed Effect** appears in the **Effects List**.
3. From the **Effects List**, click the newly added **Unnamed Effect**.
4. Click **Edit**. The **Edit** button highlights.
5. In the **Effect Name** box, enter a wipe name using established standards and consistent techniques and practices. Refer to *Standardization on page 577*.

Note Selecting PGM indicates that there is no background transition. Selecting PVW indicates that there is a preview to program background transition when the effect is executed.

6. Click **PVW**. The **PVW** button highlights.

Note When doing a background transition, the duration set for PVW determines the duration for everything including the four keyer durations. If PVW is selected, ensure that all keyer durations are set the same as PVW. If PGM is selected, keyers can be brought on and off with independent durations.

Note Auto and Cut are alternate actions of the same button. If the button shows Auto, clicking the button changes it to Cut and vice versa.

7. Check that **PVW Auto / Cut** button is toggled to **Cut** (Figure 625). If not, click **Auto** to toggle the button to **Cut**.

Figure 625. Effects Definition Dialog Box - PVW Cut



8. Click **Key 1**. The button for that Key highlights yellow (Figure 626).

Figure 626. Effects List Dialog Box – Key 1 Cut



Note It is recommended that all Key buttons be set to Cut.

Note Auto and Cut are alternate actions of the same button. If the button shows Auto, clicking the button changes it to Cut and vice versa.

9. Change **Key 2** through **Key 4** from **Auto** to **Cut** (Figure 626):
 - a. Check that **Key 2 Auto/Cut** button is toggled to **Cut** (Figure 626). If not, click **Auto** to toggle the button to **Cut**.
 - b. Check that **Key 3 Auto/Cut** button is toggled to **Cut** (Figure 626). If not, click **Auto** to toggle the button to **Cut**.

- c. Check that **Key 4 Auto/Cut** button is toggled to **Cut** (Figure 626). If not, click **Auto** to toggle the button to **Cut**.
10. Click the **Key 1 Access** button (Figure 626). The **Keyer Setup** dialog box (Figure 627) appears where:

Key	Function
Luma	Uses the luminance values in a layer to determine the transparency of that layer.
Luma-Linear	The gain is approximately one, preserving the shaping of key source edges. Linear keying using anti-aliased sources produces smooth key edges
Additive	Creates a composite image from two complementary video signals that have already been shaped by multiplication with a key signal
Chroma	Renders a specific color in a layer transparent.
Preset Pattern	Uses a preset pattern

Figure 627. Keyer Setup Dialog Box



11. Click **Luma-Linear**. Using the faders, adjust properties as necessary.
12. Click **Save**. The **Keyer Setup** dialog box closes.

Set Keyer as a DPM


Keyers can also act as DPM/DVE channels where clicking the gray area of a keyer turns on a channel of the DPM/DVE, which then fills with the

source routed to that keyer. It is designated as on air by a color highlight and a small yellow dot in the upper right hand corner (Figure 628).

Highlight colors correspond to their respective bus:

- Green with a yellow dot for keys on the DPM/DVE Program bus
- Yellow with a yellow dot for keys on the DPM/DVE Preview bus

Figure 628. Keyer as a DPM Channel



1. Click the **Browse Effects** button (Figure 629). The **Effects List** dialog box (Figure 630) appears.

Figure 629. Browse Effects Button



Figure 630. Effects List Dialog Box – Effects Controls



2. In the **Effects List** dialog box click **Add**.
3. Click **Edit**. The **Edit** button highlights.
4. In the **Effect Name** box, enter a wipe name using established standards and consistent techniques and practices. Refer to [Standardization on page 577](#).

Note Selecting PGM indicates that there is no background transition. Selecting PVW indicates that there is a preview to program background transition when the effect is executed.

5. Click **PVW**. The **PVW** button highlights.

Note When doing a background transition, the duration set for PVW determines the duration for everything including the four keyer durations. If PVW is selected, ensure that all keyer durations are set the same as PVW. If PGM is selected, keyers can be brought on and off with independent durations.

Note Auto and Cut are alternate actions of the same button. If the button shows Auto, clicking the button changes it to Cut and vice versa.

6. Check that **PVW Auto/Cut** button is toggled to **Cut** ([Figure 631](#)). If not, click **Auto** to toggle the button to **Cut**.

Figure 631. Effects Definition Dialog Box - PVW Cut



7. Click **Key 1**. The button for that Key highlights yellow (Figure 632).

Figure 632. .Effects List Dialog Box – Key 1 Cut



Note It is recommended that all Key buttons be set to Cut.

Auto and Cut are alternate actions of the same button. If the button shows Auto, clicking the button changes it to Cut and vice versa.

8. Click the **Key 1 DPM** button. The **Key 1 DPM** button highlights yellow (Figure 633).

Figure 633. Keyer – DPM Button



Note The Effects List dialog box DPM EFFECTS list is initially populated with placeholder names such as Dpm1, Dpm2, etc. Typically these are not actual DPM effects and should not be selected. DPMs in the list that follow the standard naming conventions have been created via Kayak switcher/Sidepanel program and represent a pre-determined DPM effect.

9. From the DPM list, click a DPM effect.
10. Click **Save**, and then click **Close**.

Associate An Effect With a Wipe or DPM Effect

To associate an effect with either a Wipe Effect or a DPM Effect:

1. Click the **Browse Effects** button (Figure 634). The **Effects List** dialog box (Figure 635) appears.

Figure 634. Browse Effects Button



Figure 635. Effects List Dialog Box – Effects Controls



2. In the **Effects List**, click the desired effect for association.
3. In either the **WIPE EFFECTS** list or the **DPM EFFECTS** list, click the desired wipe or DPM effect to associate with the effect.
4. Click **Save**.

Effects Management

Note The **Effects List** is divided into three groups: **All Effects**, **Hidden Effects**, and **Recycle Bin** (refer to [Effects Management on page 489](#)).

Access the Effects List

- Click the **Browse Effects** button ([Figure 636](#)). The **Effects List** dialog box ([Figure 637](#)) appears.

Figure 636. Browse Effects Button



Figure 637. Effects List Dialog Box – Effects Controls



Note The **Effects List** is divided into three groups: **All Effects**, **Hidden Effects**, and **Recycle Bin** (refer to [Effects Management on page 489](#)).

Sort an Effects List

1. Right-click anywhere in an **Effects List** group (**All Effects**, **Hidden Effects**, or **Recycle Bin**). A shortcut menu ([Figure 638](#)) appears.

Figure 638. Sort Group Shortcut Menu



2. On the shortcut menu, point to **Sort**, and then click either **Ascending** or **Descending** ([Figure 639](#)). That **Effects List** sub-list sorts accordingly.

Figure 639. Sort Group - Shortcut Menu - Order



Hide an Effect

Note The **Effects List** is divided into three groups: **All Effects**, **Hidden Effects**, and **Recycle Bin** (refer to [Effects Management on page 489](#)).

- To hide effects from the Switcher Module drop-down list, either (refer to [Figure 640](#)):
 - Drag and drop the effect into the **Hidden Effects** group of the **Effects List**.
 - Right-click and using the shortcut menu, move the selected effect to the **Hidden Effects** group of the **Effects List**.

Figure 640. Effects List Management



Recycle Bin

Note The **Effects List** is divided into three groups: **All Effects**, **Hidden Effects**, and **Recycle Bin**.

All deleted effects are automatically sent to the **Recycle Bin** where a user can **Clear Recycle Bin** (delete all), just like a typical Windows operation. Additionally, using shortcut menus, a user manages listed effects between the **Recycle Bin** and either the **All Effects** or **Hidden Effects** groups of the **Effects List** (Figure 640). Refer to *Effects Management on page 489*.

DPM Effects Management

DPM effects are managed from the **DPM Effect Setup** dialog box and the **DPM Delete** dialog box. Two modes of operation include: outside edit mode and edit mode.

Operations performed outside edit mode include:

- Deleting a DPM Effect ([page 575](#))
- Copying/Pasting a DPM ([page 578](#))
- Locking/Unlocking a DPM ([page 579](#))

Note Make sure that edit mode is not enabled for these procedures.

Operations performed in edit mode include:

- Creating a DPM Effect ([page 579](#))
- Modifying/Deleting Keyframes ([page 582](#))
- Using the Keyframe Playout Controls ([page 585](#))
- Positioning Keyframes on the DPM Timeline ([page 585](#))

Note Make sure that edit mode is enabled for these procedures.

Delete a DPM Effect

1. Click the **Browse Effects** button (Figure 641). The **Effects List** dialog box (Figure 642) appears.

Figure 641. Browse Effects Button




Figure 642. Effects List Dialog Box – Effects Control



2. From the **Effects List**, click an effect and then click **Edit**. The **Access DPM Effects** button (Figure 642) highlights.
3. Click the **Access DPM Effects** button. The **DPM Effect Setup** dialog box (Figure 643) appears.

Figure 643. DPM Effect Setup Dialog Box




4. From the **DPM EFFECTS** list, click a DPM effect.
5. Click **Delete**. The **Delete Effect** dialog box appears.
6. Either:
 - Click **Yes** to remove the DPM effect from the **DPM EFFECTS** list.
 - Click **No** to cancel the function.

Note Ignite deletes all keyframes in the DPM effect. Keyframes appear in the **DPM EFFECTS** list as DPMXX where XX is the register number.

If any effects are associated with the DPM effect currently selected for deletion, the **DPM Delete** dialog box (Figure 644) appears.

Figure 644. DPM Delete Dialog Box



To associate a new DPM Effect with the current DPM Effect:

- a. From the **DPM EFFECTS** list, click a DPM effect.
- b. Click **ASSOCIATE NEW DPM**. The **DPM Delete** dialog box closes.

To delete all associated switcher effects from a DPM Effect:

The associated switcher effects for the DPM effect are listed under the **SWITCHER EFFECTS** list.

- a. Click **DELETE ALL Associated Switcher Effect**. The **Delete Effect** dialog box appears.
- a. Either:
 - Click **Yes** to delete all associated switcher effects and remove the DPM effect from the **DPM Effects** list.
 - Click **No** to cancel the function and return to the **DPM Effect Setup** dialog box.

Copy/Paste a DPM Effect

1. From the **DPM Effect Setup** dialog box, click a DPM effect from the **DPM EFFECTS** list.
2. Click **Copy**.
3. In the **DPM EFFECTS** list, click a different DPM register.
4. Click **Paste**. The DPM effect is copied into the selected register.

Lock/Unlock a DPM

1. From the **DPM Effect Setup** dialog box, click a DPM effect in the **DPM EFFECTS** list.

2. Either:

- Click **Lock** to lock the selected DPM effect, .

Note The keyframe playout controls are the only active controls that can be applied to a locked DPM effect.

- Click **Lock** to unlock the DPM effect, .

Create a DPM Effect

Creating a DPM effect uses the parameters on the three tabs in the **DPM Effect Setup** dialog box: **Timeline**, **Transform**, and **Special Effects**.

Note Only one DPM effect can be edited at a time.

1. Click the **Browse Effects** button (Figure 645). The **Effects List** dialog box (Figure 646) appears.

Figure 645. Browse Effects Button




Figure 646. Effects List Dialog Box – Effects Control



2. From the **Effects List**, click an effect and then click **Edit**.
3. Click the **Access** button at the bottom right of the **DPM EFFECTS** function. The **DPM Effect Setup** dialog box (Figure 647) appears:

Figure 647. DPM Effect Setup Dialog Box



4. From the **DPM EFFECTS** list, click the DPM effect.
5. Click **Edit** to enable edit mode.

6. Click the appropriate keyframe options for each key. Each key corresponds to a DPM channel.

Keyframe options include:

- **INCLUDE IN EFFECT**
- **DELEGATE CONTROL**
- **ASSIGN GLOBAL**
- **DPM ON**
- **GLOBAL**

Note It is recommended that you set all channel keyframes to the **Global** keyframe delegation option. Keyframe channels that are not set to **Global** may recall off screen.

7. From the **Transform** tab and the **Special Effects** tab, manipulate the parameters on the subtabs as necessary. Either:
 - a. Click and drag the **DPM Control Knob** left or right.
 - Drag right to reach an ascending value
 - Drag left to reach a descending value
 - b. Use the **Up/Down** arrow keys.
 - c. Type a value directly into the field.


Note For a detailed explanation of all parameters on the **Transform** tab and the **Special Effects** tab, refer to the Kayak User Manual.

8. Click the **Timeline** tab.
9. To insert a keyframe into the DPM timeline, click either icon on the **Keyframe Editing** toolbar:
 - **Insert Keyframe Before** icon inserts the keyframe before the current cursor position
 - **Insert Keyframe After** icon inserts the keyframe after the current cursor position
10. If necessary, in the **Name** field, type a new name for the DPM effect, using established standards and consistent techniques and practices. Refer to *Standardization* on page 577.

Note Effects with no keyframes are considered empty effects and are named “DPMXX” where “XX” is the register number.

11. Click **Edit** to save the entire DPM effect. The **Edit Effect** confirmation dialog box appears.

Figure 648. Edit Effect Confirmation Dialog Box



12. Either:

- Click **Yes** to save the parameters to the DPM effect and save the effect to all M/Es.

Note The user is returned to outside edit mode.

- Click **No** to cancel this function without saving changes to the DPM effect.

Note The user is returned to outside edit mode.


- Click **Cancel** to return to edit mode.

Modify/Delete Keyframes

After the DPM effect is created and saved, using the keyframe editing control buttons, users can:

- Modify current keyframe parameters (Refer to [Modify Current Keyframe Parameters on page 583](#))
- Modify DPM timeline and keyframe duration (Refer to [Modify DPM Timeline Duration on page 583](#) and [Modify DPM Keyframe Duration on page 584](#))
- Delete keyframes (Refer to [Delete a Keyframe on page 584](#))
- The keyframe buttons are located in the **Keyframe Editing** toolbar ([Figure 649](#)) on the **DPM Effect Setup** dialog box. Refer to [DPM Effect Setup Dialog Box on page 493](#) for control functions.

Figure 649. Keyframe Editing Control Buttons



Modify Current Keyframe Parameters

- a. Select the keyframe on the DPM timeline.
 - b. Click **Edit**.
 - c. From the **Timeline** tab and **Special Effects** tab, manipulate the parameters as necessary.
 - d. From the **Keyframe Editing** toolbar, click the **Modify Keyframe** button.
- The keyframe is updated with the modified DPM effect parameters.

Modify DPM Timeline Duration

- a. Select the keyframe on the DPM timeline.
- b. Click **Edit**.
- c. From the **Keyframe Editing** toolbar, click the **Modify Timeline Duration** button. The **Modify Timeline Duration** dialog box appears.

Figure 650. Modify Timeline Duration Dialog Box



- d. To enter timeline duration in the **Time Code** box in **hh:mm:ss** format, either:
 - Use the key pad numbers and click **OK**.
 - Type the duration directly into the **Time Code** box and click **OK**.

Modify DPM Keyframe Duration

- a. Select the keyframe on the DPM timeline.
- b. Click **Edit**.
- c. From the **Keyframe Editing** toolbar, click the **Modify Keyframe Duration** button. The **DPM Keyframe Duration** dialog box appears.

Figure 651. Modify Keyframe Duration Dialog Box



- d. To enter keyframe duration in the **Time Code** box in **hh:mm:ss** format, either:
 - Use the key pad numbers and click **OK**.
 - Type the duration directly into the **Time Code** text box and click **OK**.

Delete a Keyframe


- a. Select the keyframe on the DPM timeline.
- b. Click **Edit**.
- c. From the **Keyframe Editing** toolbar, click the **Delete Keyframe** button. The keyframe is removed from the timeline.

Note Only one keyframe can be deleted at a time from the DPM Timeline.

Use Keyframe Playout Controls

The keyframe playout control buttons are located in the **Keyframe Playout Controls** toolbar on the **DPM Effect Setup** dialog box. Use the playout control buttons to play keyframes on the DPM timeline: Refer to [DPM Effect Setup Dialog Box on page 493](#) for control functions.

Figure 652. Keyframe Editing Control Buttons



Position Keyframes on the DPM Timeline


There are four DPM channels that correspond to four keys and each channel contains its own keyframes. Also, the global channel encompasses all four keys. Keyframes are numbered in order and the keyframe that is currently selected is highlighted green (Figure 653).

The current keyframe is determined by the timeline cursor position and the delegated channels. Keyframes assigned to channels, which are not delegated, are not affected.

General rules for positioning keyframes on a DPM timeline include:

- To position a keyframe, left-click and drag the black triangle. This enables delegate control exclusively on the key channel associated with the black triangle. Individual keyframes can be expanded and contracted on the timeline.
- To reposition an entire channel, left-click and drag any numbered white flag in a keyframe within the channel, which allows an entire key channel to be stacked and overlapped.
- To reposition the red timeline cursor, left-click and drag the red triangle.

Figure 653. Keyframe Positions on the DPM Timeline



Effect Transitions

To operate the Ignite system either from the event timeline or when making a manual transition, an effect from the switcher is required. Once effects are built, they are recalled either through a TME (refer to [Build a TME on page 46](#)) or manually from the Effect List ([Figure 654](#)).

Figure 654. Transition Drop-Down Example



Effects List Drop-down

Note Effects created by prepping an existing effect and adding keyers to create a new effect, are executed once and deleted immediately after use. Only permanent effects will be selectable from the main GUI drop down list indefinitely.

To manually view and select an effect from the Effect List:

1. Click the **Effects List** expand arrow (Figure 654). The **Effects List** expands (Figure 654) to show all visible effects previously created (refer to [Effects Management on page 489](#) and [Effects Management on page 572](#)).
2. From the **Effects** list, scroll to and click an Effects transition for the manual switch between the Preview and Program buses. The effect is assigned and will be used when making a transition.

To make a manual transition using the selected effect:

1. Click either **Auto** or **Cut** (Figure 654)
2. Click **Take** (Figure 654) to see the effect transition on program

Create a Chroma Key

1. Set up the Switcher:
 - Click background (weather computer) on PGM of P/P ME
 - Turn on a Keyer
 - Assign a camera that is pointing at the keywall to that keyer
2. In the effects bank (i.e., **P/P**, **M/E 1**, **M/E 2**, or **M/E 3**) where the Chroma Key is to be added, click the **Browse Effects** button (Figure 655). The **Effects List** dialog box (Figure 656) appears.

Figure 655. Browse Effects Button



Figure 656. Effects List Dialog Box – Effects Controls



Note To adjust individual keyer properties, inside the Effects setup dialog box, click the button to the right of a keyer.

3. In the **Effects List** dialog box click **Add**.

4. Click **Edit**. The **Edit** button highlights.

Note For all names, abbreviations, and colors, use established standards and consistent techniques and practices. Refer to *Standardization* on page 577.

5. In the **Effect Name** box, enter a wipe name using established standards and consistent techniques and practices. Refer to *Standardization* on page 577.

Note Selecting PGM indicates that there is no background transition. Selecting PVW indicates that there is a preview to program background transition when the effect is executed.

6. Click **PGM**. The **PGM** button highlights.

7. Click the Key to use (Key 1 through Key 4), for example **Key 1**.

8. In **Transition**, enter the desired transition rate (Figure 656).

9. In **Transition**, click the selected keyer **Access** button. A **Keyer Setup** dialog box (Figure 657) appears where:


Key	Function
Luma	Uses the luminance values in a layer to determine the transparency of that layer.
Luma-Linear	The gain is approximately one, preserving the shaping of key source edges. Linear keying using anti-aliased sources produces smooth key edges
Additive	Creates a composite image from two complementary video signals that have already been shaped by multiplication with a key signal

Key	Function
Chroma	Renders a specific color in a layer transparent.
Preset Pattern	Uses a preset pattern

Note Chroma setup has four separate tabs for chroma settings (Figure 657). To adjust individual settings, click the respective tab.

10. Click **Chroma** (Figure 657). Using the faders, adjust properties as necessary.

Figure 657. Keyer Setup – Chroma Dialog Boxes



11. In the **Chroma Key Control Setup** dialog box, do the following:

- To automatically adjust the key mode parameters to the following settings, click **Auto**.
 - Clip = 50%
 - Gain = 100%
 - Opacity = 100%

Note The **Auto** button selects the current color under the cursor.

- To position the cursor or the dialog, click **Cursor**.
 - Click and drag to position the cursor.
 - Right-click and drag to position the dialog.
 - To close the dialog, click **Cursor** again.

Note The aspect ratio of the dialog changes when the current video mode is 4:3 or 16:9.

12. Use the faders inside the dialog box(es) ([Figure 657](#)) to adjust levels and create any of the four types of keys as well as a preset pattern.

Note Remember to adjust primary suppression HUE and selection.

13. Click **Save**. The **Keyer Setup** dialog box closes.

Create a Chroma Key in a Double Box

Note Build these in different M/Es; e.g., Chroma Key in M/E 1 and double boxes in P/P.

1. Create a Double Box effect. Refer to *Create a Double Box* [on page 380](#).
2. Using an available mix effects bank create a chroma key. Refer to *Create a Chroma Key* [on page 587](#).
3. Ensure that the selected Chroma Key effects bank is sourced to the P/P bus.

Use the Utility Bus in an Effect

The switcher utility bus can be routed into the border of any switcher wipe. That utility bus can contain any video source currently running into the switcher. This is helpful for using moving backgrounds or logos as part of the wipe transition.

1. Click the **Browse Effects** button ([Figure 658](#)). The **Effects List** dialog box ([Figure 659](#)) appears.

Figure 658. Browse Effects Button



Figure 659. Effects List Dialog Box – Effects Controls



2. In the **Effects List** dialog box click **Add**.
3. Click **Edit**. The **Edit** button highlights.
4. In the **Effect Name** box, enter a wipe name using established standards and consistent techniques and practices. Refer to [Standardization on page 577](#).

Note Selecting PGM indicates that there is no background transition. Selecting PVW indicates that there is a preview to program background transition when the effect is executed.

5. Click **PVW**. The **PVW** button highlights.

Note When doing a background transition, the duration set for PVW determines the duration for everything including the four keyer durations. If PVW is selected, ensure that all keyer durations are set the same as PVW. If PGM is selected, keyers can be brought on and off with independent durations.

Note Mix and Wipe are alternate actions of the same button. If the button shows Mix, clicking the button changes it to Wipe and vice versa.


6. Check that **PVW Mix/Wipe** button is toggled to **Wipe** (Figure 660). If not, click **Mix** to toggle the button to **Wipe**.

Figure 660. Effects Definition Dialog Box – Wipe Effects List



7. In **Transition**, enter the desired transition rate.
8. Click the **Wipe Effects Access** button (Figure 660). The **Wipe Setup** dialog box (Figure 661) appears.

Figure 661. Wipe Effect Setup Dialog Box



9. Click **Add**.
10. From the **WIPE EFFECT** list, click the newly added **Unnamed Effect**.
11. Click **Edit**. The **Edit** button highlights.
12. In the **ADJUST COLOR Base Source** list, click the expand arrow and then click **Utility Bus**.

Note For all names, abbreviations, and colors, use established standards and consistent techniques and practices. Refer to *Standardization* on page 577.

13. In the **Effect Name** box, enter a wipe name using established standards and consistent techniques and practices. Refer to *Standardization* on page 577.

Switcher Module - Konnect

Figure 662. Switcher Module User Interface Example



Overview

Note For Switcher Module [Kayak] overview and operation information, refer to [Section 15-Switcher Module - Kayak](#)

Note Throughout this section, the Konnect features and functions are described collectively but availability depends on the system configuration; i.e., the Kayenne or Kalypso switcher model installed with the system. For specific switcher information, refer to the switcher documentation provided with the product.

The Switcher Module – Konnect version ([Figure 662 on page 595](#)) provides Ignite interface control of both the Kayenne and the Kalypso switchers. The Ignite Konnect interface provides switcher:

- Control of source bus routing and transition states
- Recall of E-Mems and Macros
- Current state display for each M/E bank

The Switcher Module ([Figure 662 on page 595](#)) routes video device inputs (including cameras, VTRs, VRs, character generators, or the internally generated matte/pattern or black screens) to:

- Primary tab
- Secondary tab
- Both Primary and Secondary tabs.
- Preview Outputs – (Prep) outputs display the next image before it is used
- Program outputs – (Active) outputs are linked to the devices indicated by the current image
- Keyer Fill
- Keyer Cut or Hole
- Aux Outputs
- Utility Bus

Note A Kayenne/Kalypso switcher panel is still required for switcher effect building and switcher setup.

Note The number of Inputs and Outputs depends on both the Ignite system and the switcher installed.

Depending on system configuration, the Switcher Module – Konnect is available with up to five total Mix Effects (M/E) banks (refer to [Figure 662 on page 595](#)) labeled:

- **P/P** – Program/Preset
- **M/E 1** – Mix Effects One
- **M/E 2** – Mix Effects Two
- **M/E 3** – Mix Effects Three
- **M/E 4** – Mix Effects Four

Depending on system configuration:

- a Kayenne switcher has 6 key layers per M/E – only keys 1 – 4 can be assigned DPM (Digital Picture Manipulator) properties. Keys 5 and 6 are linear only.
- a Kalypso switcher has 4 key layers per M/E.

Note M/E 50 hardware is 6 linear keys only.

There are 10 customizable switcher pages and each page can have 4 to 14 buttons. When an M/E bank page is customized, the customization applies to that page across all M/E banks. The Switcher Module uses a Master Routing dialog box for quick source routing to destinations on any of the four effects banks. For descriptions of the interface, refer to [Figure 663](#) and [Table 16](#).

Note System configuration determines the number of M/Es, Key layers, and Utility Buses available on a specific system.

Note Only the P/P has the Source Setup and the Setup icons.

Figure 663. Switcher Module Basic User Interface




Table 16. Basic Interface Functionality

Name	Description
PRI	Primary tab – displays the primary partition (split M/E mode)
SEC	Secondary tab – displays the secondary partition (split M/E mode)
BOTH	Both tab – displays both primary and secondary partitions
A Source Row	Program Source Row/Current Source
B Source Row	Preview Source Row/Current Source
Delegate Source Row	Keyer source row/Keyers
Keyers/DPMs	Shows the current Keyer fill (refer to Keyer on page 606).
Sources	Shows the current PGM, PVW, and Utility Bus bus sources.
Pages/Page Tabs	Selects a Page of source buttons.
Setup Menu (drop-down)	Opens the Setup drop-down menu to access Source Setup (refer to Source Setup Dialog Box on page 599), Master Router Setup (refer to Master Routing Dialog Box on page 602), M/E Setup (refer to M/E Setup Dialog Box on page 604) and Split M/E Table (refer to Split M/E Source Equivalence Table Dialog Box on page 605)
PGM/PVW Bus source buttons	Shows the current PGM and PVW bus sources.
U1 – U2	Opens the respective Utility Bus Master Routing dialog box (refer to Master Routing Dialog Box on page 602).

Table 16. Basic Interface Functionality - (continued)

K1Near Fill/Cut – K12 Near Fill/Cut	Opens the respective Key Layer Master Routing dialog box (refer to Master Routing Dialog Box on page 602).
AUTO (Toggle button)	Depending upon either the Mix or Wipe button selection, preps the next transition to be executed when Take is clicked. Also highlights blue when a TME with either a Mix or a Wipe effect is prepped on the timeline.
CUT	Preps the next transition to execute as a Cut when Take is clicked. Also highlights blue when a cut effect is prepped.
Take	Takes the selected effect to air.
PVW	Displays the selected effect transition to PGM on the PVW (Preview) monitor.
Browse Effects	Opens the Effects Manager dialog box (refer to Keyer on page 606).
Effects drop-down List	Lists available programmed effects. Also enables a user to expand, view, select, and take an effect directly to air.
RUN (Toggle button)	Runs the current E-MEM without doing a Take
A-RUN	Runs the current E-MEM upon a Take
RUN (Master on P/P bank only)	Issues a master-level run command

Note Each of the 10 switcher pages can be customized. When an M/E bank page is customized, the customization applies to that page across all available M/E banks.

Note The M/E banks can be customized to meet show/user requirements via the **Master Routing** dialog box (refer to [Master Routing Dialog Box on page 602](#)).

Setup Drop-down Menu/Setup Menus

Figure 664. Setup Drop-down Menu/Setup Menus



The Setup drop-down menu (Figure 664) provides access to:

- Source Setup dialog box (refer to [Source Setup Dialog Box on page 599](#))
- Master Router Setup dialog box (refer to [Master Routing Dialog Box on page 602](#))
- M/E Setup dialog box (refer to [M/E Setup Dialog Box on page 604](#))

Source Setup Dialog Box

Figure 665. Source Setup Dialog Box



Access to the **Source Setup** dialog box is from the **Setup** drop-down menu. The **Source Setup** dialog box (Figure 665 on page 599) includes:

- **Page Configuration** group box:
 - **Page Name** – name for the currently selected page
 - **# of Buttons** – number of source buttons to show (4 – 14) for the currently selected page; an entry in this box is effective immediately

Note **# of Buttons** requires clicking **Apply** to actually apply it to the manual switcher UI.

- **Page Tab Setup** group box – select and view the **Page** (tab) to configure. Page sources are added by dragging and dropping sources from the **Source Display Setup** area.
- **Source Configuration** group box (refer to [Source Configuration Group Box on page 600](#))
- **Source Display Setup** group box (refer to [Source Display Setup Group Box on page 601](#))
- **OK** – saves the changes and closes the dialog box

- **Cancel** – cancels all changes made since the last save operation
- **Apply** – applies the changes but does not closes the dialog box

Source Configuration Group Box

Figure 666. Source Configuration Group Box




The **Source Configuration** group box (Figure 666) comprises:

- **Details** tab – source name (limited to 5 displayed characters).
- **Color** tab – color selections for Source Display Setup.
- **Icons** tab – icon selection library.
- **Key Coupling** tab – shows available key sources that can be coupled to the currently selected source. The currently coupled key source does not appear in this list.

Source Display Setup Group Box

Figure 667. Source Display Setup Group Box



The **Source Display Setup** group box (Figure 667) comprises:

- **Frame** tab – provides frame synchronization options.
 - **Import Source names** – resets all the names of the sources with the engineering name
 - **Reset number of sources** – reset the number of sources to match the frame

Note When using a Kalypso switcher, the Source Display Setup Group also has an EMEM tab for naming EMEMs.

- **Sources** tab:
 - **Internal Sources** tab – currently available internal sources that can be configured to a Switcher Module button on the currently selected page
 - **External Sources** tab – currently available external sources that can be configured to a Switcher Module button on the currently selected page
- **EMEM** tab (Kalypso switcher only) – displays a list of EMEM names

Master Routing Dialog Box

Figure 668. Master Routing Dialog Box



The **Master Routing** dialog box (Figure 668) is the initial interface used to set up both the switcher module and the keys. Access to the **Master Routing** dialog box is from the **Setup** drop-down menu.


The **Master Routing** dialog box has two main areas:

- Destinations on the left –
 - **Route Area** – enables a user to choose a single **M/E** or **Aux** route area to route sources.
 - **P/P** buses– displays and enables selection of the available buses and keyers.
 - **M/E** buses – when an **M/E** route area is selected, the following M/E buses are displayed: **PGM**, **PVW**, **Utility**, and **Near Keyer**.
 - **Aux** buses – when selected, **AUX** route area is selected, the available AUX buses are displayed. (Both Kayenne and Kalypso have 46 logical AUX buses.)
- Sources on the right –
 - **Internal Sources** tab – depicts and enables selection of hard inputs in the switcher.
 - Kalypso has up to 36 internal sources.
 - Kayenne has up to 50 internal sources.
 - **External Sources** tab – depicts and enables selection of sources connected to the switcher.
 - Kalypso has up to 92 external sources.
 - Kayenne has up to 200 external sources.

The M/E button indications are interactive and reflect the status/assignments for that particular button. That is, when an M/E or bus destination is selected, that button and the source highlight, and the associated internal and external.

M/E Setup Dialog Box

Figure 669. M/E Setup Dialog Box




Access to the **M/E Setup** dialog box ([Figure 669 on page 604](#)) is from the **Setup** drop-down menu. The **M/E Setup** dialog box provides these options for the selected M/E:

- **Move Up** – moves the selected M/E position up on the user interface.
- **Move Down** – moves the selected M/E position down on the user interface.
- **Run E-MEM always active** check box – when selected, enable the **A-RUN** and **RUN** buttons in an M/E bank regardless of the selected effect. If not selected, these buttons are only enabled when the current effect contains an E-MEM.
- **Enable Default Effect** check box – when selected, the default effect is prepped after an effect completes on the M/E.
- **OK** – saves the changes and closes the dialog box.
- **Cancel** – cancels all changes made since the last save operation.
- **Apply** – applies the changes but does not close the dialog box.

Split M/E Source Equivalence Table Dialog Box

Figure 670. Split M/E Source Equivalence Table Dialog Box



Access to the **Split M/E Source Equivalence Table** dialog box ([Figure 670 on page 605](#)) is from the **Setup** drop-down menu. The **M/E Setup** dialog box provides these options for the selected M/E:

- **Primary Sources** – lists bus destinations for the primary partition of a split M/E where primary = secondary
- **Secondary Sources** – lists bus destinations for the secondary partition of a split M/E where primary = secondary
- **Primary** drop-down list – lists bus selections for primary sources
- **Secondary** drop-down list – lists bus selections for secondary sources
- **Add** – adds a row where an equivalency rule can be established
- **Remove** – removes an equivalency rule row
- **OK** – saves the changes and closes the dialog box

- **Cancel** – cancels all changes made since the last save operation
- **Apply** – applies the changes but does not closes the dialog box

In order for Auto-ME to be effective with Split-M/E, the IQ Auto Channel Pool portion of Ignite Konnect needs a Split-M/E Source Equivalency Table.

The general rule or standard for Auto-ME is synonymous M/Es. However, with Ignite Konnect Split M/Es the same M/E resources are shared across partitions. In a standard Auto-M/E setup, M/E 1 and M/E 2 have common bus route destinations that persist despite the M/E that is allocated.

For example, M/E1 PVW route will become M/E2 PVW route when M/E2 is allocated from the pool. This is different for Split M/E because M/E1 PVW needs to become M/E1 Util1 when M/E1 secondary partition is allocated from the pool. This there needs to be some sort of table that spawns from the IQ Auto Channel Pool setup or an addition to the linked fields table that allows for Split M/E equivalencies to be defined.

For example, an operator needs to be able to define the following Split M/E equivalence rules:

Primary Source		Secondary Source
M/E1 A Bus	=	M/E1 U1 Bus
M/E1 B Bus	=	M/E1 U2 Bus
M/E1 Key 1	=	M/E1 Key 3
M/E1 Key 2	=	M/E1 Key 4

Keyer

Available, active key layers depend on the switcher(s) installed:

- Each Kayenne M/E bank has up to six key layers (K1 through K6) active at once
- Each Kalypso M/E bank has up to four key layers (K1 through K4) active at once


Each keyer has a corresponding switcher button on both the Program Bus and the Preview Bus. Keyers can also act as DPM/DVE channels where:

- Clicking the gray area of a PVW keyer turns on a channel of the DPM/DVE, which then fills with the source routed to that keyer. It is designated as on air by a color highlight and a small yellow DPM icon in the upper right hand corner. Highlight colors correspond to their respective bus ([Figure 671 on page 607](#)):
 - Green with a yellow bar for keys on the DPM/DVE Program bus
 - Yellow for keys on the DPM/DVE Preview bus

Note PVW keys have indicator lights for Primary or Secondary M/E partition allocation.

- Clicking the gray area of a PGM key displays a context menu that toggles a channel of DPM/DVE

Figure 671. *Keys On Air*



- Click the top half of keyer to toggle the keyer

Note Right-click the top half of keyer to access the DPM context menu. Click the lower half of keyer to change source routing.


- Click the routed source font to change source routing via the Master Router

Effects Manager

Figure 672. *Browse Effects Button*



Figure 673. Effects Manager Dialog Box



874x-sc15-10

The **Effects Manager** dialog box (Figure 673) is accessed by clicking the respective **P/P**, **M/E 1**, **M/E 2**, **M/E 3** or **M/E 4 Browse Effects** button (Figure 672 on page 607). The Effects Manager dialog box is a consolidated interface for effects management, transition, and association and comprises:

- **Effects List** group box (refer to [Effects List Group Box](#) on page 609)
- **Effects Definition** group box (refer to [Effects Definition Group Box](#) on page 611)
- **Transitions/E-MEM/Macros** group box (refer to [Transitions/E-MEM/Macros Group Box](#) on page 612)
- **Preview Effect** group box (refer to [Preview Effect Group Box](#) on page 614)
- **OK** – saves the current parameters and closes the dialog box
- **Cancel** – closes the dialog box without saving changes
- **Apply** – saves the current parameters but does not close the dialog box
- **Close** – closes the dialog box when not in Edit mode

Effects List Group Box

Figure 674. Effects List Group Box



The **Effects List** group box (Figure 674) is a list of user created effects. These effects are managed using a right-click and shortcut menu. The **Effects List** separated into three sub-lists:

Note Effects in each of the three sub-lists are managed easily via shortcut menu selections. The shortcut menus are accessed via right-click.

- **All Effects** – lists all effects that are visible on the Switcher module. Using shortcut menu selections, a user manages the **All Effects** sub-list. Effects deleted from the **All Effects** sub-list are recoverable from the **Recycle Bin** using a right-click and shortcut menu selection.
- **Hidden Effects** – lists effects that are marked as **Run Hidden Transition** on the **Transition** tab.

CAUTION Effects deleted from the **Recycled Effects** cannot be recovered.

- **Recycled Effects** – all effects deleted from both **All Effects** sub-list and **Hidden Effects** sub-list are automatically moved to the **Recycle Bin** sub-list and can be recovered/moved from the **Recycled Effects** sub-list using shortcut menu selections. Effects deleted from the **Recycled Effects** sub-list cannot be recovered.

Four command buttons comprise the remainder of the Effects List function. These commands are also available by using a right-click and shortcut menu.

- **Add** – create/add a new effect to the Effects List. A default name is automatically generated for the new effect but it should be renamed to conform with established standard naming conventions.

Note For all names, abbreviations, and colors, use established standards and consistent techniques and practices. Refer to *Standardization* [on page 577](#).

- **Delete** – moves the selected effect to the Recycled Effects. If the selected effect is already in the Recycled Effects, it is deleted.
- **Restore** – moves the selected effect from the recycled area to either the **All Effects** area or the **Hidden Effects** area.
- **Edit** – enables editing of the selected effect.

Note Effects can be placed on the Ignite **Event Timeline** by right-clicking and dragging to the timeline.

Effects Definition Group Box

Figure 675. Effects Definition Group Box

Effects Definition

Effect Name:

Action:

☒ Recall E-MEM

☒ Local on M/E

☐ Master Levels (Auto Recall Off)

☐ Master (Auto Recall On)

☒ Execute Macro


874x-sc21-r0

The Effects Definition group box (Figure 675) comprises:

- **EFFECT NAME** – in edit mode, the effect name can be changed by entering a different name in the **EFFECT NAME** box
- **Action:**
 - **Recall E-MEM** – when selected, recalls an E-MEM when the effect is prepped. The following are available only if **Recall E-MEM** is selected –
 - **Local on M/E** – when selected, recalls a local E-MEM on a specific ME
 - **Master Levels (Auto Recall Off)** – when selected, recalls a Master E-MEM with definable level delegation
 - **Master (Auto Recall On)** – when selected, recalls a Master E-MEM and sets the levels to Auto-recall
 - **Execute Macro** – executes a macro when the effect is executed

Transitions/E-MEM/Macros Group Box

Figure 676. Transitions/E-MEM/Macros Group Box



The **Transitions/E-MEM/Macros** group box (Figure 676) comprises:

- **Transition** tab – sets the components to include in the transition.
 - **Perform a Transition** – select to have the effect perform a transitions.
 - **Run Hidden Transition** – select to run hidden transitions.
 - **Ignore Transition States** – when selected, only allows a Cut or Auto transition command to be issued to the switcher without setting any transition states during prep.

- **Exclude** – when selected, the corresponding keyer or background is excluded from the transition.
- **Include** – when selected, the corresponding keyer or background is included in the transition.
- **Ignore** – when selected, the corresponding keyer is ignored on the transition.

Note This does not apply to background.

During prep, Ignored keyers visibility in preview monitor reflects the keyer state when it goes to air.


- **Toggle Transition** – when selected, the corresponding keyer is toggled on the transition.

Note This does not apply to background.

- **Auto** – when selected, performs an Auto transition on the corresponding Keyer/Background.
- **Cut** – when selected, performs an Cut transition on the corresponding Keyer/Background.
- **Effect/Transition Type** combo box – choose between available **Mix**, **Wipe**, and **User Effects** on the switcher.
- **E-MEM** tab – displays a list of E-MEM registers on the switcher, and allows the user to select an E-MEM register to recall.
 - **Run E-MEM** check box –when selected, runs the E-MEM when the effect is executed.
 - **E-MEM Levels** group box – displays E-MEM recall level choices. This is only available for **Local on M/E** and **Master Levels (Auto Recall Off)** effects.
 - **E-MEM Register** group box – displays a list of E-MEM registers on the switcher and enable s a user to select an E-MEM register to recall.
 - For a Kalypso switcher, enter a name to be associated with the E-MEM register.
 - For a Kayenne switcher, E-MEM names are obtained from the switcher).
- **Macros** tab – displays a list of Macro registers on the switcher and enables the user to select an Macro register to execute.

Preview Effect Group Box

Figure 677. Preview Effects Group Box




The **Preview Effect** group box (Figure 677) comprises:

- **M/E** – select the M/E on which to test the effect
- **PREP** – preps the selected effect on the selected ME
- **TAKE** – plays the selected effect on the selected ME
- **Transition** – slider mimics the transition lever arm on the panel
- **E-MEM Run** – slider mimics the E-MEM Run lever arm on the panel

TME Property Page Dialog Box

Figure 678. TME Property Page Dialog Box




Access to the **TME Property Page** dialog box is from an icon on the Event Timeline. The **TME Property Page** dialog box (Figure 678) includes:

- **Start Time**
- **ME** – enables M/E automation
- **AUX** – enables Aux routing
- **M/E Effect** group box (refer to [M/E Effect Group Box on page 616](#))
- **Transitions/Source Routes/Options** group box (refer to [Transitions/Source Routes/Options Group Box on page 618](#))
- **OK** – saves the current parameters and closes the dialog box
- **Cancel** – closes the dialog box without saving changes

M/E Effect Group Box

Figure 679. M/E Effect Group Box




The **M/E Effect** group box (Figure on page 616) comprises:

- **Effect** drop-down list – select an effect (optional).
- **Action** group box – provides option to select and an indication that:
 - **Recall E-MEM** – when selected, recalls an E-MEM when the effect is prepped. The following are available only if **Recall E-MEM** is selected:
 - **Local on M/E** – when selected, recalls a local E-MEM on a specific ME.
 - **Master Levels (Auto Recall Off)** – when selected, recalls a Master E-MEM with definable level delegation.
 - **Master (Auto Recall On)** – when selected, recalls a Master E-MEM and sets the levels to Auto-recall.

- **Run E-MEM** – the effect runs an E-MEM.
 - **Local on M/E** – indicates E-MEM to run on an M/E.
 - **Master Levels** – indicates E-MEM to run as Master.
 - **Master** – indicates E-MEM to run as Master with Auto-recall.
 - **Direction** drop-down list – select the direction to run an E-MEM (**Forward** or **Reverse**).
- **Execute Macro** – the effect is a macro.
- **M/E group box** – select the an M/E delegate level:
 - **PRI** – primary.
 - **SEC** – secondary.

Transitions/Source Routes/OptionsGroup Box

Figure 680. Transitions/Source Routes/Options Group Box



The **Transitions/Source Routes/Options** group box (refer to [Transitions/Source Routes/OptionsGroup Box on page 618](#)) comprises:

- **Transition** tab – provides transition option selections
 - **Perform a transition** – when selected, transitions bus
 - **Ignore transition states** – when selected, ignores transition states

- **Run Hidden Transition** – when selected, runs the transition as a hidden effect
- **Primary Background** – primary background setup
- **Secondary Background** – secondary background setup
- **Key 1** (through x) – individual key feature set up

Note Primary Background, Secondary Background, and Key 1 through x use the same type drop-down list to set up the respective effect.

- Drop-down list:
 - **Exclude** – if selected, excludes that feature from the transition
 - **Include** – if selected, includes that feature in the transition
 - **Ignore** – if selected, ignores that feature during transition
 - **Toggle (PGM)** – if selected, toggle PGM that feature during transition
 - **Toggle (PVW)** – if selected, toggle PVW that feature during transition

Note Primary Background, Secondary Background, and Key 1 through x use the same type Cut/Auto buttons to set up the respective effect.

- **Auto** – if selected, sets as AUTO key
- **Cut** – if selected, sets as CUT key
- **Source Routes** tab – provides source route information and setup options for the selected **P/P**, **M/E**, **AUX** tab
- **Options** tab – provides Override Effects Queue function

IQ Auto Channel Pool Dialog Box


The **IQ Auto Channel Pool** dialog box ([Figure 681](#)) is used to add the M/Es and M/E Partitions necessary to the auto **Channel Pool** to enable Auto-ME functionality.

The **IQ Auto Channel Pool** dialog box contains two tabs:

- **M/E** (refer to [M/E Tab on page 620](#))
- **Video Channels** (refer to [Video Channels Tab on page 621](#))

M/E Tab

Figure 681. IQ Auto Pool Dialog Box – M/E Tab




Parameters, functional areas, and control functions on the **M/E** tab (Figure 681) comprise:

- **Available Channels** – a list of M/E channels that are not assigned to a channel pool.
- **Channel Pool** – a list of channels that are currently assigned in the channel pool.
- **Assign Channel** or **Right Arrow** icon – moves and assigns available channels to a designated channel pool. The channels no longer appear in the **Available Channels** list.
- **Remove Channel** or **Left Arrow** icon – moves the designated channels pools back as available channels. The channels no longer appear under the **Channel Pool** list.
- **Save** – saves changes made to the Auto M/E pool.
- **Cancel** – cancels changes made to the Auto M/E pool and closes the **IQ Auto Channel Pool** dialog box.

Video Channels Tab

Figure 682. IQ Auto Pool Dialog Box – Video Channels Tab



Click the **Video Channels** tab (Figure 682) on the **IQ Auto Channel Pool** dialog box. All parameters, functional areas, and control functions for the **Video Channels** tab appear:

- **AUTOVS** – drop-down list that displays names of the video channel pools.
- **Create New Pool** – opens the **New Channel** dialog box to create a new video channel.
- **Manage Multiple Channel Audio** – when checked,
- **Fade Down Duration** –
- **Available Channels** – a list of video channels that are not assigned to a channel pool.
- **Channel Pool** – a list of channels that are currently assigned to a channel pool.
- **Assign Channel** or **Right Arrow** icon – moves and assigns available channels to a designated channel pool. The channels no longer appear in the **Available Channels** list.
- **Remove Channel** or **Left Arrow** icon – moves the designated channels pools back as available channels. The channels no longer appear under the **Channel Pool** list.


- **Save All** – save changes made to all channel pools.
- **Delete** – deletes the currently selected pool and removes it from either list: **Available Channels** or **Channel Pool** list.

Note The channels associated with the deleted channel pool are moved back and made available under the **Available Channels** area.

- **Cancel** – cancels changes made to the video channel pools and closes the **IQ Auto Channel Pool** dialog box.

IQ Template Manager Dialog Box

Figure 683. IQ Template Manager Dialog Box



The **IQ Template Manager** dialog box ([Figure 683](#)) is used to:

- Add template parameter variables to an IQ Template
- Enable Auto-ME channel pool
- Edit the global channel pool table

Operation

Route Services

Main User Interface

Figure 684. Route Services - Sources



Note Sources can be routed to Background, Keyer bus, and Utility bus from the main UI that appears on the right monitor.

Click the page tab ([Figure 684](#)) for the desired source.

- To route a source onto the A source or B source bus, select the source.
- To route a source to a Keyer or Utility bus:
 - a.** Select the desired Delegate Keyer bus or Utility bus button.
 - b.** Select the desired source in that delegate row.


Master Routing

Figure 685. Setup Menus



1. From the **Setup** drop-down menu (Figure 685), click **Master Routing**. The **Master Routing** dialog box (Figure 686 on page 624) appears.

Figure 686. Master Routing Dialog Box



2. From the **Route Area**, select the specific M/E or AUX source for routing.

Figure 687. Master Routing Route Area



3. From the bus list (Figure 688 on page 625), select the desired bus to route:
- For M/E banks choose between the background, utility, and keyer buses.
 - For Aux buses, select the desired AUX bus from the available AUX buses.

Figure 688. Master Routing Bus Lists



4. From either the **Internal Sources** or the **External Sources** area (Figure 686 on page 624), select the desired source to route.

Manage Effects

Create An Effect


Note Refer to the manufacturer's manuals for detailed information.

1. Click the respective **P/P**, **M/E 1**, **M/E 2**, **M/E 3** or **M/E 4** **Browse Effects** button (Figure 689). The **Effects Manager** dialog box (Figure 690 on page 626) appears.

Figure 689. Browse Effects Button



Figure 690. Effects Manager Dialog Box



2. In the **Effects List** area, click **Add**. A new effect is created and added to the Effects List.

Note The edit button is automatically selected to allow the newly created effect to be edited.

3. Using the available **Effects Manager** dialog box functions: **Effects Definition**, **Transitions/E-MEM/Macros** tabs, and **Preview Effect** areas, define the effect.
4. Either click:
 - **OK** to save the current parameters and close the dialog box.
 - **Cancel** to close the dialog box without saving changes.
 - **Apply** to save the current parameters but not close the dialog box.

Edit An Effect


Note Refer to the manufacturer's manuals for detailed information.

1. Click the respective **P/P**, **M/E 1**, **M/E 2**, **M/E 3** or **M/E 4** **Browse Effects** button (Figure 691 on page 627). The **Effects Manager** dialog box (Figure 692 on page 627) appears.

Figure 691. Browse Effects Button



Figure 692. Effects Manager Dialog Box



2. In the **Effects List** area, select an effect for editing.
3. In the **Effects List** area, click **Edit**.
4. Using the available **Effects Manager** dialog box functions: **Effects Definition**, **Transitions/E-MEM/Macros** tabs, and **Preview Effect** areas, define the effect.
5. Either click:
 - **OK** to save the current parameters and close the dialog box.
 - **Cancel** to close the dialog box without saving changes.
 - **Apply** to save the current parameters but not close the dialog box.

Delete An Effect

1. From the desired M/E, click **Browse Effects** (Figure 693). The Effects Manager dialog box (Figure 694) appears.

Figure 693. Browse Effects Button





Figure 694. Effects Manager Dialog Box



2. In the **Effects List** area, select an effect for deletion.
3. Either click:
 - **OK** to save the current parameters and close the dialog box.
 - **Cancel** to close the dialog box without saving changes.
 - **Apply** to save the current parameters but not close the dialog box.

Perform Transition

1. From the Effects drop-down list (Figure 695), select an effect to prep:

Note If the effect is set to recall a local E-MEM, the E-MEM is recalled on the pertinent M/E bank.

If the effect is set to recall a master E-MEM, the E-MEM is recalled on the master level.

Figure 695. Browse Effects Button



2. Click **TAKE** to execute the effect.

Recall/Run E-MEM

1. From the Effects drop-down list (Figure 696), select an effect to recall.

Figure 696. Browse Effects Button




2. Either:
 - To play the effect and run the E-MEM, click **TAKE**.
 - To run the E-MEM on the M/E bank without executing a transition click **RUN**.
 - To pause a running E-MEM, click **RUN**.

Run/Pause Master E-MEM

1. From the Effects drop-down list (Figure 697), select an effect to recall.

Figure 697. Browse Effects Button



- Click **RUN** to:
 - Run the current master E-MEM.
 - Pause master E-MEM if running.

CAUTION Be careful when use caution when using the Master Run button. The Master Run button initializes the current work buffer of the E-MEM timeline and could potentially cause a On-Air conflict.

- Resume master E-MEM from paused state.

Execute Macro

1. From the Effects drop-down list (Figure 698), select a macro to prep:

Figure 698. Browse Effects Button



2. Click **TAKE** to execute the macro.

General Operation Guidelines

The following guidelines are meant to assist in a high-level understanding of Ignite/Ignite Konnect system operation. Because the inter-operation of the individual Ignite/Ignite Konnect modules related to show production is specific to an installation site, a full operational understanding for using the Ignite/Ignite Konnect system is obtained only through on-site specific training.

Turn On/Off

Turn On

1. Ensure all associated devices are powered on and running the appropriate software.
2. Set the Ignite/Ignite Konnect CPU power switch to On.

Turn Off

1. Close the Ignite/Ignite Konnect program
2. Set the Ignite/Ignite Konnect CPU power switch to Off.

Start Ignite/Ignite Konnect Software

Start

1. Either:
 - Double-click the Ignite/Ignite Konnect desktop icon (Figure 699).
 - Right-click the Ignite/Ignite Konnect desktop icon (Figure 699) and then click **Open**.
 - Click the **Start** button, point to **All Programs**, point to **Ignite Software**, and then click **Ignite**.

Figure 699. Ignite/Ignite Konnect Desktop Icon



2. The Ignite/Ignite Konnect Live Production Control System program opens and is ready for use.


System Status

1. Start the Ignite/Ignite Konnect program.
 1. On the Event Timeline module **File** menu, click **Open**. The **Open** dialog box appears. Navigate to and click the desired user macro. The selected show/user file (macro) sets up the **Event Timeline** with the presets/prebuilds specific to that show or user.
 2. Click sources on the switcher, confirm that switches are taking place and that, when a button is clicked, what is expected is what happens.
 3. Raise and lower audio faders to confirm that what is heard is what was expected.
 4. Import a TME onto the timeline and bus-prep it. Make sure it routes everything to **Preview** as expected and then transition it. Make sure it transitions as expected.
 5. The easiest way to confirm control of all external devices is to first start with CG and Still Stores. Try recalling a page via the hotkeys. This indicates CG/SS control.
 6. For device controls such as video and audio servers or VTRs, either recall a clip list from servers or audio servers. In the case of VTRs, load tapes and then click **Play** to determine communication.

Set Up A New Show


1. On the **Event Timeline** module **File** menu (Figure 700), click **New**. A blank **Event Timeline** appears.

Figure 700. File Menu New



2. Navigate to the C:\(station call letters)\Station_Macros subfolder (Figure 701). Refer to *Standardization on page 577*.

Figure 701. Saved Show Location Subfolder



Note In the next step it is strongly recommended that the macro name should be based upon established standards and consistent techniques and practices. Refer to *Standardization on page 577*.

3. In **File Name**, type a name for the new show. Click **Save**.

Note Typically the timeline is left blank when storing a macro for show use, since it is dynamic and imported via Rundown Conversion. The selected show/user (macro) file starts the Event Timeline module with the presets/prebuilds specific to that show or user; e.g., CG/SS Hotkeys, LBNs, and any TMEs that are on the timeline. Therefore, all changes/additions/deletions, customization, hotkeys, etc. are specific to that show/user interface.

4. Begin populating the **Event Timeline** and building any new TMEs that are required.

Note Camera preset hotkeys are global and load when the Ignite/Ignite Connect application is started.

5. On the **Event Timeline** module **File** menu, click **Save As**. The **Save As** dialog box appears.

Open An Existing Show

1. On the **File** menu, click **Open**. The **Open** dialog box appears.
2. Navigate to the C:\(station call letters)\Station_Macros subfolder ([Figure 701](#)) and click the desired user macro. The selected show/user file (macro) sets up the Event Timeline with the presets/prebuilds specific to that show or user.
 - To check system status, refer to [System Status on page 632](#).
 - To go **LIVE** with a specific workstation, refer to [Place Workstation in LIVE Mode on page 240](#).

Figure 702. Ignite/Ignite Connect Three-Monitor Display Example



Software Version

Note The software version determines the device control and features available on any given Ignite/Ignite Connect system.

To check the Ignite/Ignite Connect system software version:

- On the **Help** menu, click **About**. The **About** property sheet appears. The software version information is contained in the property sheet.

Figure 703. Software Version



Quit Ignite/Ignite Konnect Software

To quit the Ignite/Ignite Konnect application either:

- Click the **Close** button
- On the **File** menu, click **Exit**

Dock/Undock Modules

Many of the Ignite/Ignite Konnect software modules can be docked/undocked to and from the default location. Refer to [Figure 704](#).

Figure 704. Dock/Undock Buttons



To Undock a module:

1. Click the **Undock** button.

2. In a non-active area of the module, click and drag it to a new location, and then release.

Note The module remains translucent until returned to the default location.

To Dock a module at the default location:

- Click the **Dock** button. The module returns to the default location.

Building a Show

The Ignite/Ignite Konnect system is event based so directors must create individual events that execute the commands normally done by multiple people during a regular show. Instead of marking scripts and calling commands to the individuals in the control room and on the floor, directors pre-program show events on the rundown itself.

Producing a Show

Producing an Ignite/Ignite Konnect automated newscast is not much different than producing a show for standard production. There are a few things to keep in mind:

- Each story in a rundown must have a distinct name. If a segment takes place multiple times during a show it should have a specific name each time. For example, naming the a weather segment **1st Weather** and the main weather segment **Main Weather** alleviates the confusion that would occur if all weather hits during a rundown were named WX or Weather.

Note For all names, abbreviations, colors, and file structures, use established standards and consistent techniques and practices. Refer to *Standardization* [on page 577](#).

- Use the automated CG commands for each story. This information is sent to the Character Generator automatically, so be careful inputting information into the automated fields. Do not include times for a CG within the CG command; it automatically appears on the sent CG. Instead, create a Cut Sheet for the director, so they can key the appropriate graphic at the appropriate time.

- Communicate any and all rundown changes. The director marks the show through the rundown. If possible, “set” the rundown one hour before the show. After that, if any changes are made to the rundown, make sure the director knows a change has been made to a specific story. This communication can be a phone call or an IM through ENPS. If a story is added after the one hour time period, do not renumber the rundown. Instead, create a new slug using a decimal point when numbering the new element. For example, if a story is added between A5 and A6, number the new story as either A5.1 A5.2, A5.3 and so on. That way the director knows that the element is new to the rundown and goes between A5 and A6.
- Be specific when entering information in the Format, Type, and Talent columns. These columns are used by the director when marking the show. Being specific with the information in these three columns removes the need for the director to search through the story itself for the story information. If anything changes in these columns, then call the show’s director.
- Make sure that roll cues and production commands are included in the script. The director will no longer be looking at a marked script. Instead, the director reads the teleprompter along with the on-air talent. If a command for taking talent or rolling a tape is not included in the script, then the director will not know when to take this element.

Editing a Show

For the editors, there are a few things that are different from the current production method:

- All video encoded into the servers should be pre-mixed. Using the Ignite/Ignite Konnect live production system, there is no audio technician mixing levels and it is too much to ask a director (who is already minding the audio, video, machine control and graphics playback) to do a live mix of the edited piece. The final audio mixes, whether a locally produced SOT, a VO from CNN or a Package from FOX, should not have separated audio. The audio encoded or ingested into the server should already contain the final mix for both channel one and channel two.
- Missing video must be conveyed to the director. If a piece of video is not going to make it, notify the producer so they can relay this information to the director. Then the director will know to skip the missing event.

Note A director does not know if a piece of video is available until preparing the event to take to air.

- Last minute video can be aired. If video comes in during a newscast and cannot be encoded or ingested into the video server, it can be aired from one of the video tape decks. Communicate this to the producer so they can tell the director to make the appropriate changes.

Multiple CG Automation

1. Ignite/Ignite Konnect enables multiple CG Automation. After the CGs have been inserted into the scripts, the director can decide if any of the CGs need to be directed to a CG device that is not designated as the Automation CG Machine. After the CGs have been placed in the scripts by the producer or reporters, the director will go back and edit the CG command line, which will look like this:

```
[CG:locator\Bronx\New York City\New York]
```

2. Insert the CG Device Name CG1- after [CG:

Note The CG Device Name has to be the same name used on the Switcher, for example; CG1, CG2, etc.

3. The new CG Command line will look like this:

```
[CG:CG1-locator\Bronx\New York City\New York]
```

4. The Template Name points to a file in the directory specified on the **NRCS Setup** dialog (like iNEWS or ENPS) within ScriptViewer. The file is used to define the template ID used to create the CG page.
5. Within the ScriptViewer drive, under
C:\Program Files\Scriptviewer\NEWS\CG\
create the Association File to point to the template address in the CG. These files should be created in Notepad and look like this:
[Header]
 - Name=One Line Lower Third (Optional)
 - Template=2000 (This is the Template Page in the CG)
6. Save and title the file with the name to type in the INEWS CG command and then rename the file without the.txt. Usually it is some cryptic name like 2ls, gfx1. Create as many of these Template Association Files as Templates used from the CG.

Modify CG Conversion Files

CG pages can be created for lower third supers and full screen font from information contained within the scripts. A template is created within the

CG device; the user must insert a production cue from within the NRCS and place information within the data fields while editing a script.

The CG command structure is:

```
[CG:TemplateName\Field1\Field2\FieldN]
```

Example:

```
[CG:locator\Bronx\New York City\New York]
```

To skip fields within a template, place a backslash with no data:

```
[CG:21s\\Data\Data]
```

To call up a full screen CG page with no data fields, create a template association name [CG:Gfx\] that points to a CG address number where the full screen is already made.

Coding a Show

The Ignite/Ignite Konnect system supports NRCS news commands via TME Associations. The TME Associations are automation directives embedded into news items on iNEWS and ENPS news systems. Directors associate pre-tested TME files with news commands via the Ignite/Ignite Konnect user interface. Once associated to TMEs, directors embed TME Associations within the actual news items residing on the station's NRCS.

Note IDs are case sensitive; e.g., if the ID is all lower case in the server, it must be all lower case when coding.

Using the TME Associations previously created, start coding shows in the NRCS. Coding procedures differ between column based and script based coding.

Column-based Coding

Typically, column-based coding deals with three columns for inputting TMEs directly into scripts.

- TME – Use this column to input TME codes. Refer to *Standardization on page 577*.
- Still Store – Use this column to input the ID code numbers used to call up Still Store and CG pages from graphic devices. The Load Script command must be the second element in the TME string.

Note For all names, abbreviations, colors, and file structures, use established standards and consistent techniques and practices. Refer to *Standardization on page 577*.

Note When including multiple TME properties, use commas to separate them.

Typically, the SS/CG code numbers in this column are for over the shoulder graphics and lower third name fonts and banners.

Note When including multiple SS/CGs, use commas to separate them.

Note Lower thirds that are built daily are recalled via the CG playlist, so there is no need to code them here.

- Timecode – The Timecode column is where:
 - Video and audio server clips are coded
 - Specific timecodes for VTRs are coded

Note When including multiple clips or timecodes, use commas to separate them.

Script-based Coding

Input TMEs, CG/SS numbers and Time code/Tape IDs where:

- Code [TME:nnn]
(where nnn represents the TME name to use for that particular story. Separate multiple TMEs with commas; e.g., [TME:nnn,rrr,zzz])
- Code [SS:1234]
(inserts Still Store number 1234 into the first TME (with a still store number) that it encounters in the script. Separate multiple CGs/SSs with commas; e.g., [SS:1234,3456,5678])
- Code [Timecode:ttt]
(where ttt is the clip name inserted into first server load icon that is encountered in the story. Separate multiple Timecodes with commas; e.g., [Timecode:ttt,mmm,ccc])

Common Errors

- **Not a Valid TME association** – there is a miss-coded item or the TME has not been associated. Check that there are no typing mistakes in the NRCS rundown. If no typing mistakes, confirm that the TME is associated.
- **Overage of an Icon** – there is an empty icon in a TME and an SS/CG number or Clip ID to insert into it could not be found. Check that there is a number coded in the Still Store or Timecode columns.

- Note** There may be times when this error is intentional, for example, when relying on the ScriptViewer teleprompter to build a lower third in the playlist and intentionally leaving the Still Store column blank.
- **Underage of an Icon** – there is a number in the Still Store or Timecode columns but no TME for it. Check that there is a TME with one of these icons in it.

Failure Recovery

The failure recovery procedures/recommendations listed below, are based on standard Ignite/Ignite Konnect system installations and configurations:

- Note** Because some sites require/request customization, those custom sites must (with the assistance of Grass Valley Commissioning/Training personnel) develop **custom** recovery procedures appropriate for their installed Ignite/Ignite Konnect system.

- [Before a Failure Occurs - Recommendations on page 641](#)

- Note** The following procedures assume that a failure occurred on a standard (installed/configured) Ignite/Ignite Konnect system during a **LIVE** broadcast from the primary workstation, and that full recovery must occur within the timespan of a commercial break.

- [All Systems - Network Failure on page 642](#)
- [Single/Non-Redundant Failure Recovery on page 642](#)
- [Partial Redundant \(Type 1 and 2\) Failure Recovery on page 643](#)
- [Full Redundant Failure Recovery on page 644](#)
 - [Failure Recovery From Primary Workstation-A on page 645](#)
 - [Failure Recovery From Backup Workstation-B on page 646](#)

Before a Failure Occurs - Recommendations

1. Familiarize yourself with the operation of the *Device Manager Module* [on page 235](#).
2. Memorize and practice recovery procedures to the point that they become second-nature.
3. Before airing a live show from the primary workstation, mirror the show (start Ignite, load the show macro, and import the rundown) on the alternate/redundant system CPU.

4. Configure an unused LBN page (see *LBN (Late Breaking News) Module on page 365*) to mimic QUICbox TME button functions (see *QUICbox Panel on page 367*) and name the page QUICbox. If the QUICbox fails, use the QUICbox LBNs to insert TMEs onto the event timeline.

Note Unlike QUICbox inserted TMEs, LBN TMEs cannot be programmed to auto execute or run hidden.

To continue the show, execute (run/play) LBN inserted TMEs.

5. Don't attempt to analyze/repair a **redundant** system during a commercial break. Immediately switch to the alternate (mirrored) equipment and continue the show.
6. Periodically exercise the alternate workstation/equipment to verify proper working order.

All Systems - Network Failure

If there is a network failure, depending on site standard operating procedures, contact either the station engineer or an IT person immediately.

Note Ignite/Ignite Konnect requires the local area network (LAN) to communicate with all devices under its control. Do not contact Grass Valley Technical Service for local network outages.

When LAN (local area network) operation is restored:

1. Set Device Manager mode to **LIVE**.
2. Verify all Device Manager devices display green.
3. Reposition the timeline cursor to the next scheduled TME event.
4. Continue show.

Single/Non-Redundant Failure Recovery

Note Single/non-redundant systems rely on a software or hardware/software restart for failure recovery. If a restart does not resolve the condition or if the failure is hardware related, the system is off-air until standard trouble resolution and repair are completed.

1. Go to commercial.

2. Shut down the Ignite/Ignite Konnect application (if possible), or do one of the following in the order presented:
 - a. If all Ignite/Ignite Konnect modules do not close, either:
 - On the taskbar, click the Ignite Stopper icon.
 - On the desktop, double-click the Ignite Stopper icon.
 - b. Shut down the Windows operating system.
 - c. Power down the CPU.
 3. If necessary, power up the CPU, and when Windows is loaded, restart the Ignite/Ignite Konnect application.
 4. Load the show macro.
 5. Import the rundown.
 6. Set Device Manager mode to **LIVE**.
 7. Set Device Manager configuration to **1**.
- Note** With Device Manager in **LIVE** mode, configuration **1** connects the QUICbox, SHOT Director, switcher, Klotz, tally controller, cameras, and serial devices to the CPU.
8. Verify all Device Manager devices display green.
 9. Reposition the timeline cursor to the next scheduled TME event.
 10. Continue show.

Partial Redundant (Type 1 and 2) Failure Recovery

- Note** Partial redundant (Type 1) Ignite/Ignite Konnect systems include backup Ignite CPUs and an XSWITCH matrix router to switch the workstation KVM between the redundant sets of CPUs. It does not include additional component mainframes or an additional workstation.
- Note** Partial Redundant (Type 2) Ignite/Ignite Konnect systems include all Type 1 components plus an additional Prep workstation that includes a keyboard, monitors, and mouse (KVM) for both the Ignite/Ignite Konnect CPUs. It does not include additional component mainframes, QUICbox, SHOT Director, or ScriptViewer control station.

1. Go to commercial.

2. Set Device Manager mode to **PREP** (if possible), or do one of the following in the order presented:
 - a. Shut down the Ignite/Ignite Konnect application. If all Ignite/Ignite Konnect modules do not close, either:
 - On the taskbar, click the Ignite Stopper icon.
 - On the desktop, double-click the Ignite Stopper icon.
 - b. Shut down the Windows operating system.
 - c. Power down CPU-A.
3. Set XSWITCH mode to **B**.

Note XSWITCH mode **B** connects the workstation KVM to both Ignite/Ignite Konnect CPU-B.

4. If the show was **not** mirrored on Ignite/Ignite Konnect CPU-B:
 - a. Start Ignite.
 - b. Load the show macro.
 - c. Import the rundown.
5. Set Device Manager mode to **LIVE**.
6. Set Device Manager configuration to **1**.

Note With Device Manager in **LIVE** mode on Ignite/Ignite Konnect CPU-B, configuration **1** connects the QUICbox, SHOT Director, switcher, Klotz, tally controller, cameras, and serial devices to Ignite/Ignite Konnect CPU-B.

7. Verify all Device Manager devices display green.
8. Reposition the timeline cursor to the next scheduled TME event.
9. Continue show.

Full Redundant Failure Recovery

Note With full redundancy, all Ignite/Ignite Konnect components (except shared resources such as cameras, CG devices, VTRs, etc.) are doubled. This configuration provides two complete systems that, if necessary for failure recovery, are switched via the XSWITCH matrix router and Device Manager.

Two failure recovery procedures are available for full redundant Ignite/Ignite Konnect systems:

- If you prefer to stay at the primary workstation and are confident that the KVM, QUICbox, SHOT Director, and ScriptViewer are working properly, refer to [Failure Recovery From Primary Workstation-A on page 645](#).

- If you suspect that the KVM, QIUCbox, SHOT Director, or ScriptViewer are **not** working properly at the primary workstation, refer to [Failure Recovery From Backup Workstation-B on page 646](#).

Failure Recovery From Primary Workstation-A

Note This procedure assumes that the primary workstation KVM, QIUCbox, SHOT Director, and ScriptViewer are working properly. If not, refer to [Failure Recovery From Backup Workstation-B](#) procedure.

1. Go to commercial.
2. Set Device Manager mode to **PREP** (if possible), or do one of the following in the order presented:
 - a. Shut down the Ignite/Ignite Konnect application. If all Ignite/Ignite Konnect modules do not close, either:
 - On the taskbar, click the Ignite Stopper icon.
 - On the desktop, double-click the Ignite Stopper icon.
 - b. Shut down the Windows operating system.
 - c. Power down CPU-A.
3. Set XSWITCH mode to **B**.

Note XSWITCH mode **B** connects workstation-A KVM to both Ignite/Ignite Konnect CPU-B, switcher-B and Klotz-B outputs to Master Control, and serial devices to Control-B (serial controller).

4. If the show was **not** mirrored on CPU-B:
 - a. Start Ignite.
 - b. Load the show macro.
 - c. Import the rundown.
5. Set Device Manager mode to **LIVE**.
6. Set Device Manager configuration to **2**.

Note With Device Manager in **LIVE** mode on Ignite/Ignite Konnect CPU-B, configuration **2** connects QIUCbox-A, SHOT Director-A, switcher-B, Klotz-B, tally controller-B, cameras, and Control-B (serial controller) to Ignite/Ignite Konnect CPU-B.

7. Verify Device Manager devices display green.
8. Reposition the timeline cursor to the next scheduled TME event.
9. Continue show.

Failure Recovery From Backup Workstation-B

Note This procedure assumes that the primary workstation KVM, QUICbox, SHOT Director, or ScriptViewer are **not** working properly.

1. Go to commercial.
2. Set Device Manager mode to **PREP** if possible, or do one of the following, in the order presented:
 - a. Shut down the Ignite/Ignite Konnect application. If all Ignite/Ignite Konnect modules do not close, either:
 - On the taskbar, click the Ignite Stopper icon.
 - On the desktop, double-click the Ignite Stopper icon.
 - b. Shut down the Windows operating system.
 - c. Power down CPU-A.
3. Set XSWITCH mode to **C**.

Note XSWITCH mode **C** connects workstation-B KVM to both Ignite/Ignite Konnect CPU-B, switcher-B and Klotz-B outputs to Master Control, and serial devices to Control-B (serial controller).

4. Move to workstation-B.
5. If the show was not mirrored on CPU-B:
 - a. Start Ignite.
 - b. Load the show macro.
 - c. Import the rundown.
6. Set Device Manager mode to **LIVE**.
7. Verify/Set Device Manager configuration to **1**.

Note With Device Manager in **LIVE** mode on Ignite/Ignite Konnect CPU-B, configuration **1** connects QUICbox-B, SHOT Director-B, switcher-B, Klotz-B, tally controller-B, cameras, and Control-B (serial controller) to Ignite CPU-B.

8. Verify all Device Manager devices display green.
9. Reposition the timeline cursor to the next scheduled TME event.
10. Continue show.

Index

A

- Abbreviations
 - Standards [674](#)
- Abbreviations and Names
 - IQT Standards [677](#)
 - Standardization [674](#)
 - TME Standards [674](#)
 - TME Abbreviations [674](#)
 - TME Effect Names [677](#)
 - TME Names [676](#)
- Accept or Cancel Fader Configuration
 - QUICbox Panel [237](#)
- Accept, Cancel, or Restore Default Button Configuration
 - QUICbox Panel [235](#)
- Access the Effects List
 - Switcher Module - Kayak [572](#)
- Active Devices Configurations
 - Device Manager Module [338](#)
- Add a Profile
 - Katalyst Panel [217](#)
- Add a Template
 - CG List Module [269](#)
- Add a Thumbnail and a Description [424](#)
- Add A Video Clip
 - Device Control Module [316](#)
- Add an LBN to the Event Timeline
 - LBN Module [459](#)
- Add TME Associations
 - Event Timeline Module [391](#)
- Add TME Device Data Values to Parameter Name Values [429](#)
- Add/Assign/Edit a Slot or Virtual Source
 - Calrec Audio [178](#)
- Add/Rename Parameter Name and Parameter Name Values [426](#)
- Adding/Removing Virtual Sources From Aux Mixes
 - Klotz Audio [88](#)
- Additive Key Setup Dialog Box
 - Switcher Module - Kayak [525](#)
- Adjust a Single Master Fader
 - Wheatstone Audio [146](#)
- Adjust an Audio Source
 - Calrec Audio [176](#)
 - Klotz Audio [62](#)
 - Wheatstone Audio [142](#)
 - Yamaha Audio [108](#)
- Adjust Master Fader
 - Klotz Audio [65](#)
 - Yamaha Audio [111](#)
- Adjust Source Audio Profile
 - Klotz Audio [68](#)
- Adjust Source Mix Type
 - Klotz Audio [68](#)
- Adjust Source Trim Gain
 - Klotz Audio [66](#)
- Adjust/Setup/View a Group of Masters
 - Wheatstone Audio [146](#)
- Adjust/Setup/View Aux 1–Aux 6
 - Klotz Audio [65](#)
- Adjust/Setup/View Cue Input/Output Faders
 - Yamaha Audio [111](#)
- Adjust/Setup/View Matrix Faders 1–8
 - Yamaha Audio [112](#)
- Adjust/Setup/View Mixer Faders 1–6
 - Yamaha Audio [111](#)
- Advance Timeline
 - Event Timeline Module [384](#)
- Assign Available Channels to a Video Channel Pool [450](#)
- Assign Available Channels to an M/E Pool [445](#)
- Assign/Edit Button Action
 - Katalyst Panel [208](#)
- Assign/Edit Button Bitmap
 - Katalyst Panel [212](#)
- Assign/Edit Button Color
 - Katalyst Panel [206](#)
- Assign/Edit/Re-assign Button Style
 - Katalyst Panel [203](#)
- Associate a Video Format with a Scalar Object
 - Switcher Module - Kayak [545](#)

- Associate An Effect With a Wipe or DPM Effect Switcher Module - Kayak 571
 - Audio Clip Device Control
 - Device Control Module 311
 - Audio Controls, Buttons, and Indicators
 - QUICbox Panel 226
 - Audio Fader Configuration
 - Accept or Cancel Fader Configuration 237
 - Fader Type and Source 236
 - QUICbox Panel 235
 - Audio Live
 - Calrec Audio 169, 184
 - Audio Main Context Menu
 - Audio Profile Editor
 - Dynamics Dialog Box 54
 - Equalizer Dialog Box 52
 - Aux Configuration 57
 - Import Virtual Source 138
 - Klotz Audio 42
 - Layout Editor Editor Dialog Box 139
 - Layouts 138
 - Monitor Source Selection 59
 - Point To Point Routing 61
 - Source Maintenance Dialog Box
 - Klotz Audio 48
 - Virtual Source Editor Dialog Box 106, 136
 - Klotz Audio 45
 - Virtual Source Maintenance Dialog Box 44, 104, 135
 - Wheatstone Audio 134
 - Yamaha Audio 103
 - Audio Module 31
 - Calrec Audio 165
 - Operation 176
 - Adjust an Audio Source 176
 - Audio Live 184
 - Audio Preview 183
 - Configure Pages 177
 - Add/Assign/Edit a Slot or Virtual Source 178
 - Name or Rename a Page 178
 - Remove a Slot or Virtual Source 178
 - Setpoint Configuration 178, 181
 - Setup/Edit Audio Task Properties 182
 - Virtual Source Configuration 179
 - Overview 165
 - Audio Live 169
 - Audio Preview 168
 - Audio Task Configuration 174
 - Fader Manual Virtual Source Control 166
 - Individual Program Fader Controls 166
 - Masters Mains Output Faders 173
 - Setpoint Configuration 171
 - Katalyst Panel 195
 - Klotz Audio 35
 - Operation 62
 - Adjust an Audio Source 62
 - Adjust Master Fader 65
 - Adjust/Setup/View Aux 1–Aux 6 65
 - Audio Preview 92
 - Audio Program (LIVE) 94
 - Change a Page Name 63
 - Control EQ, Dynamics, and Delay via Audio Profiles 70
 - Create An Audio Profile 70
 - Delete An Audio Profile 73
 - Edit an Audio Profile 71
 - Fader Manual Virtual Source Control 63
 - Clear/Remove a Fader Control 65
 - Point To Point Routing 78
 - Select a Talk Back Source 74
 - Select/Edit Monitor Sources 75
 - Set Points 79
 - Clear a Set Point 83
 - Create a Set Point 79
 - Delete a Set Point 82
 - Edit a Set Point 80
 - Load a Set Point to a Virtual Source 81
 - Setup Audio Task Properties 91
 - Source Setting Independent of Virtual Sources 66
 - Adjust Source Audio Profile 68
 - Adjust Source Mix Type 68
 - Adjust Source Trim Gain 66
 - Virtual Sources 84
 - Adding/Removing Virtual Sources From Aux Mixes 88
 - Edit a Virtual Source 84
- Overview 35
 - Audio Main Context Menu 42
 - Audio Profile Editor
 - Dynamics Dialog Box 54
 - Equalizer Dialog Box 52
 - Aux Configuration 57
 - Monitor Source Selection 59
 - Point To Point Routing 61
 - Source Maintenance Dialog Box 48
 - Virtual Source Editor Dialog Box 45
 - Virtual Source Maintenance Dialog Box

- 44
- Audio Preview 37
- Audio Program (LIVE) 37
- Fader Manual Virtual Source Control 35
- Individual Faders 35
- Master Output Faders 41
- Set Points 38
 - Set Point Editor 40
 - Set Point Maintenance 39
- Overview 31
- Wheatstone Audio
 - Operation 141
 - Adjust a Single Master Fader 146
 - Adjust an Audio Source 142
 - Adjust/Setup/View a Group of Masters 146
 - Audio Preview 162
 - Audio Program (LIVE) 163
 - Change a Page Name 142
 - Create an Audio Layout 156
 - Delete an Audio Layout 162
 - Edit an Audio Layout 160
 - Load an Audio Layout 160
 - Manual Virtual Source Control 143
 - Clear/Remove Fader 146
 - Create a Program Fader Control – Import a Virtual Source 143
 - Save Current Audio Layout 158
 - Set Points 147
 - Create a Set Point 147
 - Delete a Set Point 151
 - Edit a Set Point 149
 - Load a Set Point to a Virtual Source 150
 - Virtual Sources 153
 - Edit a Virtual Source Entry 153
 - Operation Audio
 - Set Points
 - Clear Set Points From a Virtual Source 152
- Overview 125
 - Audio Main Context Menu 134
 - Layouts 138
 - Virtual Source Maintenance Dialog Box 135
 - Audio Preview 127
 - Audio Program (LIVE) 128
 - Fader Manual Virtual Source Control 125
 - Individual Program Fader Controls 126
 - Master Output Faders 131
 - Set Points 128
 - Set Point Editor 130
 - Set Point Maintenance 129
- Wheatstone Audio Module
 - Wheatstone Audio
 - Operation
 - Setup Audio Task Properties 155
- Yamaha Audio 95
 - Operation 107
 - Adjust an Audio Source 108
 - Adjust Master Fader 111
 - Adjust/Setup/View Cue Input/Output Faders 111
 - Adjust/Setup/View Matrix Faders 1–8 112
 - Adjust/Setup/View Mixer Faders 1–6 111
 - Audio Preview 123
 - Audio Program (LIVE) 124
 - Change a Page Name 108
 - Fader Manual Virtual Source Control 109
 - Clear/Remove Fader Control 110
 - Create Fader Control 109
 - Set Points 113
 - Clear a Set Point from a Virtual Source 118
 - Create a Set Point 113
 - Delete a Set Point 117
 - Edit a Set Point 115
 - Load a Set Point to a Virtual Source 116
 - Setup Audio Task Properties 121
 - Virtual Sources
 - Edit a Virtual Source 119
- Overview 95
 - Audio Main Context Menu 103
 - Virtual Source Maintenance Dialog Box 104
 - Audio Preview 97
 - Audio Program (LIVE) 98
 - Individual Faders 96
 - Manual Virtual Source Control 95
 - Master Output Faders 102
 - Set Points 98
 - Set Point Editor 100
 - Set Point Maintenance 99
- Audio Preview
 - Calrec Audio 168, 183
 - Klotz Audio 37, 92
 - Wheatstone Audio 127, 162
 - Yamaha Audio 97, 123
- Audio Profile Editor
 - Dynamics Dialog Box 54

- Equalizer Dialog Box [52](#)
 - Audio Program (LIVE)
 - Klotz Audio [37, 94](#)
 - Wheatstone Audio [128, 163](#)
 - Yamaha Audio [98, 124](#)
 - Audio Task Configuration
 - Calrec Audio [174](#)
 - Auto-toggle Production List [302](#)
 - Aux Configuration
 - Klotz Audio [57](#)
 - Aux Setup Dialog Box
 - Switcher Module - Kayak [476](#)
- ## B
- Build a Cut With a Key
 - Switcher Module - Kayak [564](#)
 - Build a TME
 - Event Timeline Module [386](#)
 - Build a Wipe
 - Switcher Module - Kayak [560](#)
 - Building a Show [636](#)
 - Coding a Show [639](#)
 - Column-based Coding [639](#)
 - Script-based Coding [640](#)
 - Common Errors [640](#)
 - Editing a Show [637](#)
 - Modify CG Conversion Files [638](#)
 - Multiple CG Automation [638](#)
 - Importing a Rundown (Ignite System and Ignite IQ Module) [379](#)
 - Producing a Show [636](#)
 - Rundown List/Event Timeline Correlation [369](#)
 - Button Configuration
 - Accept, Cancel, or Restore Default Button Configuration [235](#)
 - Default Appearance [232](#)
 - On Button Down [234](#)
 - QUICbox Panel [232](#)
 - Button Module
 - Button Toolbox [193](#)
 - Katalyst Panel [189](#)
 - Programmable Button Display Attributes [191](#)
 - Programmable Buttons [190](#)
 - Button Toolbox
 - Katalyst Panel [193](#)

C

- Calrec Audio
 - Audio Module [165](#)
 - Operation [176](#)
 - Adjust an Audio Source [176](#)
 - Audio Live [184](#)
 - Audio Preview [183](#)
 - Configure Pages [177](#)
 - Add/Assign/Edit a Slot or Virtual Source [178](#)
 - Name or Rename a Page [178](#)
 - Remove a Slot or Virtual Source [178](#)
 - Setup/Edit Audio Task Properties [182](#)
 - Virtual Source Configuration [179](#)
 - Overview [165](#)
 - Audio Live [169](#)
 - Audio Preview [168](#)
 - Audio Task Configuration [174](#)
 - Fader Manual Virtual Source Control [166](#)
 - Individual Program Fader Controls [166](#)
 - Masters Mains Output Faders [173](#)
 - Setpoint Configuration [171](#)
 - Setpoint Configuration [178, 181](#)
- Camera Preset Hotkey Module [241](#)
- Camera Preset/Hotkey Module
 - Common Control Buttons [242](#)
 - Operation [242](#)
 - Create a Preset Hotkey—Grass Valley HDC and CameraMan Robotic Cameras [243](#)
 - Load Presets From File [245](#)
 - Save Presets in File [245](#)
 - Create a Preset Hotkey—Telemetrics Cameras [248, 250](#)
 - Create a Preset Hotkey—Vinten/Radamac Cameras [246](#)
 - Overview [241](#)
- CG Column Order (Wide Mode only)
 - CG List Module [263](#)
- CG Column Word Wrap (Wide Mode only)
 - CG List Module [265](#)
- CG Display Pattern (Narrow Mode only)
 - CG List Module [264](#)
- CG List Module
 - CG List Settings
 - Display Settings Tab [258](#)
 - Narrow Mode [259](#)
 - Wide Mode [260](#)
 - General Tab [257](#)

- Template Table Tab [261](#)
- CG List Setup [256](#)
- CG Template Table [269](#)
 - Add a Template [269](#)
 - Delete a Template [271](#)
- Common Control Buttons and Indicators [255](#)
- Load a Script [272](#)
- Operation [262](#)
- Overview [253](#)
- Populate CG List [262](#)
- Set Display Mode [262](#)
 - CG Column Order (Wide Mode only) [263](#)
 - CG Column Word Wrap (Wide Mode only) [265](#)
 - CG Display Pattern (Narrow Mode only) [264](#)
 - Edit a CG Display Pattern [266](#)
 - Narrow or Wide Mode [262](#)
 - Set Display Colors [267](#)
- CG List Settings
 - Display Settings Tab [258](#)
 - Narrow Mode [259](#)
 - Wide Mode [260](#)
 - General Tab [257](#)
 - Template Table Tab [261](#)
- CG List Setup
 - CG List Module [256](#)
- CG Template Table
 - Add a Template [269](#)
 - CG List Module [269](#)
 - Delete a Template [271](#)
- CG/SS Module [275](#)
 - Operation [276](#)
 - Create CG/SS Hotkeys [276](#)
 - Delete CG/SS Hotkeys [279](#)
 - Place a CG on the Event Timeline [279](#)
 - Overview [275](#)
- Change a Module IP Address
 - Katalyst Panel [222](#)
- Change a Page Name
 - Klotz Audio [63](#)
 - Operation
 - Change a Page Name [63](#)
 - Wheatstone Audio [142](#)
 - Yamaha Audio [108](#)
- Change Keyer Video Association
 - Switcher Module - Kayak [556](#)
- Chroma Key Control Signal Adjustment
 - Coring [521](#)
 - FGD Fade [522](#)
 - Flare Suppression [521](#)
 - Primary Color Suppression [521](#)
 - Secondary Color Suppression [521](#)
 - Switcher Module - Kayak [520](#)
- Chroma Key Ctrl Signal Adjust
 - Primary Suppression Dialog Box [529](#)
 - Secondary Suppression Dialog Box [530](#)
- Chroma Key Ctrl Signal Adjustment
 - Miscellaneous Setup Dialog Box [532](#)
- Chroma Key Setup Dialog Box [526](#)
 - Switcher Module - Kayak [527](#)
- Clear a Set Point
 - Klotz Audio [83](#)
- Clear a Set Point from a Virtual Source
 - Yamaha Audio [118](#)
- Clear Set Points From a Virtual Source
 - Wheatstone Audio [152](#)
- Clear/Remove a Fader Control
 - Klotz Audio [65](#)
- Clear/Remove Fader [146](#)
 - Wheatstone Audio [146](#)
- Clear/Remove Fader Control
 - Yamaha Audio [110](#)
- Clip and Gain
 - Switcher Module - Kayak [519](#)
- Clip Hi/Lo
 - Switcher Module - Kayak [519](#)
- Clips and Stills Maintenance [333](#)
 - Delete Clips and Stills [333](#)
- Clips Device Control [313](#)
- Clock Module [281](#)
- Clocks
 - Clocks & Timers Module [282, 292](#)
 - Event Clock (Yellow)
 - Clocks & Timers [283, 293](#)
 - Global Timed Events [286](#)
 - Clocks & Timers Module [296](#)
 - Manual Clock (Blue)
 - Clocks & Timers [282, 293](#)
 - Production Timed Events [288](#)
 - Server Countdown Timer
 - Clocks & Timers Module [283](#)
 - Show Clock (Green)
 - Clocks & Timers [282, 293](#)
- Clocks & Timers Module
 - Operation [292](#)

- Clocks [292](#)
 - Event Clock (Yellow) [293](#)
 - Manual Clock (Blue) [293](#)
 - Show Clock (Green) [293](#)
 - Global Timed Events [296](#)
 - Auto-toggle Production List [302](#)
 - Insert Production Cues – Global Timed Events (ENPS Rundown) [298](#)
 - Curly Bracket Markup [299](#)
 - Insert Event [299](#)
 - Square Bracket Markup [298](#)
 - Insert Production Cues – Global Timed Events (NCS Rundown) [298](#)
 - Setup Global Timed Events – Direct Entry [297](#)
 - Trigger Global (Program) Clock [296](#)
 - Production Timed Events (NCS Coding) [303](#)
 - Insert Production Cues – Production Timed Events [303](#)
 - Use MOS Objects for Timed Events [303](#)
 - Server Countdown Timer
 - Configuration [294](#)
 - Timers [294](#)
 - Overview [281](#)
 - Clocks [282](#)
 - Event Clock (Yellow) [283](#)
 - Manual Clock (Blue) [282](#)
 - Show Clock (Green) [282](#)
 - Common Control Buttons [282](#)
 - Server Countdown Timer [283](#)
 - Configuration [285](#)
 - Display [283](#)
 - Timed Events [286](#)
 - Global Timed Events [286](#)
 - Production Timed Events [288](#)
 - Timers [283](#)
 - Coding a Show
 - Building a Show [639](#)
 - Column-based Coding [639](#)
 - Script-based Coding [640](#)
 - Color Background Dialog Box
 - Switcher Module - Kayak [477](#)
 - Column Filtering
 - Event Timeline Module [382](#)
 - Column-based Coding [639](#)
 - Common Control Buttons
 - Camera Preset/Hotkey Module [242](#)
 - Clocks & Timers Module [282](#)
 - Common Control Buttons and Indicators
 - CG List Module [255](#)
 - Common Errors
 - Building a Show [640](#)
 - Configuration
 - Katalyst Panel
 - Configure a Button [203](#)
 - Assign/Edit Button Action [208](#)
 - Assign/Edit Button Bitmap [212](#)
 - Assign/Edit Button Color [206](#)
 - Assign/Edit/Re-assign Button Style [203](#)
 - Configure a Panel Profile [217](#)
 - Add a Profile [217](#)
 - Delete a Profile [219](#)
 - Edit a Profile [220](#)
 - Create a Module [199](#)
 - Fader Module [201](#)
 - Identify/Change a Module IP Address [222](#)
 - Change a Module IP Address [222](#)
 - Identify a Hardware Panel [222](#)
 - QUICbox Panel [231](#)
 - Audio Fader Configuration [235](#)
 - Accept or Cancel Fader Configuration [237](#)
 - Fader Type and Source [236](#)
 - Button Configuration [232](#)
 - Accept, Cancel, or Restore Default Button Configuration [235](#)
 - Default Appearance [232](#)
 - On Button Down [234](#)
 - Functional Test [239](#)
 - Load Layout [238](#)
 - Server Countdown Timer [285, 294](#)
 - Configuration Interface
 - QUICbox Audio Modules #1 and #2
 - Configuration Dialog Boxes [231](#)
 - QUICbox Main Dialog Box (Button Layout) [230](#)
 - QUICbox Panel [227](#)
- Configure a Button
 - Assign/Edit Button Action [208](#)
 - Assign/Edit Button Bitmap [212](#)
 - Assign/Edit Button Color [206](#)
 - Assign/Edit/Re-assign Button Style [203](#)
 - Katalyst Panel [203](#)
- Configure a Panel Profile
 - Add a Profile [217](#)
 - Delete a Profile [219](#)
 - Edit a Profile [220](#)
 - Katalyst Panel [217](#)
- Configure Linked Fields [434](#)

- Configure Pages
 - Add/Assign/Edit a Slot or Virtual Source [178](#)
 - Calrec Audio [177](#)
 - Name or Rename a Page [178](#)
 - Remove a Slot or Virtual Source [178](#)
 - Configure Source Dialog Box [482](#)
 - Control EQ, Dynamics, and Delay via Audio Profiles
 - Create An Audio Profile [70](#)
 - Delete An Audio Profile [73](#)
 - Edit an Audio Profile [71](#)
 - Klotz Audio [70](#)
 - Copy/Paste a DPM Effect
 - Switcher Module - Kayak [578](#)
 - Copy/Paste Function
 - Show Builder Assistant Module [467](#)
 - Coring
 - Switcher Module - Kayak [521](#)
 - Create a Chroma Key in a Double Box
 - Switcher Module - Kayak [590](#)
 - Create a DPM Effect
 - Switcher Module - Kayak [579](#)
 - Create a Module
 - Fader Module [201](#)
 - Katalyst Panel [199](#)
 - Create a New Effect
 - Switcher Module - Kayak [558](#)
 - Create a Preset Hotkey—Grass Valley HDC and CameraMan Robotic Cameras [243](#)
 - Load Presets From File [245](#)
 - Save Presets in File [245](#)
 - Create a Preset Hotkey—Telemetrics Cameras [248, 250](#)
 - Create a Preset Hotkey—Vinten/Radamac Cameras [246](#)
 - Create a Program Fader Control – Import a Virtual Source
 - Wheatstone Audio [143](#)
 - Create a Set Point
 - Klotz Audio [79](#)
 - Wheatstone Audio [147](#)
 - Yamaha Audio [113](#)
 - Create a Video Channel Pool [447](#)
 - Create an Audio Layout
 - Wheatstone Audio [156](#)
 - Create An Audio Profile
 - Klotz Audio [70](#)
 - Create An Effect
 - Switcher Module - Konnect [625](#)
 - Create an IQ Template
 - Add a Thumbnail and a Description [424](#)
 - Add TME Device Data Values to Parameter Name Values [429](#)
 - Add/Rename Parameter Name and Parameter Name Values [426](#)
 - Configure Linked Fields [434](#)
 - Delete Parameter Name, Name Value, or TME Device Data Value [433](#)
 - Import an Existing TME File [422](#)
 - Save TME File as an IQ Template [435](#)
 - Create an LBN Hotkey
 - LBN Module [456](#)
 - Create CG/SS Hotkeys
 - CG/SS Module [276](#)
 - Create Fader Control
 - Yamaha Audio [109](#)
 - Curly Bracket Markup
 - ENPS Rundown [299](#)
 - Cursor Relocate/Jump
 - Event Timeline Module [384](#)
 - Customize Switcher Bank
 - Customize Switcher Page [538](#)
 - Set Button Properties [541](#)
 - Switcher Module - Kayak [538](#)
 - Switcher Source Setup [543](#)
 - Customize Switcher Page
 - Switcher Module - Kayak [538](#)
- ## D
- Default Appearance
 - QUICbox Panel [232](#)
 - Delete a DPM Effect
 - Switcher Module - Kayak [575](#)
 - Delete a Profile
 - Katalyst Panel [219](#)
 - Delete a Set Point
 - Klotz Audio [82](#)
 - Wheatstone Audio [151](#)
 - Yamaha Audio [117](#)
 - Delete a Template
 - CG List Module [271](#)
 - Delete an Audio Layout

- Wheatstone Audio [162](#)
- Delete An Audio Profile
 - Klotz Audio [73](#)
- Delete An Effect
 - Switcher Module - Konnect [628](#)
- Delete CG/SS Hotkeys
 - CG/SS Module [279](#)
- Delete Parameter Name, Name Value, or TME
 - Device Data Value [433](#)
- Delete TME Associations
 - Event Timeline Module [397](#)
 - Manage TME Associations
 - Event Timeline Module [397](#)
- Device Color Indications
 - Device Control Module [306](#)
- Device Control [22](#)
- Device Control Module [305](#)
 - Add A Video Clip [316](#)
 - Audio Clip Device Control [311](#)
 - Device Color Indications [306](#)
 - Device Controls [306](#)
 - Enco Audio Server Device Control [315](#)
 - Get Audio Cut [317](#)
 - Operation [315](#)
 - Overview [305](#)
 - RAM Recorder [319](#)
 - Clips and Stills Maintenance [333](#)
 - Delete Clips and Stills [333](#)
 - Play A Clip [330](#)
 - Play A Still [329](#)
 - Record A Clip [323](#)
 - Record A Still [319](#)
 - Trim A Clip [328](#)
 - RAM Recorder Device Control [311](#)
 - Clips Device Control [313](#)
 - Stills Device Control [312](#)
 - Scan/Shuttle a Video [318](#)
 - Search for a Time Code [318](#)
 - Select a Device Control [315](#)
 - Video Server Device Control [309](#)
 - VTR Device Control [310](#)
- Device Controls
 - Device Control Module [306](#)
- Device Manager Module [335](#)
 - Operation [340](#)
 - Place Workstation in LIVE Mode [341](#)
 - Place Workstation in Live Mode [341](#)
 - Place Workstation in PREP Mode [345](#)
- Set Active Devices Configuration [342](#)
- Verify Device Status [344](#)
- Verify/Clear Message Status [345](#)
- Overview [335](#)
 - Devices Tab [336](#)
 - Messages Tab [337](#)
 - Mode and Configuration Control [337](#)
 - Active Devices Configurations [338](#)
 - Mode Control [338](#)
 - Set Active Devices Configuration Dialog [338](#)
- Devices Tab
 - Device Manager Module [336](#)
- Display
 - Server Countdown Timer [283](#)
- Display Settings Tab [258](#)
 - Narrow Mode [259](#)
 - Wide Mode [260](#)
- DMP Module
 - Operation [351](#)
 - Overview [347](#)
 - Production [348](#)
 - User Interface [348](#)
 - DMP TME Item Type [349](#)
 - Event Timeline Tools Menu [348](#)
- DMP TME Item Type
 - DMP Module [349](#)
- Dock/Undock Modules [635](#)
- documentation online [7](#)
- DPM Effect Setup Dialog Box
 - Special Effects Tab [500](#)
 - Switcher Module - Kayak [493](#)
 - Timeline Tab [493](#)
 - Transform Tab [496](#)
- DPM Effects Management
 - Copy/Paste a DPM Effect [578](#)
 - Create a DPM Effect [579](#)
 - Delete a DPM Effect [575](#)
 - Lock/Unlock a DPM Effect [579](#)
 - Modify/Delete Keyframes [582](#)
 - Position Keyframes on the DPM Timeline [585](#)
 - Switcher Module - Kayak [575](#)
 - Use Keyframe Payout Controls [585](#)
- Dynamics Dialog Box
 - Klotz Audio [54](#)

E

Edit a CG Display Pattern

- CG List Module [266](#)
- Edit a Profile
 - Katalyst Panel [220](#)
- Edit a Set Point
 - Klotz Audio [80](#)
 - Wheatstone Audio [149](#)
 - Yamaha Audio [115](#)
- Edit a Virtual Source
 - Klotz Audio [84](#)
 - Yamaha Audio [119](#)
- Edit a Virtual Source Entry
 - Wheatstone Audio [153](#)
- Edit an Audio Layout
 - Wheatstone Audio [160](#)
- Edit an Audio Profile
 - Klotz Audio [71](#)
- Edit An Effect
 - Switcher Module - Konnect [626](#)
- Edit Menu
 - Event Timeline Module [357](#)
- Edit TME Associations
 - Event Timeline Module [394](#)
- Editing a Show
 - Building a Show [637](#)
 - Modify CG Conversion Files [638](#)
 - Multiple CG Automation [638](#)
- Effect Transition
 - Switcher Module - Kayak [490](#)
- Effect Transitions
 - Switcher Module - Kayak [586](#)
- Effects
 - Associate An Effect With a Wipe or DPM
 - EEffect [571](#)
 - Build a Cut With a Key [564](#)
 - Build a Wipe [560](#)
 - Create a New Effect [558](#)
 - DPM Effects Management [575](#)
 - Copy/Paste a DPM Effect [578](#)
 - Create a DPM Effect [579](#)
 - Delete a DPM Effect [575](#)
 - Lock/Unlock a DPM Effect [579](#)
 - Modify/Delete Keyframes [582](#)
 - Position Keyframes on the DPM Timeline [585](#)
 - Use Keyframe Payout Controls [585](#)
 - Effect Transitions [586](#)
 - Effects Management [572](#)
 - Access the Effects List [572](#)
 - Hide an Effect [574](#)
 - Recycle Bin [575](#)
 - Sort [573](#)
 - Set Keyer as a DPM [567](#)
 - Switcher Module - Kayak [557](#)
- Effects Definition Group Box
 - Switcher Module - Konnect [611](#)
- Effects List Group Box
 - Switcher Module - Konnect [609](#)
- Effects Management
 - Access the Effects List [572](#)
 - Hide an Effect [574](#)
 - Recycle Bin [575](#)
 - Sort [573](#)
 - Switcher Module - Kayak [489, 572](#)
- Effects Manager
 - Effects Definition Group Box [611](#)
 - Effects List Group Box [609](#)
 - Preview Effect Group Box [614](#)
 - Switcher Module - Konnect [607](#)
 - Transitions/E_MEM/Macros Group Box [612](#)
- Enco Audio Server Device Control
 - Device Control Module [315](#)
- Equalizer Dialog Box
 - Klotz Audio [52](#)
- Event Clock (Yellow)
 - Clocks & Timers Module [283, 293](#)
- Event Timeline Control
 - Event Timeline Module [354](#)
- Event Timeline Module [353](#)
 - Manage TME Associations
 - Delete TME Associations [397](#)
 - Operation [377](#)
 - Advance Timeline [384](#)
 - Cursor Relocate/Jump [384](#)
 - Import Rundowns [379](#)
 - Column Filtering [382](#)
 - Import and Monitor Rundown [379](#)
 - Pre-Load Rundown [380](#)
 - Insert a Note [382](#)
 - LBN (Late Breaking News) [383](#)
 - Manage TME Associations [391](#)
 - Add TME Associations [391](#)
 - Delete TME Associations [397](#)
 - Edit TME Associations [394](#)
 - Manual Override [383](#)
 - Page Break [385](#)
 - Pause/Stop [383](#)

- Play/Restart [383](#)
- Re-cue [384](#)
- TMEs (Transition Macro Event) [386](#)
- Overview [353](#)
- Event Timeline Control [354](#)
- Import Rundowns [370](#)
- Import Configuration (Filtering) [376](#)
- Import Rundown Update Indicator [374](#)
- Import Rundowns Pre-Load Function [373](#)
- Recommended Standard Settings [375](#)
- Menu Bar [357](#)
- Edit Menu [357](#)
- File Menu [357](#)
- Help Menu [363](#)
- Setup Menu [358](#)
- Tools Menu [363](#)
- View Menu [358](#)
- Window Menu [360](#)
- TME
- Structure [367](#)
- Icons [368](#)
- Marks [367](#)
- TME (Transition Macro Event) [364](#)
- TMEs (Transition Macro Event)
- Build a TME [386](#)
- Modify/Open a TME [389](#)
- Save a TME [388](#)
- Set/Check/Change TME Task Properties [390](#)
- Event Timeline Tools Menu
- DMP Module [348](#)
- Execute Macro
- Switcher Module - Konnect [630](#)

F

- Fader Manual Virtual Source Control
- Calrec Audio [166](#)
- Clear/Remove a Fader Control [65](#)
- Clear/Remove Fader Control [110](#)
- Create Fader Control [109](#)
- Klotz Audio [35](#)
- [63](#)
- Wheatstone Audio [125](#)
- Yamaha Audio [109](#)
- Fader Module
- Create a Module
- Katalyst [201](#)
- Fader Type and Source

- QUICbox Panel [236](#)
- Failure Recovery [641](#)
- Before a Failure Occurs [641](#)
- Full Redundant Failure Recovery [644](#)
- From Backup Workstation-B [646](#)
- From Primary Workstation-A [645](#)
- Network Failure - All Systems [642](#)
- Partial Redundant Failure Recovery [643](#)
- Single/Non-Redundant Failure Recovery [642](#)
- FAQ database [7](#)
- FGD Fade
- Switcher Module - Kayak [522](#)
- File Menu
- Event Timeline Module [357](#)
- Flare Suppression
- Switcher Module - Kayak [521](#)
- Folder/Directory
- Standards [673](#)
- Folders/Directories
- Standardization [673](#)
- frequently asked questions [7](#)
- Functional Test
- QUICbox Panel [239](#)

G

- General Operation Guidelines [631](#)
- General Setup Dialog Box
- Mainframe Setup
- Aux Setup Dialog Box [476](#)
- Color Background Dialog Box [477](#)
- MatchDef Scalar Configuration Dialog Box [478](#)
- General Setup Dialog Boxes
- M/E Setup [481](#)
- Mainframe Setup [475](#)
- Switcher Module - Kayak [474](#)
- General Tab [257](#)
- Get Audio Cut
- Device Control Module [317](#)
- Global Timed Events
- Auto-toggle Production List [302](#)
- Clocks & Timers Module [286](#), [296](#)
- Insert Production Cues – Global Timed Events (ENPS Rundown)
- Curly Bracket Markup [299](#)
- Insert Event [299](#)

- Square Bracket Markup [298](#)
- Setup Global Timed Events – Direct Entry [297](#)
- Trigger Global (Program) Clock [296](#)
- Global Timed Events (ENPS Rundown)
 - Insert Production Cues [298](#)
- Global Timed Events (NCS Rundown)
 - Insert Production Cues [298](#)
- Grass Valley web site [7](#)

H

- Hardware
 - Overview [25](#)
 - Core Components [25](#)
 - Options [26](#)
 - Production Options [27](#)
 - Redundancy Options [29](#)
- Help Menu
 - Event Timeline Module [363](#)
- Hide an Effect
 - Switcher Module - Kayak [574](#)

I

- Icons
 - Event Timeline Module [368](#)
- Identify a Hardware Panel
 - Katalyst Panel [222](#)
- Identify/Change a Module IP Address
 - Change a Module IP Address [222](#)
 - Identify a Hardware Panel [222](#)
 - Katalyst Panel [222](#)
- Ignite IQ Module [409](#)
 - Operation
 - Ignite IQ Auto Channel Assignment
 - Assigning Available Channels to a Video Channel Pool [450](#)
 - Creating a Video Channel Pool [447](#)
 - Overview [409](#)
 - Ignite IQ Templates
 - Ignite IQ Template Manager [411](#)
- Ignite IQ Template Manager [411](#)
 - Menu Bar [413](#)
 - Open Menu [413](#)
 - Save Menu [413](#)
 - Template Summary
 - Icons in this TME [414](#)
 - Thumbnail and Description [414](#)
 - TME Device Data [415](#)
 - Template Tables
 - Parameter Names and Parameter Name Values [416](#)
 - TME Device Data Values [416](#)
- Ignite IQ Templates
 - Ignite IQ Template Manager [411](#)
- Ignite Katalyst Automation Control Panel [187](#)
- Ignite Katalyst Profiles (Design Time) Dialog Box
 - Katalyst Panel [197](#)
- Ignite Katalyst Profiles (Run Time) Dialog Box
 - Katalyst Panel [196](#)
- Ignite Software
 - Open An Existing Show [634](#)
 - Set Up a New Show [633](#)
 - Software Version [634](#)
 - Start [632](#)
 - System Status [632](#)
- Import a Parameter Name [438](#)
- Import a Parameter Name From an Existing IQ Template [436](#)
 - Rename a Parameter Name at Import [443](#)
 - Save Imported Parameter Name [444](#)
- Import an Existing TME File [422](#)
- Import and Monitor Rundown
 - Event Timeline Module [379](#)
- Import Configuration (Filtering)
 - Event Timeline Module [376](#)
- Import Rundown Update Indicator
 - Event Timeline Module [374](#)
- Import Rundowns
 - Column Filtering [382](#)
 - Event Timeline Module [370, 373, 379](#)
 - Import and Monitor Rundown [379](#)
 - Import Configuration (Filtering) [376](#)
 - Import Rundown Update Indicator [374](#)
 - Import Rundowns Pre-Load Function [373](#)
 - Pre-Load Rundown [380](#)
 - Recommended Standard Settings [375](#)
- Import TMX via Import Rundown
 - Show Builder Assistant Module [467](#)
- Import Virtual Source
 - Wheatstone Audio [138](#)
- Importing a Rundown (Ignite System and Ignite IQ Module)
 - Building a Show [379](#)

- Importing Parameter Names From an Existing IQ Template
 - Import a Parameter Name [438](#)
- Individual Faders
 - Klotz Audio [35](#)
 - Yamaha Audio [96](#)
- Individual Program Fader Controls
 - Calrec Audio [166](#)
 - Wheatstone Audio [126](#)
- Insert a Note
 - Event Timeline Module [382](#)
- Insert Event
 - ENPS Rundown [299](#)
- Insert Production Cues – Global Timed Events (ENPS Rundown) [298](#)
 - Curly Bracket Markup [299](#)
 - Insert Event [299](#)
 - Square Bracket Markup [298](#)
- Insert Production Cues – Global Timed Events (NCS Rundown) [298](#)
- Insert Production Cues – Production Timed Events [303](#)
- Invert
 - Switcher Module - Kayak [520](#)
- IQ Auto Channel Assignment [417](#), [445](#)
 - Assign Available Channels to an M/E Pool [445](#)
 - Create a Video Channel Pool [447](#)
 - M/E Tab [419](#)
 - Video Channel Tab [419](#), [621](#)
- IQ Auto Channel Pool Dialog Box
 - M/E Tab [620](#)
 - Switcher Module - Konnect [619](#)
 - Video Channels Tab [621](#)
- IQ Module
 - IQ Auto Channel Assignment
 - M/E Tab [419](#)
 - Video Channel Tab [419](#), [621](#)
 - IQ Templates
 - IQ Template Manager [411](#)
 - IQ Template Manager–Initial Window [411](#)
 - IQ Template Manager–Main Window [412](#)
 - Template Manager–Menu Bar [413](#)
 - Template Summary [414](#)
 - Template Tables [415](#)
- Operation
 - IQ Auto Channel Assignment [445](#)
 - Assign Available Channels to a Video Channel Pool [450](#)
 - Assign Available Channels to an M/E Pool [445](#)
 - Create a Video Channel Pool [447](#)
 - IQ Template Manager
 - Import a Parameter Name From an Existing IQ Template [436](#)
 - Prerequisites for Creating IQ Templates [421](#)
 - Overview
 - IQ Auto Channel Assignment [417](#)
 - IQ Templates [409](#)
 - IQ Template Manager [411](#)
 - Create an IQ Template
 - Add a Thumbnail and a Description [424](#)
 - Add TME Device Data Values to Parameter Name Values [429](#)
 - Add/Rename Parameter Name and Parameter Name Values [426](#)
 - Configure Linked Fields [434](#)
 - Delete Parameter Name, Name Value, or TME Device Data Value [433](#)
 - Import an Existing TME File [422](#)
 - Save TME File as an IQ Template [435](#)
 - Import a Parameter Name From an Existing IQ Template [436](#)
 - Import a Parameter Name [438](#)
 - Rename a Parameter Name at Import [443](#)
 - Save Imported Parameter Name [444](#)
 - Prerequisites for Creating IQ Templates [421](#)
 - IQ Template Manager Dialog Box
 - Switcher Module - Konnect [622](#)
 - IQ Template Manager–Initial Window [411](#)
 - IQ Template Manager–Main Window [412](#)
 - IQ Templates [409](#)
 - IQ Auto Channel Assignment
 - M/E Tab [419](#)
 - Video Channel Tab [419](#), [621](#)
 - IQ Template Manager [411](#)
 - IQ Template Manager–Initial Window [411](#)
 - IQ Template Manager–Main Window [412](#)
 - Template Manager–Menu Bar [413](#)
 - Template Summary [414](#)
 - Template Tables [415](#)
 - IQT Standards
 - Abbreviations and Names [677](#)

K

Katalyst Panel

Audio Module [195](#)Button Module [189](#)Button Toolbox [193](#)Programmable Button Display Attributes [191](#)Programmable Buttons [190](#)Configure a Button [203](#)Assign/Edit Button Action [208](#)Assign/Edit Button Bitmap [212](#)Assign/Edit Button Color [206](#)Assign/Edit/Re-assign Button Style [203](#)Configure a Panel Profile [217](#)Add a Profile [217](#)Delete a Profile [219](#)Edit a Profile [220](#)Create a Module [199](#)Fader Module [201](#)Identify/Change a Module IP Address [222](#)Change a Module IP Address [222](#)Identify a Hardware Panel [222](#)Overview [187](#)Panel Profiles [196](#)Ignite Katalyst Profiles (Design Time) Dialog Box [197](#)Ignite Katalyst Profiles (Run Time) Dialog Box [196](#)Switcher Module [471](#)

Key Control Signal Adjustment

Clip and Gain [519](#)Clip Hi/Lo [519](#)Invert [520](#)Key Positioning [520](#)Key Size [520](#)Matte Fill [520](#)Opacity [520](#)Switcher Module - Kayak [519](#)

Key Positioning

Switcher Module - Kayak [520](#)

Key Setup Controls

Switcher Module - Kayak [518](#)

Key Setup Dialog Boxes

Additive Key Setup Dialog Box [525](#)Chroma Key Setup Dialog Box [526](#), [527](#)Luma Key Setup Dialog Box [522](#)Luma-Linear Key Setup Dialog Box [523](#)Mask Setup Dialog Box [533](#)Matte Setup Dialog Box [534](#)Preset Pattern Setup Dialog Box [532](#)Switcher Module - Kayak [522](#)

Key Size

Switcher Module - Kayak [520](#)

Keyer

Change Keyer Video Association [556](#)DPM Effect Setup Dialog Box [493](#)Special Effects Tab [500](#)Timeline Tab [493](#)Transform Tab [496](#)Effect Transition [490](#)Effects Management [489](#)Keyer Setup Menu [553](#)Switcher Module [606](#)Switcher Module - Kayak [486](#), [553](#)Take Keyer to Air [556](#)Wipe Effect Setup Dialog Box [492](#)

Keyer Setup Menu

Switcher Module - Kayak [553](#)

Keying

Chroma Key Control Signal Adjustment [520](#)Coring [521](#)FGD Fade [522](#)Flare Suppression [521](#)Primary Color Suppression [521](#)Secondary Color Suppression [521](#)

Chroma Key Ctrl Signal Adjust

Primary Suppression Dialog Box [529](#)Secondary Suppression Dialog Box [530](#)

Chroma Key Ctrl Signal Adjustment

Miscellaneous Setup Dialog Box [532](#)Key Control Signal Adjustment [519](#)Clip and Gain [519](#)Clip Hi/Lo [519](#)Invert [520](#)Key Positioning [520](#)Key Size [520](#)Matte Fill [520](#)Opacity [520](#)Key Setup Controls [518](#)Switcher Module - Kayak [517](#)

Klotz Audio

Audio Module [35](#)Operation [62](#)Adjust an Audio Source [62](#)Adjust Master Fader [65](#)Adjust/Setup/View Aux 1–Aux 6 [65](#)Audio Preview [92](#)

- Audio Program (LIVE) [94](#)
- Change a Page Name [63](#)
- Control EQ, Dynamics, and Delay via Audio Profiles [70](#)
 - Create An Audio Profile [70](#)
 - Delete An Audio Profile [73](#)
 - Edit an Audio Profile [71](#)
- Fader Manual Virtual Source Control [63](#)
 - Clear/Remove a Fader Control [65](#)
- Point To Point Routing [78](#)
- Select a Talk Back Source [74](#)
- Select/Edit Monitor Sources [75](#)
- Set Points [79](#)
 - Clear a Set Point [83](#)
 - Create a Set Point [79](#)
 - Delete a Set Point [82](#)
 - Edit a Set Point [80](#)
 - Load a Set Point to a Virtual Source [81](#)
- Setup Audio Task Properties [91](#)
- Source Setting Independent of Virtual Sources [66](#)
 - Adjust Source Audio Profile [68](#)
 - Adjust Source Mix Type [68](#)
 - Adjust Source Trim Gain [66](#)
- Virtual Sources [84](#)
 - Adding/Removing Virtual Sources From Aux Mixes [88](#)
 - Edit a Virtual Source [84](#)
- Overview [35](#)
 - Audio Main Context Menu [42](#)
 - Audio Profile Editor
 - Dynamics Dialog Box [54](#)
 - Equalizer Dialog Box [52](#)
 - Aux Configuration [57](#)
 - Monitor Source Selection [59](#)
 - Point To Point Routing [61](#)
 - Source Maintenance Dialog Box [48](#)
 - Virtual Source Editor Dialog Box [45](#)
 - Virtual Source Maintenance Dialog Box [44](#)
 - Audio Preview [37](#)
 - Audio Program (LIVE) [37](#)
 - Fader Manual Virtual Source Control [35](#)
 - Individual Faders [35](#)
 - Master Output Faders [41](#)
 - Set Points [38](#)
 - Set Point Editor [40](#)
 - Set Point Maintenance [39](#)
- Switcher Module [595](#)

L

- Layout Editor Editor Dialog Box
 - Wheatstone Audio [139](#)
- Layouts
 - Wheatstone Audio [138](#)
- LBN (Late Breaking News)
 - Event Timeline Module [383](#)
- LBN (Late Breaking News) Module [455](#)
 - Operation [456](#)
 - Overview [455](#)
- LBN Module
 - Add an LBN to the Event Timeline [459](#)
 - Create an LBN Hotkey [456](#)
 - Modify an LBN Hotkey [458](#)
- Load a Script
 - CG List Module [272](#)
- Load a Set Point to a Virtual Source
 - Klotz Audio [81](#)
 - Wheatstone Audio [150](#)
 - Yamaha Audio [116](#)
- Load an Audio Layout
 - Wheatstone Audio [160](#)
- Load Layout
 - QUICbox Panel [238](#)
- Load Presets From File
 - Camera Preset/Hotkey Module [245](#)
- Lock/Unlock a DPM Effect
 - Switcher Module - Kayak [579](#)
- Luma Key Setup Dialog Box
 - Switcher Module - Kayak [522](#)
- Luma-Linear Key Setup Dialog Box
 - Switcher Module - Kayak [523](#)

M

- M/E Effect Group Box
 - Switcher Module - Konnect [616](#)
- M/E Properties Dialog Box
 - Switcher Module - Kayak [535](#), [536](#)
- M/E Setup
 - Switcher Module - Kayak [481](#)
- M/E Setup Dialog Box
 - Switcher Module - Konnect [604](#)
- M/E Tab
 - Switcher Module - Konnect [620](#)
- Main User Interface

- Switcher Module - Konnect 623
 - Mainframe Setup
 - Aux Setup Dialog Box 476
 - Color Background Dialog Box 477
 - MatchDef Scalar Configuration Dialog Box 478
 - Switcher Module - Kayak 475
 - Manage Effects
 - Create An Effect 625
 - Delete An Effect 628
 - Edit An Effect 626
 - Switcher Module - Konnect 625
 - Manage TME ASsociations
 - Event Timeline Module 391
 - Manage TME Associations
 - Add TME Associations 391
 - Delete TME Associations 397
 - Edit TME Associations 394
 - Manual Clock (Blue)
 - Clocks & Timers Module 282, 293
 - Manual Override
 - Event Timeline Module 383
 - Manual Virtual Source Control 146
 - Create a Program Fader Control – Import a Virtual Source 143
 - Wheatstone Audio 143
 - Yamaha Audio 95
 - Marks
 - Event Timeline Module 367
 - Mask Setup Dialog Box
 - Switcher Module - Kayak 533
 - Master Output Faders
 - Klotz Audio 41
 - Wheatstone Audio 131
 - Yamaha Audio 102
 - Master Routing
 - Switcher Module - Konnect 623
 - Master Routing Dialog Box 484
 - Switcher Module - Konnect 602
 - Masters Mains Output Faders
 - Calrec Audio 173
 - MatchDef Scalar Configuration Dialog Box
 - Switcher Module - Kayak 478
 - Matte Fill
 - Switcher Module - Kayak 520
 - Matte Setup Dialog Box
 - Switcher Module - Kayak 534
 - Menu Bar 413
 - Edit Menu 357
 - Event Timeline Module 357
 - File Menu 357
 - Help Menu 363
 - Setup Menu 358
 - Template Manager 413
 - Tools Menu 363
 - View Menu 358
 - Window Menu 360
 - Messages Tab
 - Device Manager Module 337
 - Miscellaneous Dialog Setup Box
 - Switcher Module - Kayak 532
 - Mode and Configuration Control
 - Active Devices Configurations 338
 - Device Manager Module 337
 - Mode Control
 - Mode Control 338
 - Mode Control
 - Device Manager Module 338
 - Modify an LBN Hotkey
 - LBN Module 458
 - Modify CG Conversion Files 638
 - Modify MatchDef Properties of a Scalar Object
 - Switcher Module - Kayak 547
 - Modify/Delete Keyframes
 - Switcher Module - Kayak 582
 - Modify/Open a TME
 - Event Timeline Module 389
 - Monitor Source Selection
 - Klotz Audio 59
 - Multiple CG Automation 638
- ## N
- Name or Rename a Page
 - Calrec Audio 178
 - Names
 - Standards 674
 - Narrow Mode 259
 - Narrow or Wide Mode
 - CG List Module 262
 - Network Failure - All Systems
 - Failure Recovery 642

0

- On Button Down
 - QUICbox Panel [234](#)
- online documentation [7](#)
- Opacity
 - Switcher Module - Kayak [520](#)
- Open An Existing Show
 - Ignite Software [634](#)
- Operation
 - Adjust a Single Master Fader [146](#)
 - Adjust an Audio Source [62](#), [108](#), [142](#), [176](#)
 - Adjust Master Fader [65](#), [111](#)
 - Adjust/Setup/View a Group of Masters [146](#)
 - Adjust/Setup/View Aux 1–Aux 6 [65](#)
 - Adjust/Setup/View Cue Input/Output Faders [111](#)
 - Adjust/Setup/View Matrix Faders 1–8 [112](#)
 - Adjust/Setup/View Mixer Faders 1–6 [111](#)
 - Advance Timeline [384](#)
 - Audio Live [184](#)
 - Audio Preview [92](#), [123](#), [162](#), [183](#)
 - Audio Program (LIVE) [94](#), [124](#), [163](#)
 - Calrec Audio [176](#)
 - Camera Preset/Hotkey Module [242](#)
 - CG List Module [262](#)
 - CG/SS Module [276](#)
 - Change a Page Name [108](#), [142](#)
 - Clocks [292](#)
 - Event Clock (Yellow) [293](#)
 - Manual Clock (Blue) [293](#)
 - Show Clock (Green) [293](#)
 - Clocks & Timers Module [292](#)
 - Configure Pages [177](#)
 - Add/Assign/Edit a Slot or Virtual Source [178](#)
 - Name or Rename a Page [178](#)
 - Remove a Slot or Virtual Source [178](#)
 - Control EQ, Dynamics, and Delay via Audio Profiles [70](#)
 - Create An Audio Profile [70](#)
 - Delete An Audio Profile [73](#)
 - Edit an Audio Profile [71](#)
 - Copy/Paste Function [467](#)
 - Create a Preset Hotkey—Grass Valley HDC and CameraMan Robotic Cameras [243](#)
 - Load Presets From File [245](#)
 - Save Presets in File [245](#)
 - Create a Preset Hotkey—Telemetrys Cameras [248](#), [250](#)
 - Create a Preset Hotkey—Vinten/Radamac Cameras [246](#)
 - Create an Audio Layout [156](#)
 - Create CG/SS Hotkeys [276](#)
 - Cursor Relocate/Jump [384](#)
 - Delete an Audio Layout [162](#)
 - Delete CG/SS Hotkeys [279](#)
 - Device Control Module [315](#)
 - Device Manager Module [340](#)
 - DMP Module [351](#)
 - Edit an Audio Layout [160](#)
 - Event Timeline Module [377](#)
 - Fader Manual Virtual Source Control [63](#), [109](#)
 - Clear/Remove a Fader Control [65](#)
 - Clear/Remove Fader Control [110](#)
 - Create Fader Control [109](#)
 - Failure Recovery [641](#)
 - General Operation Guidelines [631](#)
 - Global Timed Events
 - Auto-toggle Production List [302](#)
 - Insert Production Cues – Global Timed Events (ENPS Rundown) [298](#)
 - Curly Bracket Markup [299](#)
 - Insert Event [299](#)
 - Square Bracket Markup [298](#)
 - Insert Production Cues – Global Timed Events (NCS Rundown) [298](#)
 - Setup Global Timed Events – Direct Entry [297](#)
 - Trigger Global (Program) Clock [296](#)
 - Import Rundowns [379](#)
 - Column Filtering [382](#)
 - Import and Monitor Rundown [379](#)
 - Pre-Load Rundown [380](#)
 - Import TMX via Import Rundown [467](#)
 - Insert a Note [382](#)
 - Klotz Audio [62](#)
 - LBN (Late Breaking News) [383](#)
 - LBN (Late Breaking News) Module [456](#)
 - Load an Audio Layout [160](#)
 - Manage TME Associations [391](#)
 - Add TME Associations [391](#)
 - Delete TME Associations [397](#)
 - Edit TME Associations [394](#)
 - Manual Override [383](#)
 - Manual Virtual Source Control [143](#)
 - Clear/Remove Fader [146](#)
 - Create a Program Fader Control – Import a

- Virtual Source 143
- Page Break 385
- Pause/Stop 383
- Place a CG on the Event Timeline 279
- Place Workstation in LIVE Mode 341
- Place Workstation in PREP Mode 345
- Play/Restart 383
- Point To Point Routing 78
- Production Timed Events (NCS Coding) 303
 - Insert Production Cues – Production Timed Events 303
 - Use MOS Objects for Timed Events 303
- Re-cue 384
- Refreshing Rundowns 469
- Save Current Audio Layout 158
- Search for TMX/IQT via Category 465
- Search for TMX/IQT via TME Search 463
- Select a Talk Back Source 74
- Select/Edit Monitor Sources 75
- Selecting a TMX 466
- Server Countdown Timer
 - Configuration 294
- Set Points 79, 113, 147
 - Clear a Set Point 83
 - Clear a Set Point from a Virtual Source 118
 - Clear Set Points From a Virtual Source 152
 - Create a Set Point 79, 113, 147
 - Delete a Set Point 82, 117, 151
 - Edit a Set Point 80, 115, 149
 - Load a Set Point to a Virtual Source 81, 116, 150
- Setpoint Configuration 178, 181
- Setup Audio Task Properties 91, 121, 155
- Setup/Edit Audio Task Properties 182
- Show Builder Assistant Module 463
- Source Setting Independent of Virtual Sources 66
 - Adjust Source Audio Profile 68
 - Adjust Source Mix Type 68
 - Adjust Source Trim Gain 66
- Switcher Module - Kayak 538
- Switcher Module - Konnect 623
- Timed Events 296
- Timers 294
- TMEs (Transition Macro Event) 386
- Verify Device Status 344
- Verify/Clear Message Status 345
- Virtual Source Configuration 179
- Virtual Sources 84, 153
 - Adding/Removing Virtual Sources From
 - Aux Mixes 88
 - Edit a Virtual Source 84
 - Edit a Virtual Source Entry 153
 - Wheatstone Audio 141
 - Yamaha Audio 107
- Other Documentation 20
- Overview
 - Audio Live 169
 - Audio Main Context Menu 42, 103, 134
 - Audio Profile Editor
 - Dynamics Dialog Box 54
 - Equalizer Dialog Box 52
 - Aux Configuration 57
 - Import Virtual Source 138
 - Layout Editor Editor Dialog Box 139
 - Layouts 138
 - Monitor Source Selection 59
 - Point To Point Routing 61
 - Source Maintenance Dialog Box 48
 - Virtual Source Editor Dialog Box 45, 106, 136
 - Virtual Source Maintenance Dialog Box 44, 104, 135
- Audio Module 31
- Audio Preview 37, 97, 127, 168
- Audio Program (LIVE) 37, 98, 128
- Audio Task Configuration 174
- Calrec Audio 165
- Camera Preset/Hotkey Module 241
 - Common Control Buttons 242
- CG List Module 253
- CG/SS Module 275
- Clocks 282
 - Event Clock (Yellow) 283
 - Manual Clock (Blue) 282
 - Show Clock (Green) 282
- Clocks & Timers Module 281
- Common Control Buttons 282
- Device Control Module 305
- Device Manager Module 335
- Devices Tab 336
- DMP Module 347
- Event Timeline Control 354
- Event Timeline Module 353
- Fader Manual Virtual Source Control 35, 125, 166
- Hardware 25
- Ignite IQ Module 409
- Import Rundowns 370
 - Import Configuration (Filtering) 376

- Import Rundown Update Indicator 374
 - Import Rundowns Pre-Load Function 373
 - Recommended Standard Settings 375
 - Individual Faders 35, 96
 - Individual Program Fader Controls 126, 166
 - IQ Auto Channel Assignment 417
 - Katalyst Panel 187
 - Audio Module 195
 - Button Module 189
 - Button Toolbox 193
 - Programmable Button Display Attributes 191
 - Programmable Buttons 190
 - Panel Profiles 196
 - Ignite Katalyst Profiles (Design Time) Dialog Box 197
 - Ignite Katalyst Profiles (Run Time) Dialog Box 196
 - Klotz Audio 35
 - LBN (Late Breaking News) Module 455
 - Manual Virtual Source Control 95
 - Master Output Faders 41, 102, 131
 - Masters Mains Output Faders 173
 - Menu Bar 357
 - Edit Menu 357
 - File Menu 357
 - Help Menu 363
 - Setup Menu 358
 - Tools Menu 363
 - View Menu 358
 - Window Menu 360
 - Messages Tab 337
 - Mode and Configuration Control 337
 - Active Devices Configurations 338
 - Mode Control 338
 - Production 348
 - QUICbox Panel 223
 - Audio Controls, Buttons, and Indicators 226
 - Configuration Interface 227
 - Audio Modules #1 and #2 Configuration Dialog Boxes 231
 - QUICbox Main Dialog Box (Button Layout) 230
 - Programmable Buttons 224
 - QUICbox Configuration Menu Bar 228
 - Server Countdown Timer 283
 - Configuration 285
 - Display 283
 - Set Points 38, 98, 128
 - Set Point Editor 40, 100, 130
 - Set Point Maintenance 39, 99, 129
 - Setpoint Configuration 171
 - Show Builder Assistant Module 461
 - Software 22
 - Switcher Module - Kayak 471
 - Switcher Module - Konnect 595
 - System 21
 - Timed Events 286
 - Global Timed Events 286
 - Production Timed Events 288
 - Timers 283
 - TME
 - Structure 367
 - Icons 368
 - Marks 367
 - TME (Transition Macro Event) 364
 - TMEs (Transition Macro Event)
 - Build a TME 386
 - Modify/Open a TME 389
 - Save a TME 388
 - Set/Check/Change TME Task Properties 390
 - User Interface 348
 - DMP TME Item Type 349
 - Event Timeline Tools Menu 348
 - Wheatstone Audio 125
 - Overview
 - Audio Main Context Menu
 - Import Virtual Source 138
 - Layout Editor Editor Dialog Box 139
 - Virtual Source Editor Dialog Box 136
 - Yamaha Audio 95
 - Overview
 - Audio Main Context Menu
 - Virtual Source Editor Dialog Box 106
- P**
- Page Break
 - Event Timeline Module 385
 - Panel Profiles
 - Ignite Katalyst Profiles (Design Time) Dialog Box 197
 - Ignite Katalyst Profiles (Run Time) Dialog Box 196
 - Katalyst Panel 196
 - Pause/Stop
 - Event Timeline Module 383
 - Perform Transition

- Switcher Module - Konnect [629](#)
- Place a CG on the Event Timeline
 - CG/SS Module [279](#)
- Place Workstation in LIVE Mode
 - Device Manager Module [341](#)
- Place Workstation in PREP Mode
 - Device Manager Module [345](#)
- Play A Clip [330](#)
- Play A Still [329](#)
- Play/Restart
 - Event Timeline Module [383](#)
- Point To Point Routing
 - Klotz Audio [61, 78](#)
- Populate CG List
 - CG List Module [262](#)
- Position Keyframes on the DPM Timeline
 - Switcher Module - Kayak [585](#)
- Pre-Load Rundown
 - Event Timeline Module [380](#)
- Prerequisites for Creating IQ Templates [421](#)
- Preset Pattern Setup Dialog Box
 - Switcher Module - Kayak [532](#)
- Preview Effect Group Box
 - Switcher Module - Konnect [614](#)
- Primary Color Suppression
 - Switcher Module - Kayak [521](#)
- Primary Suppression Dialog Box
 - Switcher Module - Kayak [529](#)
- Producing a Show
 - Building a Show [636](#)
- Production
 - DMP Module [348](#)
- Production (Timed Events)
 - Clocks & Timers Module [288](#)
- Production Timed Events (NCS Coding)
 - Clocks & Timers Module [303](#)
 - Insert Production Cues – Production Timed Events [303](#)
 - Use MOS Objects for Timed Events [303](#)
- Programmable Button Display Attributes
 - Katalyst [191](#)
- Programmable Buttons [190](#)
 - QUICbox Panel [224](#)

Q

- QUICbox Audio Modules #1 and #2
 - Configuration Dialog Boxes
 - Configuration Interface [231](#)
- QUICbox Configuration Menu Bar
 - QUICbox Panel [228](#)
- QUICbox Main Dialog Box (Button Layout)
 - Configuration Interface [230](#)
- QUICbox Panel [223](#)
 - Audio Controls, Buttons, and Indicators [226](#)
 - Audio Fader Configuration [235](#)
 - Accept or Cancel Fader Configuration [237](#)
 - Fader Type and Source [236](#)
 - Button Configuration [232](#)
 - Accept, Cancel, or Restore Default Button Configuration [235](#)
 - Default Appearance [232](#)
 - On Button Down [234](#)
 - Configuration [231](#)
 - Audio Fader
 - Setup dialog box [236](#)
 - Button Setup
 - Main dialog box [232](#)
 - Interface [227](#)
 - Save Layout [237](#)
 - Configuration Interface [227](#)
 - Audio Modules #1 and #2 Configuration Dialog Boxes [231](#)
 - QUICbox Main Dialog Box (Button Layout) [230](#)
 - Functional Test [239](#)
 - Load Layout [238](#)
 - Overview [223](#)
 - Programmable Buttons [224](#)
 - QUICbox Configuration Menu Bar [228](#)
- Quit Ignite Software [635](#)

R

- RAM Recorder
 - Clips and Stills Maintenance [333](#)
 - Delete Clips and Stills [333](#)
 - Device Control Module [319](#)
 - Play A Clip [330](#)
 - Play A Still [329](#)
 - Record A Clip [323](#)
 - Record A Still [319](#)
 - Trim A Clip [328](#)

- RAM Recorder Device Control
 - Clips Device Control [313](#)
 - Device Control Module [311](#)
 - Stills Device Control [312](#)
- Recall/Run E-MEM
 - Switcher Module - Konnect [629](#)
- Recommended Standard Settings
 - Event Timeline Module [375](#)
- Record A Clip [323](#)
- Record A Still [319](#)
- Re-cue
 - Event Timeline Module [384](#)
- Recycle Bin
 - Switcher Module - Kayak [575](#)
- Refreshing Rundowns
 - Show Builder Assistant Module [469](#)
- Remove a Slot or Virtual Source
 - Calrec Audio [178](#)
- Rename a Parameter Name at Import [443](#)
- Route Services
 - Main User Interface [623](#)
 - Master Routing [623](#)
 - Switcher Module - Konnect [623](#)
- Run/Pause Master E-MEM
 - Switcher Module - Konnect [630](#)
- Rundown List/Event Timeline Correlation
 - Building a Show [369](#)

S

- Save a TME
 - Event Timeline Module [388](#)
- Save Current Audio Layout
 - Wheatstone Audio [158](#)
- Save Imported Parameter Name [444](#)
- Save Presets in File
 - Camera Preset/Hotkey Module [245](#)
- Save TME File as an IQ Template [435](#)
- Scalar Objects
 - Associate a Video Format with a Scalar Object [545](#)
 - Modify MatchDef Properties of a Scalar Object [547](#)
- Scan/Shuttle a Video
 - Device Control Module [318](#)
- Scalar Objects
 - Switcher Module - Kayak [544](#)
- Script/CG List Module [253](#)
- Script-based Coding [640](#)
- Search for a Time Code
 - Device Control Module [318](#)
- Search for TMX/IQT via Category
 - Show Builder Assistant Module [465](#)
- Search for TMX/IQT via TME Search
 - Show Builder Assistant Module [463](#)
- Secondary Color Suppression
 - Switcher Module - Kayak [521](#)
- Secondary Suppression Dialog Box
 - Switcher Module - Kayak [530](#)
- Select a Device Control
 - Device Control Module [315](#)
- Select a Talk Back Source
 - Klotz Audio [74](#)
- Select/Edit Monitor Sources
 - Klotz Audio [75](#)
- Selecting a TMX
 - Show Builder Assistant Module [466](#)
- Server Countdown Timer
 - Clocks & Timers Module [283](#)
 - Configuration [285](#), [294](#)
 - Display [283](#)
- Set Button Properties
 - Switcher Module - Kayak [541](#)
- Set Display Colors
 - CG List Module [267](#)
- Set Display Mode
 - CG Column Order (Wide Mode only) [263](#)
 - CG Column Word Wrap (Wide Mode only) [265](#)
 - CG Display Pattern (Narrow Mode only) [264](#)
 - CG List Module [262](#)
 - Edit a CG Display Pattern [266](#)
 - Narrow or Wide Mode [262](#)
 - Set Display Colors [267](#)
- Set Keyer as a DPM
 - Switcher Module - Kayak [567](#)
- Set Point Editor
 - Klotz Audio [40](#)
 - Wheatstone Audio [130](#)
 - Yamaha Audio [100](#)
- Set Point Maintenance
 - Klotz Audio [39](#)
 - Wheatstone Audio [129](#)

- Yamaha Audio [99](#)
- Set Points
 - Clear a Set Point [83](#)
 - Clear a Set Point from a Virtual Source [118](#)
 - Clear Set Points From a Virtual Source [152](#)
 - Create a Set Point [79](#), [113](#), [147](#)
 - Delete a Set Point [82](#), [117](#), [151](#)
 - Edit a Set Point [80](#), [115](#), [149](#)
 - Klotz Audio [38](#), [79](#)
 - Load a Set Point to a Virtual Source [81](#), [116](#), [150](#)
 - Set Point Editor [40](#), [100](#), [130](#)
 - Set Point Maintenance [39](#), [99](#), [129](#)
 - Wheatstone Audio [128](#), [147](#)
 - Yamaha Audio [98](#), [113](#)
- Set Up a New Show
 - Ignite Software [633](#)
- Set/Check/Change TME Task Properties
 - Event Timeline Module [390](#)
- Setpoint Configuration
 - Calrec Audio [171](#), [178](#), [181](#)
- Setup Audio Task Properties
 - Klotz Audio [91](#)
 - Wheatstone Audio [155](#)
 - Yamaha Audio [121](#)
- Setup Drop-down Menu/Setup Menus
 - M/E Setup Dialog Box [604](#)
 - Master Routing Dialog Box [602](#)
 - Source Setup Dialog Box [599](#)
 - Source Configuration Group Box [600](#)
 - Source Display Setup Group Box [601](#)
 - Split M/E Setup SourceTable Dialog Box [605](#)
 - Switcher Module - Konnect [598](#)
- Setup Global Timed Events – Direct Entry [297](#)
- Setup Menu
 - Event Timeline Module [358](#)
- Setup/Edit Audio Task Properties
 - Calrec Audio [182](#)
- Show Builder Assistant Module
 - Operation [463](#)
 - Copy/Paste Function [467](#)
 - Import TMX via Import Rundown [467](#)
 - Refreshing Rundowns [469](#)
 - Search for TMX/IQT via Category [465](#)
 - Search for TMX/IQT via TME Search [463](#)
 - Selecting a TMX [466](#)
 - Overview [461](#)
- Show Clock (Green)
 - Clocks & Timers Module [282](#), [293](#)
- Software
 - Overview [22](#)
 - Production Automation [24](#)
 - Single-Point Device Control [22](#)
 - software download from web [7](#)
 - Software Version
 - Ignite Software [634](#)
- Sort
 - Switcher Module - Kayak [573](#)
- Source Configuration Group Box
 - Switcher Module - Konnect [600](#)
- Source Display Setup Group Box
 - Switcher Module - Konnect [601](#)
- Source Maintenance Dialog Box
 - Klotz Audio [48](#)
- Source Setting Independent of Virtual Sources
 - Adjust Source Audio Profile [68](#)
 - Adjust Source Mix Type [68](#)
 - Adjust Source Trim Gain [66](#)
 - Klotz Audio [66](#)
- Source Setup Dialog Box [481](#), [599](#)
 - Source Configuration Group Box [600](#)
 - Source Display Setup Group Box [601](#)
 - Switcher Module - Konnect [599](#)
- Special Effects Tab
 - Switcher Module - Kayak [500](#)
- Split M/E Setup SourceTable Dialog Box
 - Switcher Module - Konnect [605](#)
- Square Bracket Markup
 - ENPS Rundown [298](#)
- Standard Color Relationships – Techniques and Practices
 - Standardization [680](#)
- Standard Documentation [19](#)
- Standardization [673](#)
 - Abbreviations [674](#)
 - Abbreviations and Names [674](#)
 - Folders/Directories [673](#)
 - Names [674](#)
 - Standard Color Relationships – Techniques and Practices [680](#)
- Standards
 - Abbreviations [674](#)
 - Folder/Directory [673](#)
 - Names [674](#)
- Start
 - Ignite Software [632](#)

- Start Ignite Software [632](#)
- Stills Device Control [312](#)
- Structure
 - Icons [368](#)
 - Marks [367](#)
 - TME [367](#)
- Switcher Module
 - Effects
 - DPM Effects Management
 - Delete a DPM Effect [575](#)
 - Key Setup Dialog Boxes
 - Chroma Key Setup Dialog Box [526](#)
 - Source Setup Dialog Box [599](#)
- Switcher Module - Kayak
 - Configure Source Dialog Box [482](#)
 - Create a Chroma Key in a Double Box [590](#)
 - Customize Switcher Bank [538](#)
 - Customize Switcher Page [538](#)
 - Set Button Properties [541](#)
 - Switcher Source Setup [543](#)
 - Effects [557](#)
 - Associate An Effect With a Wipe or DPM Effect [571](#)
 - Build a Cut With a Key [564](#)
 - Build a Wipe [560](#)
 - Create a New Effect [558](#)
 - DPM Effects Management [575](#)
 - Copy/Paste a DPM Effect [578](#)
 - Create a DPM Effect [579](#)
 - Delete a DPM Effect [575](#)
 - Lock/Unlock a DPM Effect [579](#)
 - Modify/Delete Keyframes [582](#)
 - Position Keyframes on the DPM Timeline [585](#)
 - Use Keyframe Playout Controls [585](#)
 - Effect Transitions [586](#)
 - Effects Management [572](#)
 - Access the Effects List [572](#)
 - Hide an Effect [574](#)
 - Recycle Bin [575](#)
 - Sort [573](#)
 - Set Keyer as a DPM [567](#)
 - General Setup Dialog Box [474](#)
 - M/E Setup [481](#)
 - Mainframe Setup [475](#)
 - Aux Setup Dialog Box [476](#)
 - Color Background Dialog Box [477](#)
 - MatchDef Scalar Configuration Dialog Box [478](#)
 - Key Setup Dialog Boxes [522](#)
 - Additive Key Setup Dialog Box [525](#)
 - Chroma Key Setup Dialog Box [527](#)
 - Luma Key Setup Dialog Box [522](#)
 - Luma-Linear Key Setup Dialog Box [523](#)
 - Mask Setup Dialog Box [533](#)
 - Matte Setup Dialog Box [534](#)
 - Preset Pattern Setup Dialog Box [532](#)
 - Keyer [486, 553](#)
 - Change Keyer Video Association [556](#)
 - DPM Effect Setup Dialog Box [493](#)
 - Special Effects Tab [500](#)
 - Timeline Tab [493](#)
 - Transform Tab [496](#)
 - Effect Transition [490](#)
 - Effects Management [489](#)
 - Keyer Setup Menu [553](#)
 - Take Keyer to Air [556](#)
 - Wipe Effect Setup Dialog Box [492](#)
 - Keying [517](#)
 - Chroma Key Control Signal Adjustment [520](#)
 - Coring [521](#)
 - FGD Fade [522](#)
 - Flare Suppression [521](#)
 - Primary Color Suppression [521](#)
 - Secondary Color Suppression [521](#)
 - Chroma Key Ctrl Signal Adjust
 - Primary Suppression Dialog Box [529](#)
 - Secondary Suppression Dialog Box [530](#)
 - Chroma Key Ctrl Signal Adjustment
 - Miscellaneous Setup Dialog Box [532](#)
 - Key Control Signal Adjustment [519](#)
 - Clip and Gain [519](#)
 - Clip Hi/Lo [519](#)
 - Invert [520](#)
 - Key Positioning [520](#)
 - Key Size [520](#)
 - Matte Fill [520](#)
 - Opacity [520](#)
 - Key Setup Controls [518](#)
 - M/E Properties Setup Dialog Box [536](#)
 - Master Routing Dialog Box [484](#)
 - Operation [538](#)
 - Overview [471](#)
 - Scalar Objects [544](#)
 - Associate a Video Format with a Scalar Object [545](#)
 - Modify MatchDef Properties of a Scalar Object [547](#)
 - Source Setup Dialog Box [481](#)

- Transitions [535](#)
 - Use Utility Bus in Effect [590](#)
 - Switcher Module - Konnect
 - Effects Manager [607](#)
 - Effects Definition Group Box [611](#)
 - Effects List Group Box [609](#)
 - Preview Effect Group Box [614](#)
 - Transitions/E_MEM/Macros Group Box [612](#)
 - Execute Macro [630](#)
 - IQ Auto Channel Pool Dialog Box [619](#)
 - M/E Tab [620](#)
 - Video Channels Tab [621](#)
 - IQ Template Manager Dialog Box [622](#)
 - Keyer [606](#)
 - Manage Effects [625](#)
 - Create An Effect [625](#)
 - Delete An Effect [628](#)
 - Edit An Effect [626](#)
 - Operation [623](#)
 - Overview [595](#)
 - Perform Transition [629](#)
 - Recall/Run E-MEM [629](#)
 - Route Services [623](#)
 - Main User Interface [623](#)
 - Master Routing [623](#)
 - Run/Pause Master E-MEM [630](#)
 - Setup Drop-down Menu/Setup Menus [598](#)
 - M/E Setup Dialog Box [604](#)
 - Master Routing Dialog Box [602](#)
 - Source Setup Dialog Box [599](#)
 - Source Configuration Group Box [600](#)
 - Source Display Setup Group Box [601](#)
 - Split M/E Setup SourceTable Dialog Box [605](#)
 - TME Property Page Dialog Box [615](#)
 - M/E Effect Group Box [616](#)
 - Transitions/Source Routes/Options Group Box [618](#)
 - Switcher Source Setup
 - Switcher Module - Kayak [543](#)
 - System Overview [21](#)
 - Hardware [25](#)
 - Core Components [25](#)
 - Options [26, 27, 29](#)
 - Software [22](#)
 - Production Automation [24](#)
 - Single-Point Device Control [22](#)
 - System Status
 - Ignite Software [632](#)
- ## T
- Take Keyer to Air
 - Switcher Module - Kayak [556](#)
 - Techniques and Practices
 - Standard Color Relationships [680](#)
 - Template Manager–Menu Bar [413](#)
 - Template Summary [414](#)
 - Template Table Tab [261](#)
 - Template Tables [415](#)
 - Timed Events
 - Clocks & Timers Module [286](#)
 - Global Timed Events [286](#)
 - Production Timed Events [288](#)
 - Timeline Tab
 - Switcher Module - Kayak [493](#)
 - Timers
 - Clocks & Timers Module [283, 294](#)
 - TME
 - Structure [367](#)
 - Icons [368](#)
 - Marks [367](#)
 - TME (Transition Macro Event)
 - Event Timeline Module [364](#)
 - TME Abbreviations [674](#)
 - TME Effect Names [677](#)
 - TME Names [676](#)
 - TME Property Page Dialog Box
 - M/E Effect Group Box [616](#)
 - Switcher Module - Konnect [615](#)
 - Transitions/Source Routes/Options Group Box [618](#)
 - TME Standards
 - Abbreviations and Names [674](#)
 - TME Abbreviations [674](#)
 - TME Effect Names [677](#)
 - TME Names [676](#)
 - TMEs (Transition Macro Event)
 - Build a TME [386](#)
 - Event Timeline Module [386](#)
 - Modify/Open a TME [389](#)
 - Save a TME [388](#)
 - Set/Check/Change TME Task Properties [390](#)
 - Tools Menu
 - Event Timeline Module [363](#)
 - Transform Tab
 - Switcher Module - Kayak [496](#)

- Transitions
 - Switcher Module - Kayak [535](#)
- Transitions/E_MEM/Macros Group Box
 - Switcher Module - Konnect [612](#)
- Transitions/Source Routes/Options Group Box
 - Switcher Module - Konnect [618](#)
- Trigger Global (Program) Clock [296](#)
- Trim A Clip [328](#)
- Turn On/Off [631](#)
 - Turn Off [631](#)
 - Turn On [631](#)

U

- Use Keyframe Playout Controls
 - Switcher Module - Kayak [585](#)
- Use MOS Objects for Timed Events [303](#)
- Use Utility Bus in Effect
 - Switcher Module - Kayak [590](#)
- User Interface
 - DMP [348](#)
 - DMP TME Item Type [349](#)
 - Event Timeline Tools Menu [348](#)

V

- Verify Device Status
 - Device Manager Module [344](#)
- Verify/Clear Message Status
 - Device Manager Module [345](#)
- Video Channels Tab
 - Switcher Module - Konnect [621](#)
- Video Server Device Control
 - Device Control Module [309](#)
- View Menu
 - Event Timeline Module [358](#)
- Virtual Source Configuration
 - Calrec Audio [179](#)
- Virtual Source Editor Dialog Box
 - Klotz Audio [45](#)
 - Wheatstone Audio [136](#)
 - Yamaha Audio [106](#)
- Virtual Source Maintenance Dialog Box
 - Klotz Audio [44](#)
 - Wheatstone Audio [135](#)
 - Yamaha Audio [104](#)
- Virtual Sources

- Adding/Removing Virtual Sources From Aux Mixes [88](#)
- Edit a Virtual Source [84, 119](#)
- Edit a Virtual Source Entry [153](#)
- Klotz Audio [84](#)
- Wheatstone Audio [153](#)
- VTR Device Control
 - Device Control Module [310](#)

W

- web site documentation [7](#)
- web site FAQ database [7](#)
- web site Grass Valley [7](#)
- web site software download [7](#)
- Wheatstone Audio
 - Operation [141](#)
 - Adjust a Single Master Fader [146](#)
 - Adjust an Audio Source [142](#)
 - Adjust/Setup/View a Group of Masters [146](#)
 - Audio Preview [162](#)
 - Audio Program (LIVE) [163](#)
 - Change a Page Name [142](#)
 - Create an Audio Layout [156](#)
 - Delete an Audio Layout [162](#)
 - Edit an Audio Layout [160](#)
 - Load an Audio Layout [160](#)
 - Manual Virtual Source Control [143](#)
 - Clear/Remove Fader [146](#)
 - Create a Program Fader Control – Import a Virtual Source [143](#)
 - Save Current Audio Layout [158](#)
 - Set Points [147](#)
 - Clear Set Points From a Virtual Source [152](#)
 - Create a Set Point [147](#)
 - Delete a Set Point [151](#)
 - Edit a Set Point [149](#)
 - Load a Set Point to a Virtual Source [150](#)
 - Setup Audio Task Properties [155](#)
 - Virtual Sources [153](#)
 - Edit a Virtual Source Entry [153](#)
- Overview [125](#)
 - Audio Main Context Menu [134](#)
 - Import Virtual Source [138](#)
 - Layout Editor Editor Dialog Box [139](#)
 - Layouts [138](#)
 - Virtual Source Editor Dialog Box [136](#)
 - Virtual Source Maintenance Dialog Box [135](#)

- Audio Preview [127](#)
- Audio Program (LIVE) [128](#)
- Fader Manual Virtual Source Control [125](#)
- Individual Program Fader Controls [126](#)
- Master Output Faders [131](#)
- Set Points [128](#)
 - Set Point Editor [130](#)
 - Set Point Maintenance [129](#)
- Wide Mode [260](#)
- Window Menu
 - Event Timeline Module [360](#)
- Wipe Effect Setup Dialog Box
 - Switcher Module - Kayak [492](#)

Y

- Yamaha Audio
 - Audio Module [95](#)
 - Operation [107](#)
 - Adjust an Audio Source [108](#)
 - Adjust Master Fader [111](#)
 - Adjust/Setup/View Cue Input/Output Faders [111](#)
 - Adjust/Setup/View Matrix Faders 1–8 [112](#)
 - Adjust/Setup/View Mixer Faders 1–6 [111](#)
 - Audio Preview [123](#)
 - Audio Program (LIVE) [124](#)
 - Change a Page Name [108](#)
 - Fader Manual Virtual Source Control [109](#)
 - Clear/Remove Fader Control [110](#)
 - Create Fader Control [109](#)
 - Set Points [113](#)
 - Clear a Set Point from a Virtual Source [118](#)
 - Create a Set Point [113](#)
 - Delete a Set Point [117](#)
 - Edit a Set Point [115](#)
 - Load a Set Point to a Virtual Source [116](#)
 - Setup Audio Task Properties [121](#)
 - Virtual Sources
 - Edit a Virtual Source [119](#)
 - Overview [95](#)
 - Audio Main Context Menu [103](#)
 - Virtual Source Editor Dialog Box [106](#)
 - Virtual Source Maintenance Dialog Box [104](#)
 - Audio Preview [97](#)
 - Audio Program (LIVE) [98](#)
 - Individual Faders [96](#)
 - Manual Virtual Source Control [95](#)

Standardization

Folders/Directories


Note For all file structures, use standard and consistent techniques and practices.

Organize TMEs very carefully when saving them so they can be found easily and quickly. To do so, it is necessary to:

- Use standard and consistent techniques and practices.
- Create a standardized file management structure ([Figure 705](#)).

Note With a standard, it is easy to maintain control of existing files and to enable better back-up procedures.

Figure 705. Sample File Structures.



1. Create a folder at the root level of the C: drive and name it with the station identifier; e.g., [Figure 705](#).
2. Under the station identifier folder, create sub-folders ([Figure 705](#)) for Standard-Practices, Station-Macros, Station-TMEs, and the IQ option; e.g., C:\ABCD\Station-TMEs\Graphics.

Note Ignite IQ is an option and is not available for configurations not using the IQ option.

- The IQ sub-folder
C:\(station identifier)\IQ
should contain all IQTs and TMXs. This IQ folder should have separate sub-folders for each type; e.g.:
 - C:\(station identifier)\IQ\IQTs
 - C:\(station identifier)\IQ\TMXs
- The Station-Macros sub-folder
C:\(station identifier)\Station-Macros
should contain all macros for all shows and directors.
- The Station-TMEs sub-folder
C:\(station call letters)\Station-TMEs
should contain all TMEs. This TME folder should have separate sub-folders for each TME type; e.g.:
 - C:\(station identifier)\TMEs\Cameras
 - C:\(station identifier)\TMEs\Graphics
 - C:\(station identifier)\TMEs\Live-Elements
 - C:\(station identifier)\TMEs\Miscellaneous
 - C:\(station identifier)\TMEs\Taped-Elements
- The Standard-Practices sub-folder
C:\(station call letters)\Standard-Practices
should contain all the standard naming, abbreviations, colors, and file structure techniques and practices used. This file should be kept current.

Note Typically, for ease of use and access, the Standards file(s) is a text file created and maintained with Microsoft® Notepad.

Abbreviations and Names

TME Standards

TME Abbreviations

Note For all abbreviations, use standard and consistent techniques and practices. For quick and easy reference, create and maintain a site specific list of standard abbreviations text file at
C:\(station call letters)\Standard_Practices\TME-Abbreviations.txt.

The most commonly used Ignite TME abbreviations are listed in [Table 17 on page 675](#) and [Table 18 on page 675](#)

Note The following list is not all inclusive but rather a starting point and guideline for establishing site relative abbreviations.

Table 17. TME Abbreviation Examples

Abbreviation	Definition
C	Camera
CG	Character Generator
CK	Chroma Key
DB	Double Box
FS REM RTR	FrameSync Remote Router
FUL	Full Screen
LP	Load Prompter
M	Mic
MON	Monitor
NR	Newsroom
OTS	Over The Shoulder
RAM	RAM Recorder
SOT	Any Video with sound full
SS	Still Store
SVO	SOT VO or NATS Pause
SX	Sports
T	Talent
TB	Triple Box
TZ	Teases
V	For Video sources (tapes or servers)
VO	Anything with NAT sound
WX	Weather

Using the standard abbreviations in [Table 17 on page 675](#) and adding a sequential number to identify each instance of that item, the site abbreviations might resemble those in [Table 18 on page 675](#).

Note This following list is not all inclusive but rather a starting point and guideline for establishing site relative abbreviations.:

Table 18. Site Specific TME Abbreviation Examples

Site Abbreviation	Definition
C1	Camera 1
C2	Camera 2

Table 18. Site Specific TME Abbreviation Examples - (continued)

Site Abbreviation	Definition
C3	Camera 3
CG1	Character Generator Channel 1
CG2	Character Generator 2
M1	Mic 1
M2	Mic 2
M3	Mic 3
T1	Talent 1
T2	Talent 2
T3	Talent 3
V1	Video Source 1
V2	Video Source 2
T4	Talent 4
T5	Talent 5
T6	Talent 6

Note For all names, use standard and consistent techniques and practices.

TME Names

Note For all names, use standard and consistent techniques and practices. For quick and easy reference, create and maintain a site specific list of standard TME names at
C:\(station call letters)\Standard_Practices\TME-Names.txt.

Typically, the most common naming conventions use the standard abbreviations and answers to the four questions below.

Table 19. Common TME Naming Convention Examples

Question	Sample Answer
What is the transition?	Dissolve
What Video is involved?	Camera 1
What Audio is included?	Talent 1
What CG/SS elements that might be needed?	CG2 keyed

For example, based upon the standard site abbreviations and the answers above, the standard naming would be **DC1T1CG2**; i.e., Dissolve, Camera One, Talent One, With Character Generator Channel 2 keyed on top.

TME Effect Names

Note For quick and easy reference, create and maintain a site specific list of standard effects naming at
C:\(station call letters)\Standard_Practices\TME-EffectNames.txt.

Typically, the most common effect naming uses the standard abbreviations and answers to the three questions below:

Question	Sample Answer
What is the effect type? (Cut, Wipe, Chroma Key, Double Box, etc.)	DB
What is the M/E? bank (ME1, ME2, ME3, ME4)	ME1
What is the keyer? (Key 1, Key 2, Key 3, Key 4)	K1K2

For example, based upon the standard site abbreviations and the answers above, the standard effect name would be **DBME1K1K2**; i.e., The effect is a **Chroma Key**, on **M/E 1**, and the keyer(s) is **Key 1** and **Key 2**.

IQT Standards

IQ Template Abbreviations

Note For all IQ Template abbreviations, use standard and consistent techniques and practices. For quick and easy reference, create and maintain a site specific list of standard abbreviations text file at
C:\(station call letters)\Standard_Practices\IQ-TemplateAbbreviations.txt.

The most commonly used Ignite IQ Template abbreviations are listed in [Table 20 on page 677](#). Guidelines for these abbreviations are:

- The number of characters should be limited to 3
- Per station, all IQ templates should have the same number of characters

Note The following list is not all inclusive but rather a starting point and guideline for establishing site relative abbreviations. Based on the guidelines provided in [IQ Template Abbreviations on page 677](#), station sites can add/delete as necessary to meet their individual production needs.

Table 20. IQ Template Abbreviation Examples

Abbreviation	Definition
AUX	Auxiliary
BOX	Double Box, Triple Box, Quad Box, Split Screen, etc.
CAM	Camera

Table 20. IQ Template Abbreviation Examples - (continued)

Abbreviation	Definition
CKY	Chroma Key, Weather, etc.
DIG	DigiCart®
DPM	Wipe, Page Turn, Slab, etc.
GFX	Graphics Device (CG, SS)
MDK	Minidisk
MIC	Microphone
MON	Monitor
OTS	Camera with OTS, Camera with Key Graphic
RAM	RAM Recorder
REM	Remote or FrameSync
SVR	Video Server
TAL	Talent
VTR	Video Tape Recorder/Video Cassette

IQT Parameter Names

Note For all abbreviations and names, use standard and consistent techniques and practices. For quick and easy reference, create and maintain a site specific list of standard abbreviations text file at
C:\(station call letters)\Standard_Practices\IQ-ParamNameAbbreviations.txt.

The most commonly used Ignite IQ Parameter Name abbreviations are listed in [Table 21 on page 678](#). Guidelines for these abbreviations are:

- The number of characters should be limited to 1
- Per station, all IQ parameter names should have the same number of characters

Note The following list is not all inclusive but rather a starting point and guideline for establishing site relative abbreviations. Based on these guidelines, station sites can add/delete as necessary to meet their individual production needs.

Table 21. IQ Parameter Name Abbreviations

Abbreviation	Definition
C	Camera
E	Switcher and DPM effects
G	Graphics
M	Microphone
P	Camera Presets

IQT Value Abbreviations

Note For all abbreviations, use standard and consistent techniques and practices. For quick and easy reference, create and maintain a site specific list of standard abbreviations text file at
C:\(station call letters)\Standard_Practices\IQ-ValueAbbreviations.txt.

The most commonly used Ignite IQ Value abbreviations are listed in [Table 22 on page 679](#). Per station, all IQ value abbreviations should be consistent.

Note The following list is not all inclusive but rather a starting point and guideline for establishing site relative abbreviations.

Table 22. IQ Value Abbreviations

Parameter Name	Value
C	1–16 (maximum value range)
E	C = Cut W = Wipe F = Fade CK1, CK2, CK3, CK4 = Cut Key 1–4 FK1, FK@, FK3, FK4 = Fade Key 1–4 WK1, WK@, WK3, WK4 = Wipe Key 1–4 etc.
G	1–4 (or more based on the number of graphic device channels)
M	1–99999999 (maximum value range)
P	1–125 per camera

IQT Effect Names

Note For quick and easy reference, create and maintain a site specific list of standard effects naming at
C:\(station call letters)\Standard_Practices\IQ-EffectNaming.txt.

Typically, the most common effect naming uses the standard abbreviations and answers to the three questions below:

Table 23.

















Question	Sample Answer
What is the effect type? (Cut, Wipe, Chroma Key, Double Box, etc.)	DB
What is the M/E? bank (ME1, ME2, ME3, ME4)	ME1
What is the keyer? (Key 1, Key 2, Key 3, Key 4)	K1K2

For example, based upon the standard site abbreviations and the answers above, the standard effect name would be **DBME1K1K2**; i.e., The effect is a **Double Box**, on **M/E 1**, and the keyers are **Key 1** and **Key 2**.

Color Relationships

Note For all colors, use standard and consistent techniques and practices. For quick and easy reference, create and maintain a site specific list of standard abbreviations text file at
C:\(station call letters)\Standard_Practices\Colors.txt.

The most commonly applied color relationships are:.

	SOT-VO
	Chroma Key
	SS/CG, Graphics Devices
	DPM Effects
	Teases
	Fade to Black
	Music-DigiCart, Minidisk
	Camera-C
	Aux
	VO
	Mics
	Camera-OTS
	Live-Remotes
	SOT
	Boxes
	RAM Recorder

Glossary

A

AES/EBU

The standard for digital audio as defined by the Audio Engineering Society and the European Broadcast Union. The standard specified for professional post production audio, a sample frequency of 48 kHz and a quantizing level of either 16 or 20 bits. Used by most forms of digital audio from CDs to D1—Sony 19mm cassette tape format—the first digital tape format, hence D1.

Aspect

The horizontal and vertical display dimension ratio of a picture; i.e., the width divided by the height (usually expressed as x:y). The aspect ratio of a traditional standard definition (SD) television screen is 4:3, or 1.33:1. High definition (HD) television uses an aspect of 16:9 (5 1/3 to 3), or about 1.78:1.

Auto Transition

A transition having a predefined duration generally initiated by pressing a control panel button.

Automation Section

Consists of a rundown list, event timeline, rundown converter, and LBN buttons.

B

Background Bus

A row of buttons on an M/E used to select background video signals. Typically labeled A and B, with A representing the current output and B representing the next output.

Background Transition

A transition between the background video signals selected on an M/E.

Background Video

Video that forms a background scene into which a key may be inserted.

Backing Color

The color in a chroma key scene that will be replaced with another video signal.

Bit Rate

The number of bits per second passed from one point to another.

Black

A black video signal generated within the switcher.

Box Wipe

A rectangular wipe pattern. For masking, the system provides a special box wipe pattern generator allowing independent control of the placement of each side of the box.

C

CCD (Charge-Coupled Device)

An image sensor used in digital photography.

CCFL (Cold-Cathode Fluorescent)

CCFL tubes are used for backlighting an LCD display.

CG (Character Generator)

Generates text and sometimes graphics for video titles.

Chroma

The depth or saturation of color. Chroma, hue, and luminance make up the three characteristics of television color.

Chroma Gain (chroma, color, saturation)

The gain of an amplifier as it pertains to the intensity of colors in the active picture.

Chroma Key

A video key effect in which one video signal (insert video) is inserted in place of areas of a particular color in another video signal. Blue and green are the chroma key colors most frequently used.

Clean Feed

A final output of the switcher that does not include downstream key effects or fade to black. Also refer to **Programmable Clean Feed**.

Clip

A threshold level adjustment to which the keying attribute (luminance, chrominance) is compared for generating the internal key control signal. Clip, in conjunction with gain, sets the switching point between the background and the key fill. Also refer to **Gain**.

Clip High, Clip Low

An alternative to Clip and gain keying, providing independent control of the points where the background video and the key fill video are each fully visible.

Complex Wipe Pattern Generator

A wipe pattern generator with additional capabilities (for example, matrix wipes).

Component Video

A video signal that keeps color and luminance information separate. RGB; Y, R Y, B Y; and Y, Cr, Cb are examples of component video.

Composite Video

An encoded video signal that combines color information with luminance information. NTSC, PAL, and D 2 are examples of composite video.

Compositing

Combining two or more video signals together into one output signal.

Control Signal

A signal used to perform an alteration or transition of video signals. For example, control signals are used for keying, masking, and wipe transitions.

Control Surface

The set of controls available to a single operator. These controls may reside on separate but related control panels.

Cross Fade

Refer to **Mix**.

Crosspoint

An electronic switch, usually controlled by a button on the panel, that allows video or audio to pass when the switch is closed.

Cut

An instantaneous switch from one picture to another. Switching circuitry allows cuts only during the vertical interval of the video signal to prevent disruption of the picture.

Cutaway

The act of momentarily "cutting away" (taking a shot of something else) from the main scene to hide jump cuts. This brief shot establishes continuity between two other shots, provides the necessary video pad when editing according to sound bites (portion of videotaped interview in which you see and hear the person talk), and helps to bridge jumps in time and/or location.

Cutback

The act of “cutting back” to the main scene to hide jump cuts. This brief shot establishes continuity between two other shots, provides the necessary video pad when editing according to sound bites (portion of video-taped interview in which you see and hear the person talk), and helps to bridge jumps in time and/or location.

D**DDR (Digital Data Recorder)**

Refer to **DVR**.

DE

Digital Effects

Delegate

To assign panel controls to a particular operating function. Some panel controls (buttons, knobs, and joystick) can affect more than one function. The operator can choose an alternative function by delegating the panel controls to that function (typically by pressing or holding down a panel button).

Deserializer

A device that converts serial digital information to parallel.

Dissolve

Refer to **Mix**.

DPM® (Digital Picture Manipulator)

Grass Valley USA, LLC term for digital video effects equipment that performs digital effects such as: compression and transformations; e.g., change its size, shape, angle, flying a picture, turning a page, shattering an image. Also refer to **DVE**.

DPOP (Double Press Open)

Rapidly pressing a control panel button twice to open a related menu. On the system, buttons supporting DPOP are labeled with a graphical indicator.

DVE (Digital Video Effects)

Refers to video equipment that performs digital effects for production such as: compression and transformations; e.g., flying a picture, turning a page, shattering an image. (A registered trademark of Nippon Electric Company.) Also refer to **DPM**.

DVR (Digital Video Recorder)

[Also **DDR** (Digital Data Recorder), **VDR** (Video Disk Recorder)]

A video recorder/playback device that uses a hard disk drive or optical disk drive mechanism. Disk recorders offer nearly instantaneous access to recorded material.

E**Effect**

A setup of panel controls specifying the sources involved and any processing applied to those sources. Effects can be learned (saved) and recalled by the E MEM effects memory system.

Effect Transition

Recalling an E MEM effect so that a transition is automatically performed at the start of the recall.

Effects Processor

The portion of a switcher that performs mixes, wipes, and cuts between background and/or effects key video signals.

E-MEM (Effects Memory)

A feature that permits control panel setups (effects) to be stored for later recall.

Engineering Setups

On the system, a collection of configuration settings that establishes an essential baseline for system operation and integrates the system into a facility.

ENPS

Electronic News Production System

Ethernet

A form of high speed data transport between devices on a network.

Event Timeline

A timeline that combines all production events in the form of TMEs that allow one person to direct a live show.

F

Fade To Black

A mix transition to black.

Field

One scan of an interlaced video image. In interlace systems, two fields are required to make a complete picture (video frame) because alternate lines are scanned. Also refer to **Frame**.

Fill Video

A video signal that fills a hole cut in background video by a key control signal.

Fixed Linear Key

A linear key that uses predetermined Clip and gain settings that are not adjustable.

Flip-Flop

A transition where the sources selected on the background buses (for example, preset and program) of an M/E are exchanged at the end of a transition. The original preset bus source becomes selected on the program bus and the original program bus source becomes selected on the preset bus.

FPGA

Field Programmable Gate Array.

Frame

One complete scan of a video image. For interlace video, alternate lines are scanned so a frame containing all the picture information consists of two fields. Also refer to **Field**.

Frame Rate

The number of frames presented per second. For interlace systems the frame rate is half the field presentation rate.

G

Gain

An amplification factor applied to a key control signal by a keyer that determines how much, if any, of the background and key fill video will be mixed together at the key edge areas. Low gain (1, or unity) generally results in a linear key.

GPI (General Purpose Input)

GPO (General Purpose Output)

A digital signal interface, used to activate a device or piece of equipment for limited remote control of a device's functions.

GUI (Graphical User Interface)

A Windows based user interface screen or series of screens allowing the user to point-and-click to select icons rather than typing commands

H

HD

High Definition

House Sync

Sync generated within a facility that is used as a reference for generating and/or timing other signals.

Hue

The location of a color on the color spectrum (i.e. red, yellow, green, blue). Chroma, hue, and luminance make up the three characteristics of television color.

I**iDPM™**

Internal Digital Picture Manipulator. Also refer to **DPM**.

iNEWS

Avid Newsroom Computer System (formerly AvStar)

Interlace

A system of video scanning where the odd and even numbered lines of a picture are presented consecutively as two separate interleaved fields. The two fields required to make a complete picture are called a frame.

IP (Internet Protocol)

A data-oriented protocol used for communicating data across a packet-switched inter-network.

J**Jitter**

An undesirable variation in the timing of transitions in a digital signal.

Joystick

A hardware positioner with control of multiple axes.

K**Key**

An effect where a portion of a background scene is replaced by a new video. Key cut and key fill signals are involved, though in some cases the same signal may be used for both (self key).

Key Cut

In key effects, the key cut signal is used to specify where to cut a hole in the background that will be filled with the key fill video. The key cut signal determines the shape of the key effect.

Key Fill

In key effects, the video signal that fills the hole cut in the background video.

Key Frame (Keyframe)

A complete definition of an effect at a single point in time. Default key frame values can be set for a suite.

Key Invert

Reversing the polarity of a key, such that material formerly keyed out will be keyed in, and vice versa.

Key Mask

[Also **Mask**]

A key mode that allows use of a wipe pattern generator to prevent some undesirable portions of the key cut signal from cutting holes in the background video.

Key Memory

A feature where the last keying and video processing settings for a source are retained and re-imposed when that source is re-selected. Default source memory values can be set for each source on each bus.

Key Priority

The stacking order of multiple keys. The keyed signal with the highest priority appears in front of all the others. Keyed signals appear below higher priority keys and in front of lower priority keys, in a stack. A key priority transition changes the order of the keys without changing the background output.

Keyer

An electronic circuit that creates a control signal to control a video multiplier based on selective information contained in a video signal.

L

LBN (Late Breaking News) Hotkey

A quick way (hotkey) to insert a stored element onto the Event Timeline during a show. TMEs or sequences of multiple TMEs can be stored on a single LBN hotkey.

LCD

Liquid Crystal Display

Learn

To save a panel setup using E-MEM.

LED

Light-Emitting Diode

Linear Key

A key in which the keyer signal is faithfully reproduced in the final key effect. Linear keying preserves soft key edges, and generally has a gain of 1, or unity.

Look Ahead Preview

Video that shows the result of the currently setup next transition.

Looping, Loop-Through

An input that includes two connectors. One connector accepts the input signal, and the other connector is used as an output for connecting the input signal to another piece of equipment. Only the analog reference input is loop through.

Luminance

The brightness of the picture or area of the screen being considered. Chroma, hue, and luminance make up the three characteristics of television color.

The color video picture information contains two components: luminance (brightness and contrast) and chrominance (hue and saturation).

Luminance Key

A key effect in which the portions of the key cut signal that are greater in luminance than the clip level cuts the hole in the background scene. Generally used when the key cut and key fill signals originate from the same source. Luminance key clip and gain is adjustable.

Lux

A standardized model of human brightness perception, it is the SI unit of illuminance and luminous emittance, used as a measure of apparent light intensity hitting or passing through a surface.

M

M/E (Mix/Effects)

Pertaining to the video production circuitry and controls of a switcher involved in compositing video signals where a composite of two or more images can be created.

Mask

Refer to **Key Mask**.

Matte

Internally-generated color video that can be adjusted for luminance, hue, and chroma. Matte can be used to fill areas of keys and borders.

Matte Fill

Using matte video to fill the hole of a key effect.

Matte Generator

A video generator that produces matte signals.

Mix

[Also **Dissolve**, **Cross Fade**]

A transition between two video signals in which one signal fades out as the other signal fades in.

Multiplier

A control circuit in which a control signal is multiplied with one or more input video signals. The resulting video output level varies from full on to full off according to the state of the control signal.

N**NRCS**

Newsroom Computer System

NTSC (National Television System Committee)

U.S. government and industry committee that defined the 525-line 60 (59.94) interlaced fields per second analog broadcast TV standard over 50 years ago. (This format is referred to as NTSC.) Of the 525 scan lines, 480 (give or take a few) contain the picture and the rest contain synchronizing information, hold the encoded closed caption text, and provide a time delay to move the electron beam back to the top of the screen. NTSC is used mainly in North America and Japan.

O**Object**

An individual functional area of a system, typically one of several having similar capabilities.

P**PAL (Phase Alternate Line)**

A 625 line 50 interlaced fields per second analog broadcast standard used in many parts of the world, primarily Europe, but not the U.S.A. So named because the chroma sub-signal phase is different on each successive scan line to reduce picture artifacts.

Pattern Border

A variable width border that occurs at the edges of a wipe pattern.

Pixel

A picture element. A pixel is a digital sample of the luminance and color values of a picture at a single point.

Point of Use

A location in the system where a resource is used. A resource is generally used at different locations at different times. However, with some resources it is possible to use the same resource at different locations at the same time.

Preference

Refer to **Suite Preference** and **User Preference**.

Preset Bus

[Also **B bus**]

A row of source buttons used to select the source that will be output by that M/E during the next background transition. .

Preset Pattern

A key effect in which a wipe pattern that has been preset to a desired size and location is used to cut the key hole. The characteristics of the pattern are set using pattern controls.

Preview

A video signal that is viewed before it is output by the switcher. Also refer to **Look Ahead Preview** and **Switched Preview**.

Production Switcher

Refer to **Switcher**.

Profile

Model name of a Grass Valley USA, LLC Video Disk Recorder.

Program Bus

[Also **A bus**]

A row of source buttons used to select the source for the current output of that M/E. It is the final output from a switcher that is broadcast or recorded. (.)

Programmable Clean Feed

A type of clean feed where different keys can be selected for inclusion or exclusion from the clean feed.

Q

R

RAM Recorder

A device that captures, saves, and outputs a still video image or in some cases motion video clips. On the Kayak system the RAM Recorder option can capture still images, motion video, and animation for playback. The RAM Recorder is also referred to as a Still Store.

Recall

To restore a previous panel setup that has been learned using E-MEM.

Reclocking

The process of clocking the data with a re-generated clock to remove jitter.

Register

A place to store an effect.

Resource

A capability of the system, typically consisting of a set of circuitry.

Rundown Converter

Converts a producer's rundown into a full script with graphics, cues, and prompter scripts.

Rundown List

Illustrates story, page and all events associated with that specific story. The Ignite replica of the show rundown.

S

Saturation

The degree of purity of a color. Adding white to a color reduces its degree of saturation.

SD

Standard Definition.

Self Key

A key effect in which a single video signal serves as both the key cut and key fill.

Sequence

On the system, a feature allowing a series of E MEMs to be recalled in a specific order with a single command.

Serial Digital Interface (SDI)

[Also **Serial Digital Video**]

A standard for digital video transmission over coaxial cable; i.e., passing video data bits in serial form (one bit after another), along a single wire. Standard Definition serial digital video (SMPTE 259M) operates at 270 Mbits/sec ($2 \times 13.5 \text{ MHz} \times 10 \text{ bits}$).

The SDI standard uses data words that are 8 or 10 bits in length. Signals are uncompressed and are self-synchronizing between the source (transmitter) and destination (receiver). A signal in SDI can contain up to four independent digital audio signals along with the video signal.

Serial Interface

An interface that allows the switcher to be controlled remotely by a computer editor or other serial controller. Data is passed serially between the editor and the switcher at selectable baud (transmission) rates.

Serializer

A device that converts parallel digital information to serial.

Snapshot

An E-MEM with only one keyframe.

S/N (Signal to Noise) Ratio

The ratio of a signal power to the noise power corrupting the signal. In less technical terms, signal-to-noise ratio compares the level of a desired signal to the level of background noise. The higher the ratio, the less obtrusive the background noise is.

Soft Border

A wipe pattern border that is mixed on the edges to give a soft effect.

Soft Edge

A pattern edge between two video signals in which the signals are mixed for a soft effect.

Source

- 1) An external device providing video. A source may provide only one video signal, or it may provide two signals (key fill and key cut).
- 2) The video signal(s) from a source, along with the source definition information associated with that source. Also refer to **Source Definition**.

Source Definition

A definition of the video signals making up a source, the device type and name of source, and the default processing and other parameters to be used for that source. The system is based on source selection, rather than choosing crosspoints.

Source Memory

A feature where the last keying and video processing settings for a source are retained and re-imposed when that source is re-selected. Default source memory values can be set for each source on each bus.

SPOP (Single Press Open)

Automatically opening a related menu when a control panel button is pressed. On the system, buttons supporting SPOP are labeled with a graphical indicator.

Stack

Refer to **Key Priority**.

Still Store

A device that captures, saves, and outputs individual video frames, either in analog or digital form, allowing extremely fast access time.

Suite

One or more control surfaces configured for use on the same project.

Suite Preference

A collection of settings used to configure a suite to create a consistent working environment for all involved.

Supers

Information from the show script that is sent to the character generator, and then output (superimposed/placing text over a video signal) to the lower third with the correct story.

Switched Preview

A special output of the system connected to a dedicated monitor. The operator can select and switch various system video signals to that output to preview them.

Switcher

A device that accepts inputs from a variety of video sources and allows the operator to select a particular source to be sent to the switcher's output(s). Also does transitions between sources and special effects (video mixing, wiping, keying, and such).

Sync

1) General term for a synchronizing signal or signal component. Digital systems generally employ an analog external timing reference signal (such as color black or tri-level sync) to synchronize different pieces of equipment. Within the digital signal itself, however, synchronizing information is carried by special digital codes inserted at the beginning and end of each active line.

2) In analog television systems, sync is the portion of the video signal that occurs during blanking and is used to synchronize the operation of cameras, monitors, and other equipment. Horizontal sync occurs within the blanking period in each horizontal scanning line, and vertical sync occurs within the vertical blanking period. A color black signal is often used for synchronizing different pieces of analog equipment.

T

Tally

A lighted indication that the associated video source is in use. Tally lights may be in front of a camera to show that it is the camera being used at that moment, or they may be used to light up the pushbuttons of video switchers.

Terminate, Termination

To complete a circuit by connecting a resistive load to it.

Timecode

Electronic guide track added to film, video or audio material to provide a time reference for editing, synchronization, etc.

TFT

Thin-film Transistor – often called “active matrix” display, this is the brightest, most viewable kind of LCD flat-panel display. It is also more expensive than “passive matrix” screens. In a TFT display, each pixel is actively controlled by one or more transistors.

TME

Refer to **Transition Macro Event**.

Transition

A change from one picture to another. Cut, mix, and wipe are transitions.

Transition Macro™ Event

A group of individual production tasks that are combined to create an automated video production event. A TME is created by dragging and dropping task icons on the timeline, defining the individual task properties, and then saving the resulting TME as an individual event macro.

TTL

Through-the-Lens – term used to describe a type of prompter. A TTL prompter mounts in front of the camera. A glass screen mounted 45° above the prompter reflects the script so that the announcer can read the text while looking at the camera behind the screen.

U**User Preference**

A collection of user-available control configuration settings that enables working environment customization.

V**VDR (Video Disk Recorder)**

Refer to **DVR**.

Vertical Interval

The portion of the video signal that occurs between the end of one field or frame and the beginning of the next.

Video Fill

A video signal used to fill the hole made by a key cut signal.

Video Mixer

Refer to **Switcher**.

Video Path

The path that video takes through the switcher.

Video Switcher

Refer to **Switcher**.

VTR (Video Tape Recorder)

A video recorder and playback device that records audio and video signals on magnetic tape.

W**Wash Matte**

A type of matte that contains two elements rather than a single flat color. For example, a wash matte can have one color that mixes gradually across the screen to another color.

Wipe

A transition between two video signals that occurs in the shape of a selected pattern.

Wipe Pattern Generator

Circuitry that creates patterns that can be used to create wipe transitions, preset patterns, key masks, and matte washes.

Work Buffer

An active area of memory where the current effect parameters are stored, allowing the operator to use and modify the effect without changing the data stored in E MEM.

X**Y****Z**

