


# Densité 3+ FR4 Frame

High-density Modular Frame for Advanced Signal Processing



24 slots in a frame, double the power per slot.

The 4 RU Densité 3+ FR4 Frame from Grass Valley, a Belden Brand, is a modular frame and controller designed to deliver more power per slot and higher speed connectivity needed by the increased feature set of the latest Densité products. The Densité 3+ FR4 frame offers true multiformat operation, with the ability to process simultaneously SDI and IP 12G, 3G, HD, SD, and analog video, as well as AES and analog audio. The frame provides advanced monitoring and back-up capabilities along with a color LCD panel with integrated touchscreen for ease of status and control navigation on the front panel.

The front-opening frame features dual hot-swappable power supplies (PSUs) and fans. The processing modules or cards for the frame are also hot-swappable, and can be configured automatically when a card is replaced. The frame is front-to-back air-cooled and all modules, redundant PSUs and fans are monitored to provide status via GPI or the Ethernet port. All frame configurations include two PSUs and a controller card with internal GbE switch connectivity, which allows card parameters adjustments from the front panel.

The Densité 3+ FR4 ADV is a version of the frame with an advanced controller that delivers additional functionality with a second reference and timecode inputs, and support of SMPTE ST 2059 genlock over IP reference option. Existing Densité 3+ FR4 frame Ethernet Controllers and rear panels can be field upgraded with the D3+FR4-ADV-UPG kit to deliver the same advanced controller features.

## Fitting 3 RU and 2 RU cards in the Densité 3+ Frame

The Densité 3+ FR4 frame can host any of the latest high powered Densité modules, such as the XIP-3901, and the IPG-3901 and KMX-3901 but is also fully backwards compatible with all existing 3 RU and 2 RU Densité modules. With over 100 modules to choose from, this gives you mix and match flexibility and preserves your investment.

# Densité 3+ FR4 Frame High-density Modular Frame for Advanced Signal Processing


## KEY FEATURES

### Key product capabilities:

- Fully backwards compatible with Densité 2 and Densité 3 cards
- 24 slots with a power budget of 25 watts per slots
- Optional frame reference on controller card providing:
  - Digitally generated reference for intra-frame distribution
  - Timecode extraction and embedding
  - Supports SMPTE ST 318 for perfect audio/video phasing
  - Easy control and monitoring
  - URS simplifies interformat processing
- Dual GbE port for system wide redundancy with internal GbE switch connectivity to each cards
- Full touchscreen color LCD panel for module status and control
- Modular frame controller with associated modular rear panel
- Advanced frame controller configuration provides:
  - Second reference and timecode inputs (with optional frame reference)
  - Support of SMPTE ST 2059 genlock over IP reference option

### Standard Densité capabilities:

- Multiple video and audio formats can be fitted in a single frame
- Densité 3 RU and Densité 2 RU modules can co-exist in the same frame
- Easy configuration by front panel or remotely via the Ethernet frame controller
- Choice of control panels, including the PC-based iControl Solo GUI
- Two hot-swappable power supplies
- Supports full range of Densité Series modules
- Frame can be stacked without additional cooling spaces
- Optional redundant Ethernet connection



Back of the Densité 3+ FR4 chassis shown with Advanced Controller rear.

# Densité 3+ FR4 Frame High-density Modular Frame for Advanced Signal Processing

## SPECIFICATIONS

### Mechanical

**Dimensions:** 4 RU x 485 mm (19 in.) x 302 mm (11.88 in.) with connectors

**Weight:** 8.4 kg (18.5 lbs.), 2 PSUs and 1 controller

### Power

**Input range:** AC 50-60 Hz, 100-240V

**Rating:** 700W

### Control and Monitoring

**Communication ports:** Dual Gigabit Ethernet (Also provides PTP (IEEE 1588) support on advanced controller for SMPTE ST 2059 reference)

**Alarm:** GPI contact

### Cooling

**Variable speed fans:**

2 sets of 3 fans on the rear of the frame

2 on each PSU

**Operating temp. range:** 0°- 40° C (32°- 104° F)

### Reference Input

**Load:** Passive loop-through

**Impedance:** 75Ω bridging

**Return loss:** >30 dB up to 30 MHz

**Signal type:** Composite NTSC-M, PAL-B black-burst with optional VITC

**Standard:** SMPTE ST 170, ITU-R BT.1700-1, SMPTE ST 318

**Signal level:** 1 Vp-p

**Signal type:** HD tri-level sync

**Standard:** SMPTE ST 274, SMPTE ST 296

**Signal level:** 600 mVp-p

### LTC-IN

**Signal type:** LTC

**Standard:** SMPTE ST 12

**Signal level:** 0.5 Vp-p to 4.5 Vp-p

### Media Ports

In Advanced Controller only (future use)

## ORDERING

### DENSITÉ 3+ FR4 STD

4 RU modular frame, 24 slots, 2 power supplies, standard controller card with redundant Ethernet ports and direct access touchscreen, DENSITÉ 3+ CPU-ETH3-RP rear and blank rear panels

### DENSITÉ 3+ FR4 ADV

4 RU modular frame, 24 slots, 2 power supplies, advanced controller card with redundant Ethernet ports and direct access touchscreen, DENSITÉ 3+ CPU-ETH3-RP-ADV rear and blank rear panels

### Options

DENSITÉ 3+ CPU-ETH3-OPT-LNK

DENSITÉ 3+ CPU-ETH3-REF

D3+FR4-ADV-PTP

D3+FR4-ADV-UPG

### Description


Full link redundancy using Channel Bonding (software option)

Frame reference software option

IEEE 1588 and SMPTE ST 2059 option on Densité 3+ FR4 Advanced Controller

Densité 3+ FR4 Advanced Controller with rear panel field upgrade

Note: Rear panels must be specified and ordered with appropriate cards.



DENSITÉ 3+ FR4 STD Controller Functional Block Diagram


### CONTROLLER OPTIONAL PLATFORM

DENSITÉ 3+ FR4 ADV additional functions (Advanced Controller Platform) with DENSITÉ 3+ CPU-ETH3-RP-ADV rear

### OPTIONAL LICENSES

DENSITÉ 3+ CPU-ETH3-REF

D3+FR4-ADV-PTP option



WWW.GRASSVALLEY.COM

Join the Conversation at [GrassValleyLive](#) on Facebook, Twitter, YouTube and [Grass Valley - A Belden Brand](#) on LinkedIn.



[www.grassvalley.com/blog](http://www.grassvalley.com/blog)

Belden, Belden Sending All The Right Signals, the Belden logo, Grass Valley and the Grass Valley logo are trademarks or registered trademarks of Belden Inc. or its affiliated companies in the United States and other jurisdictions. Grass Valley products listed above are trademarks or registered trademarks of Belden Inc., GVBB Holdings S.A.R.L. or Grass Valley Canada. Belden Inc., GVBB Holdings S.A.R.L., Grass Valley Canada and other parties may also have trademark rights in other terms used herein.

Copyright © 2015, 2017-2018 Grass Valley Canada. All rights reserved. Specifications subject to change without notice.